

Correspondence

Correction to “Modeling and Performance Analysis of a Symmetric Fast-Circuit Switched Robust-WDM LAN with the AR/LTP Protocol”

Tarek S. El-Bawab and Anura P. Jayasumana

In the paper above,¹ the authors would like to note two important corrections to their paper.

Manuscript received June 12, 1999.

T. S. El-Bawab is with Alcatel USA Inc., Corporate Research Center, Richardson, TX 75081 USA.

A. P. Jayasumana is with the Department of Electrical and Computer Engineering, Colorado State University, Fort Collins, CO 80523 USA.

Publisher Item Identifier S 0733-8724(99)07585-4.

¹T. S. El-Bawab and A. P. Jayasumana, *J. Lightwave Technol.*, vol. 17, pp. 973–988, June 1999.

First, (11) was subject to a printer error and the denominator was inadvertently omitted. The corrected equation is shown as follows:

$$\bar{T}_R = \frac{\overline{T_{tr}^2}}{2\bar{T}_{tr}}$$

where $\overline{T_{tr}^2}$ is the second moment of T_{tr} .

Second, in the short paragraph before (12), an inline expression containing a fraction was missing the correct mathematical parentheses. The sentence with the corrected expression is as follows:

“Hence, the effective traffic intensity of the node would be $\rho = \lambda[P_{ad}/(1 - P_B)](1 + \bar{m}_{tr})\bar{T}_{tr}$.”