

IEEE

# PHOTONICS TECHNOLOGY LETTERS

A PUBLICATION OF THE IEEE LASERS AND ELECTRO-OPTICS SOCIETY



JANUARY 2004

VOLUME 16

NUMBER 1

IPTLEL

(ISSN 1041-1135)

---

|  |  |    |
|--|--|----|
| Editorial . . . . .  | <i>N. Dagli</i>  | 5  |
| <hr/>  |  |    |
| <i>Semiconductor Lasers and Amplifiers</i>   |  |    |
| Lasing Emission of InGaAs Quantum Dot Microdisk Diodes . . . . .   | <i>L. Zhang and E. Hu</i>  | 6  |
| Polarization-Resolved Relative Intensity Noise Measurements of a Vertical-Cavity Surface-Emitting Laser Subjected to Strong Optical Feedback . . . . . | <i>S. Sivaprakasam, S. Bandyopadhyay, Y. Hong, P. S. Spencer, and K. A. Shore</i>                  | 9  |
| Curved Waveguides for Spatial Mode Filters in Semiconductor Lasers. . . . .  | <i>R. B. Swint, T. S. Yeoh, V. C. Elarde, J. J. Coleman, and M. S. Zediker</i>                     | 12 |
| Design and Analysis of Widely Tunable Sampled Grating DFB Laser Diode Integrated With Sampled Grating Distributed Bragg Reflector . . . . .            | <i>S. Kim, Y. Chung, S.-H. Oh, and M.-H. Park</i>  | 15 |
| 22-GHz Modulation Bandwidth of Long Cavity DBR Laser by Using a Weakly Laterally Coupled Grating Fabricated by Focused Ion Beam Lithography. . . . .   | <i>L. Bach, W. Kaiser, J. P. Reithmaier, A. Forchel, M. Gioannini, V. Feies, and I. Montrosset</i> | 18 |
| Influence of Electrical Parasitics and Drive Impedance on the Laser Modulation Response . . . . .  | <i>M. N. Akram, R. Schatz, and O. Kjebon</i>   | 21 |
| Quantum-Well Design for Monolithic Optical Devices With Gain and Saturable Absorber Sections. . . . .  | <i>V. V. Nikolaev and E. A. Avrutin</i>  | 24 |
| High-Performance Quantum-Dot Superluminescent Diodes . . . . .   | <i>Z. Y. Zhang, Z. G. Wang, B. Xu, P. Jin, Z. Z. Sun, and F. Q. Liu</i>                            | 27 |
| High Reliability of AlGaInP Light-Emitting Diodes With Tensile Strain Barrier-Reducing Layer. . . . .  | <i>J.-Y. Su, W.-B. Chen, M.-C. Wu, Y.-K. Su, and K.-M. Liang</i>                                   | 30 |
| InGaN Microring Light-Emitting Diodes. . . . .   | <i>H. W. Choi, C. W. Jeon, and M. D. Dawson</i>  | 33 |
| Light Emission Near 1.3 $\mu\text{m}$ Using ITO–Al <sub>2</sub> O <sub>3</sub> –Si <sub>0.3</sub> Ge <sub>0.7</sub> –Si Tunnel Diodes. . . . .         | <i>C. Y. Lin, A. Chin, Y. T. Hou, M. F. Li, S. P. McAlister, and D. L. Kwong</i>                   | 36 |
| Performance Implications of Wide-Band Lasers for FSK Modulation Labeling Scheme . . . . .  | <i>Y. Yu, G. Mulvihill, S. O’Duill, and R. O’Dowd</i>  | 39 |

---

(Contents Continued on Page 1)



---

|  |     |
|--|-----|
| Adjustment of Laser Facet Film Reflectivity by Ablation Etching . . . . .  | 42  |
| . . . . . <i>T. Takeshita, M. Sugo, Y. Shibata, H. Kamioka, and Y. Tohmori</i>   |     |
| Realization of All-Optical Flip-Flop Using Directionally Coupled Bistable Laser Diode . . . . .  | 45  |
| . . . . . <i>M. Takenaka and Y. Nakano</i>   |     |
| The Structure and Maximal Gain of CW-Pumped GaP-AlGaP Semiconductor Raman Amplifier With Tapers on Both Sides . . . . .  | 48  |
| . . . . . <i>S. Saito, J.-I. Nishizawa, K. Suto, and T. Kimura</i>   |     |
| <i>Fiber Amplifiers and Lasers</i>   |     |
| 4 × 10 GHz Mode-Locked Multiple-Wavelength Fiber Laser . . . . .   | 51  |
| . . . . . <i>J. W. Lou, T. F. Carruthers, and M. Currie</i>  |     |
| Multiwavelength-Switchable SOA-Fiber Ring Laser Based on Polarization-Maintaining Fiber Loop Mirror and Polarization Beam Splitter . . . . .   | 54  |
| . . . . . <i>Y. W. Lee, J. Jung, and B. Lee</i>  |     |
| Advanced Configuration of Erbium Fiber Passively Q-Switched Laser With Co <sup>2+</sup> :ZnSe Crystal as Saturable Absorber . . . . .  | 57  |
| . . . . . <i>V. N. Philippov, A. V. Kir'yanov, and S. Unger</i>  |     |
| Wavelength Switching of a Fiber Laser With a Sagnac Loop Reflector. . . . .  | 60  |
| . . . . . <i>G. Das and J. W. Y. Lit</i>   |     |
| Thermal Effects in Kilowatt Fiber Lasers. . . . .  | 63  |
| . . . . . <i>Y. Wang, C.-Q. Xu, and H. Po</i>  |     |
| Transient Effects in Gain-Clamped Discrete Raman Amplifier Cascades . . . . .  | 66  |
| . . . . . <i>G. Bolognini and F. Di Pasquale</i>   |     |
| A Simple Algorithm for Gain Spectrum Adjustment of Backward-Pumped Distributed Fiber Raman Amplifiers . . . . .  | 69  |
| . . . . . <i>W. Zhang, X. Feng, J. Peng, and X. Liu</i>  |     |
| Design of Transmission Optical Fiber With a High Raman Gain, Large Effective Area, Low Nonlinearity, and Low Double Rayleigh Backscattering . . . . .                                      | 72  |
| . . . . . <i>H. S. Seo, Y. G. Choi, and K. H. Kim</i>  |     |
| Evaluation of Raman Gain Coefficient Distribution Independent of Imperfection Contributions . . . . .  | 75  |
| . . . . . <i>K. Toge and K. Hogari</i>   |     |
| Raman-Generated Pump Impact on Optical Parametric Amplification . . . . .  | 78  |
| . . . . . <i>L. Marazzi, P. Parolari, S. Seghizzi, and M. Martinelli</i>   |     |
| Effective Suppression of Penalties Induced by Parametric Nonlinear Interaction in Distributed Raman Amplifiers Based on NZ-DS Fibers . . . . .   | 81  |
| . . . . . <i>S. Sugliani, G. Sacchi, G. Bolognini, S. Faralli, and F. Di Pasquale</i>  |     |
| All-Optical Gain-Clamped Erbium-Doped Fiber Amplifier With Improved Noise Figure and Freedom From Relaxation Oscillation. . . . .  | 84  |
| . . . . . <i>J. T. Ahn and K. H. Kim</i>   |     |
| Dynamically Gain Control in the Serial Structure C + L Wide-Band EDFA. . . . .   | 87  |
| . . . . . <i>Q. Jiang, X. Liu, Q. Wang, and X. Feng</i>  |     |
| S Band Gain-Clamped Erbium-Doped Fiber Amplifier by Using Optical Feedback Method . . . . .  | 90  |
| . . . . . <i>C.-H. Yeh, C.-C. Lee, C.-Y. Chen, and S. Chi</i>  |     |
| <i>Modulators and Switches</i>   |     |
| Thermal Stability Enhancement of Electrooptic Polymer Modulator . . . . .  | 93  |
| . . . . . <i>S. Park, J. J. Ju, J. Y. Do, S. K. Park, and M.-H. Lee</i>  |     |
| Polymer-Based Electrooptical Circular-Polarization Modulator. . . . .  | 96  |
| . . . . . <i>J. Yang, Q. Zhou, X. Jiang, M. Wang, and R. T. Chen</i>   |     |
| A Hybrid MEMS-Waveguide Wavelength Selective Cross Connect . . . . .   | 99  |
| . . . . . <i>D. T. Fuchs, C. R. Doerr, V. A. Aksyuk, M. E. Simon, L. W. Stulz, S. Chandrasekhar, L. L. Buhl, M. Cappuzzo, L. Gomez, A. Wong-Foy, E. Laskowski, E. Chen, and R. Pafchek</i> |     |
| Packet Switching Performance at 10 Gb/s Across a 4 × 4 Optical Crosspoint Switch Matrix . . . . .  | 102 |
| . . . . . <i>I. B. Djordjevic, R. Varrazza, M. Hill, and S. Yu</i>   |     |
| <i>Propagation and Waveguiding</i>   |     |
| PMD Compensator With Second-Order PMD Mitigation Using Mode-Coupled Fixed Delay. . . . .   | 105 |
| . . . . . <i>K. Ikeda</i>  |     |
| A Random Walk Procedure for Evaluating Probability Distribution Functions in Communication Systems. . . . .  | 108 |
| . . . . . <i>D. Yevick and W. Bardyszewski</i>   |     |
| Performance Degradation Due to Polarization Effects in a Dispersion-Managed-Soliton Recirculating Loop System. . . . .   | 111 |
| . . . . . <i>C. Xie, A. R. Grant, L. F. Mollenauer, and X. Liu</i>   |     |
| Ideal Microlens Design for Flattening the Equiphase Distribution of a Gaussian Laser Beam . . . . .  | 114 |
| . . . . . <i>Y. He and F. G. Shi</i>   |     |
| Optical Transmission of Polymer Pillars for Chip I/O Optical Interconnections . . . . .  | 117 |
| . . . . . <i>M. S. Bakir, T. K. Gaylord, O. O. Ogunsola, E. N. Glytsis, and J. D. Meindl</i>   |     |
| Single-Mode Rb <sup>+</sup> -K <sup>+</sup> Ion-Exchanged BK7 Glass Waveguides With Low Losses at 1550 nm . . . . .  | 120 |
| . . . . . <i>K. Liu and E. Y. B. Pun</i>   |     |
| Hole-Assisted Multiring Fiber With Low Dispersion Around 1550 nm. . . . .  | 123 |
| . . . . . <i>M. Yan, P. Shum, and C. Lu</i>  |     |
| Photonic Crystal Fiber Analysis Through the Vector Boundary-Element Method: Effect of Elliptical Air Hole . . . . .  | 126 |
| . . . . . <i>T.-L. Wu and C.-H. Chao</i>   |     |
| A Frequency-Domain Finite Element Method for Modeling of Nonlinear Optical Waveguide Discontinuities. . . . .  | 129 |
| . . . . . <i>T. Fujisawa and M. Koshiba</i>  |     |
| Spatio-Temporal Finite-Element Propagator for Ultrashort Optical Pulses . . . . .  | 132 |
| . . . . . <i>L. L. Bravo-Roger, K. Z. Nóbrega, H. E. Hernández-Figueroa, and A. P. López-Barbero</i>   |     |

---

---

*Passive Components*

Wide Range Center Wavelength Trimming of Vertically Coupled Microring Resonator Filter by Direct UV Irradiation to SiN Ring Core . . . . . *H. Haeiwa, T. Naganawa, and Y. Kokubun* 135

Optical Characteristics of a Self-Aligned Microlens Fabricated on the Sidewall of a 45°-Angled Optical Fiber . . . . . *K.-W. Jo, M.-S. Kim, J. H. Lee, E.-K. Kim, and K.-H. Park* 138

Optimal Design of Guided-Mode Grating Resonance Filters . . . . . *G. Bao and K. Huang* 141

A Novel Straight Arrayed Waveguide Grating With Linearly Varying Refractive-Index Distribution . . . . . *Y. Kawakita, T. Saitoh, S. Shimotaya, and K. Shimomura* 144

Resonance in Fiber-Based Acoustooptic Devices via Acoustic Radiation to Air . . . . . *S. H. Yun and H. S. Kim* 147

Effects of Acoustic Reflection on the Performance of a Cladding-Etched All-Fiber Acoustooptic Variable Optical Attenuator . . . . . *A. A. Au, Q. Li, C.-H. Lin, and H. P. Lee* 150

Group Delay Control of Super-Imposed Fiber Gratings Using a Two-Column System Mounted on a Rotatable Disk . . . . . *S. Chung, J. Kwon, S. Baek, and B. Lee* 153

Packaging to Reduce Thermal Gradients Along the Length of Long Fiber Gratings . . . . . *J. F. Brennan, III, P. M. Bungarden, C. E. Fisher, and R. M. Jennings* 156

Novel Growth Behaviors of Fiber Bragg Gratings in Polymer Optical Fiber Under UV Irradiation With Low Power . . . . . *H. B. Liu, H. Y. Liu, G. D. Peng, and P. L. Chu* 159

Focusing Grating Coupler for Blue Laser Light . . . . . *Y. Sohn, Y. Park, D. Suh, H. Ryu, and M. C. Paek* 162

Rigorous Analysis of Polarization-Dependence Loss (PDL) for Equilateral 3 × 3 Fused Fiber Couplers . . . . . *T.-L. Wu and H.-J. Ou* 165

All-Fiber 3 × 3 Interleaver Design With Flat-Top Passband . . . . . *Q. Wang, Y. Zhang, and Y. C. Soh* 168

A Novel Directional Coupler Utilizing a Left-Handed Material . . . . . *S. Xiao, L. Shen, and S. He* 171

Fiber Fuse Generation in Single-Mode Fiber-Optic Connectors . . . . . *Y. Shuto, S. Yanagi, S. Asakawa, M. Kobayashi, and R. Nagase* 174

Athermal Holographic Filters . . . . . *H.-T. Hsieh, G. Panotopoulos, M. Liger, Y.-C. Tai, and D. Psaltis* 177

Fiber Fuse Effect in Microstructured Fibers . . . . . *E. M. Dianov, I. A. Bufetov, A. A. Frolov, Y. K. Chamorovsky, G. A. Ivanov, and I. L. Vorobjev* 180

Absolutely Single Polarization Photonic Crystal Fiber . . . . . *H. Kubota, S. Kawanishi, S. Koyanagi, M. Tanaka, and S. Yamaguchi* 182

A Reflective Curved Mirror With Low Coupling Loss for Optical Interconnection . . . . . *S.-P. Han, J. T. Kim, S.-W. Jung, S.-H. Ahn, C.-G. Choi, and M.-Y. Jeong* 185

*Active Components*

Tunable Dispersion Compensation in a 10-Gb/s Optical Transmission System by Employing a Novel Tunable Dispersion Compensator . . . . . *X. Chen, X. Xu, M. Zhou, D. Jiang, X. Li, J. Feng, and S. Xie* 188

Multistate Latching MEMS Variable Optical Attenuator . . . . . *R. R. A. Syms, H. Zou, J. Stagg, and D. F. Moore* 191

Erbium-Doped Waveguides Fabricated With Atomic Layer Deposition Method . . . . . *K. Solehmainen, M. Kapulainen, P. Heimala, and K. Polamo* 194

*Wavelength Converters*

Wavelength Conversion Using an Integrated DFB Laser-Phase Shifter . . . . . *M. Fisher and S. L. Chuang* 197

*All-Optical Techniques*

Optimization of Pulse Regeneration at 40 Gb/s Based on Spectral Filtering of Self-Phase Modulation in Fiber . . . . . *T.-H. Her, G. Raybon, and C. Headley* 200

All-Optical Format Conversion From NRZ to CSRZ and Between RZ and CSRZ Using SOA-Based Fiber Loop Mirror . . . . . *W. Li, M. Chen, Y. Dong, and S. Xie* 203

*Measurements*

Polarization-Mode Dispersion Measurement in a System With Polarization-Dependent Loss or Gain . . . . . *L. Chen, O. Chen, S. Hadjifaradji, and X. Bao* 206

Polarization-Mode Dispersion of Installed Recent Vintage Fiber as a Parametric Function of Temperature . . . . . *M. Brodsky, P. Magill, and N. J. Frigo* 209

Direct Observation of Local Birefringence and Axis Rotation in Spun Fiber With Centimetric Resolution . . . . . *S. M. Pietralunga, M. Ferrario, P. Martelli, and M. Martinelli* 212

Polarization-Insensitive Optical Sampling System Using Two KTP Crystals . . . . . *N. Yamada, H. Ohta, and S. Nogiwa* 215

*Sensors*

Bragg Grating-Based Fiber-Optic Laser Probe for Temperature Sensing . . . . . *J. Mandal, S. Pal, T. Sun, K. T. V. Grattan, A. T. Augousti, and S. A. Wade* 218

---

---

|   |  |     |
|---|--|-----|
| Simultaneous Strain and Temperature Measurements With Fiber Bragg Grating Written in Novel Hi-Bi Optical Fiber . . . . .                | <i>G. Chen, L. Liu, H. Jia, J. Yu, L. Xu, and W. Wang</i>  | 221 |
| Temperature-Independent Fiber Bragg Grating Tilt Sensor . . . . .   | <i>B.-O. Guan, H.-Y. Tam, and S.-Y. Liu</i>  | 224 |
| Improving the Performance of FBG Sensors in a WDM Network Using a Simulated Annealing Technique . . . . .                               | <i>C. Z. Shi, N. Zeng, C. C. Chan, Y. B. Liao, W. Jin, and L. Zhang</i>  | 227 |
| Intensity and Wavelength-Division Multiplexing FBG Sensor System Using a Tunable Multiport Fiber Ring Laser . . . . .                   | <i>P.-C. Peng, J.-H. Lin, H.-Y. Tseng, and S. Chi</i>  | 230 |
| Characterization and Passivation Effects of an Optical Accelerometer Based on Antiresonant Waveguides . . . . .                         | <i>A. Llobera, J. A. Plaza, I. Salinas, J. Berganzo, J. García, J. Esteve, and C. Domínguez</i>  | 233 |
| <i>Photodetectors and Photoreceivers</i>  |  |     |
| A Monolithically Integrated Long-Wavelength Balanced Photodiode Using Asymmetric Twin-Waveguide Technology . . . . .                    | <i>S. S. Agashe, S. Datta, F. Xia, and S. R. Forrest</i>   | 236 |
| Thermally Induced Nonlinearities in High-Speed p-i-n Photodetectors. . . . .  | <i>T. H. Stievater and K. J. Williams</i>  | 239 |
| Nonlinear Behaviors of Low-Temperature-Grown GaAs-Based Photodetectors Around 1.3- $\mu\text{m}$ Telecommunication Wavelength . . . . . | <i>J.-W. Shi, Y.-H. Chen, K.-G. Gan, Y.-J. Chiu, J. E. Bowers, M.-C. Tien, T.-M. Liu, and C.-K. Sun</i>                                | 242 |
| Long Wavelength Resonant Cavity Photodetector Based on InP/Air-Gap Bragg Reflectors . . . . .   | <i>H. Huang, Y. Huang, X. Wang, Q. Wang, and X. Ren</i>  | 245 |
| Noise and Intersymbol-Interference Properties of OTDM and ETDM Receivers . . . . .  | <i>M. M. Strasser, P. J. Winzer, and A. Napoli</i>   | 248 |
| <i>RF Photonics</i>   |  |     |
| A Radio-on-Fiber Intelligence Transport System Based on Electroabsorption Modulator and Semiconductor Optical Amplifier. . . . .        | <i>H.-H. Lu, Y.-C. Lin, Y.-H. Su, and H.-S. Su</i>   | 251 |
| FBG-Based Optical Interface to Support a Multisector Antenna in a Spectrally Efficient Fiber Radio System . . . . .                     | <i>C. Marra, A. Nirmalathas, C. Lim, M. Attygalle, D. Novak, B. Ashton, L. Poladian, W. S. T. Rowe, T. Wang, and J. A. Besley</i>      | 254 |
| Efficient Architecture for WDM Photonic Microwave Filters . . . . .   | <i>B. Vidal, V. Polo, J. L. Corral, and J. Martí</i>   | 257 |
| Wide Dynamic Range Doppler-Shift Compensation for Space-Borne Optical Communications . . . . .  | <i>C. B. Svec and T. M. Shay</i>   | 260 |
| <i>Subsystems</i>   |  |     |
| Ultralow Timing Jitter 40-Gb/s Clock Recovery Using a Self-Starting Optoelectronic Oscillator . . . . .                                 | <i>J. Lasri, P. Devgan, R. Tang, and P. Kumar</i>  | 263 |
| A Polymer PLC Platform With a Fiber-Alignment V-Groove for a Low-Cost 10-GbE WDM Transmitter . . . . .                                  | <i>M. Takahashi, T. Ido, and T. Nagara</i>   | 266 |
| Alignment-Insensitive Coupling for PLC-Based Surface Mount Photonics . . . . .  | <i>D. W. Vernooy, J. S. Paslaski, H. A. Blauvelt, R. B. Lee, and K. J. Vahala</i>  | 269 |
| Multicast Optical Switch Fabric With Ultrafast Channel Access Based on Heterodyne Receivers. . . . .                                    | <i>L. Möller, M. Kauer, A. Adamiecki, J. Sinsky, and L. Buhl</i>   | 272 |
| Micromechanical Optical Crossconnect With 4- $F$ Relay Imaging Optics . . . . .   | <i>M. Kozhevnikov, R. Ryf, D. T. Neilson, P. Kolodner, C. A. Bolle, A. R. Papazian, J. Kim, and J. V. Gates</i>                        | 275 |
| Single Transverse Mode Operation of a Self-Seeded Commercial Multimode VCSEL . . . . .  | <i>D.-L. Cheng, E.-C. Liu, and T.-C. Yen</i>   | 278 |
| Harmonic Synchronization of Fourier-Synthesized Optical Pulses to an External Optical Clock. . . . .                                    | <i>M. Hyodo, K. S. Abedin, N. Onodera, and M. Watanabe</i>   | 281 |
| 10-Gb/s All-Optical Half-Adder With Interferometric SOA Gates . . . . .   | <i>D. Tsiokos, E. Kehayas, K. Vyrsokinos, T. Houbavlis, L. Stampoulidis, G. T. Kanellos, N. Pleros, G. Guekos, and H. Avramopoulos</i> | 284 |
| An Asymmetric Bidirectional Amplifier With All-Optical Gain Control for Randomly Variable Data Traffic . . . . .                        | <i>B.-H. Choi and C.-J. Chae</i>   | 287 |
| Polarization-Mode Dispersion Mitigation by a Fiber-Based 2R Regenerator Combined With Synchronous Modulation . . . . .                  | <i>M. Matsumoto</i>  | 290 |
| Extended-Cavity Semiconductor Wavelength-Swept Laser for Biomedical Imaging . . . . .   | <i>S. H. Yun, C. Boudoux, M. C. Pierce, J. F. de Boer, G. J. Tearney, and B. E. Bouma</i>  | 293 |
| Wide Dynamic Range 10-Gb/s DPSK Packet Receiver Using Optical-Limiting Amplifiers . . . . .   | <i>Y. Su, X. Liu, and J. Leuthold</i>  | 296 |

---

---

*Networks and Systems*

Fiber Dispersion and Dispersion Slope Compensation in a 40-Channel 10-Gb/s 3200-km Transmission Experiment Using Cascaded Single-Cavity Gires-Tournois Etalons. . . . . *D. Yang, C. Lin, W. Chen, and G. Barbarossa* 299

Performance Analysis of Time-Polarization Multiplexed 40-Gb/s RZ-DPSK DWDM Transmission . . . . . *X. Liu, C. Xu, and X. Wei* 302

Impact of Group-Delay Ripple in Transmission Systems Including Phase-Modulated Formats. . . . . *X. Liu, L. F. Mollenauer, and X. Wei* 305

The Effect of Interferometer Phase Error on Direct-Detection DPSK and DQPSK Signals. . . . . *K.-P. Ho* 308

Modified Duobinary Polarization-Shift Keying Transmission Scheme . . . . . *J. M. Gené, M. Soler, J. Comellas, and J. Prat* 311

Quantitative Experimental Study of Intrachannel Nonlinear Timing Jitter in a 10-Gb/s Terrestrial WDM Return-To-Zero System . . . . . *H. Xu, J. Zweck, L. Yan, C. R. Menyuk, and G. M. Carter* 314

A Multirate Upgradeable 1.6-Tb/s Hierarchical OADM Network . . . . . *Y. Su, S. Chandrasekhar, R. Ryf, C. R. Doerr, L. Möller, I. Widjaja, G. Raybon, D. T. Neilson, T. Zhou, L. Buhl, and S. Radic* 317

A Novel Technique for Optical Label and Payload Generation and Multiplexing Using Optical Carrier Suppression and Separation . . . . . *J. Yu and G.-K. Chang* 320

BER Performance of All-Optical Subcarrier Label Swapping With 2R Regeneration . . . . . *M. Y. Jeon, Z. Pan, J. Cao, and S. J. B. Yoo* 323

An Optimization Process for Raman-Amplified Long-Span Transmission . . . . . *J.-C. Bouteiller, J. Bromage, H.-J. Thiele, L. E. Nelson, K. Brar, and S. Stulz* 326

Optimization of Pumping Schemes for 160-Gb/s Single-Channel Raman Amplified Systems . . . . . *Z. Xu, K. Rottwitt, C. Peucheret, and P. Jeppesen* 329

A Novel Bipolar Wavelength-Time Coding Scheme for Optical CDMA Systems . . . . . *U. N. Griner and S. Arnon* 332

Experimental Study on Time-Spread/Wavelength-Hop Optical Code Division Multiplexing With Group Delay Compensating En/Decoder . . . . . *H. Tamai, H. Iwamura, N. Minato, and S. Oshiba* 335

Irregular Low-Density Parity-Check Codes for Long-Haul Optical Communications . . . . . *I. B. Djordjevic, S. Sankaranarayanan, and B. Vasic* 338

Optically Compensating the PMD-Induced RF Power Fading for Single-Sideband Subcarrier-Multiplexed Systems . . . . . *C. Yu, Q. Yu, Z. Pan, A. B. Sahin, and A. E. Willner* 341

Raman Crosstalk in Fiber-Optic Hybrid CATV Systems With Wide Channel Separations . . . . . *F. Tian, R. Hui, B. Colella, and D. Bowler* 344

---

IEEE COPYRIGHT FORM . . . . . 347

---