

Static Analysis for Security

All software projects are guaranteed to have one artifact in common—source code. Together with architectural risk analysis,¹ code review for security ranks very high on the list of software security best practices (see Figure 1).² Here, we'll look at how to automate

tool without being aware of the finer points of security bugs.

Testing for security vulnerabilities is complicated by the fact that they often exist in hard-to-reach states or crop up in unusual circumstances. Static analysis tools can peer into more of a program's dark corners with less fuss than dynamic analysis, which requires actually running the code. Static analysis also has the potential to be applied before a program reaches a level of completion at which testing can be meaningfully performed.

Aim for good, not perfect

Static analysis can't solve all your security problems. For starters, static analysis tools look for a fixed set of patterns, or rules, in the code. Although more advanced tools allow new rules to be added over time, if a rule hasn't been written yet to find a particular problem, the tool will never find that problem. When it comes to security, what you don't know is likely to hurt you, so beware of any tool that says something like, "zero defects found, your program is, rather, now secure." The appropriate output is, "sorry, couldn't find any more bugs."

A static analysis tool's output still requires human evaluation. There's no way for a tool to know exactly which problems are more or less important to you automatically, so there's no way to avoid trawling through the output and making a judgment call about which issues should be fixed and which ones represent an acceptable level of risk. Knowledgeable people still need to get a program's design right to avoid any flaws—although static analysis

BRIAN CHESSE
*Fortify
Software*

GARY
MCGRAW
Cigital

source-code security analysis with static analysis tools.

Since ITS4's release in early 2000 (www.cigital.com/its4/), the idea of detecting security problems through source code has come of age. ITS4 is extremely simple—the tool basically scans through a file looking for syntactic matches based on several simple "rules" that might indicate possible security vulnerabilities (for example, use of `strcpy()` should be avoided). Much better approaches exist.

Catching implementation bugs early

Programmers make little mistakes all the time—a missing semicolon here, an extra parenthesis there. Most of the time, these gaffes are inconsequential; the compiler notes the error, the programmer fixes the code, and the development process continues. This quick cycle of feedback and response stands in sharp contrast to what happens with most security vulnerabilities, which can lie dormant (sometimes for years) before discovery. The longer a vulnerability lies dormant, the more expensive it can be to fix, and adding insult to injury, the programming community has a long history of repeating

the same security-related mistakes. The promise of static analysis is to identify many common coding problems automatically before a program is released.

Static analysis tools examine the text of a program statically, without attempting to execute it. Theoretically, they can examine either a program's source code or a compiled form of the program to equal benefit, although the problem of decoding the latter can be difficult. We'll focus on source code analysis here because that's where the most mature technology exists.

Manual auditing, a form of static analysis, is very time-consuming, and to do it effectively, human code auditors must first know what security vulnerabilities look like before they can rigorously examine the code. Static analysis tools compare favorably to manual audits because they're faster, which means they can evaluate programs much more frequently, and they encapsulate security knowledge in a way that doesn't require the tool operator to have the same level of security expertise as a human auditor. Just as a programmer can rely on a compiler to consistently enforce the finer points of language syntax, the operator of a good static analysis tool can successfully apply that

tools can find bugs in the nitty-gritty details, they can't critique design. Don't expect any tool to tell you, "I see you're implementing a funds transfer application. You should tighten up the user password requirements."

Finally, there's Rice's theorem, which says (in essence) that any nontrivial question you care to ask about a program can be reduced to the halting problem. In other words, static analysis problems are undecidable in the worst case. The practical ramifications of Rice's theorem are that all static analysis tools are forced to make approximations and that these approximations lead to less-than-perfect output. A tool can also produce *false negatives* (the program contains bugs that the tool doesn't report) or *false positives* (the tool reports bugs that the program doesn't contain). False positives cause immediate grief to any analyst who has to sift through them, but false negatives are much more dangerous because they lead to a false sense of security. A tool is sound if, for a given set of assumptions, it produces no false negatives, but the down side to always erring on the side of caution is a potentially debilitating number of false positives. The static analysis crowd jokes that too high a percentage of false positives leads to 100 percent false negatives because that's what you get when people stop using a tool. A tool is *unsound* if it tries to reduce false positives at the cost of sometimes letting a false negative slip by.

Approaches to static analysis

Probably the simplest and most straightforward approach to static analysis is the Unix utility `grep`. Armed with a list of good search strings, `grep` can reveal quite a lot about a code base. The down side is that `grep` is rather lo-fi because it doesn't understand anything about the files it scans. Comments, string literals, declarations, and function




Figure 1. The software development life cycle. Throughout this series, we'll focus on specific parts of the cycle; here, we're examining static analysis.

calls are all just part of a stream of characters to be matched against.

Better fidelity requires taking into account the lexical rules that govern the programming language being analyzed. By doing this, a tool can distinguish between a vulnerable function call

```
gets (&buf);
```

a comment

```
/* never ever call gets */
```

and an innocent and unrelated identifier

```
int begetsNextChild = 0;
```

Basic lexical analysis is the approach taken by early static analysis tools, including ITS4, FlawFinder (www.dwheeler.com/flawfinder/), and RATS (www.securesoftware.com), all of which preprocess and tokenize source files (the same first steps a compiler would take) and then match the resulting token stream against a library of vulnerable constructs. Earlier, Matt Bishop and Mike Dilger built a special-purpose lexical analysis tool specifically for the purpose of identifying time-of-check to time-of-use (TOC-TOU) flaws.³

While lexical analysis tools are certainly a step up from `grep`, they produce a hefty number of false positives because they make no effort to

account for the target code's semantics. A stream of tokens is better than a stream of characters, but it's still a long way from understanding how a program will behave when it executes. Although some security defect signatures are so strong that they don't require semantic interpretation to be identified accurately, most are not so straightforward.

To increase precision, a static analysis tool must leverage more compiler technology. By building an abstract syntax tree (AST) from source code, such a tool can take into account the basic semantics of the program being evaluated.

Armed with ASTs, the next decision to make is the scope of the analysis. *Local analysis* examines the program one function at a time and doesn't consider relationships between functions. *Module-level analysis* considers one class or compilation unit at a time, so it takes into account relationships between functions in the same module and considers properties that apply to classes, but it doesn't analyze calls between modules. *Global analysis* involves analyzing the entire program, so it takes into account all relationships between functions.

The scope of the analysis also determines the amount of context the tool considers. More context is better when it comes to reducing false positives, but it can lead to a huge amount of computation to perform.

Researchers have explored many

methods for making sense of program semantics. Some are sound, some aren't; some are built to detect specific classes of bugs, while others

specification-checking framework for C programs.⁷ It can help find common security problems like buffer overflows,

static analysis, moving some of the approaches touched on here into the mainstream.

Static analysis for security should be applied regularly as part of any modern development process.

are flexible enough to read definitions for what they're supposed to detect. Let's review some of the most recent tools:

- *BOON* applies integer range analysis to determine whether a C program can index an array outside its bounds.⁴ While capable of finding many errors that lexical analysis tools would miss, the checker is still imprecise: it ignores statement order, it can't model interprocedural dependencies, and it ignores pointer aliasing.
- Inspired by Perl's taint mode, *CQual* uses type qualifiers to perform a taint analysis, which detects format string vulnerabilities in C programs.⁵ *CQual* requires a programmer to annotate a few variables as either tainted or untainted and then uses type inference rules (along with pre-annotated system libraries) to propagate the qualifiers. Once the qualifiers are propagated, the system can detect format string vulnerabilities by type checking.
- The *xg++* tool uses a template-driven compiler extension to attack the problem of finding kernel vulnerabilities in the Linux and OpenBSD.⁶ It looks for locations where the kernel uses data from an untrusted source without checking it first, methods by which a user can cause the kernel to allocate memory and not free it, and situations in which a user could cause the kernel to deadlock.
- The *Eau Claire* tool uses a theorem prover to create a general

file access race conditions, and format string bugs. Developers can use specifications to ensure that function implementations behave as expected.

- *MOPS* takes a model-checking approach to look for violations of temporal safety properties.⁸ Developers can model their own safety properties, and some have used the tool to check for privilege management errors, incorrect construction of chroot jails, file access race conditions, and ill-conceived temporary file schemes.
- *Splint* extends the lint concept into the security realm.⁹ By adding annotations, developers can enable the tool to find abstraction violations, unannounced modifications to global variables, and possible use-before-initialization errors. *Splint* can also reason about minimum and maximum array bounds accesses if it is provided with function pre- and postconditions.

Many static analysis approaches hold promise, but have yet to be directly applied to security. Some of the more noteworthy ones include ESP (a large-scale property verification approach),¹⁰ model checkers such as SLAM and Blast (which use predicate abstraction to examine program safety properties),^{11,12} and FindBugs (a lightweight checker with a good reputation for unearthing common errors in Java programs).¹³

Several commercial tool vendors are starting to address the need for

Good static analysis tools must be easy to use, even for non-security people. This means that their results must be understandable to normal developers who might not know much about security and that they educate their users about good programming practice. Another critical feature is the kind of knowledge (the rule set) the tool enforces. The importance of a good rule set can't be overestimated.

In the end, good static checkers can help spot and eradicate common security bugs. This is especially important for languages such as C, for which a very large corpus of rules already exists. Static analysis for security should be applied regularly as part of any modern development process. □

References

1. D. Verndon and G. McGraw, "Risk Analysis in Software Design," *IEEE Security & Privacy*, vol. 2, no. 5, 2004, pp. 79–84.
2. G. McGraw, "Software Security," *IEEE Security & Privacy*, vol. 2, no. 2, 2004, pp. 80–83.
3. M. Bishop and M. Dilger, "Checking for Race Conditions in File Accesses," *Computing Systems*, vol. 9, no. 2, 1996, pp. 131–152.
4. D. Wagner et al., "A First Step Towards Automated Detection of Buffer Overrun Vulnerabilities," *Proc. 7th Network and Distributed System Security Symp. (NDSS 00)*, Internet Soc., 2000, pp. 3–17.
5. J. Foster, T. Terauchi, and A. Aiken, "Flow-Sensitive Type Qualifiers," *Proc. ACM Conf. Programming Language Design and Implementation (PLDI 02)*, ACM Press, 2002, pp. 1–12.
6. K. Ashcraft and D. Engler, "Using Programmer-Written Compiler Extensions to Catch Security Holes," *Proc. IEEE Symp. Security*

and Privacy, IEEE CS Press, 2002, pp. 131-147.

7. B. Chess, "Improving Computer Security using Extended Static Checking," *Proc. IEEE Symp. Security and Privacy*, IEEE CS Press, 2002, pp. 118-130.
8. H. Chen and D. Wagner, "MOPS: An Infrastructure for Examining Security Properties of Software," *Proc. 9th ACM Conf. Computer and Communications Security (CCS 02)*, ACM Press, 2002, pp. 235-244.
9. D. Larochelle and D. Evans, "Statically Detecting Likely Buffer Overflow Vulnerabilities," *Proc. 10th Usenix Security Symp.* (Usenix 01), Usenix Assoc., 2001, pp. 177-189.
10. M. Das, S. Lerner, and M. Seigle, "ESP: Path-Sensitive Program Ver-

ification in Polynomial Time," *Proc. ACM Conf. Programming Language Design and Implementation (PLDI 02)*, ACM Press, 2002, pp. 57-68.

11. T. Ball and S.K. Rajamani, "Automatically Validating Temporal Safety Properties of Interfaces," *Proc. 8th Int'l SPIN Workshop on Model Checking of Software*, LNCS 2057, Springer-Verlag, 2001, pp. 103-122.
12. T.A. Henzinger et al., "Software Verification with Blast," *Proc. 10th Int'l Workshop Model Checking of Software*, LNCS 2648, Springer-Verlag, 2003, pp. 235-239.
13. D. Hovemeyer and W. Pugh, "Finding Bugs is Easy," to appear in *Companion of the 19th Ann. ACM Conf. Object-Oriented Programming,*

Systems, Languages, and Applications, ACM Press, 2004.

Brian Chess is chief scientist at Fortify Software. His technical interests include static analysis, defect modeling, and Boolean satisfiability. He received a PhD in computer engineering from the University of California, Santa Cruz. Contact him at brian@fortifysoftware.com.

Gary McGraw is chief technology officer of Cigital. His real-world experience is grounded in years of consulting with major corporations and software producers. McGraw is the coauthor of *Exploiting Software* (Addison-Wesley, 2004), *Building Secure Software* (Addison-Wesley, 2001), *Java Security* (John Wiley & Sons, 1996), and four other books. He has a BA in philosophy from the University of Virginia and a dual PhD in computer science and cognitive science from Indiana University. Contact him at gem@cigital.com.


PURPOSE The IEEE Computer Society is the world's largest association of computing professionals, and is the leading provider of technical information in the field.

MEMBERSHIP Members receive the monthly magazine *Computer*, discounts, and opportunities to serve (all activities are led by volunteer members). Membership is open to all IEEE members, affiliate society members, and others interested in the computer field.

COMPUTER SOCIETY WEB SITE The IEEE Computer Society's Web site, at www.computer.org, offers information and samples from the society's publications and conferences, as well as a broad range of information about technical committees, standards, student activities, and more.

BOARD OF GOVERNORS
Term Expiring 2004: Jean M. Bacon, Ricardo Baeza-Yates, Deborah M. Cooper, George V. Cybenko, Harubisha Ichikawa, Thomas W. Williams, Yervant Zorian
Term Expiring 2005: Oscar N. Garcia, Mark A. Grant, Michel Israel, Stephen B. Seidman, Kathleen M. Swigger, Makoto Takizawa, Michael R. Williams
Term Expiring 2006: Mark Christensen, Alan Clements, Annie Combelles, Ann Gates, Susan Mengel, James W. Moore, Bill Schilit
Next Board Meeting: 11 Mar. 2005, Portland, OR

IEEE OFFICERS
President: ARTHUR W. WINSTON
President-Elect: W. CLEON ANDERSON
Past President: MICHAEL S. ADLER
Executive Director: DANIEL J. SENESE
Secretary: MOHAMED EL-HAWARY
Treasurer: PEDRO A. RAY
VP, Educational Activities: JAMES M. TIEN
VP, Pub. Services & Products: MICHAEL R. LIGHTNER
VP, Regional Activities: MARC T. APTER
VP, Standards Association: JAMES T. CARLO
VP, Technical Activities: RALPH W. WYNDRUM JR.
IEEE Division V Director: GENE F. HOFFNAGLE
IEEE Division VIII Director: JAMES D. ISAAK
President, IEEE-USA: JOHN W. STEADMAN



COMPUTER SOCIETY OFFICES

Headquarters Office
 1730 Massachusetts Ave. NW
 Washington, DC 20036-1992
 Phone: +1 202 371 0101
 Fax: +1 202 728 9614
 E-mail: hq.ofc@computer.org

Publications Office
 10662 Los Vaqueros Cir., PO Box 3014
 Los Alamitos, CA 90720-1314
 Phone: +1 714 821 8380
 E-mail: help@computer.org
Membership and Publication Orders:
 Phone: +1 800 272 6657
 Fax: +1 714 821 4641
 E-mail: help@computer.org

Asia/Pacific Office
 Watanabe Building
 1-4-2 Minami-Aoyama, Minato-ku
 Tokyo 107-0062, Japan
 Phone: +81 3 3408 3118
 Fax: +81 3 3408 3553
 E-mail: tokyo.ofc@computer.org



EXECUTIVE COMMITTEE

President:
 CARL K. CHANG*
*Computer Science Dept.
 Iowa State University
 Ames, IA 50011-1040
 Phone: +1 515 294 4377
 Fax: +1 515 294 0258
 c.chang@computer.org*
President-Elect: GERALD L. ENGEL*
Past President: STEPHEN L. DIAMOND*
VP, Educational Activities: MURALI VARANASI*
VP, Electronic Products and Services:
 LOWELL G. JOHNSON (1ST VP)*
VP, Conferences and Tutorials:
 CHRISTINA SCHOBERT†
VP, Chapters Activities:
 RICHARD A. KEMMERER (2ND VP)*
VP, Publications: MICHAEL R. WILLIAMS*
VP, Standards Activities: JAMES W. MOORE*
VP, Technical Activities: YERVANT ZORIAN*
Secretary: OSCAR N. GARCIA*
Treasurer: RANGACHAR KASTURI†
2004-2005 IEEE Division V Director:
 GENE F. HOFFNAGLE†
2003-2004 IEEE Division VIII Director:
 JAMES D. ISAAK†
2004 IEEE Division VIII Director-Elect:
 STEPHEN L. DIAMOND*
Computer Editor in Chief: DORIS L. CARVERT†
Executive Director: DAVID W. HENNAGE†
 * voting member of the Board of Governors
 † nonvoting member of the Board of Governors

EXECUTIVE STAFF

Executive Director: DAVID W. HENNAGE
Assoc. Executive Director: ANNE MARIE KELLY
Publisher: ANGELA BURGESS
Assistant Publisher: DICK PRICE
Director, Administration:
 VIOLET S. DOAN
Director, Information Technology & Services:
 ROBERT CARE