

IEEE JOURNAL OF EMERGING AND SELECTED TOPICS IN POWER ELECTRONICS

A PUBLICATION OF
THE IEEE POWER ELECTRONICS SOCIETY
THE IEEE INDUSTRY APPLICATIONS SOCIETY



SEPTEMBER 2020

VOLUME 8

NUMBER 3

IJESN2

(ISSN 2168-6777)

SPECIAL ISSUE ON TOPOLOGIES, MODELING METHODOLOGIES AND CONTROL TECHNIQUES FOR HIGH-FREQUENCY POWER CONVERSION

GUEST EDITORIAL

| | |
|---|------|
| Special Issue on Topologies, Modeling Methodologies, and Control Techniques for High-Frequency Power Conversion | 1967 |
| L. Corradini, G. Spiazzi, and Z. Zhang | |

SPECIAL ISSUE PAPERS

Topologies for High-Frequency Power Conversion

| | |
|--|------|
| Bus Converter Using Isolation Capacitance for ZVS and Invariant Operation | 1971 |
| S. Lim, A. J. Hanson, J. A. Santiago-González, and D. J. Perreault | |
| High-Frequency Bidirectional Resonant Converter for High Conversion Ratio and Variable Load Operation | 1983 |
| L. Gu, K. Surakitbovorn, G. Zulauf, S. Chakraborty, and J. Rivas-Davila | |
| High-Frequency and High-Efficiency Isolated Two-Stage Bidirectional DC–DC Converter for Residential Energy Storage Systems | 1994 |
| Y.-C. Liu, C. Chen, K.-D. Chen, Y.-L. Syu, and N. A. Dung | |
| Nonisolated High Step-Up Soft-Switching DC–DC Converter With Interleaving and Dickson Switched-Capacitor Techniques | 2007 |
| H. Lei, R. Hao, X. You, and F. Li | |
| Active Variable Reactance Rectifier—A New Approach to Compensating for Coupling Variations in Wireless Power Transfer Systems | 2022 |
| S. Sinha, A. Kumar, B. Regensburger, and K. K. Afridi | |
| A Hybrid Multioutput Divided Power Converter for LED Applications | 2041 |
| T. McRae, A. Prodić, S. Chakraborty, W. McIntyre, and A. Aguilar | |
| Analysis and Design of a Resonant Power Converter With a Wide Input Voltage Range for AC/DC Applications | 2056 |
| F. M. Spleid, A. M. Ammar, and A. Knott | |
| Analysis and Design of a Charge-Pump-Based Resonant AC–DC Converter With Inherent PFC Capability | 2067 |
| A. M. Ammar, F. M. Spleid, Y. Nour, and A. Knott | |
| <i>Control and Modeling Techniques</i> | |
| Flying Capacitor Voltage Programmed Mode Control for Switched-Capacitor Converters | 2082 |
| T. McRae, T. Souvignet, B. Eleftheriades, A. Prodić, and B. Allard | |
| Multi-Loop Control for Power Transfer Regulation in Capacitive Wireless Systems by Means of Variable Matching Networks ... | 2095 |
| E. Abramov and M. M. Peretz | |

(Contents Continued on Back Cover)



| | | |
|--|---|------|
| High-Switching-Frequency TCM Digital Control for Bidirectional-Interleaved Buck Converters Without Phase Error for Battery Charging | <i>Y.-C. Liu, Y.-L. Syu, N. A. Dung, C. Chen, K.-D. Chen, and K. A. Kim</i> | 2111 |
| A Backpropagation Neural Network-Based Explicit Model Predictive Control for DC–DC Converters With High Switching Frequency | <i>J. Chen, Y. Chen, L. Tong, L. Peng, and Y. Kang</i> | 2124 |
| A High-Frequency Power Factor Correction Stage With Low Output Voltage | <i>A. J. Hanson and D. J. Perreault</i> | 2143 |
| An Improved Linear Model for High-Frequency Class-DE Resonant Converter Using the Generalized Averaging Modeling Technique | <i>N. J. Dahl, A. M. Ammar, A. Knott, and M. A. E. Andersen</i> | 2156 |
| <i>Design Approaches for High-Frequency Converters</i> | | |
| A Method to Eliminate Discrete Inductors in a Class-E Inverter Used in Wireless Power Transfer Applications | <i>K. Surakitbovorn and J. M. Rivas-Davila</i> | 2167 |
| Design and Control of a GaN-Based, 13-Level, Flying Capacitor Multilevel Inverter | <i>C. B. Barth, P. Assem, T. Foulkes, W. H. Chung, T. Modeer, Y. Lei, and R. C. N. Pilawa-Podgurski</i> | 2179 |
| A Systematic Design Methodology for Series-Stacked Energy Decoupling Buffers Based on Loss–Volume Pareto Optimization | <i>Z. Liao, D. J. Lohan, N. C. Brooks, J. T. Allison, and R. C. N. Pilawa-Podgurski</i> | 2192 |
| Design Considerations for Hybrid, Energy-Efficient, and Fast Industrial Power Amplifiers With Supply Modulation | <i>V. Ž. Lazarević, M. Vasić, E. Boere, J. Eltze, and J. A. Cobos</i> | 2206 |
| High-Density Current-Transformer-Based Gate-Drive Power Supply With Reinforced Isolation for 10-kV SiC MOSFET Modules | <i>J. Hu, J. Wang, R. Burgos, B. Wen, and D. Boroyevich</i> | 2217 |
| Synchronous Rectifier for High-Frequency Switch-Mode Power Supplies Using Phase-Locked Loops | <i>J. C. Hertel, J. E. F. Overgaard, I. H. H. Jørgensen, T. M. Andersen, M. Rødgaard, and A. Knott</i> | 2227 |
| <i>Characterization of Active and Passive Components for High-Frequency Applications</i> | | |
| Experimental Characterization of Silicon and Gallium Nitride 200 V Power Semiconductors for Modular/Multi-Level Converters Using Advanced Measurement Techniques | <i>M. Guacci, J. Azurza Anderson, K. L. Pally, D. Bortis, J. W. Kolar, M. J. Kasper, J. Sanchez, and G. Deboy</i> | 2238 |
| A 48-V:16-V, 180-W Resonant Switched-Capacitor Converter With High-Q Merged Multiphase LC Resonator | <i>P. H. McLaughlin, P. A. Kyaw, M. H. Kiani, C. R. Sullivan, and J. T. Stauth</i> | 2255 |
| Effect of Class 2 Ceramic Capacitor Variations on Switched-Capacitor and Resonant Switched-Capacitor Converters | <i>J. Xu, L. Gu, and J. Rivas-Davila</i> | 2268 |
| Rapid Thermal Analysis of Nanocrystalline Inductors for Converter Optimization | <i>J. Scoltock, Y. Wang, G. Calderon-Lopez, and A. J. Forsyth</i> | 2276 |
| Numerical Methods for Event-Detection State Vector Simulation of Switched-Mode Power Supplies | <i>C. Reiman and E. Rosenbaum</i> | 2285 |
| <hr/> REGULAR PAPERS | | |
| A Fast-Response and High-Stability Power Supply for a Corrector Magnet in HALS | <i>Z. Shao, H. Zhang, H. Gao, P. Liu, G. Liu, and L. Wang</i> | 2293 |
| Topology and Control Method of a Single-Cell Matrix-Type Solid-State Transformer | <i>H. Wang, Y. Zhang, Y. Sun, M. Zheng, X. Liang, G. Zhang, K. Tan, and J. Feng</i> | 2302 |
| Two-Stage Parameter Design Methodology of a Generalized Resonant DC Transformer in Hybrid AC/DC Microgrid With Optimum Active Power Transmission | <i>J. Huang, X. Zhang, and C. Wen</i> | 2313 |
| An Integrated Semi-Double Stage-Based Multilevel Inverter With Voltage Boosting Scheme for Photovoltaic Systems | <i>S. Dhara and V. T. Somasekhar</i> | 2326 |
| Novel Multicarrier PWM Scheme for a Reconfigurable Single-Phase Inverter to Achieve Manifold Higher Effective Switching Frequency | <i>A. K. Gupta, M. S. Joshi, and V. Agarwal</i> | 2340 |
| Utilizing the Dead-Time Effect to Achieve Decentralized Reactive Power Sharing in Islanded AC Microgrids | <i>Y. Qi, J. Fang, and Y. Tang</i> | 2350 |
| Smart Lighting Systems as a Demand Response Solution for Future Smart Grids | <i>C. K. Lee, H. Liu, D. Fuhs, A. Kores, and E. Waffenschmidt</i> | 2362 |
| Reliable and Effective Ride-Through Controller Operation for Smart PV Systems Connected to LV Distribution Grid Under Abnormal Voltages | <i>H. Khan, S. J. Chacko, B. G. Fernandes, and A. Kulkarni</i> | 2371 |
| Support Vector Machine-Based Islanding and Grid Fault Detection in Active Distribution Networks | <i>H. R. Baghaee, D. Mlakić, S. Nikolovski, and T. Dragičević</i> | 2385 |
| A Configurable Virtual Impedance Method for Grid-Connected Virtual Synchronous Generator to Improve the Quality of Output Current | <i>Y. Hu, Y. Shao, R. Yang, X. Long, and G. Chen</i> | 2404 |
| A Design Method of Phase-Locked Loop for Grid-Connected Converters Considering the Influence of Current Loops in Weak Grid | <i>X. Li and H. Lin</i> | 2420 |
| Partially Rated Power Flow Control Converter Modeling for Low-Voltage DC Grids | <i>P. Purgat, N. H. van der Blij, Z. Qin, and P. Bauer</i> | 2430 |
| Harmonic Interaction Analysis of Delta-Connected Cascaded H-Bridge-Based Shunt Active Power Filter | <i>H. Wang and S. Liu</i> | 2445 |

| | | |
|--|---|------|
| Advanced Current-Droop Control for Storage Converters for Fault Ride-Through Enhancement | <i>H. Wang, Q. Zhang, D. Wu, and J. Zhang</i> | 2461 |
| A Systematic Approach to Extract State-Space Averaged Equations and Small-Signal Model of Partial-Power Converters | <i>A. Nabinejad, A. Rajaei, and M. Mardaneh</i> | 2475 |
| A Fault-Tolerant, Passivity-Based Controller Enhanced by the Equilibrium-to-Equilibrium Maneuver Capability for the DC-Voltage Power Port VSC in Multi-Infeed AC/DC Modernized Grids | <i>M. Davari, W. Gao, and F. Blaabjerg</i> | 2484 |
| Negative-Sequence Second-Order Circulating Current Injection for Hybrid MMC Under Over-Modulation Conditions | <i>P. Hu, R. Teodorescu, and J. M. Guerrero</i> | 2508 |
| Impedance-Based Analysis of Interconnected Power Electronics Systems: Impedance Network Modeling and Comparative Studies of Stability Criteria | <i>C. Zhang, M. Molinas, A. Rygg, and X. Cai</i> | 2520 |
| Modeling of the Phase Detector of a Synchronous-Reference-Frame Phase-Locked Loop Based on Second-Order Approximation | <i>Z.-X. Zou, R. Rosso, and M. Liserre</i> | 2534 |
| Comparison of Impedance Model and Amplitude-Phase Model for Power-Electronics-Based Power System | <i>Z. Yang, C. Mei, S. Cheng, and M. Zhan</i> | 2546 |
| Multi Objective Modulated Model Predictive Control of Stand-Alone Voltage Source Converters | <i>B. Majmunović, T. Dragičević, and F. Blaabjerg</i> | 2559 |
| Coordinated Control of Parallel DR-HVDC and MMC-HVDC Systems for Offshore Wind Energy Transmission | <i>R. Li, L. Yu, L. Xu and G. P. Adam</i> | 2572 |
| A Single Method for Multiple IGBT, Current, and Speed Sensor Faults Diagnosis in Regenerative PMSM Drives | <i>I. Jlassi and A. J. Marques Cardoso</i> | 2583 |
| Diagnosis of Multiple Open-Circuit Switch Faults Based on Long Short-Term Memory Network for DFIG-Based Wind Turbine Systems | <i>Z. Y. Xue, K. S. Xiahou, M. S. Li, T. Y. Ji, and Q. H. Wu</i> | 2600 |
| Principle of Torque Ripple Reduction in Synchronous Reluctance Motors With Shifted Asymmetrical Poles | <i>Q. Chen, Y. Yan, G. Xu, M. Xu, and G. Liu</i> | 2611 |
| Active Disturbance Rejection Control for Bearingless Induction Motor Based on Hyperbolic Tangent Tracking Differentiator | <i>Z. Yang, J. Ji, X. Sun, H. Zhu, and Q. Zhao</i> | 2623 |
| Assessment of Virtual-Voltage-Based Model Predictive Controllers in Six-Phase Drives Under Open-Phase Faults | <i>I. González-Prieto, M. J. Durán, M. Bermúdez, F. Barrero, and C. Martín</i> | 2634 |
| Computation Efficiency and Robustness Improvement of Predictive Control for PMS Motors | <i>M. Khalilzadeh and S. Vaez-Zadeh</i> | 2645 |
| Low Complexity Dual-Vector Model Predictive Current Control for Surface-Mounted Permanent Magnet Synchronous Motor Drives | <i>J. Chen, Y. Qin, A. M. Bozorgi, and M. Farasat</i> | 2655 |
| A Two-Degree-of-Freedom Internal Model-Based Active Disturbance Rejection Controller for a Wind Energy Conversion System | <i>S. Das and B. Subudhi</i> | 2664 |
| Coil Layout Optimization for Maximizing the Power Transfer Efficiency of Wireless Power Transfer Systems With Multiple Transmitter Coils | <i>S. B. Lee and I. G. Jang</i> | 2672 |
| Magnetic Core Solenoid Power Inductors on Organic Substrate for System-in-Package Integrated High-Frequency Voltage Regulators | <i>M. L. F. Bellaredj, A. Kavungal Davis, P. Kohl, and M. Swaminathan</i> | 2682 |
| Magnetizable Concrete Flux Concentrators for Wireless Inductive Power Transfer Applications | <i>C. Carretero, I. Lope, and J. Acero</i> | 2696 |
| Parameter Design Method With Constant Output Voltage Characteristic for Bilateral LC-Compensated CPT System | <i>X.-D. Qing, Z.-H. Wang, Y.-G. Su, Y.-M. Zhao, and X.-Y. Wu</i> | 2707 |
| Dielectric Losses in Dry-Type Insulation of Medium-Voltage Power Electronic Converters | <i>T. Guillod, R. Faerber, D. Rothmund, F. Krismer, C. M. Franck, and J. W. Kolar</i> | 2716 |
| Implementation of a Novel Hybrid UPQC Topology Endowed With an Isolated Bidirectional DC-DC Converter at DC link | <i>T. Koroglu, A. Tan, M. M. Savrun, M. U. Cuma, K. C. Bayindir, and M. Tumay</i> | 2733 |
| Ultrahigh-Step-Up Nonisolated Interleaved Boost Converter | <i>M. Shaneh, M. Niroomand, and E. Adib</i> | 2747 |
| Investigation of the Root Causes of Electromagnetic Noise of an Interleaved DC-DC Converter With GaN or Si Transistors and Corresponding Optimization Strategies | <i>L. Middelstaedt, B. Strauss, A. Chupryn, and A. Lindemann</i> | 2759 |
| A High Voltage-Gain Bidirectional DC-DC Converter With Full-Range ZVS Using Decoupling Control Strategy | <i>J. Zeng, Z. Yan, J. Liu, and Z. Huang</i> | 2775 |
| A New Single-Switch Structure of a DC-DC Converter With Wide Conversion Ratio for Fuel Cell Vehicles: Analysis and Development | <i>N. Elsayad, H. Moradisizkoochi, and O. A. Mohammed</i> | 2785 |
| A Self-Sustained Circuit Building Block Based on 10-kV Silicon Carbide Devices for High-Voltage Applications | <i>B. Hu, Z. Wei, H. Li, D. Xing, M. J. Scott, R. Na, and J. Wang</i> | 2801 |
| A High-Efficiency DC/DC Converter for High-Voltage-Gain, High-Current Applications | <i>Y. Qin, Y. Yang, S. Li, Y. Huang, S.-C. Tan, and S. Y. Hui</i> | 2812 |
| Improved Large DC Gain Converters With Low Voltage Stress on Switches Based on Coupled-Inductor and Voltage Multiplier for Renewable Energy Applications | <i>M. Chen, C. Yin, P. C. Loh, and A. Ioinovici</i> | 2824 |
| A Digital Control Scheme for PSR Flyback Converter in CCM and DCM | <i>S. Xu, Q. Shen, C. Wang, D. Ding, and W. Sun</i> | 2837 |

| | | |
|---|--|------|
| Investigation of Self-Output Voltage Balancing in Input-Parallel Output-Series DC–DC Converter | <i>S. Kim, H.-T. Nam, H. Cha, and H.-G. Kim</i> | 2850 |
| A Novel Current Injection DC Circuit Breaker Integrating Current Commutation and Energy Dissipation | <i>Y. Wu, Y. Wu, F. Yang, M. Rong, and Y. Hu</i> | 2861 |
| A New Three-Level Neutral-Point-Clamped Fifteen-Switch Inverter for Independent Control of Two Three-Phase Loads | <i>L. Pan, J. Zhang, J. Zhang, K. Wang, Y. Pang, and B. Wang</i> | 2870 |
| Generalized Topology of a Hybrid Switched-Capacitor Multilevel Inverter for High-Frequency AC Power Distribution | <i>Y. C. Fong, S. R. Raman, Y. Ye, and K. W. E. Cheng</i> | 2886 |
| An Indirect Approach to Control an Active Capacitor | <i>J. Lin and G. Weiss</i> | 2898 |
| Simplified Model Predictive Control for AC/DC Matrix Converters With Active Damping Function Under Unbalanced Grid Voltage | <i>T.-L. Nguyen and H.-H. Lee</i> | 2907 |
| Common-Mode Voltage Reduction With Improved Output Voltage for Three-to-Five-Phase Indirect Matrix Converters | <i>G. Zhang, H. Wang, Y. Yang, M. Su, C. Zhang, and F. Blaabjerg</i> | 2918 |
| A Family of Improved Dual-Buck DC–AC Inverters and Dual-Boost AC–DC Converters | <i>U. A. Khan, H. Cha, J.-W. Park, A. A. Khan, and W. Eberle</i> | 2930 |
| Finite-Control-Set Model Predictive Control of Modular Multilevel Converters With Cascaded Open-Circuit Fault Ride-Through | <i>D. Zhou, P. Tu, H. Qiu, and Y. Tang</i> | 2943 |
| Enhanced Modular Multilevel Converter With Reduced Number of Cells and Harmonic Content | <i>D. Vozikis, G. P. Adam, P. Rault, O. Despouys, D. Holliday, and S. J. Finney</i> | 2954 |
| An Active Impedance-Source Three-Level T-Type Inverter With Reduced Device Count ... | <i>M.-K. Nguyen, T.-T. Tran, and F. Zare</i> | 2966 |
| Single-Phase Voltage Source Inverter With Voltage Boosting and Power Decoupling Capabilities ... | <i>S. Xu, L. Chang, and R. Shao</i> | 2977 |
| Inclusive Design and Development of Front-End Multiphase Rectifier With Reduced Magnetic Rating and Improved Efficiency | <i>P. S. Prakash, R. Kalpana, and B. Singh</i> | 2989 |
| Low-Voltage Sub-Nanosecond Pulsed Current Driver IC for High-Speed LIDAR Applications | <i>E. Abramov, M. Evzelman, and M. M. Peretz</i> | 3001 |
| Control of Three-Phase Solid-State Transformer With Phase-Separated Configuration for Minimized Energy Storage Capacitors | <i>T. Isobe, R. A. Barrera-Cardenas, Z. He, Y. Zou, K. Terazono, and H. Tadano</i> | 3014 |
| A PWM Scheme for a Fault-Tolerant Three-Level Quasi-Switched Boost T-Type Inverter | <i>D.-T. Do, M.-K. Nguyen, T.-H. Quach, V.-T. Tran, F. Blaabjerg, and D. M. Vilathgamuwa</i> | 3029 |
| Enhanced-Boost Bidirectional Quasi-Z-Source Inverter With Novel Active Switched Inductor Cells | <i>X. Pan, Z. Pang, Y. Liu, S. Yin, and C. Ju</i> | 3041 |
| DC Faults Ride-Through and Fast Recovery of MVDC System Based on Improved HB-MMC | <i>B. Li, H. Liu, W. Wen, H. Cao, X. Wang, and H. Lv</i> | 3056 |
| A Circuit Analysis-Based Fault Finding Algorithm for Photovoltaic Array Under L–L/L–G Faults | <i>A. F. Murtaza, M. Bilal, R. Ahmad, and H. A. Sher</i> | 3067 |
| A Comprehensive Suppression Strategy for Common Ground Circulating Current Caused by Grounding Fault in PV Modules ... | <i>Y. Zhang, M. Yu, Y. Xia, and W. Wei</i> | 3077 |
| A Soft-Switched Power Module With Integrated Battery Interface for Photovoltaic-Battery Power Architecture | <i>S. Moury and J. Lam</i> | 3090 |
| Mitigation of Leakage-Ground Currents in Transformerless Grid-Tied Inverters via Virtual-Ground Connection | <i>G. Escobar, P. R. Martinez-Rodriguez, S. Iturriaga-Medina, J. C. Mayo-Maldonado, J. Lopez-Sarabia, and O. M. Micheloud-Vernackt</i> | 3111 |
| Parallel Resonant DC Link Inverter Topology and Analysis of Its Operation Principle | <i>E. Chu, H. Xie, Z. Chen, J. Bao, Y. Zhou, and H. Zhang</i> | 3124 |
| A Resonant Switched-Capacitor Converter With GaN Transistors for High-Efficiency Power Delivery to Series-Stacked Processors | <i>A. Stillwell and R. C. N. Pilawa-Podgurski</i> | 3139 |
| A Series Resonant Energy Storage Cell Voltage Balancing Circuit | <i>Y. Yu, R. Saasaa, A. A. Khan, and W. Eberle</i> | 3151 |
| Lifting-Off of Al Bonding Wires in IGBT Modules Under Power Cycling: Failure Mechanism and Lifetime Model | <i>Y. Huang, Y. Jia, Y. Luo, F. Xiao, and B. Liu</i> | 3162 |
| High Step-Up Y-Source Coupled-Inductor Impedance Network Boost DC–DC Converters With Common Ground and Continuous Input Current | <i>Y. Ji, H. Liu, Y. Feng, F. Wu, and P. Wheeler</i> | 3174 |
