

Received April 19, 2020, accepted May 4, 2020, date of publication May 8, 2020, date of current version May 20, 2020.

Digital Object Identifier 10.1109/ACCESS.2020.2993265

# Integral Reinforcement Learning Control for a Class of High-Order Multivariable Nonlinear Dynamics With Unknown Control Coefficients

QINGLING WANG<sup>1</sup>, (Senior Member, IEEE)

School of Automation, Southeast University, Nanjing 210096, China

e-mail: csuwql@gmail.com

This work was supported in part by the Science and Technology on Information System Engineering Laboratory under Grant 05201902, and in part by the Fundamental Research Funds for the Central Universities.

**ABSTRACT** This paper develops an integral reinforcement learning (IRL) controller for a class of high-order multivariable nonlinear systems with unknown control coefficients (UCCs). A new long-term performance index is first presented, and then the critic neural network (NN) and the action NN are presented to estimate the unobtainable long-term performance index and the unknown drift of systems, respectively. By combining the critic and action NNs with Nussbaum-type functions, the IRL controllers for high-order, nonsquare multivariable systems are proposed to cope with the problem of UCCs. The analysis is given to illustrate that the stability of the closed-loop system can be obtained, and the signals of the closed-loop systems are semiglobally uniformly ultimately bounded (UUB). Finally, one simulation example is provided to show the effectiveness of the proposed IRL controllers.

**INDEX TERMS** Nussbaum-type functions, integral reinforcement learning, unknown control coefficients, nonsquare multivariable systems.

## I. INTRODUCTION

Adaptive control of multivariable systems has attracted significant attention in the last several decades, where the design of control laws is much more challenging than the single-input systems due to the dynamic couplings of the high-frequency gain matrix [1], [2]. In general, the high-frequency gain matrix of these works are known in advance to design controllers. However, some practical systems can not possess the knowledge of the high-frequency gain matrix in priori, see for example, in [3]–[5]. Hence, one of fundamental problems of multivariable systems is how to deal with the unknown high-frequency gain matrix known as UCCs, which makes the extension from single-input systems to multivariable systems far from trivial.

To address the problem of UCCs, one of effective methods is employing Nussbaum-type functions, which was first proposed in [6] to deal with single-input systems with UCCs, and then extended to deal with various single-input dynamics [7]–[10]. However, when multiple control inputs

with UCCs are considered, i.e., in multivariable systems, one critical challenge is how to deal with the problem of multiple Nussbaum-type functions, where the effects of Nussbaum-type functions may counteract each other. Attempts to cope with this problem, the work of [11] proposed an adaptive control scheme for the strict-feedback system, where a new designed Nussbaum-type function was introduced to allow multiple Nussbaum-type functions in a single inequality. However, the method of [11] still cannot be directly extended to multivariable systems. Furthermore, the authors in [12] suggested to construct a partial Lyapunov function for each control input where only one Nussbaum-type function exists. Inspired by this idea, some extended results were applied to multi-agent systems with UCCs [13]–[15]. Although the whole multi-agent system can be regarded as a multivariable system, it still needs more efforts to make an extension to the case of general multivariable systems. To completely solve this issue, the work of [16] designed a novel adaptive control algorithm for uncertain multivariable systems with UCCs by using the backstepping control technique. In addition to employ Nussbaum-type functions, there are some other methods to

The associate editor coordinating the review of this manuscript and approving it for publication was Leo Chen.

deal with the problem of UCCs, such as nonlinear PI functions in [17]–[21], switching and monitoring functions in [22] and the logic-based switching mechanism in [23], [24].

Recently, along with the advantage of the IRL technique, the long-term performance index was widely adopted to evaluate the control performance of control systems, see for example, in [25]–[28]. Along with the IRL technique, adaptive controllers were designed in [29] for tracking control of second-order, square multivariable dynamics with UCCs, where a long-term performance index was adopted and the Nussbaum-type function was used to deal with the problem of UCCs. Nevertheless, the results of [29] focused on the tracking control problem of second-order, square multi-input multi-output (MIMO) systems. However, extending the current results in [29] to the case of high-order, nonsquare multivariable systems subject to UCCs by employing the IRL technique is still an unsolved and challenging problem.

Based on the analysis of the previous literature, the aim of this work is to present an IRL controller for a class of high-order multivariable nonlinear systems with UCCs. The long-term performance index will be first presented, and then the critic and action NNs are designed to estimate the unobtainable long-term performance index and the unknown drift of systems, respectively. Combined with Nussbaum-type functions, we can design IRL controllers for high-order, nonsquare multivariable systems to cope with the problem of UCCs. It is shown that all signals of the corresponding closed-loop systems are semiglobally UUB. The contributions of this paper are presented as follows.

- 1) This study first proposes a new long-term performance index. Different from the existing long-term performance index in [29], [30], where a small threshold should be designed, in this paper, the small threshold is not necessary.
- 2) Compared with the existing result [29], where the IRL controller is designed for tracking control of second-order, square MIMO dynamics, in this paper, the obtained results are generalized to high-order, nonsquare multivariable systems with UCCs.

We organize the rest of this study in the following. Preliminaries and the problem of this study is presented in Section II, while Section III mainly presents the IRL control laws for high-order, nonsquare multivariable systems with UCCs. One example is provided to show the effectiveness of proposed results in Section IV, and Section V gives the conclusion.

## II. PRELIMINARIES AND PROBLEM FORMULATION

*Notation:* The notation  $I$  denotes an identity matrix with compatible dimensions.  $\mathcal{L}_\infty$  denotes the bounded signals. For a vector  $a$ ,  $\|a\|$  is the Euclidean norm.  $\|A\|_F$  denotes the Frobenius norm for matrix  $A$ .  $\lambda_{\min}(\cdot)$  and  $\lambda_{\max}(\cdot)$  denote the minimum and maximum eigenvalues.

### A. PRELIMINARIES

*Definition 1* [6]: A function  $N(\cdot)$  is the Nussbaum-type function if

$$\begin{cases} \lim_{k \rightarrow \infty} \sup \left( \frac{1}{k} \int_0^k N(\tau) d\tau \right) = +\infty \\ \lim_{k \rightarrow \infty} \inf \left( \frac{1}{k} \int_0^k N(\tau) d\tau \right) = -\infty. \end{cases} \quad (1)$$

*Lemma 1* [31]: Suppose  $V(\cdot)$  and  $k(\cdot)$  are smooth functions over  $[0, t_f)$  satisfying  $V(t) \geq 0 \forall t \in [0, t_f)$ ,  $N(\cdot)$  is the Nussbaum-type function, and  $\phi$  is some nonzero constant. If we have

$$V(t) \leq \int_0^t (\phi N(k(\tau)) + 1) \dot{k}(\tau) d\tau + c, \quad \forall t \in [0, t_f) \quad (2)$$

where  $c \in \mathbb{R}$  is a constant, then  $V(t)$ ,  $k(t)$  and  $\int_0^t (\phi N(k(\tau)) + 1) \dot{k}(\tau) d\tau$  are bounded on  $[0, t_f)$ .

We will present some basic knowledge on radial basis function neural network (RBFNN), and by which we can approximate any continuous nonlinear functions. In view of [32], we can use the RBFNN to approximate a continuous function  $h(x) : \mathbb{R}^q \rightarrow \mathbb{R}$  by

$$h_{nn}(x) = W^T \Psi(x), \quad (3)$$

where  $x \in \Omega_x \subset \mathbb{R}^q$  is the vector of input,  $W \in \mathbb{R}^l$  is the vector of weight,  $l \geq 1$  is the node number of neural network, and  $\Psi(x) = [\psi_1(x), \psi_2(x), \dots, \psi_l(x)]^T$  with  $\psi_i(x)$ ,  $i = 1, 2, \dots, l$  being the Gaussian function as

$$\psi_i(x) = \exp \left[ \frac{-(x - \bar{\mu}_i)^T (x - \bar{\mu}_i)}{\eta_i^2} \right], \quad (4)$$

where  $\bar{\mu}_i = [\mu_{i1}, \mu_{i2}, \dots, \mu_{iq}]^T$  is the center of receptive field and  $\eta_i$  is the width of the Gaussian function. It is known [33] that if  $l$  is sufficiently large, (3) can approximate any continuous nonlinear functions on  $\Omega_x \subset \mathbb{R}^q$  with any accuracy

$$h(x) = W^{*T} \Psi(x) + \epsilon, \quad \forall x \in \Omega_x, \quad (5)$$

where the ideal weight is  $W^*$  and  $\epsilon$  is the approximation error. Furthermore, there exist ideal unknown, constant weights  $W^*$  such that  $|\epsilon| \leq \epsilon^*$  with constant  $\epsilon^* > 0$  for all  $x \in \Omega_x$ . Furthermore, let  $\hat{W}$  be the estimate of  $W^*$ , then the weight estimation error can be defined as  $\tilde{W} = \hat{W} - W^*$ .

In order to derive main results of this study, the following lemmas are needed:

*Lemma 2* [29]: For any two matrices  $A = (a_{ij})_{m \times n} \in \mathbb{R}^{m \times n}$  and  $B = (b_{ij})_{m \times n} \in \mathbb{R}^{m \times n}$ , one has  $\text{tr}(A^T B) \leq \|A\|_F \|B\|_F$ . Furthermore, it is known that  $\text{tr}(A^T A) = \|A\|_F^2$  and  $\|A^T B\|_F \leq \|A\|_F \|B\|_F$ . For any  $a \in \mathbb{R}^n$  and  $b \in \mathbb{R}^n$ , one has  $\|a^T b\|_F \leq \|a\| \|b\|$  and  $\|Aa\|_F \leq \|A\|_F \|a\|$ .

*Lemma 3* [34]: Let  $S \in \mathbb{R}^{m \times m}$  be a matrix, and  $x \in \mathbb{R}^m$  is a nonzero vector. If we define  $\kappa = \frac{x^T S x}{x^T x}$ , then at least one eigenvalue of matrix  $S$  is in  $(-\infty, \kappa]$  and at least one in  $[\kappa, +\infty)$ .

## B. PROBLEM FORMULATION

Consider a continuous-time high-order nonlinear system with  $n$ th-order ( $n \geq 1$ ) as

$$\dot{x}^{(n)}(t) = f(\bar{x}(t)) + g(\bar{x}(t))u(t) + d(t) \quad (6)$$

where  $\bar{x}(t) = [x(t), \dot{x}(t), \dots, x^{(n-1)}(t)]^T$  with  $x(t) \in \mathbb{R}^k$ ,  $x^{(m)}(t) \in \mathbb{R}^k$ ,  $m = 1, 2, \dots, n-1$  being the  $m$ th derivative of the system state. The smooth function  $f(\bar{x}(t)) \in \mathbb{R}^k$  represents an unknown nonlinear drift,  $g(\bar{x}(t)) \in \mathbb{R}^{k \times l}$  ( $k \leq l$ ) is the high-frequency gain,  $d(t) \in \mathbb{R}^k$  is the unknown, bounded disturbance, and  $u(t) \in \mathbb{R}^l$  represents the control input.

The aim is to design IRL controllers for high-order nonlinear system (6) such that the stability is guaranteed, i.e.,

$$\begin{cases} \lim_{t \rightarrow \infty} x(t) = 0_{k \times 1} \\ \lim_{t \rightarrow \infty} x^{(m)}(t) = 0_{k \times 1} \end{cases} \quad (7)$$

for  $m = 1, 2, \dots, n-1$ . Furthermore, all the signals of the closed-loop system are semiglobally UUB.

## III. MAIN RESULTS

In this section, we present IRL controllers for the high-order nonlinear system with UCCs. To facilitate the design procedure, we first introduce the following state variables,

$$\begin{aligned} \varpi(t) &= \left( \beta + \frac{d}{dt} \right)^{n-1} x(t) \\ &= C_{n-1}^0 \beta^{n-1} x(t) + C_{n-1}^1 \beta^{n-2} \dot{x}(t) \\ &\quad + \dots + C_{n-1}^{n-2} \beta x^{(n-2)}(t) + C_{n-1}^{n-1} x^{(n-1)}(t) \end{aligned} \quad (8)$$

and

$$\begin{aligned} \vartheta(t) &= C_{n-1}^0 \beta^{n-1} \dot{x}(t) + C_{n-1}^1 \beta^{n-2} \ddot{x}(t) + \dots \\ &\quad + C_{n-1}^{n-3} \beta^2 x^{(n-2)}(t) + C_{n-1}^{n-2} \beta x^{(n-1)}(t), \end{aligned} \quad (9)$$

where  $\beta > 0$  is a constant, and  $C_i^j$ 's are coefficients of the binomial expansion.

In what follows, the following assumption is needed.

**Assumption 1:** The matrix  $g(\bar{x}(t))$  is nonsquare and partially unknown with

$$g(\bar{x}(t)) = g_0(\bar{x}(t))g_u(\bar{x}(t)), \quad (10)$$

where the matrix  $g_0(\bar{x}(t)) \in \mathbb{R}^{k \times l}$  is known, bounded with full row rank, and the matrix  $g_u(\bar{x}(t)) \in \mathbb{R}^{l \times l}$  is unknown. Furthermore, the matrix  $g_0(\bar{x}(t)) [g_u(\bar{x}(t)) + g_u^T(\bar{x}(t))] g_0^T(\bar{x}(t))$  is either positive or negative definite.

According to Lemma 3 with Assumption 1, we have

$$\begin{aligned} \rho(t) \|\varpi(t)\|^2 &= \frac{1}{2 \|g_0(\bar{x}(t))\|} \varpi^T(t) g_0(\bar{x}(t)) \\ &\quad \times \left( g_u^T(\bar{x}(t)) + g_u(\bar{x}(t)) \right) g_0^T(\bar{x}(t)) \varpi(t) \end{aligned} \quad (11)$$

where  $\lambda_{\min}(t) \leq \rho(t) \leq \lambda_{\max}(t)$ ,  $\lambda_{\min}(t)$  and  $\lambda_{\max}(t)$  are respectively the minimum and maximum eigenvalues of matrix  $\frac{1}{2 \|g_0(\bar{x}(t))\|} g_0(\bar{x}(t)) (g_u^T(\bar{x}(t)) + g_u(\bar{x}(t))) g_0^T(\bar{x}(t))$ , and  $\varpi(t)$  is defined in (8). From Assumption 1 and the definition of (11), we know that the sign of  $\rho(t)$  is nonzero, constant but unknown.

## 1) CRITIC NN DESIGN

A long-term performance index is proposed as

$$J_s(t) = \int_t^\infty \gamma^{\frac{t-\tau}{T}} p(\varpi(\tau)) d\tau, \quad (12)$$

where  $p(\varpi(\tau)) = [p(\varpi_1(\tau)), p(\varpi_2(\tau)), \dots, p(\varpi_k(\tau))]^T$  with  $p(\varpi_i(\tau)) = \tanh(\varpi_i^2(\tau))$ . To construct the Bellman error for system (6), we define

$$\begin{aligned} J_s(t-T) &= \int_{t-T}^\infty \gamma^{\frac{t-T-\tau}{T}} p(\varpi(\tau)) d\tau \\ &= \gamma^{-1} J_s(t) + \gamma^{-1} \int_{t-T}^t \gamma^{\frac{t-\tau}{T}} p(\varpi(\tau)) d\tau \\ &= \gamma^{-1} (J_s(t) + p_{sc}) \end{aligned} \quad (13)$$

with

$$p_{sc} = \int_{t-T}^t \gamma^{\frac{t-\tau}{T}} p(\varpi(\tau)) d\tau, \quad (14)$$

where  $p_{sc}$  represents the value cost on  $[t-T, t)$ . It is known that  $p_{sc} = [p_{sc1}, p_{sc2}, \dots, p_{sc_k}]^T$  with  $p_{sc_i} = \int_{t-T}^t \gamma^{\frac{t-\tau}{T}} \tanh(\varpi_i^2(\tau)) d\tau \leq \int_{t-T}^t \gamma^{\frac{t-\tau}{T}} d\tau = \frac{T}{\ln \gamma} (\gamma - 1)$ , which implies  $\|p_{sc}\| \leq d_{p_{sc}}$  with a positive constant  $d_{p_{sc}}$ . Furthermore, it is seen from (12) that  $J_s(t)$  contains future dynamical information. Then, the RBFNN is adopted to approximate it, i.e.,

$$J_s(t) = W_{sc}^{*T} \Psi_{sc}(x_{sc}(t)) + \epsilon_{sc}(x_{sc}(t)), \quad \forall x_{sc} \in \Omega_{x_{sc}}, \quad (15)$$

where the bounded ideal weight is  $W_{sc}^*$  satisfying  $\|W_{sc}^*\|_F \leq d_{W_{sc}}$ , the RBF vector  $\Psi_{sc}(x_{sc}(t))$  is bounded with  $\|\Psi_{sc}(x_{sc}(t))\| \leq d_{\Psi_{sc}}$ , and the approximation error  $\epsilon_{sc}(x_{sc}(t))$  is bounded with  $\|\epsilon_{sc}(x_{sc}(t))\| < d_{\epsilon_{sc}}$ . In general, the weight  $W_{sc}^*$  is unknown. Therefore, we have to estimate  $J_s(t)$  by

$$\hat{J}_s(t) = \hat{W}_{sc}^T \Psi_{sc}(x_{sc}(t)) \quad (16)$$

and  $J_s(t-T)$  is estimated by

$$\hat{J}_s(t-T) = \hat{W}_{sc}^T \Psi_{sc}(x_{sc}(t-T)), \quad (17)$$

where  $x_{sc}(t) = \bar{x}(t)$ . In what follows, we design the updated law of weight  $\hat{W}_{sc}$ . A difference error of the long-term performance index is defined as

$$\begin{aligned} e_{sc} &= \hat{J}_s(t) - \gamma \hat{J}_s(t-T) + p_{sc} \\ &= \hat{W}_{sc}^T \Delta \Psi_{sc}(t) + p_{sc} + W_{sc}^{*T} \Delta \Psi_{sc}(t), \end{aligned} \quad (18)$$

where  $\Delta \Psi_{sc}(t) = \Psi_{sc}(x_{sc}(t)) - \gamma \Psi_{sc}(x_{sc}(t-T))$  and  $\tilde{W}_{sc} = \hat{W}_{sc} - W_{sc}^*$ . Then,  $\hat{W}_{sc}$  is updated by

$$\dot{\hat{W}}_{sc} = -\Pi_{sc} \Delta \Psi_{sc}(t) \left[ \hat{W}_{sc}^T \Delta \Psi_{sc}(t) + p_{sc} \right]^T - \delta_{sc} \Pi_{sc} \hat{W}_{sc}, \quad (19)$$

where  $\Pi_{sc} > 0$  and  $\delta_{sc} > 0$  is to be prescribed. The first term of (19) is to minimize the critic error  $\|e_{sc}\|$ , and the second term is a modification term to make (19) robust to the disturbances [35].

2) ACTION NN DESIGN

To design the action NN, the RBFNN is first established to approximate the unknown function  $f(\bar{x}(t))$ , i.e.,

$$f(\bar{x}(t)) = W_{sa}^{*T} \Psi_{sa}(x_{sa}(t)) + \epsilon_{sa}(t), \quad \forall x_{sa} \in \Omega_{x_{sa}}, \quad (20)$$

where the ideal weight is  $W_{sa}^*$  satisfying  $\|W_{sa}^*\|_F \leq d_{W_{sa}}$ , the RBF vector  $\Psi_{sa}(x_{sa}(t))$  satisfies  $\|\Psi_{sa}(x_{sa}(t))\| \leq d_{\Psi_{sa}}$ , and  $\epsilon_{sa}(t)$  with  $\|\epsilon_{sa}(x_{sa}(t))\| < d_{\epsilon_{sa}}$  is the approximation error. Since the weight  $W_{sa}^*$  is unknown, we must estimate  $f(\bar{x}(t))$  by

$$\hat{f}(\bar{x}(t)) = \hat{W}_{sa}^T \Psi_{sa}(x_{sa}(t)), \quad (21)$$

where  $x_{sa}(t) = \bar{x}(t)$ . Next, we design the updated law of weight  $\hat{W}_{sa}$ . The aim of designing the action NN is to let  $\varpi(t)$  and  $J_s(t)$  approach to zero, which implies the state  $x(t)$  and its derivatives  $x^{(m)}(t)$ ,  $m = 1, 2, \dots, n - 1$  converge to zero. In this way, we define the action error as

$$e_{sa} = \varpi(t) + \hat{J}_s(t) = \varpi(t) + \hat{W}_{sc}^T \Psi_{sc}(x_{sc}(t)). \quad (22)$$

Then,  $\hat{W}_{sa}$  is undated by

$$\dot{\hat{W}}_{sa} = \Pi_{sa} \Psi_{sa}(x_{sa}(t)) \left[ \varpi(t) + \hat{W}_{sc}^T \Psi_{sc}(x_{sc}(t)) \right]^T - \delta_{sa} \Pi_{sa} \hat{W}_{sa}, \quad (23)$$

where  $\Pi_{sa} > 0$  and  $\delta_{sa} > 0$  is to be designed. Define  $\tilde{W}_{sa} = \hat{W}_{sa} - W_{sa}^*$ . Similarly, the first term of (23) is to minimize the action error  $\|e_{sa}\|$ , and the second term is a modification term to make (23) robust to the disturbances [35].

Based on the above critic and action NNs, the IRL controller for nonsquare multivariable systems with UCCs can be proposed as

$$u(t) = N(\chi(t)) \frac{g_0^T(\bar{x}(t)) \varpi(t) \varpi^T(t) \bar{u}(t)}{\|g_0(\bar{x}(t))\| \|\varpi(t)\|^2} \quad (24)$$

with

$$\begin{cases} \dot{\chi}(t) = \varpi^T(t) \bar{u}(t) \\ \bar{u}(t) = \xi(t) + \vartheta(t) + \hat{W}_{sa}^T \Psi_{sa}(x_{sa}(t)) \end{cases} \quad (25)$$

and

$$\begin{cases} \xi(t) = \varphi(t) \tanh(\varpi(t) \lambda_t) + \varpi(t) \\ \dot{\varphi}(t) = \varpi^T(t) \tanh(\varpi(t) \lambda_t), \end{cases} \quad (26)$$

where  $\lambda_t = 1 + t^2$ , and  $\tanh(\cdot)$  is the hyperbolic tangent function. Then, the stability results for the controller (24) are summarized as follows:

*Theorem 1:* Consider a continuous-time nonsquare multivariable system with UCCs given in (6) satisfying Assumption 1. The IRL controller (24), (25) and (26) with the critic NN (16) and (19), and the action NN (21) and (23) can achieve the objective (7) if the designed parameters are properly chosen, i.e.,

$$\begin{cases} \delta_{sa} \geq d_{\Psi_{sa}}^2 \\ \delta_{sc} \geq d_{\Psi_{sc}}^2 \end{cases} \quad (27)$$

Furthermore, all signals of the closed-loop system are semiglobally UUB.

*Proof:* Considering the following positive definite function

$$V_s(t) = \frac{1}{2} \varpi^T(t) \varpi(t) + \frac{1}{2} \text{tr} \left( \tilde{W}_{sa}^T(t) \Pi_{sa}^{-1} \tilde{W}_{sa}(t) \right) + \frac{1}{2} \text{tr} \left( \tilde{W}_{sc}^T(t) \Pi_{sc}^{-1} \tilde{W}_{sc}(t) \right) + \frac{1}{2} \tilde{\varphi}^2(t), \quad (28)$$

where we have defined  $\tilde{W}_{sa}(t) = \hat{W}_{sa}(t) - W_{sa}^*$ ,  $\tilde{W}_{sc}(t) = \hat{W}_{sc}(t) - W_{sc}^*$ ,  $\tilde{\varphi}(t) = \varphi(t) - (D + d_{\epsilon_{sa}})$  and  $D > 0$  is the unknown upper bound of the two-norm of  $\|d(t)\|$ . Furthermore, the elements of vector  $\varpi(t)$  are defined as  $\varpi_i(t)$  for  $i = 1, 2, \dots, k$ .

Let define  $V_1(t) = \frac{1}{2} \varpi^T(t) \varpi(t) + \frac{1}{2} \tilde{\varphi}^2(t)$ ,  $V_2(t) = \frac{1}{2} \text{tr}(\tilde{W}_{sa}^T(t) \Pi_{sa}^{-1} \tilde{W}_{sa}(t))$  and  $V_3(t) = \frac{1}{2} \text{tr}(\tilde{W}_{sc}^T(t) \Pi_{sc}^{-1} \tilde{W}_{sc}(t))$ . By employing (24), (25) and (26) with the critic NN (16) and (19), and the action NN (21) and (23), we have

$$\begin{aligned} \dot{V}_1(t) &= \varpi^T(t) \dot{\varpi}(t) + \tilde{\varphi}(t) \dot{\tilde{\varphi}}(t) \\ &= \varpi^T(t) [f(\bar{x}(t)) + g(\bar{x}(t))u(t) + d(t) + \vartheta(t)] \\ &\quad + [\varphi(t) - (D + d_{\epsilon_{sa}})] \dot{\varphi}(t) \\ &= [\rho(t)N(\chi(t)) + 1] \dot{\chi}(t) - \varpi^T(t) \varpi(t) \\ &\quad - \varpi^T(t) \tilde{W}_{sa}^T(t) \Psi_{sa}(x_{sa}(t)) \\ &\quad + \varpi^T(t) [d(t) + \epsilon_{sa}(t)] \\ &\quad - \varpi^T(t) \tanh(\varpi(t) \lambda_t) (D + d_{\epsilon_{sa}}) \\ &\leq [\rho(t)N(\chi(t)) + 1] \dot{\chi}(t) \\ &\quad - \varpi^T(t) \tilde{W}_{sa}^T(t) \Psi_{sa}(x_{sa}(t)) + (D + d_{\epsilon_{sa}}) \\ &\quad \times \sum_{i=1}^k [|\varpi_i(t)| - \varpi_i(t) \tanh(\varpi_i(t) \lambda_t)] \\ &\leq [\rho(t)N(\chi(t)) + 1] \dot{\chi}(t) + \frac{0.285}{\lambda_t} k (D + d_{\epsilon_a}) \\ &\quad - \varpi^T(t) \tilde{W}_{sa}^T(t) \Psi_{sa}(x_{sa}(t)), \end{aligned} \quad (29)$$

where we have used  $|y| - y \tanh(y \lambda_t) \leq 0.2785/\lambda_t$ . Furthermore, we have from  $V_2(t) = \frac{1}{2} \text{tr}(\tilde{W}_{sa}^T(t) \Pi_{sa}^{-1} \tilde{W}_{sa}(t))$  that

$$\begin{aligned} \dot{V}_2(t) &= \text{tr} \left( \tilde{W}_{sa}^T(t) \Pi_{sa}^{-1} \dot{\tilde{W}}_{sa}(t) \right) \\ &= \text{tr} \left[ \tilde{W}_{sa}^T(t) \Psi_{sa}(x_{sa}(t)) \varpi^T(t) \right] \\ &\quad - \delta_{sa} \text{tr} \left[ \tilde{W}_{sa}^T(t) \hat{W}_{sa}(t) \right] \\ &\quad + \text{tr} \left[ \tilde{W}_{sa}^T(t) \Psi_{sa}(x_{sa}(t)) \Psi_{sc}^T(x_{sc}(t)) \hat{W}_{sc}(t) \right] \\ &\leq \text{tr} \left[ \tilde{W}_{sa}^T(t) \Psi_{sa}(x_{sa}(t)) \varpi^T(t) \right] \\ &\quad + d_{\Psi_{sa}} d_{\Psi_{sc}} \left\| \tilde{W}_{sa}(t) \right\|_F \left\| \tilde{W}_{sc}(t) \right\|_F \\ &\quad - \delta_{sa} \text{tr} \left[ \tilde{W}_{sa}^T(t) \tilde{W}_{sa}(t) \right] + d_{V_2} \left\| \tilde{W}_{sa}(t) \right\|_F, \end{aligned} \quad (30)$$

where  $d_{V_2} = d_{\Psi_{sa}} d_{\Psi_{sc}} d_{W_{sc}} - \delta_{sa} d_{W_{sa}}$ . In addition, we have from  $V_3(t) = \frac{1}{2} \text{tr} \left( \tilde{W}_{sc}^T(t) \Pi_{sc}^{-1} \tilde{W}_{sc}(t) \right)$  that

$$\begin{aligned} \dot{V}_3(t) &= \text{tr} \left( \tilde{W}_{sc}^T(t) \Pi_{sc}^{-1} \dot{\tilde{W}}_{sc}(t) \right) \\ &= \text{tr} \left[ \tilde{W}_{sc}^T(t) \Delta \Psi_{sc}(t) \left( \hat{W}_{sc}^T \Delta \Psi_{sc}(t) + p_{sc} \right)^T \right] \\ &\quad - \delta_{sc} \text{tr} \left[ \tilde{W}_{sc}^T(t) \hat{W}_{sc} \right] \\ &\leq -\delta_{sc} \text{tr} \left[ \tilde{W}_{sc}^T(t) \tilde{W}_{sc}(t) \right] - d_{V_3} \left\| \tilde{W}_{sc}(t) \right\|_F, \end{aligned} \quad (31)$$

where  $d_{V_3} = (1 + \gamma) d_{\Psi_{sc}} d_{p_c} + (1 + \gamma)^2 d_{\Psi_{sc}}^2 d_{W_{sc}} + (1 + \gamma) \delta_{sc} d_{\Psi_{sc}} d_{W_{sc}}$ . Then the derivative of  $V_s(t)$  is given as

$$\begin{aligned} \dot{V}_s(t) &= \dot{V}_1(t) + \dot{V}_2(t) + \dot{V}_3(t) \\ &\leq [\rho(t)N(\chi(t)) + 1] \chi(t) + \frac{0.285}{\lambda_t} k (D + d_{\epsilon_a}) \\ &\quad - \varpi^T(t) \tilde{W}_{sa}^T(t) \Psi_{sa}(x_{sa}(t)) + d_{V_2} \left\| \tilde{W}_{sa}(t) \right\|_F \\ &\quad - \delta_{sa} \text{tr} \left[ \tilde{W}_{sa}^T(t) \tilde{W}_{sa}(t) \right] - \delta_{sc} \text{tr} \left[ \tilde{W}_{sc}^T(t) \tilde{W}_{sc}(t) \right] \\ &\quad + \text{tr} \left[ \tilde{W}_{sa}^T(t) \Psi_{sa}(x_{sa}(t)) \varpi^T(t) \right] - d_{V_3} \left\| \tilde{W}_{sc}(t) \right\|_F \\ &\quad + d_{\Psi_{sa}} d_{\Psi_{sc}} \left\| \tilde{W}_{sa}(t) \right\|_F \left\| \tilde{W}_{sc}(t) \right\|_F \\ &\leq [\rho(t)N(\chi(t)) + 1] \chi(t) + \frac{0.285}{\lambda_t} k (D + d_{\epsilon_a}) \\ &\quad - \frac{1}{2} \left( \delta_{sa} - d_{\Psi_{sa}}^2 \right) \left\| \tilde{W}_{sa}(t) \right\|_F^2 + \frac{d_{V_2}^2}{2\delta_{sa}} \\ &\quad - \frac{1}{2} \left( \delta_{sc} - d_{\Psi_{sc}}^2 \right) \left\| \tilde{W}_{sc}(t) \right\|_F^2 + \frac{d_{V_3}^2}{2\delta_{sc}} \\ &\quad - \frac{\delta_{sa}}{2} \left[ \left\| \tilde{W}_{sa}(t) \right\|_F - \frac{d_{V_2}}{\delta_{sa}} \right]^2 \\ &\quad - \frac{\delta_{sc}}{2} \left[ \left\| \tilde{W}_{sc}(t) \right\|_F - \frac{d_{V_3}}{\delta_{sc}} \right]^2 \\ &\quad - \frac{1}{2} \left[ d_{\Psi_{sa}} \left\| \tilde{W}_{sa}(t) \right\|_F - d_{\Psi_{sc}} \left\| \tilde{W}_{sc}(t) \right\|_F \right]^2 \\ &\leq [\rho(t)N(\chi(t)) + 1] \chi(t) + \frac{0.2785}{\lambda_t} k (D + d_{\epsilon_a}) \\ &\quad + \frac{d_{V_2}^2}{2\delta_{sa}} + \frac{d_{V_3}^2}{2\delta_{sc}}, \end{aligned} \quad (32)$$

where we have used  $\delta_{sa} \geq d_{\Psi_{sa}}^2$  and  $\delta_{sc} \geq d_{\Psi_{sc}}^2$  given in (27). Since  $V_s(t)$  and  $\chi(t)$  are smooth functions on  $[0, t_f)$  with  $V_s(t) \geq 0$ , using Lemma 1 we have

$$V_s(t), \chi(t), \int_0^t [\rho(\tau)N(\chi(\tau)) + 1] \dot{\chi}(\tau) d\tau \quad (33)$$

are semiglobally UUB on  $[0, t_f)$ .

If the designed parameters of the closed-loop system are properly chosen, i.e., the inequality (27), there exists a compact set  $\Omega$  being the domain of attraction. Note that the compact set can be made to include any initial conditions by designing parameters. Therefore, the signals of the closed-loop system are semiglobally UUB.

It is seen that  $\varpi^T(t)\varpi(t) \in \mathcal{L}_\infty$ ,  $\|\varpi(t)\| \in \mathcal{L}_\infty$ ,  $\|\hat{W}_{sa}(t)\|_F \in \mathcal{L}_\infty$ ,  $\|\hat{W}_{sc}(t)\|_F \in \mathcal{L}_\infty$ , and  $\varphi(t) \in \mathcal{L}_\infty$ , which implies  $\varpi_i(t), \dot{V}_1(t), \dot{V}_2(t), \dot{V}_3(t) \in \mathcal{L}_\infty$ . Thus, we have  $\frac{d(\varpi^T(t)\varpi(t))}{dt} = 2\varpi^T(t)\dot{\varpi}(t) = 2\left[\dot{V}_1(t) - \tilde{\varphi}(t)\dot{\varphi}(t)\right] \in \mathcal{L}_\infty$ , which means  $\dot{\varpi}_i(t) \in \mathcal{L}_\infty$ . Meanwhile, it is seen from (29) that  $\int_0^t \varpi^T(\tau)\varpi(\tau)d\tau \in \mathcal{L}_\infty$ , which implies  $\int_0^t \varpi_i^2(\tau)d\tau \in \mathcal{L}_\infty$ . Therefore, by using Barbalat's lemma with  $\varpi_i(t), \dot{\varpi}_i(t), \int_0^t \varpi_i^2(\tau)d\tau \in \mathcal{L}_\infty$ , we have  $\lim_{t \rightarrow \infty} \varpi_i(t) = 0$  for  $i = 1, 2, \dots, k$ .

Let  $x_i(t), i = 1, 2, \dots, k$  be the elements of  $x(t)$ . Similarly, let  $x_i^{(m)}(t), m = 1, 2, \dots, n - 1, i = 1, 2, \dots, k$  be the elements of  $x^{(m)}(t), m = 1, 2, \dots, n - 1$ . Suppose  $\vartheta_i(t), i = 1, 2, \dots, k$  are the elements of  $\vartheta(t)$ . It is seen from (8) and (9) that the elements  $\varpi_i(t)$  and  $\vartheta_i(t)$  are represented as

$$\begin{aligned} \varpi_i(t) &= \left( \beta + \frac{d}{dt} \right)^{n-1} x_i(t) \\ &= C_{n-1}^0 \beta^{n-1} x_i(t) + C_{n-1}^1 \beta^{n-2} \dot{x}_i(t) + \dots \\ &\quad + C_{n-1}^{n-2} \beta x_i^{(n-2)}(t) + C_{n-1}^{n-1} x_i^{(n-1)}(t) \end{aligned} \quad (34)$$

and

$$\begin{aligned} \vartheta_i(t) &= C_{n-1}^0 \beta^{n-1} \dot{x}_i(t) + C_{n-1}^1 \beta^{n-2} \ddot{x}_i(t) + \dots \\ &\quad + C_{n-1}^{n-3} \beta^2 x_i^{(n-2)}(t) + C_{n-1}^{n-2} \beta x_i^{(n-1)}(t). \end{aligned} \quad (35)$$

Therefore, according to Lemma 3 in [36], since  $\lim_{t \rightarrow \infty} \varpi_i(t) = 0$  for  $i = 1, 2, \dots, k$ , the elements  $x_i(t), i = 1, 2, \dots, k$  and its derivatives  $x_i^{(m)}(t), m = 1, 2, \dots, n - 1, i = 1, 2, \dots, k$  converge to zero as  $t \rightarrow \infty$ , i.e., the objective (7) is achieved. ■

*Remark 1:* Compared with existing results [29], where the IRL controller is designed for tracking control of second-order, square multivariable dynamics, in this paper, the proposed controllers are developed for high-order, nonsquare multivariable systems.

In what follows, we will consider the system (6) in a special case, namely, the  $g(\bar{x}(t))$  is assumed to be a square matrix. In this case, the following assumption is needed.

*Assumption 2:* The matrix  $g(\bar{x}(t)) + g^T(\bar{x}(t))$  is either positive or negative definite.


According to Lemma 3 with Assumption 2, we define

$$\frac{1}{2} \varpi^T(t) \left( g^T(\bar{x}(t)) + g(\bar{x}(t)) \right) \varpi(t) = \rho(t) \|\varpi(t)\|^2, \quad (36)$$

where  $\lambda_{\min}(t) \leq \rho(t) \leq \lambda_{\max}(t)$ ,  $\lambda_{\min}(t)$  and  $\lambda_{\max}(t)$  are respectively the minimum and maximum eigenvalues of matrix  $\frac{1}{2} (g^T(\bar{x}(t)) + g(\bar{x}(t)))$ , and  $\varpi(t)$  is defined in (8). From Assumption 2 and the definition of (36), we know that the sign of  $\rho(t)$  is nonzero, constant but unknown.

It is easy to see that the Assumption 2 can be regarded as a special case of Assumption 1. Therefore, following the similar design procedure of nonsquare multivariable systems, the IRL controller for the square multivariable system with UCCs can be proposed as

$$u(t) = N(\chi(t)) \frac{\varpi(t)\varpi^T(t)\bar{u}(t)}{\|\varpi(t)\|^2} \quad (37)$$



**FIGURE 1.** The state trajectories  $x_i(t)$  and  $\dot{x}_i(t)$  of the multivariable system.

with (25) and (26) Then, the stability results are summarized as follows:

*Corollary 1:* Consider a continuous-time square multivariable system with UCCs given in (6) satisfying Assumption 2. The IRL controller (37), (25) and (26) with the critic NN (16) and (19), and the action NN (21) and (23) can achieve the objective (7) if the designed parameters are properly chosen, i.e., the conditions (27) are satisfied. Furthermore, all signals of the closed-loop system are semiglobally UUB.

*Proof:* It is seen that the Assumption 2 can be regarded as a special case of Assumption 1. Therefore, the result of this corollary is a direct consequence of Theorem 1. ■

**IV. SIMULATION EXAMPLES**

In this section, one example is adopted to illustrate the effectiveness of the proposed controllers. We consider a system with second-order dynamics ( $k = 2$ ) described by (6), where

$$g(\bar{x}(t)) = g_0(\bar{x}(t))g_u(\bar{x}(t)),$$


in which

$$g_0(\bar{x}(t)) = \begin{bmatrix} 1 & 2 & 0 \\ -2 & 0 & 1 \end{bmatrix}$$


is the known, bounded matrix with full row rank, and

$$g_u(\bar{x}(t)) = \begin{bmatrix} 2 & 0 & 0 \\ 0 & 4 - \cos(x_1) & 1 \\ 0 & 1 & 3 - \sin(x_2) \end{bmatrix}$$


is the unknown matrix. It is seen that  $g(\bar{x}(t)) \in \mathbb{R}^{2 \times 3}$  is a nonsquare and partially unknown matrix. Let  $d(t) = [\sin(t), \sin(2t) + 1]^T$ . Therefore, this is a nonsquare multivariable system satisfying all the imposed conditions in Section III. The initial condition of the system is  $x(0) = [-1, 3]$ ,  $\dot{x}(0) = [2, -5]$ ,  $\gamma = 0.8$  and  $T = 0.4$ . The NN terms  $\hat{W}_{sa}^T \Psi_{sa}(\bar{x})$  and  $\hat{W}_{sc}^T \Psi_{sc}(\bar{x})$  with input vector  $\bar{x} = [x(t), \dot{x}(t)]^T$  have 21 nodes with centers  $\mu_l, l = 1, 2, \dots, 21$ , evenly spaced in  $[-4, 4] \times [-4, 4] \times [-4, 4] \times [-4, 4]$ , and widths  $\eta_l = 4, l = 1, 2, \dots, 21$ . Furthermore, to satisfy the conditions in Theorem 1, let the parameters  $\delta_{sa} = \delta_{sc} = 2$ . The Nussbaum-type function is  $N(\chi(t)) = \chi(t)^2 \cos(\chi(t))$ , the initial states of  $\chi(t)$  and  $\hat{W}_{sa}(t)$  are zero, the initial state  $\hat{W}_{sc}(0) = I_{21 \times 2}$ , and the parameters  $\Pi_{sa} = \Pi_{sc} = 0.3I_{21}$ . The simulation results are given in Fig. 1-4, where it is shown that the objective (7) can be achieved. Moreover, the signals of the closed-loop system are all bounded.



**FIGURE 2.** The weight norms  $\|\hat{W}_a(t)\|_F$  and  $\|\hat{W}_c(t)\|_F$  of the multivariable system.



**FIGURE 3.** The Nussbaum parameters  $\chi(t)$  and  $N(\chi(t))$  of the multivariable system.



**FIGURE 4.** The estimated performance index  $\hat{J}(t)$  of the multivariable system.

**V. CONCLUSION**

In this paper, we have developed an IRL controller for a class of high-order multivariable nonlinear systems with UCCs. A new long-term performance index is first proposed to estimate the control performance, where a critic NN is designed since the long-term performance index contains unknown future states. Then, the action NN is prescribed to approximate the unknown drift of systems. By designing the critic and action NNs with Nussbaum-type functions, the IRL controllers of high-order, nonsquare multivariable systems can solve the problem of UCCs. It is proven rigorously that the signals of the closed-loop systems are semiglobally UUB. Finally, one example has been employed to illustrate the effectiveness of the proposed IRL controllers. Future work may focus on input saturation, sampled-data and time-delay with dynamics subject to UCCs.

**REFERENCES**

[1] S. S. Ge, F. Hong, and T. H. Lee, "Adaptive neural control of nonlinear time-delay systems with unknown virtual control coefficients," *IEEE Trans. Syst. Man, Cybern. B, Cybern.*, vol. 34, no. 1, pp. 499–516, Feb. 2004.

- [2] G. Tao, "Multivariable adaptive control: A survey," *Automatica*, vol. 50, no. 11, pp. 2737–2764, Nov. 2014.
- [3] Y. Liu, G. Tao, and S. M. Joshi, "Modeling and model reference adaptive control of aircraft with asymmetric damage," *J. Guid., Control, Dyn.*, vol. 33, no. 5, pp. 1500–1517, Sep. 2010.
- [4] A. Astolfi, L. Hsu, M. S. Netto, and R. Ortega, "Two solutions to the adaptive visual servoing problem," *IEEE Trans. Robot. Autom.*, vol. 18, no. 3, pp. 387–392, Jun. 2002.
- [5] J. Du, C. Guo, S. Yu, and Y. Zhao, "Adaptive autopilot design of time-varying systems with completely unknown control coefficient," *IEEE J. Ocean. Eng.*, vol. 32, no. 2, pp. 346–352, Apr. 2007.
- [6] R. D. Nussbaum, "Some remarks on a conjecture in parameter adaptive control," *Syst. Control Lett.*, vol. 3, no. 5, pp. 243–246, Nov. 1983.
- [7] Y. Zhang, C. Wen, and Y. C. Soh, "Adaptive backstepping control design for systems with unknown high-frequency gain," *IEEE Trans. Autom. Control*, vol. 45, no. 12, pp. 2350–2354, 2000.
- [8] W. Chen, X. Li, W. Ren, and C. Wen, "Adaptive consensus of multi-agent systems with unknown control directions based on a novel nussbaum-type function," *IEEE Trans. Autom. Control*, vol. 59, no. 7, pp. 1887–1892, Jul. 2014.
- [9] Z. Ding, "Adaptive consensus output regulation of a class of nonlinear systems with unknown high-frequency gain," *Automatica*, vol. 51, pp. 348–355, Jan. 2015.
- [10] Z. Yu, S. Li, Z. Yu, and F. Li, "Adaptive neural output feedback control for nonstrict-feedback stochastic nonlinear systems with unknown backlash-like hysteresis and unknown control directions," *IEEE Trans. Neural Netw. Learn. Syst.*, vol. 29, no. 4, pp. 1147–1160, Apr. 2018.
- [11] J. Huang, W. Wang, C. Wen, and J. Zhou, "Adaptive control of a class of strict-feedback time-varying nonlinear systems with unknown control coefficients," *Automatica*, vol. 93, pp. 98–105, Jul. 2018.
- [12] J. Peng and X. Ye, "Cooperative control of multiple heterogeneous agents with unknown high-frequency-gain signs," *Syst. Control Lett.*, vol. 68, pp. 51–56, Jun. 2014.
- [13] Q. Wang, H. E. Psillakis, and C. Sun, "Adaptive cooperative control with guaranteed convergence in time-varying networks of nonlinear dynamical systems," *IEEE Trans. Cybern.*, early access, Jun. 3, 2019, doi: [10.1109/TCYB.2019.2916563](https://doi.org/10.1109/TCYB.2019.2916563).
- [14] G. Wang, "Distributed control of higher-order nonlinear multi-agent systems with unknown non-identical control directions under general directed graphs," *Automatica*, vol. 110, Dec. 2019, Art. no. 108559, doi: [10.1016/j.automatica.2019.108559](https://doi.org/10.1016/j.automatica.2019.108559).
- [15] Q. Wang and C. Sun, "Adaptive consensus of multiagent systems with unknown high-frequency gain signs under directed graphs," *IEEE Trans. Syst., Man, Cybern. Syst.*, early access, Mar. 13, 2018, doi: [10.1109/TSMC.2018.2810089](https://doi.org/10.1109/TSMC.2018.2810089).
- [16] C. Wang, C. Wen, and L. Guo, "Multivariable adaptive control with unknown signs of the high-frequency gain matrix using novel nussbaum functions," *Automatica*, vol. 111, Jan. 2020, Art. no. 108618.
- [17] R. Ortega, A. Astolfi, and N. E. Barabanov, "Nonlinear PI control of uncertain systems: An alternative to parameter adaptation," *Syst. Control Lett.*, vol. 47, no. 3, pp. 259–278, Oct. 2002.
- [18] H. E. Psillakis, "An extension of the Georgiou–Smith example: Boundedness and attractivity in the presence of unmodelled dynamics via nonlinear PI control," *Syst. Control Lett.*, vol. 92, pp. 1–4, Jun. 2016.
- [19] Q. Wang, H. E. Psillakis, and C. Sun, "Cooperative control of multiple agents with unknown high-frequency gain signs under unbalanced and switching topologies," *IEEE Trans. Autom. Control*, vol. 64, no. 6, pp. 2495–2501, Jun. 2019.
- [20] H. E. Psillakis, "Consensus in networks of agents with unknown high-frequency gain signs and switching topology," *IEEE Trans. Autom. Control*, vol. 62, no. 8, pp. 3993–3998, Aug. 2017.
- [21] Q. Wang, H. E. Psillakis, and C. Sun, "Cooperative control of multiple high-order agents with nonidentical unknown control directions under fixed and time-varying topologies," *IEEE Trans. Syst., Man, Cybern. Syst.*, early access, May 27, 2019, doi: [10.1109/TSMC.2019.2916641](https://doi.org/10.1109/TSMC.2019.2916641).
- [22] T. R. Oliveira, A. J. Peixoto, and L. Hsu, "Sliding mode control of uncertain multivariable nonlinear systems with unknown control direction via switching and monitoring function," *IEEE Trans. Autom. Control*, vol. 55, no. 4, pp. 1028–1034, Apr. 2010.
- [23] J. Wu, W. Chen, and J. Li, "Global finite-time adaptive stabilization for nonlinear systems with multiple unknown control directions," *Automatica*, vol. 69, pp. 298–307, Jul. 2016.
- [24] C. Huang and C. Yu, "Tuning function design for nonlinear adaptive control systems with multiple unknown control directions," *Automatica*, vol. 89, pp. 259–265, Mar. 2018.
- [25] D. Vrabie, O. Pastravanu, M. Abu-Khalaf, and F. L. Lewis, "Adaptive optimal control for continuous-time linear systems based on policy iteration," *Automatica*, vol. 45, no. 2, pp. 477–484, Feb. 2009.
- [26] H. Modares, F. L. Lewis, and M.-B. Naghibi-Sistani, "Integral reinforcement learning and experience replay for adaptive optimal control of partially-unknown constrained-input continuous-time systems," *Automatica*, vol. 50, no. 1, pp. 193–202, Jan. 2014.
- [27] H. Li, D. Liu, and D. Wang, "Integral reinforcement learning for linear continuous-time zero-sum games with completely unknown dynamics," *IEEE Trans. Autom. Sci. Eng.*, vol. 11, no. 3, pp. 706–714, Jul. 2014.
- [28] R. Song, F. L. Lewis, Q. Wei, and H. Zhang, "Off-policy actor-critic structure for optimal control of unknown systems with disturbances," *IEEE Trans. Cybern.*, vol. 46, no. 5, pp. 1041–1050, May 2016.
- [29] X. Guo, W. Yan, and R. Cui, "Integral reinforcement learning-based adaptive NN control for continuous-time nonlinear MIMO systems with unknown control directions," *IEEE Trans. Syst., Man, Cybern. Syst.*, early access, Mar. 5, 2019, doi: [10.1109/TSMC.2019.2897221](https://doi.org/10.1109/TSMC.2019.2897221).
- [30] P. He and S. Jagannathan, "Reinforcement learning-based output feedback control of nonlinear systems with input constraints," *IEEE Trans. Syst. Man, Cybern. B, Cybern.*, vol. 35, no. 1, pp. 150–154, Feb. 2005.
- [31] W. Wang and S. Tong, "Adaptive fuzzy bounded control for consensus of multiple strict-feedback nonlinear systems," *IEEE Trans. Cybern.*, vol. 48, no. 2, pp. 522–531, Feb. 2018.
- [32] S. Haykin, *Neural Networks: A Comprehensive Foundation*. Upper Saddle River, NJ, USA: Prentice-Hall, 1999.
- [33] R. M. Sanner and J.-J.-E. Slotine, "Gaussian networks for direct adaptive control," *IEEE Trans. Neural Netw.*, vol. 3, no. 6, pp. 837–863, Nov. 1992.
- [34] W. Shi, "Adaptive fuzzy control for MIMO nonlinear systems with nonsymmetric control gain matrix and unknown control direction," *IEEE Trans. Fuzzy Syst.*, vol. 22, no. 5, pp. 1288–1300, Oct. 2014.
- [35] S. S. Ge and C. Wang, "Direct adaptive NN control of a class of nonlinear systems," *IEEE Trans. Neural Netw.*, vol. 13, no. 1, pp. 214–221, Jan. 2002.
- [36] S. Su and Z. Lin, "Distributed consensus control of multi-agent systems with higher order agent dynamics and dynamically changing directed interaction topologies," *IEEE Trans. Autom. Control*, vol. 61, no. 2, pp. 515–519, Feb. 2016.



**QINGLING WANG** (Senior Member, IEEE) received the B.S. and M.S. degrees from Central South University, Changsha, China, in 2007 and 2010, respectively, and the Ph.D. degree in control science and engineering from the Harbin Institute of Technology, Harbin, China, in 2014. He was a Visiting Student with Australia National University, Canberra, ACT, Australia, from 2012 to 2014. He was also a Visiting Scholar with the Technical University of Berlin, Germany, in 2016. He is currently an Associate Professor with the School of Automation, Southeast University, Nanjing, China. His current research interests include constrained control, adaptive control, and cooperative control of multiagent systems.

•••