

Received July 29, 2020, accepted August 11, 2020, date of publication August 19, 2020, date of current version August 28, 2020.

Digital Object Identifier 10.1109/ACCESS.2020.3017799

Power Control for Two-Way AF Relay Assisted D2D Communications Underlying Cellular Networks

LIANG HAN^{1,2}, (Member, IEEE), RANRAN ZHOU², YUPENG LI^{1,2}, (Member, IEEE),
BO ZHANG^{1,2}, (Member, IEEE), AND XIN ZHANG^{1,2}, (Member, IEEE)

¹Tianjin Key Laboratory of Wireless Mobile Communications and Power Transmission, Tianjin Normal University, Tianjin 300387, China

²College of Electronics and Communication Engineering, Tianjin Normal University, Tianjin 300387, China

Corresponding author: Liang Han (hanliang@tjnu.edu.cn)

This work was supported in part by the National Natural Science Foundation of China under Grant 61701345 and Grant 61901301, in part by the Natural Science Foundation of Tianjin under Grant 18JCZDJC31900 and Grant 18JCQNJC70900, and in part by the Tianjin Education Commission Scientific Research Plan under Grant 2017KJ121.

ABSTRACT As a key technology of the 5G communication system, device-to-device (D2D) communications have drawn significant research interests. However, the advantage of D2D communications may be limited when D2D users are far away from each other or the communication environments are harsh. In order to extend the range of D2D communications, a promising way is to use relaying technique to assist the communications. In this paper, we use a two-way amplify-and-forward (AF) relay to assist the underlay D2D communications and investigate the power control problem. Specifically, we formulate the power control problem as the optimization of the performance of the D2D link while fulfilling the quality-of-service (QoS) requirement of the cellular link. Two optimization objectives are considered for the D2D link, i.e., maximization of the minimum SINR at D2D users and maximization of the sum-rate of D2D users. For the first optimization objective, we can compare the possible optimal solutions for the three boundary conditions and obtain the optimal solutions. For the second optimization objective, we can convert the objective function into a concave function based on difference of convex (D. C.) structure, and use an iterative algorithm to solve the optimization problem. The simulation results show that the proposed power control scheme can improve the performance of the D2D link.

INDEX TERMS D2D communications, two-way AF relay, power control.

I. INTRODUCTION

In recent years, the fifth-generation (5G) mobile communication system has attracted worldwide research interests and begun to be deployed all over the world [1]–[6]. With the rapid development of the 5G mobile communications, people's lives and society will change dramatically.

As one of the most important techniques for the 5G mobile communication system, device-to-device (D2D) communications have been studied widely [7]–[9]. Unlike traditional cellular communication where all the communication signals must pass through the base station (BS), D2D communications can offload traffic from cellular networks by enabling mobile devices in proximity to communicate directly with each other. As such, D2D communications can increase

spectral efficiency, improve cellular coverage, reduce transmission delay, and decrease energy consumption of mobile devices. According to whether the licensed cellular spectrum is exploited, D2D communications can be divided into two categories, i.e., inband D2D and outband D2D. So far, most of the literature on D2D communications focuses on inband D2D because the spectrum can be fully controlled by the BS and user quality-of-service (QoS) requirements can be fulfilled. Inband D2D can be further divided into underlay mode and overlay mode [8], [9]. In underlay D2D mode, the cellular and D2D users can share the same spectrum resources, while in overlay D2D mode, the D2D users are allocated dedicated cellular spectrum resources. Underlay D2D communications can improve the spectrum efficiency by reusing spectrum resources, but it will cause interference between D2D and cellular users. This interference can be mitigated by power control and resource allocation [11]–[13].

The associate editor coordinating the review of this manuscript and approving it for publication was Qilian Liang¹.

So far, most of the studies on D2D communications consider the scenarios where D2D users can establish a direct link. However, in practice, the advantage of D2D communications may be limited when D2D users are far away from each other or the communication environments are harsh. In order to substantially extend the range of D2D communications, a promising way is to use relaying technique to assist the communications. In [14], the authors investigated the resource allocation under channel gain uncertainty for relay-assisted D2D communication in LTE-A cellular networks where D2D pairs are served by the relay nodes. In [15], relay-assisted D2D communication was proposed as a supplement to direct D2D communications for enhancing traffic offloading capacity in LTE-A systems. The proposed relay selection schemes can improve D2D communication performance significantly. In [16], the authors investigated the performance trade-off between spectral efficiency and energy efficiency in relay-assisted D2D-cellular networks, where D2D users reuse the resource of cellular uplink transmissions. It is worth noting that all these works are limited to half-duplex one-way relaying (OWR), which suffers from a spectral efficiency loss since additional resources are required for relaying transmission.

To compensate spectral efficiency loss in one-way relaying system, two-way relaying (TWR) using an amplify-and-forward (AF) or a decode-and-forward (DF) protocol has been proposed [17]–[19]. Generally, TWR comprises two source nodes and one relay node. The two source nodes simultaneously send their information to the relay node in the first phase and the relay node forwards the combined signal to the two source nodes in the second phase. To complete one-round of information exchange between two source nodes, OWR requires four time-slots while TWR only needs two time-slots. As such, some papers have begun to integrate TWR into D2D communications. References [20] and [21] investigated the outage probability of underlay D2D communications assisted by two-way DF relaying and AF relaying, respectively. However, the authors only consider the performance of D2D link and ignore the cellular link. In [22], the authors investigated the linear precoder-decoder schemes for a multiple-input multiple-output (MIMO) underlay D2D communication system. Two transmit modes for D2D communications were considered: two-way relaying based D2D and direct D2D. In the two-way relaying based D2D mode, physical layer network coding (PNC) was used. In [23], the authors investigated the average energy efficiency and spectral efficiency of multihop D2D communications where one user may help the other two users to exchange information with PNC scheme. In [24], Huang and Gharavi presented an analytical approach to evaluate the performance of two-way asymmetric D2D communications with and without network coding. In [25], the authors investigated the performance of D2D communication assisted by two-way DF relaying. The analytical results showed that D2D communication assisted by two-way DF relaying provides better performance

in terms of maximum achievable sum-rate as compared to cellular communication mode.

In this paper, we propose a two-way AF relaying scheme to assist the underlay D2D communications and investigate the power control problems, which are formulated as the optimization of the performance of the D2D link while fulfilling the QoS requirement of the cellular link. Two optimization objectives are considered for the D2D link, i.e., maximization of the minimum SINR at D2D users and maximization of the sum-rate of D2D users. Simulation results show that the performance can be improved by using power control.

The rest of the paper is organized as follows. In section II, the system model is introduced. The power control algorithms are investigated in section III. Afterward, in section IV, some simulation results are given. Finally, section V concludes this paper.

II. SYSTEM MODEL

Consider a single-cell scenario with two types of communication, i.e., traditional cellular communication and D2D communication aided by two-way AF relaying. Underlay D2D mode is assumed, i.e., the cellular link and D2D link share the same spectrum resources. The cellular link consists of a cellular user (CU) and a BS, while the D2D link consists of a pair of D2D users (DU_1 and DU_2) and an assisted relay user (RU). We assume the direct link between DU_1 and DU_2 does not exist due to the large separation or obstacles. DU_1 and DU_2 communicate with each other via RU which uses two-way AF relaying protocol.

We assume time division duplex (TDD) mode is used, then the first phase and second phase of the two-way D2D communication can share the uplink or downlink resource of the cellular communications. Therefore, there are four possible transmission schemes according to the relationship between the uplink and downlink phases of cellular communication and the two phases of the two-way D2D communication. Since the power control algorithms are similar for all the possible transmission schemes, this paper focuses on one specific transmission scheme, as shown in Fig. 1, where the first phase of the two-way D2D communication shares the downlink resource of the cellular communications, while the second phase of the two-way D2D communication shares the uplink resource of the cellular communications.

We assume all the channels are reciprocal and time-invariant over two phases, i.e., the channel from node A to node B, and the channel from node B to node A are the same. For the cellular link, the desired channel between BS and CU is denoted as h_0 . For the D2D link, the desired channels between DU_1 , DU_2 and RU are denoted as h_1 and h_2 , respectively. We denote the interference channel between BS and RU as f_0 , and the interference channel between DU_1 , DU_2 and CU as f_1 and f_2 , respectively. Furthermore, we assume that perfect channel state information (CSI) is available at both the transmitter and the receiver, and the BS can obtain all the CSI.




FIGURE 1. System model of two-way AF relay assisted D2D communications underlying cellular networks.

We denote the unit-power transmitted symbol of the BS, CU, DU₁, and DU₂ as x_b , x_c , x_1 , and x_2 , respectively. The transmit power of BS, CU, RU, DU₁, and DU₂ are denoted as P_b , P_c , P_r , P_1 , and P_2 , respectively. We assume the maximum transmit power of BS and CU are P_b^{\max} and P_c^{\max} , respectively, and the maximum transmit power of RU, DU₁, and DU₂ are the same and denoted as P_d^{\max} . The complex additive white Gaussian noise (AWGN) at the BS, CU, RU, DU₁, and DU₂ are denoted by n_b , n_c , n_r , n_1 , and n_2 , respectively, which have zero mean and variance N_0 .

During the first phase, the received signals at the CU and the RU are given as

$$y_c = \sqrt{P_b}h_0x_b + \sqrt{P_1}f_1x_1 + \sqrt{P_2}f_2x_2 + n_c, \quad (1)$$

$$y_r = \sqrt{P_1}h_1x_1 + \sqrt{P_2}h_2x_2 + \sqrt{P_b}f_0x_b + n_r. \quad (2)$$

During the second phase, the RU multiplies its received signal in the first phase by a scaling factor β which is chosen

to satisfy the power constraint at the RU, i.e.,

$$\beta = \frac{\sqrt{P_r}}{\sqrt{P_1|h_1|^2 + P_2|h_2|^2 + P_b|f_0|^2 + N_0}}. \quad (3)$$

Then, the RU forwards the amplified signal $x_r = \beta y_r$ to DU₁ and DU₂, and the received signal at the BS, DU₁ and DU₂ are given as

$$y_b = \sqrt{P_c}h_0x_c + f_0x_r + n_b, \quad (4)$$

$$\begin{aligned} y_1 &= h_1\beta y_r + \sqrt{P_c}f_1x_c + n_1 \\ &= \sqrt{P_1}\beta h_1h_1x_1 + \sqrt{P_2}\beta h_1h_2x_2 + \sqrt{P_b}\beta h_1f_0x_b \\ &\quad + \beta h_1n_r + \sqrt{P_c}f_1x_c + n_1, \end{aligned} \quad (5)$$

$$\begin{aligned} y_2 &= h_2\beta y_r + \sqrt{P_c}f_2x_c + n_2 \\ &= \sqrt{P_1}\beta h_1h_2x_1 + \sqrt{P_2}\beta h_2h_2x_2 + \sqrt{P_b}\beta h_2f_0x_b \\ &\quad + \beta h_2n_r + \sqrt{P_c}f_2x_c + n_2. \end{aligned} \quad (6)$$

Since both DU₁ and DU₂ know their own transmitted symbols and the knowledge of the CSI, the self-interference can be removed from the received signal. After the self-interference cancellation, the signal-to-interference-and-noise ratios (SINRs) at DU₁ and DU₂ can be expressed as

$$\text{SINR}_1 = \frac{P_2|\beta|^2|h_1|^2|h_2|^2}{P_b|\beta|^2|h_1|^2|f_0|^2 + |\beta|^2|h_1|^2N_0 + P_c|f_1|^2 + N_0}, \quad (7)$$

$$\text{SINR}_2 = \frac{P_1|\beta|^2|h_1|^2|h_2|^2}{P_b|\beta|^2|h_2|^2|f_0|^2 + |\beta|^2|h_2|^2N_0 + P_c|f_2|^2 + N_0}. \quad (8)$$

By substituting (3) into (7) and (8) and after some manipulations, the SINRs can be rewritten as in (9) and (10), shown at the bottom of the page.

III. POWER CONTROL ALGORITHMS

In this section, we formulate the power control problem as the optimization of the performance of the D2D link while fulfilling the QoS requirement of the cellular link. Two optimization objectives are considered for the D2D link: (1) Maximization of the minimum SINR at DU₁ and DU₂, and (2) Maximization of the sum-rate of DU₁ and DU₂. We denote the uplink and downlink SINR requirement of the cellular link as τ_u and τ_d , respectively. Then the QoS requirement of the cellular link can be given as

$$\frac{P_b|h_0|^2}{P_1|f_1|^2 + P_2|f_2|^2 + N_0} \geq \tau_d, \quad \frac{P_c|h_0|^2}{P_r|f_0|^2 + N_0} \geq \tau_u. \quad (11)$$

$$\text{SINR}_1 = \frac{P_2P_r|h_1|^2|h_2|^2}{(P_b|f_0|^2 + N_0)(P_c|f_1|^2 + P_r|h_1|^2 + N_0) + (P_c|f_1|^2 + N_0)(P_1|h_1|^2 + P_2|h_2|^2)} \quad (9)$$

$$\text{SINR}_2 = \frac{P_1P_r|h_1|^2|h_2|^2}{(P_b|f_0|^2 + N_0)(P_c|f_2|^2 + P_r|h_2|^2 + N_0) + (P_c|f_2|^2 + N_0)(P_1|h_1|^2 + P_2|h_2|^2)} \quad (10)$$

Obviously, feasible solution exists under the condition $\frac{P_b^{\max}|h_0|^2}{N_0} > \tau_d$ and $\frac{P_c^{\max}|h_0|^2}{N_0} > \tau_u$. In this paper, we assume this condition is always satisfied.

From (9) and (10), we can see both SINR_1 and SINR_2 are monotonic decreasing functions respect to P_b and P_c , so the inequality constraints in (11) should be equality constraints. Otherwise, we can decrease the values of P_b and P_c till the equality constraints are satisfied while increasing the minimum SINR at DU_1 and DU_2 or the sum-rate of DU_1 and DU_2 . Therefore, we have

$$P_b = \frac{(P_1|f_1|^2 + P_2|f_2|^2 + N_0) \tau_d}{|h_0|^2}, \quad (12)$$

$$P_c = \frac{(P_r|f_0|^2 + N_0) \tau_u}{|h_0|^2}. \quad (13)$$

Substituting (13) into (9) and (10), it is easy to see that both SINR_1 and SINR_2 are monotonically increasing functions of the transmit power of RU. Considering the constraints $P_c \leq P_c^{\max}$ and $P_r \leq P_d^{\max}$, the optimal value of P_r is given as

$$P_r^* = \min \left(P_d^{\max}, \frac{P_c^{\max}|h_0|^2}{|f_0|^2 \tau_u} - \frac{N_0}{|f_0|^2} \right). \quad (14)$$

Substituting (12), (13) and (14) into (9) and (10) and after some manipulations, we can obtain

$$\text{SINR}_1 = \frac{P_2 P_r^*}{A_1 P_1 + A_2 P_2 + A_3}, \quad (15)$$

$$\text{SINR}_2 = \frac{P_1 P_r^*}{B_1 P_1 + B_2 P_2 + B_3}, \quad (16)$$

where

$$A_1 = \left(\frac{(P_r^*|f_0|^2 + N_0) |f_1|^2 \tau_u}{|h_0|^2} + N_0 \right) \times \left(\frac{|f_0|^2 |f_2|^2 \tau_d}{|h_0|^2 |h_1|^2 |h_2|^2} + \frac{1}{|h_2|^2} \right) + \frac{P_r^* |f_0|^2 |f_1|^2 \tau_d}{|h_0|^2 |h_2|^2},$$

$$A_2 = \left(\frac{(P_r^*|f_0|^2 + N_0) |f_1|^2 \tau_u}{|h_0|^2} + N_0 \right) \times \left(\frac{|f_0|^2 |f_2|^2 \tau_d}{|h_0|^2 |h_1|^2 |h_2|^2} + \frac{1}{|h_1|^2} \right) + \frac{P_r^* |f_0|^2 |f_2|^2 \tau_d}{|h_0|^2 |h_2|^2},$$

$$A_3 = \left(\frac{(P_r^*|f_0|^2 + N_0) |f_1|^2 \tau_u}{|h_0|^2 |h_1|^2 |h_2|^2} + \frac{P_r^*}{|h_2|^2} + \frac{N_0}{|h_1|^2 |h_2|^2} \right) \times \left(\frac{|f_0|^2 \tau_d}{|h_0|^2} + 1 \right) N_0,$$

$$B_1 = \left(\frac{(P_r^*|f_0|^2 + N_0) |f_2|^2 \tau_u}{|h_0|^2} + N_0 \right) \times \left(\frac{|f_0|^2 |f_1|^2 \tau_d}{|h_0|^2 |h_1|^2 |h_2|^2} + \frac{1}{|h_2|^2} \right) + \frac{P_r^* |f_0|^2 |f_1|^2 \tau_d}{|h_0|^2 |h_1|^2},$$

$$B_2 = \left(\frac{(P_r^*|f_0|^2 + N_0) |f_2|^2 \tau_u}{|h_0|^2} + N_0 \right)$$

$$\times \left(\frac{|f_0|^2 |f_2|^2 \tau_d}{|h_0|^2 |h_1|^2 |h_2|^2} + \frac{1}{|h_1|^2} \right) + \frac{P_r^* |f_0|^2 |f_2|^2 \tau_d}{|h_0|^2 |h_1|^2},$$

$$B_3 = \left(\frac{(P_r^*|f_0|^2 + N_0) |f_2|^2 \tau_u}{|h_0|^2 |h_1|^2 |h_2|^2} + \frac{P_r^*}{|h_1|^2} + \frac{N_0}{|h_1|^2 |h_2|^2} \right) \times \left(\frac{|f_0|^2 \tau_d}{|h_0|^2} + 1 \right) N_0.$$

A. MAXIMIZATION OF THE MINIMUM SINR

In this subsection, we formulate the power control problem as the maximization of the minimum SINR at DU_1 and DU_2 . The optimization problem can be formulated as

$$\begin{aligned} \max_{P_1, P_2} \quad & \min(\text{SINR}_1, \text{SINR}_2) \\ \text{s.t.} \quad & 0 < P_1 |f_1|^2 + P_2 |f_2|^2 \leq \eta, \\ & 0 < P_1, P_2 \leq P_d^{\max}. \end{aligned} \quad (17)$$

where $\eta = \frac{P_b^{\max}|h_0|^2}{\tau_d} - N_0$. To solve this optimization problem, we first introduce the following two propositions.

Proposition 1: The optimal solution to problem (17) must satisfy $\text{SINR}_1 = \text{SINR}_2$.

Proof: We can prove this assertion by the following argument. Note that SINR_1 is a monotonic decreasing function with respect to P_1 and a monotonic increasing function with respect to P_2 , and SINR_2 is a monotonic increasing function with respect to P_1 and a monotonic decreasing function with respect to P_2 . Suppose that at the optimal solution, $\text{SINR}_1 > \text{SINR}_2$, then we can decrease the value of P_2 to decrease SINR_1 and increase SINR_2 till $\text{SINR}_1 = \text{SINR}_2$ while increasing the smaller SINR. Suppose that at the optimal solution, $\text{SINR}_1 < \text{SINR}_2$, then we can decrease the value of P_1 to increase SINR_1 and decrease SINR_2 till $\text{SINR}_1 = \text{SINR}_2$ while also increasing the smaller SINR. As such, we can conclude that $\text{SINR}_1 = \text{SINR}_2$ at the optimal solution.

Proposition 2: The optimal solution to problem (17) must be on the boundary of the feasible region.

Proof: This can be proved by contradiction. Suppose the optimal solution of (23) is (P_1^*, P_2^*) , which is in the interior of the feasible region. Then there exist a constant $\lambda = \min \left(\frac{P_d^{\max}}{P_1^*}, \frac{P_d^{\max}}{P_2^*}, \frac{\eta}{P_1^* |f_1|^2 + P_2^* |f_2|^2} \right) > 1$ such that $(\lambda P_1^*, \lambda P_2^*)$ is on the boundary of the feasible region. It is easy to see that the new solution satisfy

$$\begin{aligned} \frac{\lambda P_2^* P_r^*}{A_1 \lambda P_1^* + A_2 \lambda P_2^* + A_3} &= \frac{P_2^* P_r^*}{A_1 P_1^* + A_2 P_2^* + \frac{A_3}{\lambda}} \\ &> \frac{P_2^* P_r^*}{A_1 P_1^* + A_2 P_2^* + A_3} \quad \text{as } \lambda > 1, \end{aligned} \quad (18)$$

$$\begin{aligned} \frac{\lambda P_1^* P_r^*}{B_1 \lambda P_1^* + B_2 \lambda P_2^* + B_3} &= \frac{P_1^* P_r^*}{B_1 P_1^* + B_2 P_2^* + \frac{B_3}{\lambda}} \\ &> \frac{P_1^* P_r^*}{B_1 P_1^* + B_2 P_2^* + B_3} \quad \text{as } \lambda > 1, \end{aligned} \quad (19)$$

Since both SINRs are improved, the smaller SINR is improved. This contradicts the assumption that (P_1^*, P_2^*) is the optimal solution. Therefore, we can conclude the optimal solution must be on the boundary of the feasible region.

Since the boundary of the feasible region can be divided into three cases, we need to investigate each case separately.

CASE A: $P_1 = P_d^{\max}$. In this case, substituting $P_1 = P_d^{\max}$ into SINR_1 and SINR_2 and using $\text{SINR}_1 = \text{SINR}_2$, we can obtain

$$B_2 P_2^2 + [(B_1 - A_2) P_d^{\max} + B_3] P_2 - P_d^{\max} (A_1 P_d^{\max} + A_3) = 0. \quad (20)$$

It is easy to ascertain that this quadratic equation has only one positive solution. If this positive solution is less than or equal to P_d^{\max} and $\frac{\eta - P_d^{\max} |f_1|^2}{|f_2|^2}$, the optimal solution may be on this boundary. Otherwise, the optimal solution must not be on this boundary.

CASE B: $P_2 = P_d^{\max}$. In this case, substituting $P_2 = P_d^{\max}$ into SINR_1 and SINR_2 and using $\text{SINR}_1 = \text{SINR}_2$, we can obtain

$$A_1 P_1^2 + [(A_2 - B_1) P_d^{\max} + A_3] P_1 - P_d^{\max} (B_2 P_d^{\max} + B_3) = 0. \quad (21)$$

Similar to case A, this quadratic equation has only one positive solution. If this positive solution is less than or equal to P_d^{\max} and $\frac{\eta - P_d^{\max} |f_2|^2}{|f_1|^2}$, the optimal solution may be on this boundary. Otherwise, the optimal solution must not be on this boundary.

CASE C: $P_1 |f_1|^2 + P_2 |f_2|^2 = \eta$. In this case, substituting $P_1 = \frac{\eta - P_2 |f_2|^2}{|f_1|^2}$ into SINR_1 and SINR_2 and using $\text{SINR}_1 = \text{SINR}_2$, we can obtain

$$\begin{aligned} & (A_1 |f_2|^4 - B_2 |f_1|^4 - A_2 |f_1|^2 |f_2|^2 + B_1 |f_1|^2 |f_2|^2) P_2^2 \\ & - (2A_1 |f_2|^2 \eta + A_3 |f_1|^2 |f_2|^2 + B_3 |f_1|^4 - A_2 |f_1|^2 \eta \\ & + B_1 |f_1|^2 \eta) P_2 + A_1 \eta^2 + A_3 |f_1|^2 \eta = 0. \end{aligned} \quad (22)$$

By solving this quadratic equation, we can get one or two positive solutions for P_2 . For each positive solution of P_2 , we can obtain the corresponding P_1 . If the obtained P_1 is positive and both the obtained P_1 and P_2 are less than or equal to P_d^{\max} , the optimal solution may be on this boundary. Otherwise, the optimal solution must not be on this boundary.

Finally, we compare the obtained possible optimal solutions for the three boundary conditions. The solution that maximizes the objective function is the optimal solution.

B. MAXIMIZATION OF THE SUM-RATE

In this subsection, we formulate the power control problem as the maximization of the sum-rate of DU_1 and DU_2 . The optimization problem can be formulated as

$$\begin{aligned} & \max_{P_1, P_2} \log_2(1 + \text{SINR}_1) + \log_2(1 + \text{SINR}_2) \\ & \text{s.t. } 0 < P_1 |f_1|^2 + P_2 |f_2|^2 \leq \eta, \\ & \quad 0 < P_1, P_2 \leq P_d^{\max}. \end{aligned} \quad (23)$$

Since the objective function is non-convex, the standard convex optimization methods cannot directly be used to solve this problem. Note that the objective function has a difference of convex (D. C.) structure, we can use an efficient iterative algorithm to solve this problem. We denote $\mathbf{P} = [P_1, P_2]^T$, where superscript $(\cdot)^T$ denotes the transpose, and the objective function can be written as

$$\log_2(1 + \text{SINR}_1) + \log_2(1 + \text{SINR}_2) = f_1(\mathbf{P}) - f_2(\mathbf{P}), \quad (24)$$

where

$$\begin{aligned} f_1(\mathbf{P}) &= \log_2(A_1 P_1 + (A_2 + P_r^*) P_2 + A_3) \\ & \quad + \log_2((B_1 + P_r^*) P_1 + B_2 P_2 + B_3), \end{aligned}$$

and

$$\begin{aligned} f_2(\mathbf{P}) &= \log_2(A_1 P_1 + A_2 P_2 + A_3) \\ & \quad + \log_2(B_1 P_1 + B_2 P_2 + B_3). \end{aligned}$$

It is easy to verify that $f_1(\mathbf{P})$ and $f_2(\mathbf{P})$ are concave on \mathbf{P} , thus (24) is a D. C. function. Besides, the constraints in (23) are all linear. Thus, we can solve (23) based on D. C. programming.

Based on [30], the term $f_2(\mathbf{P})$ can be approximated by $f_2(\mathbf{P}^{(k)}) + \langle \nabla f_2(\mathbf{P}^{(k)}), \mathbf{P} - \mathbf{P}^{(k)} \rangle$ at point $\mathbf{P}^{(k)}$ by using the first order Taylor expansion, where $\langle \mathbf{x}, \mathbf{y} \rangle = \mathbf{x}^T \mathbf{y}$ denotes the inner product between vectors \mathbf{x} and \mathbf{y} , and $\nabla f_2(\mathbf{P}^{(k)})$ denotes the gradient of $f_2(\mathbf{P})$ at $\mathbf{P}^{(k)} = [P_1^{(k)}, P_2^{(k)}]^T$. Since the term $f_2(\mathbf{P})$ is linearized, the D. C. function (24) can be converted into a concave function. Then, we can select a feasible initial value $\mathbf{P}^{(0)}$ and obtain $\mathbf{P}^{(k+1)}$ at k -th iteration by the optimal solution of the following convex optimization problem:

$$\begin{aligned} & \max_{\mathbf{P}} \left\{ f_1(\mathbf{P}) - f_2(\mathbf{P}^{(k)}) - \langle \nabla f_2(\mathbf{P}^{(k)}), \mathbf{P} - \mathbf{P}^{(k)} \rangle \right\}, \\ & \text{s.t. } 0 < P_1 |f_1|^2 + P_2 |f_2|^2 \leq \eta, \\ & \quad 0 < P_1, P_2 \leq P_d^{\max}. \end{aligned} \quad (25)$$

This optimization problem can be solved by using standard convex optimization techniques, such as the interior-point method [28], [29]. The iterative algorithm is summarized in Algorithm 1.

Algorithm 1 Iterative Algorithm

- 1: Set $k = 0$, choose a feasible $\mathbf{P}^{(0)}$, $\varepsilon > 0$.
 - 2: **repeat**
 - 3: Solve convex optimization problem (25) to obtain the solution \mathbf{P}^* ;
 - 4: Set $k = k + 1$;
 - 5: Set $\mathbf{P}^{(k)} = \mathbf{P}^*$;
 - 6: Set $\mathbf{P}^{(k)} = \mathbf{P}^*$;
 - 7: **until** $\|\mathbf{P}^{(k)} - \mathbf{P}^{(k-1)}\| < \varepsilon$.
-

According to [30], the non-convex optimization problem (23) is well approximated by the convex optimization problem (25). Besides, the improved solutions always converge so that the iterative process stops after limited iterations.

IV. NUMERICAL AND SIMULATION RESULTS

In this section, we present some numerical and simulation results to validate our analysis. The simulation scenario is shown in Fig. 2, where the BS is located at the origin, CU and RU are located on the y-axis, and DU₁, RU and DU₂ are located in a straight line. The coordinates of CU, RU, DU₁, and DU₂ are given as (0, 200), (0, -d_{br}), (-d_{1r}, -d_{br}), and (d_{2r}, -d_{br}), respectively, where d_{br}, d_{1r}, and d_{2r} denote the distances between BS and RU, DU₁ and RU, and DU₂ and RU, respectively. Other basic simulation parameters are given as follows: N₀ = -100 dBm, P_b^{max} = 26 dBm, P_c^{max} = P_d^{max} = 20 dBm, and τ_u = 10 dB.




FIGURE 2. The simulation scenario.

We assume the channels comprise both Rayleigh fading and path loss, and the path loss exponent is assumed to be 4. We use Monte-Carlo simulations to get the average of the performance metric. For comparison, we also simulate the performance of equal transmit power scheme, i.e.,

$$P_1 = P_2 = \frac{\eta}{|f_1|^2 + |f_2|^2}. \tag{26}$$

Fig. 3 and Fig. 4 show the average minimum SINR at DU₁ and DU₂ with different locations of RU, DU₁ and DU₂.




FIGURE 3. The average minimum SINR at DU₁ and DU₂ with d_{1r} = d_{2r} = 60 m.




FIGURE 4. The average minimum SINR at DU₁ and DU₂ with d_{br} = 200 m and d_{2r} = 60 m.

In Fig. 3, we assume d_{1r} = d_{2r} = 60 m, and plot the average minimum SINR at DU₁ and DU₂ versus d_{br} for τ_d = 10 dB and 16 dB, respectively. From Fig. 3, we can see that the proposed optimal transmit power scheme performs about 1.5 dB better than the equal transmit power scheme. In Fig. 4, we assume d_{br} = 200 m and d_{2r} = 60 m, and plot the average minimum SINR at DU₁ and DU₂ versus d_{1r} for τ_d = 10 dB and 16 dB, respectively. From Fig. 4, we can see that the gap between the optimal transmit power scheme and the equal transmit power scheme becomes bigger and bigger as the difference between d_{1r} and d_{2r} increases. For example, when d_{1r} = 10 m, the proposed optimal transmit power scheme performs about 5 dB better than the equal transmit power scheme. Both Fig. 3 and Fig. 4 show that the proposed power control scheme can improve the performance of the minimum SINR at DU₁ and DU₂.

Fig. 5 and Fig. 6 illustrate the average sum-rate of DU₁ and DU₂ with different locations of RU, DU₁ and DU₂. In Fig. 5, we assume d_{1r} = d_{2r} = 60 m, and plot the average sum-rate




FIGURE 5. The average sum-rate of DU₁ and DU₂ with d_{1r} = d_{2r} = 60 m.




FIGURE 6. The average sum-rate of DU_1 and DU_2 with $d_{br} = 200$ m and $d_{2r} = 60$ m.

at DU_1 and DU_2 versus d_{br} for $\tau_d = 10$ dB and 16 dB, respectively. Fig. 5 shows that the proposed optimal transmit power scheme performs better than the equal transmit power scheme, but the benefits are not that great. In Fig. 6, we assume $d_{br} = 200$ m and $d_{2r} = 60$ m, and plot the average sum-rate at DU_1 and DU_2 versus d_{1r} for $\tau_d = 10$ dB and 16 dB, respectively. Fig. 6 shows that the gap between the optimal transmit power scheme and the equal transmit power scheme becomes bigger and bigger as the difference between d_{1r} and d_{2r} increases. For example, when $d_{1r} = 10$ m, the proposed optimal transmit power scheme performs more than 1 bps/Hz better than the equal transmit power scheme. Both Fig. 5 and Fig. 6 show that the proposed power control scheme can improve the performance of the sum-rate of DU_1 and DU_2 .

V. CONCLUSION

In this paper, we proposed a two-way AF relaying scheme to extend the range of D2D communications and investigated its power control problems, which were formulated as the maximization of the minimum SINR at D2D users or maximization of the sum-rate of D2D users while fulfilling the QoS requirement of the cellular link. For each optimization objective, we proposed the corresponding power control algorithm. It was shown by the simulation results that the proposed power control schemes present a better performance than the equal transmit power scheme. Note that this paper focuses on two-way AF relay assisted D2D communications, and we will extend this research to two-way DF relay in the future.

REFERENCES

- [1] *Study on Scenarios and Requirements for Next Generation Access Technologies*, document TR 38.913, 3GPP, V15.0.0, Jun. 2018.
- [2] J. G. Andrews, S. Buzzi, W. Choi, S. V. Hanly, A. Lozano, A. C. K. Soong, and J. C. Zhang, "What will 5G be?" *IEEE J. Sel. Areas Commun.*, vol. 32, no. 6, pp. 1065–1082, Jun. 2014.

- [3] A. Gupta and R. K. Jha, "A survey of 5G network: Architecture and emerging technologies," *IEEE Access*, vol. 3, pp. 1206–1232, 2015.
- [4] M. Agiwal, A. Roy, and N. Saxena, "Next generation 5G wireless networks: A comprehensive survey," *IEEE Commun. Surveys Tuts.*, vol. 18, no. 3, pp. 1617–1655, 3rd Quart., 2016.
- [5] Y. Liu, P. Roblin, X. Quan, W. Pan, S. Shao, and Y. Tang, "A full-duplex transceiver with two-stage analog cancellations for multipath self-interference," *IEEE Trans. Microw. Theory Techn.*, vol. 65, no. 12, pp. 5263–5273, Dec. 2017.
- [6] X. Quan, Y. Liu, D. Chen, S. Shao, Y. Tang, and K. Kang, "Blind nonlinear self-interference cancellation for wireless full-duplex transceivers," *IEEE Access*, vol. 6, pp. 37725–37737, 2018.
- [7] M. N. Tehrani, M. Uysal, and H. Yanikomeroglu, "Device-to-device communication in 5G cellular networks: Challenges, solutions, and future directions," *IEEE Commun. Mag.*, vol. 52, no. 5, pp. 86–92, May 2014.
- [8] A. Asadi, Q. Wang, and V. Mancuso, "A survey on device-to-device communication in cellular networks," *IEEE Commun. Surveys Tuts.*, vol. 16, no. 4, pp. 1801–1819, 4th Quart., 2014.
- [9] R. I. Ansari, C. Chrysostomou, S. A. Hassan, M. Guizani, S. Mumtaz, J. Rodriguez, and J. J. P. C. Rodrigues, "5G D2D networks: Techniques, challenges, and future prospects," *IEEE Syst. J.*, vol. 12, no. 4, pp. 3970–3984, Dec. 2018.
- [10] C.-H. Yu, K. Doppler, C. B. Ribeiro, and O. Tirkkonen, "Resource sharing optimization for Device-to-Device communication underlying cellular networks," *IEEE Trans. Wireless Commun.*, vol. 10, no. 8, pp. 2752–2763, Aug. 2011.
- [11] D. Feng, L. Lu, Y. Yuan-Wu, G. Y. Li, G. Feng, and S. Li, "Device-to-device communications underlying cellular networks," *IEEE Trans. Commun.*, vol. 61, no. 8, pp. 3541–3551, Aug. 2013.
- [12] N. Lee, X. Lin, J. G. Andrews, and R. W. Heath, "Power control for D2D underlaid cellular networks: Modeling, algorithms, and analysis," *IEEE J. Sel. Areas Commun.*, vol. 33, no. 1, pp. 1–13, Jan. 2015.
- [13] Y. Jiang, Q. Liu, F. Zheng, X. Gao, and X. You, "Energy-efficient joint resource allocation and power control for D2D communications," *IEEE Trans. Veh. Technol.*, vol. 65, no. 8, pp. 6119–6127, Aug. 2016.
- [14] M. Hasan, E. Hossain, and D. I. Kim, "Resource allocation under channel uncertainties for relay-aided Device-to-Device communication underlying LTE-A cellular networks," *IEEE Trans. Wireless Commun.*, vol. 13, no. 4, pp. 2322–2338, Apr. 2014.
- [15] R. Ma, Y.-J. Chang, H.-H. Chen, and C.-Y. Chiu, "On relay selection schemes for relay-assisted D2D communications in LTE-A systems," *IEEE Trans. Veh. Technol.*, vol. 66, no. 9, pp. 8303–8314, Sep. 2017.
- [16] R. Zhang, Y. Li, C.-X. Wang, Y. Ruan, and H. Zhang, "Performance tradeoff in relay aided D2D-cellular networks," *IEEE Trans. Veh. Technol.*, vol. 67, no. 10, pp. 10144–10149, Oct. 2018.
- [17] B. Rankov and A. Wittneben, "Spectral efficient protocols for half-duplex fading relay channels," *IEEE J. Sel. Areas Commun.*, vol. 25, no. 2, pp. 379–389, Feb. 2007.
- [18] Y. Han, S. H. Ting, C. K. Ho, and W. H. Chin, "Performance bounds for two-way amplify-and-forward relaying," *IEEE Trans. Wireless Commun.*, vol. 8, no. 1, pp. 432–439, Jan. 2009.
- [19] V. Havary-Nassab, S. Shabbazpanahi, and A. Grami, "Optimal distributed beamforming for two-way relay networks," *IEEE Trans. Signal Process.*, vol. 58, no. 3, pp. 1238–1250, Mar. 2010.
- [20] Y. Ni, S. Jin, R. Tian, K.-K. Wong, H. Zhu, and S. Shao, "Outage analysis for device-to-device communication assisted by two-way decode-and-forward relaying," in *Proc. Int. Conf. Wireless Commun. Signal Process.*, Hangzhou, China, Oct. 2013, pp. 1–6.
- [21] Y. Ni, S. Jin, K.-K. Wong, H. Zhu, and S. Shao, "Outage performances for device-to-device communication assisted by two-way amplify-and-forward relay protocol," in *Proc. IEEE Wireless Commun. Netw. Conf. (WCNC)*, Istanbul, Turkey, Apr. 2014, pp. 502–507.
- [22] K. Jayasinghe, P. Jayasinghe, N. Rajatheva, and M. Latva-Aho, "Linear precoder-decoder design of MIMO Device-to-Device communication underlying cellular communication," *IEEE Trans. Commun.*, vol. 62, no. 12, pp. 4304–4319, Dec. 2014.
- [23] L. Wei, R. Q. Hu, Y. Qian, and G. Wu, "Energy efficiency and spectrum efficiency of multihop Device-to-Device communications underlying cellular networks," *IEEE Trans. Veh. Technol.*, vol. 65, no. 1, pp. 367–380, Jan. 2016.
- [24] J. Huang and H. Gharavi, "Performance analysis of relay-based two-way D2D communications with network coding," *IEEE Trans. Veh. Technol.*, vol. 67, no. 7, pp. 6642–6646, Jul. 2018.

- [25] P. Khuntia and R. Hazra, "Device-to-device communication aided by two-way relay underlying cellular network," in *Proc. Int. Conf. Wireless Commun., Signal Process. Netw. (WiSPNET)*, Chennai, India, Mar. 2018, pp. 1–6.
- [26] C. Qing, B. Cai, Q. Yang, J. Wang, and C. Huang, "Deep learning for CSI feedback based on superimposed coding," *IEEE Access*, vol. 7, pp. 93723–93733, Jul. 2019.
- [27] C. Qing, B. Cai, Q. Yang, J. Wang, and C. Huang, "ELM-based superimposed CSI feedback for FDD massive MIMO system," *IEEE Access*, vol. 8, pp. 53408–53418, Mar. 2020.
- [28] S. Boyd and L. Vandenberghe, *Convex Optimization*. Cambridge, U.K.: Cambridge Univ. Press, 2004.
- [29] M. Grant and S. Boyd. (Dec. 2018). *CVX: MATLAB Software for Disciplined Convex Programming, Version 2.1*. [Online]. Available: <http://cvxr.com/cvx>
- [30] H. H. Kha, H. D. Tuan, and H. H. Nguyen, "Fast global optimal power allocation in wireless networks by local D.C. programming," *IEEE Trans. Wireless Commun.*, vol. 11, no. 2, pp. 510–515, Feb. 2012.



YUPENG LI (Member, IEEE) received the Ph.D. degree in communication and information systems from the Beijing University of Posts and Telecommunications (BUPT), Beijing, China, in 2015. He is currently an Associate Professor with the Tianjin Key Laboratory of Wireless Mobile Communications and Power Transmission, Tianjin Normal University (TJNU), Tianjin, China. His current research interests include advanced modulation schemes, optical access networks, and coherent optical communication systems.



LIANG HAN (Member, IEEE) received the B.S. degree in applied mathematics, and the M.S. and Ph.D. degrees in communication and information systems from the University of Electronic Science and Technology of China, Chengdu, China, in 2007, 2010, and 2013, respectively. Since 2014, he has been with the Tianjin Key Laboratory of Wireless Mobile Communications and Power Transmission, Tianjin Normal University, Tianjin, China, where he is currently an Associate Professor. From 2016 to 2017, he was a Postdoctoral Fellow of The University of Texas at Arlington, USA. His current research interests include full-duplex communications, D2D communications, and V2X communications.



BO ZHANG (Member, IEEE) received the B.Sc. degree from Tianjin Normal University, China, in 2011, and the M.Sc. and Ph.D. degrees from the Department of Electrical and Electronics Engineering, The University of Sheffield, in 2013 and 2018, respectively. He is working with the College of Electronics and Communication Engineering, Tianjin Normal University. His research interests include array signal processing (beamforming and direction of arrival estimation), directional modulation, sparse array design, and natural language processing.



RANRAN ZHOU is currently pursuing the master's degree with Tianjin Normal University, Tianjin, China. Her research interests include full-duplex communications, D2D communications, and cognitive radios.



XIN ZHANG (Member, IEEE) received the B.Sc. degree from Ludong University, in 2006, the M.Sc. degree from the Shandong University of Science and Technology, in 2009, and the Ph.D. degree from the City University of Hong Kong, in 2013. Since 2015, he has been with the Tianjin Key Laboratory of Wireless Mobile Communications and Power Transmission, Tianjin Normal University, Tianjin, China, where he is currently an Associate Professor. His main research interests include resource allocation, evolutionary computation, and machine intelligence.

...