

Received July 17, 2020, accepted August 21, 2020, date of publication August 26, 2020, date of current version October 5, 2020.

Digital Object Identifier 10.1109/ACCESS.2020.3019590

A Prospective Look: Key Enabling Technologies, Applications and Open Research Topics in 6G Networks

LINA BARIAH¹, (Member, IEEE), LINA MOHJAZI², (Senior Member, IEEE),
SAMI MUHAIDAT¹, (Senior Member, IEEE),
PASCHALIS C. SOFOTASIOS^{1,3}, (Senior Member, IEEE),
GUNES KARABULUT KURT⁴, (Senior Member, IEEE),
HALIM YANIKOMEROGLU⁵, (Fellow, IEEE),
AND OCTAVIA A. DOBRE⁶, (Fellow, IEEE)

¹KU Center for Cyber-Physical Systems, Department of Electrical and Computer Engineering, Khalifa University, Abu Dhabi, United Arab Emirates

²School of Engineering, University of Glasgow, Glasgow G12 8QQ, U.K.

³Department of Electrical Engineering, Tampere University, 33101 Tampere, Finland

⁴Electronics and Communication Engineering Department, Istanbul Technical University, 34469 Istanbul, Turkey

⁵Department of Systems and Computer Engineering, Carleton University, Ottawa, ON K1S 5B6, Canada

⁶Department of Electrical and Computer Engineering, Memorial University, St. John's, NL A1C 5S7, Canada

Corresponding author: Sami Muhaidat (muhaidat@ieee.org)

This work was supported in part by Khalifa University under Grant KU/FSU-8474000122 and Grant KU/RC1-C2PS-2/847400012237.

The work of Octavia A. Dobre was supported in part by Natural Sciences and Engineering Research Council of Canada (NSERC), through its Discovery Program.

ABSTRACT The fifth generation (5G) mobile networks are envisaged to enable a plethora of breakthrough advancements in wireless technologies, providing support of a diverse set of services over a single platform. While the deployment of 5G systems is scaling up globally, it is time to look ahead for beyond 5G systems. This is mainly driven by the emerging societal trends, calling for fully automated systems and intelligent services supported by extended reality and haptics communications. To accommodate the stringent requirements of their prospective applications, which are data-driven and defined by extremely low-latency, ultra-reliable, fast and seamless wireless connectivity, research initiatives are currently focusing on a progressive roadmap towards the sixth generation (6G) networks, which are expected to bring transformative changes to this premise. In this article, we shed light on some of the major enabling technologies for 6G, which are expected to revolutionize the fundamental architectures of cellular networks and provide multiple homogeneous artificial intelligence-empowered services, including distributed communications, control, computing, sensing, and energy, from its core to its end nodes. In particular, the present paper aims to answer several 6G framework related questions: What are the driving forces for the development of 6G? How will the enabling technologies of 6G differ from those in 5G? What kind of applications and interactions will they support which would not be supported by 5G? We address these questions by presenting a comprehensive study of the 6G vision and outlining seven of its disruptive technologies, i.e., mmWave communications, terahertz communications, optical wireless communications, programmable metasurfaces, drone-based communications, backscatter communications and tactile internet, as well as their potential applications. Then, by leveraging the state-of-the-art literature surveyed for each technology, we discuss the associated requirements, key challenges, and open research problems. These discussions are thereafter used to open up the horizon for future research directions.

INDEX TERMS 6G, backscatter communications, drone-based communications, terahertz communications, metasurfaces, mm-wave, optical wireless communications, tactile internet.

The associate editor coordinating the review of this manuscript and approving it for publication was Zihuai Lin.

I. INTRODUCTION

The phenomenal growth of connected devices and the increasing demand for high data rate services have been the main driving forces for the evolution of wireless technologies

in the past decades. A forecast study reported by the International Telecommunication Union demonstrates that the volume of mobile data will continue to grow at an exponential rate, reaching up to a remarkable figure of about 5 zettabytes per month in 2030 [1]. Meanwhile, due to the emergence of the Internet-of-Everything (IoE) paradigm, supporting smart homes, smart cities, and e-health applications seamlessly through connecting billions of people and devices over a single unified communication interface, there is an urgent need to shift the focus from the rate-centric enhanced mobile broadband services to ultra-reliable low-latency communications (URLLC) in order to provide a networked society through massive machine-type communications (MTC) [2], [3]. Besides generating massive data, the upsurge of IoE will naturally give rise to a myriad of new traffic and data service types, leading to diverse communication requirements. This grand vision requires a radical departure from the conventional “one-size-fits-all” network model of fourth generation systems.

The fifth generation (5G) of wireless technology represents a technological breakthrough with respect to the previous communication networks. In addition to reducing latency, enhancing connectivity and reliability, and achieving gigabits per second speeds, 5G is set to deliver a variety of service types, often characterized by conflicting requirements and diverse sets of key performance indicators, simultaneously over one platform [4]. These features make 5G a key enabler for the Internet-of-Things (IoTs) application environments, where machine-to-people (M2P) communications (e.g., industry automation, smart cities, and intelligent mobility) and machine-to-machine (M2M) communications (e.g., autonomous communications between sensors and actuators) are expected to take place alongside people-to-people communications, (e.g., voice over internet protocol (IP), video conferencing, video streaming, and web browsing).

Delivering a plethora of services, with profound differences in terms of quality of service (QoS) requirements, poses major challenges, such as the need to manage a huge volume of a mixture of human-type and machine-type traffic, which is heterogeneous in nature. To cater to these unique challenges, 5G deployment tends to adopt two main network functionalities, namely softwarization and virtualization [5], [6]. By jointly exploiting softwarization and virtualization, cognition and programmability of the end-to-end network chain may be achieved by decoupling the network functions from the hardware platform. This yields enhanced flexibility and reliability, as well as fast network auto-reconfiguration, enabling a larger portfolio of use cases and applications to be supported concurrently.

In parallel with addressing the aforementioned challenges, 5G has introduced potential disruptive technologies to meet stringent requirements in terms of capacity, connectivity, communication resilience, reliability, deployment costs, power consumption, latency, and data rate. These technologies include, but are not limited to, millimeter wave (mmWave) communications, massive multiple-input

TABLE 1. List of abbreviations.

Abbreviation	Definition
AI	Artificial Intelligence
AR	Augmented Reality
BackCom	Backscatter Communications
BS	Base Station
B5G	Beyond 5G
CAV	Connected and Autonomous Vehicle
CED	Cellular-Enabled Drones
CI	Communication Infrastructure
CR	Cognitive Radio
EM	Electromagnetic
IoE	Internet-of-Everything
IoT	Internet-of-Things
LED	Light-Emitting Diode
LiFi	Light Fidelity
LOS	Line-of-Sight
MEC	Multi-Access Edge Computing
MIMO	Multiple-Input Multiple-Output
mmWave	Millimeter Wave
MTC	Machine-type Communication
M2M	Machine-to-Machine
M2P	Machine-to-People
NLOS	non-LOS
NOMA	Non-Orthogonal Multiple Access
OCC	Optical Camera Communications
PU	Primary User
QoS	Quality of Service
RF-EH	Radio Frequency Energy Harvesting
SU	Secondary User
S-I	Signal-Idler
Si	Silicon
TI	Tactile Internet
THz	Terahertz
UAV	Unmanned Aerial Vehicle
UE	User Equipment
URLLC	Ultra-Reliable Low-Latency Communications
VLBC	Visible Light BackCom
VLC	Visible Light Communications
VR	Virtual Reality
WBSN	Wireless Body Sensor Network
WID	Wireless Infrastructure Drone
WiFi	Wireless Fidelity
WLAN	Wireless Local Area Network
WPAN	Wireless Personal Area Network
WPT	Wireless Power Transfer
XR	Extended Reality
5G	Fifth Generation
6G	Sixth Generation

multiple-output (MIMO), non-orthogonal multiple access (NOMA), and network ultra-densification [7], [8].

Despite the strong belief that 5G will support the basic MTC and URLLC related applications, it is arguable whether the capabilities of 5G systems will succeed in keeping the pace with the rapid proliferation of ultimately new IoE applications, which are expected to increase by 12% yearly, and which are enabled by massive connectivity and are based on data-centric and automated processes. Meanwhile, following the revolutionary changes in the individual and societal trends, in addition to the noticeable advancement in human-machine interaction technologies, the market demands by 2030 are envisaged to witness the penetration of a new spectrum of IoE services. These services span

from *extended reality* (XR), which comprises *augmented reality* (AR), *virtual reality* (VR), and *mixed reality* services, to flying vehicles, haptics, telemedicine, autonomous systems, and human-machine interfaces. The unprecedented requirements imposed by these services, such as delivering ultra-high reliability, extremely high data rates, and ultra-low latency simultaneously over uplink and downlink, will push the performance of 5G systems to its limits within 10 years of its launch, as speculated in [9]. Moreover, the emergence of such new IoE services necessitates integrating the computing, control, and communication functionalities into a single network design.

In order to deliver future cutting-edge services and accommodate their aforementioned heterogeneous requirements, a new breed of challenges have to be effectively addressed. Examples of these challenges include leveraging sub-terahertz (THz) bands, governing the network performance set by a targeted rate-reliability-latency trade-off, provisioning flexibility in the network architecture and functionalities, and designing an intelligent holistic orchestration platform to coordinate all network resource aspects, including communication, control, computing, and sensing, in an efficient, self-sustainable, and scalable manner, which is tailored to the demands of a specific application scenario or use case [10]–[13].

A. 6G VISION AND REQUIREMENTS

The evolution of 5G has urged the conceptualization of beyond 5G (B5G) wireless systems, including the sixth generation (6G), which should be capable of unleashing the full potentials of abundant autonomous services comprising past, as well as emerging trends. More precisely, 6G is envisioned to bring novel disruptive wireless technologies and innovative network architecture into perspective. It is further envisaged that 6G will ultimately realize the next-generation connectivity, driven by the evolution from *connected everything* to *connected intelligence*, thus enabling “Human-Thing-Intelligence” interconnectivity. Additionally, it will support high-precision communications for tactile and haptic applications in order to provide the required sensory experience at different levels, including smell, touch, vision, and hearing [14]. The key technical requirements to realize this vision include:

- Offering extreme data rates to address the corresponding massive-scale connectivity aspect and to provide ultra-high throughput, even in extreme conditions or emergency scenarios, where varying device densities, spectrum and infrastructure availability, as well as traffic patterns may exist.
- Achieving the targeted quality of immersion and per-user capacity and offering a unified quality of experience required by AR and VR applications, which will hit retail, tourism, education, etc.
- Delivering real-time tactile feedback with sub-millisecond (ms) latency to fulfill the requirements of haptic applications, such as e-health.

- Incorporating artificial intelligence (AI) to support seamless data-centric context-aware communications for controlling environments such as smart structures, autonomous transportation systems, and smart industry [15].
- Meeting the extremely high levels of communication reliability (e.g., more than 99.9999%) and the low end-to-end latency to support ultra-high mobility scenarios, such as flying vehicles.

The envisioned 6G requirements, technologies and applications are presented in Fig. 1.

B. RELATED WORK AND CONTRIBUTIONS

While 5G services have begun to roll out across markets, interest in 6G trends has already gained significant momentum both in academia and industry. Several research studies have appeared in the recent literature reporting key technological trends and new research directions that would bring 6G into reality, for example, see [9]–[13], [16]–[21]. In [9], the authors presented a speculative study on the main use cases that are expected to be brought by 6G and discussed their associated challenges and the potential enabling technologies. The authors in [10] presented a vision of some potential 6G applications and trends, and discussed the associated service classes and their performance requirements. Additionally, they briefly listed their enabling technologies and pointed out some key open research avenues. In [11], the authors presented an overview of a number of potential 6G revolutionary technologies and the associated network architectural innovations that are envisioned to address the shortcomings of 5G systems. Likewise, the authors in [12] delivered a roadmap towards enabling AI in 6G. In particular, they discussed key AI methodologies that can play a central role in the design and optimization of 6G networks. In [13], the authors highlighted that in order to support future use cases, the current communication infrastructure has to evolve at both physical and architectural levels. They also discussed the need to develop mechanisms for enabling a holistic resource management platform and described the resulting challenges in terms of privacy and security. In [17], the authors investigated the 6G vision from the economic standpoint, where they compared the previous wireless generations to the envisioned 6G networks, and predicted that 6G networks will offer a cost reduction by 1000 times, when compared to 5G mobile networks. Moreover, they demonstrated the role of AI towards accomplishing this vision. In the same context, the authors in [18] presented the new themes that are likely to emerge and shape the future 6G wireless networks, such as human-machine interface, universal local and cloud computing, multi-sensory data fusion and precision sensing. Furthermore, they emphasized on the potential of AI as the foundation of 6G networks, in addition to transformative 6G technologies, such as spectrum sharing techniques, novel network architectures, and new security mechanisms. The contribution in [19] outlines the envisioned new use cases of 6G networks in addition to the revealed paradigms




FIGURE 1. 6G vision: requirements, technologies and applications.

of future wireless networks, including the new radio frontier, micro-service network architecture, deterministic services, and network automation. In [20], the authors re-stated the 6G vision, trends, requirements and challenges. In particular, they provided an in-depth discussion about future 6G methods, including the integration of terrestrial and satellite communications, new spectrum utilization, modulation schemes, AI, and intelligent mobility management. Dong *et al.* in [21] provided a framework to define the expected future applications and outline the required technologies and anticipated challenges. Finally, the authors in [16] presented a vision of 6G and its requirements. With respect to users' perspectives, they also identified innovations that need to be considered towards realizing this vision.

It is noted that the aforementioned reported contributions mainly take a rather use cases-centric approach to the roadmap of 6G era with a focus on the associated services and technological trends. Conversely, in this survey, we approach the 6G vision from the angle of enabling technologies that manifest themselves as the paradigms needed for the realization of 6G. Specifically, we present an in-depth conceptual overview of the main revolutionary technologies in a holistic manner, taking into explicit account the key drivers, performance metrics, and major ongoing research for every single technology. Apart from the technologies discussed in the previous surveys, which are reviewed here in detail, we shed light on additional innovative technologies, such

as mmWave communications, THz communications, optical wireless communications, metasurfaces (also known as intelligent reflective surfaces), backscatter communications (BackCom), tactile internet (TI), and aerial networks, which are envisaged to ultimately promote the 6G revolution. This survey also delves into the emerging applications of each technology and identifies their associated challenges. This discussion is used to provide a directional guidance towards future research work.

The remainder of the article is organized as follows: In Section II, we present a comprehensive overview of five disruptive 6G technologies. This is followed by outlining some of their potential applications in Section III, whereas Section IV highlights the fundamental challenges associated with each technology discussed in Section II. Finally, the article is concluded in Section V.

II. KEY ENABLING TECHNOLOGIES FOR 6G NETWORKS

Future 6G systems will require the support of novel technologies to enable unprecedented functionalities in the network. These technologies are envisioned to introduce a plethora of new applications associated with remarkably stringent requirements in terms of latency, reliability, energy, efficiency, and capacity, compared to their 5G counterparts. In this section, we provide a concrete conceptual background of major disruptive technologies that will shape the future 6G networks, which includes mmWave

communications, THz communications, OWC, programmable metasurfaces, drone-based communications, BackCom, and TI.

A. MILLIMETER-WAVE AND TERAHERTZ COMMUNICATIONS

One of the key challenges towards realizing 6G networks is the scarcity of spectrum, owing to the unprecedented broadband penetration rate and the emergence of new use cases with rigorous bandwidth requirements. In a recent meeting, 3GPP introduced many new features for the upcoming 3GPP-Rel. 17 towards the evolution of 5G New Radio. Most notably, the enhancement of the physical layer through the support of frequency bands beyond 52.6 GHz, up to 71 GHz. To this effect, it is envisioned that future releases will go beyond this range towards the THz band [22]. Yet, there are several challenges that must be addressed in order to realize this vision. Specifically, the current PHY-layer, which has been mainly optimized for bands below 52.6 GHz, has to be technically redesigned and redeveloped.

1) MILLIMETER-WAVE COMMUNICATIONS

Millimeter-wave (mmWave) communications operate over the 30-300 GHz frequency band, with a corresponding wavelength ranging from 10 to 1 mm [23]. Thanks to the short wavelength, mmWave communications allow the realization of small-sized antenna arrays with a large number of elements in a small physical dimension. Accordingly, narrow directional beam can be achieved, yielding multipath reflection suppression [24], high immunity against jamming and eavesdropping attacks [25], as well as robustness to co-user interference, since the involved wireless channels will be largely uncorrelated. Due to these promising potentials, several activities were carried out to standardize the mmWave technology. In particular, mmWave communication was introduced in IEEE 802.11ad and IEEE 802.15.3c standards [26]. The specifications of mmWave communications are summarized in Table 2.

Nevertheless, despite the undoubted advantages of mmWave communications, there are still many associated challenges that need to be addressed prior to effective design, and successful deployment and operation. For example, small-sized components manufacturing constitutes a major challenge, due to the increased manufacturing cost. Moreover, severe signal attenuation (as high as 15 dB/km degradation [27]), caused by strong atmospheric absorption, limits the transmission range of mmWave communications to few kilometers.

2) STATE-OF-THE-ART

Wireless links in mmWave systems are extremely prone to obstacles blockage (including humans), especially when the physical size of the obstacles is greater than that of the wavelength, which is in general short in mmWave communications. In particular, it was shown that a human blockage can cause 20-30 dB degradation in the mmWave link.

TABLE 2. mmWave communications specifications.

Parameters	mmWave
Data rate	≥ 10 Gbps
Latency	≤ 1 ms
Transmission range	Hundreds of meters to a couple of kilometers
Channel bandwidth	Up to 2.16 GHz
Mobility	≤ 100 km/hr

Motivated by this, several research efforts have been devoted on developing blockage control or scheduling protocols to minimize the effect of blockage in mmWave transmissions. For example, the authors in [28] utilized multiple relays with optimum relay selection and scheduling schemes to steer the signal around obstacles, and hence, to minimize incurred signal blockages. In [29], the authors addressed the issue of blockage by proposing a proactive base station (BS) selection scheme based on human blockage prediction, where they utilized RGB depth cameras to estimate the location and velocity of a passing pedestrian, and consequently, estimating the time when the pedestrian blocks the line-of-sight (LOS) component of a mmWave link. In the same context, several other research contributions have investigated the blockage issue in mmWave systems, e.g., [30]–[32].

In addition to the above, there has recently been a vast attention on the application of non-orthogonal multiple access (NOMA) in the context of mmWave communication scenarios [33]–[42]. In particular, the research activity in NOMA-based mmWave systems is mainly directed towards investigating the secrecy rate of these systems, in addition to their performance in different realistic communication scenarios, such as drone-based communications, massive MIMO, simultaneous wireless information and power transfer (SWIPT) and M2M communications.

Other relevant research directions are focused on the areas of mmWave channel modeling [43]–[47], transceiver design [48]–[52] and antenna design [53]–[58]. The core research directions in mmWave wireless systems are summarized in Table 3.

TABLE 3. Research directions in mmWave wireless systems.

Research direction	Refs.
Blockage control	[28]–[32]
NOMA-based mmWave	[33]–[40]
Channel modeling	[43]–[47]
Transceiver design	[48]–[52]
Antenna design	[53]–[58]

3) TERAHERTZ COMMUNICATIONS

As noted earlier, a promising solution to the current spectrum crunch is to explore the THz-band, which is envisioned to bridge the gap between the mmWave band and infrared light-waves (optical communications), by providing a considerably wider bandwidth and enabling the development of new use cases with high data rates requirements. In addition

to extending the bandwidth, THz communications offer an amplified gain due to the shorter wavelength experienced at these bands, allowing for the deployment of a large number of antennas.

On the other hand, THz based communications require rethinking of existing solutions and investigate novel approaches that offer a seamless operation over the entire THz band. For example, the design of efficient beamforming and tracking techniques that are able to dynamically and precisely track down the location of THz-enabled devices is of great importance, and an open research problem. Other open issues include hardware architecture design and the integration of massive MIMO and intelligent surfaces. An overview of the opportunities and challenges associated with THz communications is given in [59].

4) STATE-OF-THE-ART

Motivated by the important role of THz modulators in enabling THz technology in future wireless systems, the performance of several amplitude and phase modulators was examined for various materials and fabrication processes [60]–[67]. For example, silicon (Si) substrates, coated with effective materials such as gold [60] and manganese iron oxide [61], as well as graphene-based modulators [68], [69] are proven to offer a performance enhancement to the THz modulators by extending the transmission range and pumping power density, in addition to their tunability and high-speed characteristics. Nevertheless, the main drawbacks of these nano-particle-based THz modulators are the high cost and the increased complexity. On the contrary, graphene-based modulators suffer from a low modulation depth and high energy consumption.

The implementation of THz communications in outdoor environments is rather challenging, which is particularly due to the inevitable loss caused by molecular absorption and other atmospheric conditions, such as rain [70]. Accordingly, THz transceiver and antenna designs have to be thoroughly investigated prior to the effective design and deployment of these systems. To this end, antenna and transceiver designs have attracted great interests in the research community [71]–[84]. Specifically, the development of Si-germanium signal generators, quantum cascade laser photonic sources, compact graphene antennas and graphene/liquid crystal based phase shifters are some of the reported research work in the field of THz transceiver and antenna designs [85].

Moreover, channel modeling is vital in THz communications in order to ensure reliability and high spectral efficiency. Existing research is focusing on the characterization of LOS and non-LOS (NLOS) components, with emphasis on scattering properties for the NLOS component and free space loss, molecular absorption and harsh weather conditions for the LOS component. In particular, research efforts are mainly centered around characterizing channel coefficients for deterministic and statistical conditions in indoor and outdoor environments. Ray-tracing is a reliable

method for modeling LOS and NLOS components and is utilized extensively to characterize the deterministic and stochastic channel coefficients. For instance, in [86]–[92], the authors proposed efficient propagation deterministic models for THz nano-communications while incorporating the LOS and NLOS components for 2D and 3D scenarios. Although deterministic models provide higher accuracy in describing channel coefficients compared to stochastic models, the underlying high computational complexity and the required geometrical information of the propagation environment are critical drawbacks of such models. On the other hand, statistical characterization of THz channels is rather challenging, especially when taking into account channel mobility, channel state information estimation, and channel correlation. The recent advancements in the design of THz communications systems are summarized in Table 4.

TABLE 4. Advancements in the design of THz wireless systems.

Design aspects	Refs.
THz modulator	[60]–[67]
Antenna design	[71]–[78]
Transceiver design	[79]–[84]
Channel modeling	[86]–[100]

B. OPTICAL WIRELESS COMMUNICATIONS

Optical wireless communication (OWC) systems has emerged as a key technology for 6G networks and beyond, enabling broadband connectivity. There has been an increasing interest in OWC with terrestrial, space and underwater applications. This interest is stimulated by the advancement in solid state optical technology, in addition to the promising features of OWC. These features include ultra-high bandwidth, inherent physical layer security, spatial reuse, ultra-low latency, high data rates, immunity to interference, and low cost, hence, fulfilling the demanding requirements of beyond 5G wireless networks [101]. It is recalled that information in OWC is carried over optical links, whose wavelengths vary between infrared and ultraviolet, including the visible light. OWC systems in the infrared frequency range enables long-range data transmission over high-speed wireless links, which are often encountered in wireless backhaul networks [102]. In the following, we summarize the most common OWC technologies.

Visible light communication (VLC) has emerged as a prominent technology that is anticipated to offer high-speed indoor connectivity. In VLC systems, light-emitting diodes (LEDs)/laser diodes (LDs) are used as transmitters while the receivers consist of photodetectors (PDs) [103], [104]. The transmission range of VLC can reach up to 20 m, with data rates of 10 Gbps and 100 Gbps, when using LEDs and LDs, respectively [105]. Furthermore, low-complexity implementation in VLC scenarios can be realized by using LEDs, where extra power supplies are not required. In this case, LEDs can be utilized to perform illumination, communication and localization simultaneously [104], [105].

Light-Fidelity (LiFi), a promising optical solution that is envisioned to complement wireless fidelity (WiFi), is a subset of OWCs that realizes bidirectional and high-speed wireless communication [106]. LiFi leverages visible light in downlink to realize illumination as well as wireless communication, and infrared or RF in uplink. Similar to VLC, LiFi communication systems depend on LEDs and PDs as transmitters and receivers, respectively [107].

Optical camera communication (OCC), is another promising OWC technology, which is mainly used for positioning and navigation in indoor environments. An OCC receiver consists of embedded cameras or image sensors, while transmitter is a typical commercial LED [108]. Moreover, OCC spectrum spans between the infrared and ultraviolet bands, with wavelength in the range of 10,000 nm [109]. Due to the wide spread of smartphone devices with sophisticated embedded cameras, OCC can be easily implemented in these smart devices, rendering it as the practical version of VLC.

Free space optical (FSO) communication, which takes place in the near infrared, is considered an effective approach in realizing high data rate communications over several kilometers [110]. For example, for reasonable distances (around 1 km), FSO can achieve data rates in the order of 10 Gbps [111]. High frequency reuse factor, physical security, and robustness against electromagnetic interference are other advantages exhibited by FSO systems, when restricting the use of a very narrow laser beam at the transmitter side [112].

1) STATE-OF-THE-ART

Despite their superior features, OWC systems are impaired by several factors that have detrimental effects on their performance, such as ambient light noise, nonlinearity of LEDs, etc. The authors in [113]–[120] quantified the effect of ambient light noise on the performance of different optical systems, and presented efficient solutions to enhance the performance of OWC in the presence of ambient light noise. Atmospheric loss represents another major challenge in OWC, and severely degrades the performance of OWC systems in indoor and outdoor environments. Particularly, free space loss is dominating in indoor scenarios, while path loss and atmospheric turbulence are the main affecting factors on the performance of outdoor OWC. Research works in [121]–[130] investigated the effect of atmospheric loss on the performance of OWC systems. Moreover, OWC performance is vulnerable to pointing errors, which is caused by the horizontal movement of high buildings due to thermal expansion, weak earthquakes and wind [131]. Due to pointing errors, transmitters and receivers in OWC may experience misalignment, resulting in the degradation of the system performance. The consequences of pointing errors on OWC systems under different scenarios have been thoroughly investigated in the literature, e.g., [132]–[138]. A summary of the research efforts in OWC impairments is provided in Table 5.

TABLE 5. Research in OWC impairments.

Impairment	Refs.
Ambient light	[113]–[120]
Atmospheric loss	[121]–[130]
Pointing errors	[132]–[138]

C. PROGRAMMABLE METASURFACES FOR WIRELESS COMMUNICATIONS

The mmWave and THz communications are envisioned as key enablers for 6G systems. They are expected to satisfy the stringent requirements of various potential 6G use cases by exploiting higher frequency bands. However, owing to the severe attenuation and scattering properties, the detrimental effects on communication efficiency remains the grand challenge in wireless communications. For example, small and large objects in indoor environments, e.g., walls and furniture, typically scatter rays in all directions, leading to severe multipath propagation environments. The Doppler effect is another key challenge, which can limit the realization of ultra-broadband communications, particularly in the mmWave and THz bands [139]. Existing solutions mainly rely on device-side approaches, which consider the wireless environment to be uncontrollable and hence, it remains unaware of the on-going communication processes.

1) METASURFACES

Metasurfaces have recently emerged as an innovative technology, which is envisioned to revolutionize wireless communications by allowing wireless system designers to fully manipulate the propagation of electromagnetic (EM) waves in a wireless link. The building block of a metasurface is a meta-atom, which is an artificial conductive structure with engineered EM properties that is repeated periodically across a rectangular surface (also called tile). At the macroscopic level, metasurfaces exhibit unique EM properties such as customized permittivity and permeability levels, and negative refraction [140]. As a consequence, metasurfaces enable unprecedented capabilities when interacting with impinging EM waves, which include wave focusing, absorption, imaging, scattering, polarization, to name but a few [140]. It is worth mentioning that metasurfaces leverage these unique abilities without any limitation on their operating frequency.

Recently, there has been a steadily growing interest in both industry and academia on tunable metasurfaces, also called programmable metasurfaces. In this context, the meta-atom design can be dynamically altered through a simple external stimuli, such as a binary switch, empowering metasurfaces with unique adaptivity. More specifically, dynamic meta-atoms are fitted with tunable switching components, such as micro-electro-mechanical switches or CMOS transistors, which can alter the structure of the meta-atoms. This allows metasurface tiles to receive commands from an external programming interface, where parameters of the incident and reflected waves, e.g., phase, amplitude, frequency, and

polarization, are carefully manipulated in order to enable the EM behavior of interest [139]. Moreover, the discovery of communicating nodes in the surrounding wireless environment can be realized by equipping the metasurface tile with efficient sensing and reporting features.

Tunable mechanisms of metasurfaces facilitate massive connectivity, interference mitigation, and enhanced diversity by introducing an additional degree of freedom. These tunable features are essential in order to realize the flexibility needed for future wireless communications. The authors in [141] presented the first model to describe a programmable wireless indoor environment using programmable metasurfaces. The introduction of programmatically controlled wireless environments has undeniably opened the door for a broad range of functionalities to be ultimately achieved even at the mmWave and THz bands. Some metasurface functionalities are summarized as follows:

- *Beam steering*: This function can be achieved by allowing a metasurface to change the direction of the impinging wave towards the desired direction through manipulating either the refraction or reflection index which can override the outgoing directions defined by the Snell's Law [139].
- *Beam splitting*: In this function, a metasurface tile splits an incident wave into customized orthogonal multiple beams steered towards multiple directions to serve multiple users simultaneously [141].
- *Wave absorption*: Blocking the access of an unauthorized wireless device can be accomplished by adjusting the properties of the metasurfaces to ensure no or minimal reflection or refraction of the incident wave. This functionality can be utilized to prevent eavesdropping and optimize the network physical-layer security. As demonstrated in [142], for a given incident wave, metasurfaces are able to reduce the wave power by 35 dB.
- *Wave polarization*: This function allows a metasurface to fully control the polarization of impinging waves and manipulate their oscillation orientation [141].
- *Phase control*: This functionality of metasurfaces allows for the alteration of the carrier phase [141].

2) ARTIFICIAL INTELLIGENCE (AI)-EMPOWERED METASURFACES

To facilitate simultaneous functionalities within an uninterrupted connectivity, AI tools are envisioned to be indispensable in programmable metasurfaces as they enable the identification of the best operation policy based on data driven techniques [143], [144]. Leveraging AI is particularly attractive in heterogeneous wireless applications, with diverse networks, and QoS user requirements, as it can potentially provide an efficient and dynamic means to adapt network parameters, such as coding rate, route selection, frequency band, and symbol modulation.

Machine learning (ML)-enabled solutions, which are a subfield of AI, are expected to be a core component in

smart programmable metasurfaces, allowing them to achieve a complex level of coordination, and thereby maintaining a desired global behavior while ensuring scalability, energy and overhead reduction [144]. In this setup, a metasurface interface can be empowered with intelligence by applying novel data processing paradigms that can learn from data and perform functionalities to complete complex tasks efficiently. This would support self-organization and automation of all metasurface functions, including maintenance, management, and operational tasks. A recent research study proposed a deep learning (DL)-based ML approach to achieve signal focusing through learning the mapping between the estimated channel state information (CSI) at a user location and the optimal configuration of the metasurface's unit cell [145]. Furthermore, adaptive control and coordination of multiple metasurfaces in programmable wireless environments was demonstrated for a set of users through the application of neural networks [146]. More recently, convolutional neural network approaches were proven to exhibit their merit for beamforming by learning the physics of the beamforming from computed data to make online prediction of the coding matrices, to fulfill the network requirements [147]. Additionally, the principle of ML-enabled imager was proposed for programmable metasurfaces to produce high-quality EM imaging and high-accuracy object recognition [148]. The results are promising in real-time compressed imaging applications in the microwave, millimeter-wave, and THz frequencies [148].

3) STATE-OF-THE-ART

Programmable metasurfaces have recently attracted a large attention of the international scientific community. In particular, a number of research studies examined the potentials of programmable metasurfaces as modulators [149]–[153]. Furthermore, the research works in [154]–[157] investigated the design of smart beamforming in metasurface-based wireless secrecy communication systems. Researchers also explored the use of metasurfaces in wireless power transfer (WPT) [158]–[160]. The role of machine learning in controlling the functionalities of metasurfaces to actively improve the coverage of the highly dynamic indoor environments is analyzed in [161]–[163]. The aforementioned state-of-the-art is summarized in Table 6.

TABLE 6. Advancements in metasurfaces.

Addressed Schemes	Refs.
Modulation	[149]–[153]
Beamforming	[154]–[157]
Wireless power transfer (WPT)	[158]–[160]
Machine learning	[161]–[163]

D. DRONE-BASED COMMUNICATIONS AND AUTONOMOUS SYSTEMS

A key driving force behind the vision of 6G is the deployment of connected and autonomous vehicle (CAV) systems and




FIGURE 2. Advantages, categories, applications, and challenges of drone-based systems.

drone-based communications. The research efforts in CAV and drone (also known as unmanned aerial vehicles (UAVs))-based communication systems, have been steadily growing in both academia and industry, targeting strict requirements, particularly ultra-low latency and unprecedented communication reliability. The advantages, categories, applications, and challenges of drone-based systems are depicted in Fig. 2. In the following, we focus our attention on the current and futuristic application scenarios of UAVs, as well as the state-of-the-art. An in-depth discussion of the underlying challenges is then provided in the following section.

1) DRONE-ASSISTED WIRELESS COMMUNICATIONS

Drones constitute the basic building block of aerial networks, whose inherent features, such as mobility and flexibility, enable several imminent and futuristic applications in wireless networks [164]. It is shown that the use of drones can significantly improve the coverage and transmission rates [165]. Furthermore, standardization activities led by 3GPP are currently ongoing to adapt the necessary changes in order to integrate drones in the future wireless networks [166].

Drone-assisted wireless communications can be categorized as follows:

a: CELLULAR-ENABLED DRONES (CED)

CEDs are operated as user equipments (UEs) (i.e., drone-UEs) in order to enable several key applications such as mining, oil and gas, transportation, surveying and monitoring, with a velocity of 160 km/h in urban and rural environments [167]. To ensure connectivity with cellular networks, several essential requirements, which include reliable and low-latency communications between the drone-UEs and

ground BSs, have to be met. User-centric cell-free massive MIMO, also known as distributed massive MIMO, was recently proposed as a prominent solution to efficiently increase the system coverage and energy efficiency of aerial networks [168], [169]. By efficiently utilizing cell-free massive MIMO, in which massive number of antennas are distributed over a wide area to serve multiple drone-UEs, the effect of large scale fading becomes less as all users approximately have equal distances to the allocated access point. This is beneficial for cell-edge users who experience severe large scale fading. Recent results showed that the utilization of cell-free massive MIMO architecture brings substantial benefits to the performance of drone-UEs, compared to multi-cell massive MIMO, as inter-cell interference is eliminated in the former [170]. In some applications, drone-UEs will require high-speed connectivity from ground BSs or from drone-BSs (i.e., drones operating as BSs). It should be pointed out that nowadays cellular networks are designed for ground users with unique mobility and traffic characteristics that are considerably distinct from those experienced with drone-UEs. Therefore, the integration of drone-UEs into cellular networks in a single wireless network presents a set of new key challenges and design considerations that must be addressed for the efficient realization and successful deployment of CEDs [171].

b: WIRELESS INFRASTRUCTURE DRONES (WIDs)

WIDs are intended to extend the network capabilities by enhancing network coverage or capacity. WIDs can be further classified based on their functionalities into:

- *Drone-BSs*: Drone-BSs are aerial nodes with some BS features and functionalities, that are envisioned to

provide capacity and coverage enhancements for 6G networks. They are cost-effective solutions that render wireless connectivity to hard-to-reach areas, as well as geographical areas with limited cellular infrastructure. Drone-BSs are also attractive solutions for delivering reliable, broadband and wide-scale temporary wireless connectivity in special events or harsh scenarios, such as sport events and natural disasters. Furthermore, high altitude drone-BSs are expected to provide a long-term and cost effective connectivity for rural areas. The integration of drone-BSs with other physical layer techniques such as mmWave and massive MIMO, cognitive radios, etc., is a promising solution to provide data-hungry services and is expected to create a new set of challenges for the next generation of flying BSs [171]. Optimal positioning of the drone-BSs is one of the critical challenges that needs to be addressed in dense deployment scenarios [172].

- *Aerial Relays*: Relaying has been extensively investigated in the context of terrestrial communications aiming to enhance network reliability, throughput, and coverage. However, such relays are subject to limited mobility and often are constrained by wired backhauling [173]. On the contrary, drones acting as wireless relays, are versatile and offer high mobility. This feature makes them a promising candidate for providing enhanced wireless connectivity beyond LOS. Moreover, aerial relays can play a significant role in extending the battery life of drones [174].
- *Aerial Backhaul for Cellular Networks*: Wireless back-hauling has been shown to provide a cost-effective solution compared to wired backhauling. However, it is subject to interference, blockage and path loss, which can significantly degrade the performance and reduce the data rate [175]. In this respect, drone-based networks are foreseen to play a fundamental role in achieving robust and high-speed backhaul connectivity for cellular networks [176]. Such networks are expected to provide flexible drone-based backhaul communications that will enhance the network capacity, reliability, as well as the operation cost [171].

2) AIR-GROUND-SPACE INTEGRATED Networks

There is a strong belief that existing terrestrial, aerial and satellite networks will not be able to cope with the massive volume of generated data, which will continue to grow at an exponential rate together with the rapid proliferation of new IoE applications. On the other hand, the integration of these networks is viewed as the next evolution of wireless infrastructure, that is envisioned to cater to diverse use cases with different QoS requirements, particularly in realistic scenarios such as urban, rural, and lightly dense areas. Yet, despite their indispensable benefits, the envisioned integrated architecture will introduce unprecedented challenges that include, but are not limited to, heterogeneity, security, resource

management, self-organization, energy consumption, and backhauling [177].

3) DRONE-BASED MULTI-ACCESS EDGE COMPUTING

Multi-access edge computing (MEC), enables cloud computing capabilities at the edge of cellular networks, and has recently emerged as one of the potential technologies for 5G networks. In particular, MEC enables mobile devices with limited resources to offload their computation tasks to the edge of the network.

In drone-enabled networks, mobile devices can offload their computationally demanding tasks to drones with MEC capabilities, typically at the edge of the network, thus reducing the network congestion and allowing for the rapid deployment of new applications. Additionally, the drone-based network can provide an effective mobility management without the necessity of handover, as well as uninterrupted MEC services for high mobility users, due to their large-scale coverage and LOS connection [178], [179].

Within the same context, the limited on-board processing capabilities of drones, which are mainly due to their storage and battery constraints, bring about several concerns towards the efficient execution of complex tasks [180]. In particular, heavy computation demanding applications, such as real-time image processing, may not be supported by the anticipated vision of drones. Recent research efforts proposed efficient techniques to tackle these limitations by leveraging cloud computing to offload the computation-intensive tasks from the drones to remote cloud servers [181]. The role of these servers can be summarized as follows [182]:

- *Storage*: Storage services can be offered by the cloud to store drones data streams that include environment and mission-related parameters, captured images and sensed data.
- *Computation*: Intensive computations are executed in the cloud in order to minimize the processing time and energy consumption at the drone. Moreover, the large amount of stored data from the drones can be exploited to perform data analytic tasks in order to enhance the performance of drones-enabled networks, in terms of trajectory adaptation, altitude optimization, and energy consumption customization, in an intelligent manner.

4) SWIPT-ENABLED DRONES

Short built-in battery lifetime restricts the utilization of drones in numerous applications, due to the limited size and weight of drones, which results in a limited energy storage, and consequently, short cruising duration. Aiming to prolong the system's lifetime, trajectory design, location adjustment, and power allocation optimization approaches have been proposed in the literature as promising mechanisms to overcome the energy shortage issue in drones [183]–[185]. However, these schemes are not always feasible in practice and do not provide fundamental solutions to the involved energy inefficiency problem [186]. In this

context, SWIPT has been foreseen as an emerging energy-replenishment solution, in which drones harvest energy from received RF signals to extend the cruising duration [187]–[189]. Despite their remarkable advantages, SWIPT-enabled drones are more vulnerable to physical layer attacks, such as eavesdropping, spoofing and jamming attacks, due to the LOS and broadcast features of drone channels. There have been several attempts to propose efficient solutions in order to enhance the secrecy rate performance of SWIPT-enabled drones, including conventional physical layer security mechanisms, such as cooperative jamming, artificial noise, and multiple antenna techniques, in addition to position optimization and resource allocation [186], [190], [191]. An interesting work reported in [192] investigated the resource allocation optimization in UAV-assisted SWIPT systems, in which drones are exploited to send data to specific ground receivers, in addition to transmitting the same RF signals to ground energy receivers, which are equipped with wireless power harvesting devices. These energy receivers may be possible eavesdroppers. Therefore, the authors in [192] formulated an optimization problem to obtain the optimum resource allocation scheme that maximizes the secrecy rate of the information receivers.

5) STATE-OF-THE-ART

The research efforts have focused thus far on basic and more advanced design aspects of drones, including CEDs and WIDs. Specifically, extensive research efforts are directed towards proposing encryption and authentication mechanisms to ensure a robust secure communication infrastructure that also maintains privacy [193]–[203].

The energy efficiency and battery properties are key practical design aspects, in which the battery lifetime, charging mechanism and energy consumption must be optimized to enable seamless and uninterrupted wireless communications. In this context, the optimization of energy consumption and charging time of drones have lately received significant attention [204]–[211].

Various design issues, that allow for the realization of the full potential of drone networks, are tackled in the literature, such as network architecture [177], [212]–[214], image processing [215]–[217], interference management [218]–[223] and storage [224], [225]. Recent advances in aerial networks are summarized in Table 7.

TABLE 7. Recent advancements in aerial networks.

Addressed issue	Refs.
Security & privacy	[193]–[203]
Energy and battery efficiency	[204]–[211]
Network architecture	[177], [212]–[214]
Image processing	[215]–[217]
Interference management	[218]–[223]
Storage	[224], [225]

E. THE NEXT FRONTIER FOR IoE: BACKSCATTER COMMUNICATIONS AND WIRELESS POWERED NETWORKS

The exponential growth of connected devices, constituting the emerging IoE, is a major driving force towards the development of energy-efficient solutions to sustain wireless communication among connected nodes [226]. Nonetheless, despite the notable advancements, the short battery lifetime of the deployed battery-operated devices still constitutes a major design challenge, which requires a paradigm shift towards the development of the next generation green communication architecture. Accordingly, ambient BackCom have emerged as a new communication paradigm for low power communications in 5G networks. This approach is based on the concept that a transmitter sends data to its receiver by backscattering ambient signals, e.g., TV or Wi-Fi signals. Compared to conventional systems, backscatter transceivers consume significantly less power (orders of magnitude), rendering it a strong candidate for low power networks and IoE applications [227]. Owing to its promising features, several new and disruptive technologies can be integrated with BackCom.

1) RADIO-FREQUENCY (RF)-POWERED BackCom NETWORKS

RF energy harvesting (RF-EH) has been recently proposed as a promising solution to provide perpetual energy replenishment for such networks. RF-EH is realized by allowing wireless devices, equipped with dedicated EH circuits, to harvest energy from either ambient RF signals or dedicated RF sources. It can be divided into two main categories, namely wireless-powered communications [228] and simultaneous wireless information and power transfer, which have been shown to provide noticeable gains in terms of power and spectral efficiencies by enabling simultaneous information process. Despite the remarkable advantages, RF-EH techniques still suffer from particular limitations, especially in the context of low power wireless networks. Specifically, wireless-powered devices are not able to communicate perpetually, as they require dedicated time for energy harvesting. Additionally, these devices depend on active RF signals for communication; as a consequence, they suffer from relatively high power consumption, which can pose major issues, particularly in large-scale low power wireless networks [227]. Motivated by this concern, a new trend is to integrate BackCom systems with various RF-EH techniques in a single network. This promising paradigm is envisioned to address some of these challenges and catalyze the deployment of new technologies and services [229].

2) RF-POWERED COGNITIVE RADIO NETWORKS AND AMBIENT BackCom

The integration of RF-EH techniques with cognitive radio (CR) networks has led to the development of a new communication paradigm, called RF-powered CR networks [230]. In such networks, a CR transmitter harvests

RF energy when a primary (licensed) user (PU) is active, which is subsequently utilized for data transmissions between secondary (unlicensed) users (SUs) [230], [231]. Evidently, the performance of these networks greatly depends on the availability of PU signals. In this context, BackCom is envisioned as a potential solution to address this challenge by allowing SUs to harvest energy from PU signals in addition to transmitting data by backscattering the PU signals. Therefore, it is evident that although BackCom and energy harvesting have not played a major role yet in 5G, they are envisaged to be a core part of 6G with full potentials.

3) VISIBLE LIGHT BackCom

VLC is a new paradigm that is foreseen to provide ubiquitous connectivity while addressing some of the limitations and challenges of RF communications. It is based on intensity modulation and direct detection, where the intensity of LEDs is modulated to convey information, and then demodulated/detected directly using a photodiode. There are several key advantages of VLC that include inherent communication security, high degree of spatial reuse, and its immunity to RF interference, which makes it safe to be used in critical places with high electromagnetic interference, e.g., hospitals and industrial plants. The principle of visible light BackCom (VLBC) systems is similar to its RF counterpart, in which VLBC leverages ambient light to harvest energy and then modulates VLC signals to transmit its data to backscatter receivers [232], [233].

4) QUANTUM BackCom

Quantum backscatter communications is another promising technology which is anticipated to contribute towards the development of 6G and the next generation IoT, particularly in terms of performance and security [234]. In this new paradigm, a transmitter produces entangled signal-idler (S-I) photon pairs. The S-photon is transmitted and backscattered from a backscatter transmitter, while the I-photon is kept at the receiver. This quantum setting provides a significant gain in the error exponent for the communication link and facilitates secure communication by exploiting quantum cryptography.

5) STATE-OF-THE-ART

BackCom networks are subject to critical security threats, such as eavesdropping and jamming. This stems from the typical simplicity and low-complexity of BackCom transceivers. As a result, existing security solutions, including encryption and digital signatures, may not be applicable due to the power and complexity constraints of BackCom devices. This has motivated the international research community to investigate new security mechanisms that can guarantee fully secure and private wireless communications [235]–[242]. Self-interference is another major limitation in BackCom systems. The sources of self-interference include: (i) signals from ambient RF sources, and (ii) multipath propagation. Based on this, several self-interference cancellation

techniques have been recently reported in the open technical literature [243]–[250].

It is noted that BackCom networks are not optimized and/or designed for large-scale low power networks comprising a massive number of IoT devices, e.g., sensors in environmental monitoring, sensors in smart roads to collect data about the pavement conditions and traffic, etc. Furthermore, such systems are different from human-centric communications with diverse and unique traffic characteristics as well as QoS requirements, which requires the development of efficient physical layer and media access control schemes to prevent access congestion. Within this context, multiple access techniques in BackCom systems are regarded to be instrumental in improving the efficiency of backscatter networks. In particular, conventional orthogonal multiple access and non-orthogonal schemes (e.g., NOMA [251] and rate splitting multiple access), are recognized as promising candidates for enabling massive connectivity, while maintaining high energy and spectral efficiency [252]–[260].

In addition to the aforementioned studies, major research efforts have focused on channel modeling and estimation [261]–[266], resource allocation [252], [253], [267]–[269] and wireless energy harvesting [270]–[276] in BackCom systems. Table 8 summarizes the timely open research topics in the field of BackCom.

TABLE 8. Open research topics in BackCom systems.

Research topics	Refs.
Security	[235]–[242]
Interference control	[243]–[250]
Multiple access	[252]–[260]
Channel modeling & estimation	[261]–[266]
Resource allocation	[253], [267]–[269]
Wireless energy harvesting	[270]–[276]

F. TACTILE INTERNET

Tactile Internet (TI) is seen as the next frontier of IoE, focusing on M2P and M2M interactions. With the recent advances in tactile/haptic devices, it is predicted that TI will catalyze the deployment of a plethora of new applications ranging from health care to education and smart manufacturing. Therefore, it is expected to reshape our daily lives and ultimately realize the full potential of the next industrial revolution, also known as Industry 4.0.

To fully realize TI, the communication infrastructure (CI) has to meet strict design guidelines, as it is currently unable to address the stringent requirements of the use cases envisioned for TI. In particular, the CI has to support extremely low end-to-end latency with high-reliability [277]. Furthermore, it must ensure data security without jeopardizing the latency requirements imposed by the computationally demanding encryption techniques.

To address these requirements and catalyze the deployment of new use cases with unique requirements, the development of unique and disruptive B5G wireless communication

technologies is of paramount importance. To this end, we envision the development of: 1) communication technologies in the THz band; 2) novel wireless network architectures; and 3) AI-enabled communication networks.

1) STATE-OF-THE-ART

The use cases of TI have recently drawn significant research and industrial attention, as they are envisioned to have great potential to advance all aspects of our daily lives. As reported in the literature, TI has been adopted in numerous applications, such as VR and AR [278]–[287], healthcare [288]–[294], education [295]–[299], intelligent transportation [300]–[303], industry [304]–[307] and robotics [308]–[313]. Table 9 summarizes the envisioned applications of TI.

TABLE 9. Applications of tactile internet.

Applications	Refs.
VR and AR	[278]–[287]
Healthcare	[288]–[294]
Education	[295]–[299]
Intelligent transportation	[300]–[303]
Industry	[304]–[307]
Robotics	[308]–[313]

III. DRIVING APPLICATIONS OF 6G TECHNOLOGIES

In this section, we highlight the potential applications associated with the aforementioned technologies, which are expected to realize the vision of 6G systems.

A. MILLIMETER-WAVE COMMUNICATIONS

- *Wireless Backhaul:* Due to ultra-dense deployment of heterogeneous multi-tier small cells in future wireless communications, fiber-based backhauling will no longer be an economical option to connect multiple BSs to each others and to the gateway, due to several installation restrictions. Therefore, wireless backhaul represents a scalable promising alternative to connect multiple BSs in small cells. This can be achieved by utilizing the wide and underutilized mmWave bandwidth, such as the unlicensed 60 GHz band, as well as the 70-80 GHz band. Specifically, leveraging the mmWave band to realize wireless backhaul solutions is expected to provide increased flexibility, high speed transmission, cost efficiency and enhanced data rates [314]. Another key advantage of adopting the mmWave band in wireless backhauling is the controlled level of inter-cell interference, due to the LOS nature of the mmWave links [315].
- *Wearable devices:* Recent advancements in miniature electronics fabrication technology prompts the spread of smart high-end wearable devices, which require higher data rates and longer battery lifetime, such as smart watches, smart AR/VR glasses and helmets, health-care gadget, and motion trackers [27]. Given that the transmission range constraint is relaxed in these applications,

wireless communication between wearable devices and the smart receiver (which can be a smartphone) can be efficiently realized by incorporating mmWave communications as a perfect candidate to establish high data rate, low interference and reliable communication between the device and the receiver, especially in densely populated indoor environments [316].

- *Imaging and Tracking:* Given that signals in the 60 GHz band will be mostly reflected from objects larger than their short wavelength, mmWave communications is considered as a promising candidate in imaging and tracking systems. Particularly, objects' dimensions can be accurately measured by relying on the highly directional beams of the 60 GHz links, which also helps reducing the interference, and subsequently, providing a precise imaging and tracking systems. Furthermore, the miniaturized antenna arrays facilitate the integration of these antennas in small receivers (such as smart phones or tablets).

B. TERAHERTZ COMMUNICATIONS

The wide bandwidth in the THz band is envisioned to drive the deployment of a large array of new use cases, as outlined next.

- *Wireless Data Centers:* Today's data centers suffer from high complexity, power consumption, maintenance cost, and wasted spaces occupied by large cables. Therefore, there have been attempts to address these issues in order to enable fast and reliable access to cloud-based services. According to [317], the power consumption of all data centers will reach 73 billion KWh by 2020. Therefore, THz communications could be a promising candidate for the next generation of data centers, satisfying the peak data rate of 10-20 Gbps required by 5G, and even higher [318]. Although still in infancy, there have been recent research investigations on channel modeling for indoor environments, which have paved the way for utilizing THz communications in indoor wireless data centers [319], [320]. Initial results showed that the cabling cost can be reduced without compromising the bandwidth.
- *Secure Drone Communications:* Drone communications in the THz band is one of the envisioned applications of THz communications that are expected to achieve higher capacity gains and support increased mobility [321]. Moreover, the deployment of large antenna arrays for coverage extension enables extremely narrow beams, which inherently limits the probability of eavesdropping, and therefore, it achieves secure communications [322].
- *Health Monitoring:* THz communications is a promising candidate in the field of health care. Specifically, several nano-sensors can be utilized to monitor different ions in the human blood, such as glucose and sodium, in addition to cholesterol levels, infections and cancer bio-markers. The collected data by the sensors are




FIGURE 3. Indoor and outdoor applications of THz communications.

forwarded to a micro interface, e.g., a cellular phone or a medical device, using THz communications [317]. It is noted that the THz radiations are considered safe for the human-being bodies compared to the gamma rays [323].

- *Wireless local area networks (WLANs)/Wireless personal area networks (WPANs)*: THz band communications are envisioned to enable bandwidth-intensive applications such as high definition holographic video conferencing and ultra-high speed data transfer. This stems from the fact that a seamless interconnection may be facilitated between ultra-high wired networks (e.g., fiber optical links) and wireless devices (e.g., laptops or tablets) in WLANs or between personal wireless devices in WPANs [322].

Potential applications of THz communications are outlined in Fig. 3.

C. OPTICAL WIRELESS COMMUNICATIONS

- *Smart Transportation Systems*: The wide spread of LEDs in current transportation lighting systems, such as vehicles lights, street lamps and traffic signals, facilitates the utilization of these LEDs to perform wireless communications besides their original role of illumination. LEDs can be exploited to implement OWC to realize safe and smart transportation systems, by allowing vehicles to communicate road-related information, including vehicles speed, navigation, and traffic status, while maintaining low-complexity and low-cost implementation [324].
- *Airplane Passenger Lights*: OWC can be interestingly applied to travelers lighting in airplanes, in which LEDs can realize wireless communications for in-flight

passengers audio and video files transmission, in addition to instant messaging and data exchange [325].

- *Underground Mining*: Serious accidents, due to cave collapsing, chemical leakage, and gas explosions, in underground mining raise a critical issue in the mining industries. In such events, it is of paramount importance to detect the location of the miners in order to provide the proper assistance. Recently, VLC has emerged as a promising technology for indoor positioning, due to its suitability in enclosed places, in addition to its low cost, low interference and high data rates features [326].
- *Healthcare*: Electromagnetic interference caused by RF signals is considered as a threatening factor for expensive medical machines. Moreover, intensive care units pose restrictions on the use of mobile phones operating over the RF band [327]. Intra-clinical data transmission is considered an attractive application to OWC, which is reported as safe for human health. OWC can be implemented in healthcare buildings to provide safe and high data rate transmission over short distances, in addition to lighting, which minimizes the implementation cost and provides a health-friendly alternative to RF communications [328].

D. METASURFACES FOR WIRELESS COMMUNICATIONS

- *Metasurfaces in WPT Applications*: WPT is foreseen as a game-changing technology, in which future networks are envisioned to provide perpetual energy replenishment, particularly for low power devices/sensors. A major concern, however, is the ability of devices to harvest enough energy in wireless channels. The unique properties of metasurfaces, that include their abilities to steer and concentrate electromagnetic waves,

enable efficient power transfer and energy harvesting. The work in [329] discussed the potentials of integrating smart tables with metasurfaces in order to enable multiple wireless devices to be powered/charged simultaneously. The integration of WPT in metasurfaces for biological applications was studied in [159], where a metasurface-based wearable device was placed over the human skin surface to improve the efficiency of an implanted WPT system.

- *Metasurface-based Textiles for Wireless Body Sensor Networks (WBSNs)*: Very recently, metasurface-based textiles were developed for energy-efficient and secure WBSN applications [330]. In this approach, regular clothing is fitted with conductive metasurface textiles, where wireless signals can glide around the surface of the body on the clothes to interconnect wireless wearable devices with each other forming a WBSN. In this application scenario, wearable devices are located in close proximity to the body. This results in a significant reduction in the power dissipated by the wireless devices, leading to an improvement in the battery life and data rates of these devices. In fact, this innovative WBSN is foreseen to boost the received signal compared to conventional technologies. Furthermore, metasurface-based textiles may enable personal sensor networks, which are highly efficient, immune to interference, and inherently secure [330]. Looking ahead, they are envisioned to have future applications in high-tech athletic wear, health monitoring, and human-machine interfaces.

E. DRONE-BASED COMMUNICATIONS AND AUTONOMOUS SYSTEMS

- *Search and Rescue Missions*: Search and rescue missions are some of the critical driving applications of drone networks. This is primarily due to the flexibility of drones compared to manned vehicles, which take a longer time to deploy [331].
- *Mailing and Delivery*: Package delivery is one of the attractive civil applications of drones, adopted by major courier companies around the world in order to accomplish fast, cost-effective and reliable delivery. This is motivated by the fact that most of the packages' weights are below the maximum tolerable load of a single drone [180]. For example, Amazon reported that 83% of their packages weights fall below the 2.5 kg [332], while FedEx average package weight is less than 5 kg [180].
- *Marine Drones*: Underwater drones can accomplish several military and civil underwater missions, such as oil spills exploration and identification, in addition to performing intensive studies relating to marine organisms and ecosystem [333].

F. BackCom AND ENERGY HARVESTING

- *Smart Homes*: Low power battery-less backscatter sensors equipped with energy harvesting devices can be

efficiently embedded in homes to perform a wide range of tasks, such as gas leak detection, smoke and carbon oxide detection, and movement monitoring. Another driving application of BackCom is smart dustbins, in which backscatter devices keep track of the garbage level and report it to garbage collecting trucks.

- *Smart Cities*: Backscatter enabled sensors can be flexibly placed in street lamps, parking lots, buildings, and bridges to realize the envisioned energy-efficient low-cost smart cities. BackCom can be utilized in smart cities to enhance air quality by monitoring the pollution and noise level in the air. Additionally, it can be used to manage traffic in closed parking areas and ease the process of finding an available parking place by indicating the available slots.
- *Biomedical Applications*: Wearable and implantable human medical devices, in addition to plants and animals monitoring, are some of the key drivers of BackCom technology. For example, Smart Google contact lenses, which are equipped with miniaturized BackCom devices, are designed to continuously measure the glucose levels in the tears for diabetes patients and backscatter the reported results to a wireless controller. Other serious diseases, such as epilepsy and Parkinson's, are envisioned to be diagnosed and treated by the assistance of BackCom technology. In particular, it is envisaged that brain-implantable BackCom neural devices will play the role of the brain-computer interface needed for studying and diagnosing diseases of interest.

Potential applications of BackCom systems are presented in Fig. 4.

G. TACTILE INTERNET

- *Industry*: Automation in industry realizes the control of machinery and processes through a large network of sensors and actuators in order to improve productivity and reduce labor costs. Industrial automation is steadily growing in the context of TI, enabling the full control of rapidly moving devices with high sensitivity while meeting the end-to-end latency requirements. However, the ever-growing need for control processes with different latency, reliability, data rate, and security demands is envisioned to catalyze the development of new wireless solutions tailored to these requirements.
- *Virtual Reality (VR)*: VR enables users to physically interact with each other by applying various motor skills over a VR simulation platform. In this context, TI is anticipated to provide the low latency required to facilitate shared virtual environments. High-fidelity interaction requires haptic feedback to allow users to touch objects in a VR environment and enable users to feel one another's actions on the same touched object. This requires a stable and seamless user communication coordination, which is not supported by today's VR systems. Hence, TI is foreseen as a key enabler for haptic




FIGURE 4. Applications of BackCom systems.

communications with ultra-low delay communication and reliability requirements.

- **Augmented Reality (AR):** AR applications are fast growing, owing to the availability of AR glasses and powerful smart devices equipped with small sensors and cameras. However, the present AR systems are restricted to deliver pre-processed content due to the limited computational capabilities of the small wireless devices and the inherent delays in the communication network. TI, on the other hand, is perceived to enable the augmentation of dynamic and real-time information to the contents.
- **Healthcare:** Potential applications of TI in healthcare include tele-surgery, tele-rehabilitation, and tele-diagnosis. Different from healthcare services provided by current communication networks, which are location-dependent, medical expertise provided by the TI will not be bounded by time and/or a physical location. For example, a physician can diagnose patients at their locations by remotely controlling a robot while receiving haptic feedback as well as audio-visual information. Tele-surgery is another example, which has the potential to revolutionize healthcare delivery in the next decade.
- **Education:** Improved learning experiences over distances can be achieved via TI by allowing teachers and learners to exchange haptic information. Identical multi-modal human-machine interfaces are required to enable auditory, visual, and haptic interactions, which can be realized by enabling ultra-low latency communication systems. For example, TI may allow a remote

music instructor to apply instant actions over the haptic overlay to correct the hand moves of a student learning a musical instrument.

IV. CHALLENGES AND FUTURE DIRECTIONS

In this section, we discuss the open research issues associated with the previously presented potential 6G technologies and highlight their research challenges.

A. MILLIMETER-WAVE COMMUNICATIONS

- **User Mobility:** User mobility constitutes a major challenge in the implementation of mmWave networks, that severely affects the system's capacity. Therefore, to realize the full potential of mmWave communications, there is a need to develop novel, efficient and adaptive modulation and coding schemes in order to compensate for channel variations. Moreover, in indoor small cell scenarios, which comprise sets of access points serving multiple devices (each set called basic service set), user mobility causes severe and rapid load fluctuations in each set, in addition to recurrent handovers between multiple access points [334]. This calls for the development of sophisticated user association and handovers mechanisms between multiple access points, which are capable of providing a guaranteed QoS, balanced load, and improved system capacity for the realization of efficient mmWave communications in future wireless networks.
- **Interference Management:** To overcome the short range limitation in mmWave communications, a large number of access points are employed to extend the link

coverage in small cell environments. In several indoor scenarios, such as office cubicles and conference rooms, networks experience interference due to the deployment of a large number of access points (i.e., large number of basic service sets). This interference can be detrimental if the device is close to the interfering access point, which is a highly probable event. Therefore, research interests should be directed towards developing novel interference management mechanisms to prevent significant deterioration in the performance of mmWave communications.

- *Blockage and Shadowing Control*: Sensitivity to blockage represents a fundamental challenge for wireless mmWave communications. Specifically, a sudden blockage for the LOS transmission between the BS and the user causes a disconnected session, yielding a significant degradation in the system's reliability. Additionally, re-establishing a new connection between the user and another BS increases the network overhead, affecting the system's latency, which is a major issue in the envisioned 6G mobile networks. Signal steering, to avoid human blocking, requires a very large number of access points, which augments the level of interference in addition to the increased complexity. Therefore, the design of reliable anti-blockage schemes is necessary before implementing efficient mmWave communications in future wireless networks.

B. TERAHERTZ COMMUNICATIONS

- *Transceiver Architecture*: Transceiver architectures in the THz band is one of the critical aspects to be considered due to the unique characteristics of the propagation environment of THz links. In order to realize the full potentials of the THz-band, there is a growing interest in the development of novel transceiver architectures that can operate across the entire THz-band. The developed architectures are expected to combat the severe path loss, thus, enabling high sensitivity and high power gains. Moreover, the co-existence of different frequency bands, such as THz, mmWave, and microwave cells, requires thorough investigations over different layers.
- *THz Modulator*: The characteristics of THz modulators, including amplitude and phase modulators, play a central role in quantifying the efficiency of THz communication systems. These characteristics include, but not limited to, modulation speed and depth in amplitude modulators and phase shift amount in phase modulators. Current modulators designs, with the adopted architecture and utilized materials, limit the modulator ability to achieve ultra-high speed and consequently to realize efficient THz wireless systems. This stems from the fact that the existing modulators do not allow EM radiation manipulation in the THz band, which is required in order to facilitate high-speed control of the modulator characteristics. Therefore, this calls for research intervention to develop intelligent and tunable ultra-high speed

modulators, with approximately 1 picosecond response time, to enable efficient and reliable THz wireless communications [317].

- *Channel Modeling for THz Communications*: Existing low frequency channel models can not accurately capture the entire behavior of high frequency THz links, which experience severe attenuation due to molecular absorption and antenna aperture, in addition to the free space loss. Note that the multi-path channel of THz communications compromises LOS and NLOS components. On the contrary, LOS attenuation, represented by path loss, is measured by the addition of the spreading and molecular absorption losses, which are encountered due to wave expansion and molecular absorption, respectively. The severity of molecular absorption is determined based on the density of molecules experienced along with the transmission link, distance, weather conditions (e.g., heavy rain), and frequency window in the THz band. Accordingly, LOS channel component in the THz band is described as severely frequency selective. Therefore, it is essential to develop an accurate model to represent the LOS component in the THz wireless system, which is necessary to identify the performance limits of THz communications and propose enhancement schemes for such technology [335]. On the other hand, due to the unavailability of the LOS components in some scenarios, the THz link might be limited to the NLOS component, which can be classified into specular reflected, diffusely scattered and diffracted EM waves. Therefore, for precise channel characterization, it is required to accurately trace the reflection, scattering and diffraction coefficients of the incident beam in the THz system [336], which depend on the incident angle and surface material and geometry. Hence, the development of realistic and accurate channel models for THz links is still an open research problem, which requires thorough investigation to enable the implementation of an efficient THz wireless system.

C. OPTICAL WIRELESS COMMUNICATIONS

- *Physical Layer Security*: Heterogeneous ultra-dense networks are envisioned to shape the future 6G wireless networks, in which hybrid RF/optical wireless communications are widely deployed. Although physical layer security in OWC is thoroughly investigated in the literature, implementing secure hybrid RF/optical networks, which require the development of efficient physical layer security mechanisms, represents a major challenge in such systems. By noting that legitimate users and eavesdroppers in hybrid networks are connected to either RF or VLC sources, it is essential to propose physical layer security mechanisms to associate users to the appropriate source in a way that maximizes the system secrecy rate [337].
- *Multiple Access Networks*: The limited modulation bandwidth and peak optical power represents

a performance limiting factor in the realization of efficient OWC systems, as it directly affects the spectral efficiency in such systems, particularly in VLC scenarios. Several multiple access schemes have been proposed in the literature to accommodate multiple users, and hence improve the spectral efficiency in OWC networks, such as NOMA, rate splitting multiple access (RSMA) and space-division multiple access (SDMA) [338]. It is worth noting that existing research in the field of optical multiple access is primarily relying on perfect impractical scenarios. In specific, in the reported work, perfect CSI, Gaussian noise, and availability of LOS assumptions are considered. Therefore, it is essential to examine the performance of OWC systems under imperfect scenarios, such as investigating the effect of ambient light. Additionally, considering that VLC links may experience fading and shadowing, it is essential to examine the performance of different optical multiple access schemes under imperfect channel conditions. Moreover, physical layer security of NOMA, RSMA, and SDMA systems, in the context of OWC, remains an open research problem.

- *Reconfigurable Intelligent Surfaces for FSO*: The existence of a LOS link constraint constitutes a major challenge in the implementation and generic deployment of FSO networks. This is due to the fact that optical links in FSO systems are usually impaired by several factors, such as atmospheric turbulence and geometric and misalignment losses [339]. Consequently, optical reconfigurable intelligent surfaces (RIS) have emerged as an efficient solution to relax the LOS constraint in FSO networks. Different than relay, RIS is considered an energy efficient technology to extend the coverage area of FSO wireless networks at low implementation cost and complexity. Motivated by the promising potentials of RIS in FSO networks, the research community has recently started to actively investigate the integration of RIS in FSO scenarios [339]–[341].

D. METASURFACES FOR WIRELESS COMMUNICATIONS

In spite of the promising prospects of metasurfaces in 6G, several design aspects should be further investigated in order to realize the full potential of this promising technology.

- *Dynamic Structure Design*: The ability to manipulate the configurations of meta-atoms constitutes a key design challenge for the efficient operation of reconfigurable metasurfaces, whose deployment is needed to support a wide range of functionalities in highly dynamic wireless environments. Although there exist some research studies that have successfully demonstrated that multiple functionalities can be achieved by multiple metasurfaces, only a few have presented the capability of a metasurface to perform different functionalities simultaneously [342]. In this case, each unit cell of the metasurface has to be controlled

independently, raising the need to develop effective distributed meta-atom control mechanisms and to examine the performance of the variety of functions supported by each metasurface. Additionally, since metasurfaces are envisioned to be deployed in application scenarios involving the operation over a wide frequency range (varying from 1 to 60 GHz), designing efficient metasurface structures that are capable of dynamically switching the operation frequency poses an essential research goal [140].

- *Efficient Programmable Interface*: Apart from the need to develop metasurface structures capable of realizing different functions in real-time, there is a compelling need to investigate advanced multi-functional metasurfaces that can switch from one EM behavior to another in a fast manner to cater for the increasingly diverse user demands, especially in high mobility scenarios where the system convergence rate may not be within the coherence time of the surrounding wireless environment. As a result, research efforts should be directed towards developing control software that incorporates low-complexity and fast configuration optimizers to facilitate the optimization and adaptation of metasurfaces functionalities to the surrounding environment. Also, advanced signal processing and machine learning algorithms may be developed to leverage the sensing capabilities of metasurfaces for enabling intelligent system performance optimization, which can converge within the coherence time of the environment and can be aligned with the network requirements of 6G systems, such as massive connectivity, ultra-low latency, and high reliability [140].
- *High-order Modulation*: The design of high-order modulation and novel waveform designs for metasurface-based wireless communication systems constitute promising solutions for enabling high data rate transmissions. This is of paramount importance since current metasurface-based transmitters are limited to single-carrier low-order modulation schemes, such as binary/quadrature phase-shift-keying [150], [151].
- *WPT in Metasurfaces*: It is recalled that the last years witnessed remarkable advancements in battery design. Nonetheless, the short battery life of wireless devices still constitutes a major design challenge and requires a paradigm shift towards the development of the next generation green communication architectures. WPT was proposed recently as a promising solution to provide perpetual energy replenishment for such networks. It is realized by allowing wireless devices, equipped with dedicated energy harvesting circuits, to harvest energy from either ambient RF signals or dedicated RF sources. Given that metasurfaces have the ability to steer, absorb and collimate EM waves, particular research efforts should be dedicated to exploit the unique functionalities of metasurfaces to wirelessly charge the wireless devices from long distances.

E. DRONE-BASED COMMUNICATIONS AND AUTONOMOUS SYSTEMS

- *Network Architecture and Analysis:* Network planning, performance evaluation and resource allocation are some of the challenges that drone-BSs encounters in aerial networks. While terrestrial mobile networks are designed to meet the requirements of ground users, they are not optimized to support aerial networks. Specifically, terrestrial BS antennas are not designed to support the ultra-low latency requirements of high elevation angle users in aerial networks. Therefore, there is a need to develop a novel and efficient system architecture that can efficiently integrate terrestrial BSs with drone-based UEs.
- *Energy and Storage Efficiency:* Energy constraint is a limiting factor in mobile-enabled drones, particularly since solar energy and the limited size of built-in batteries are the only sources of power. This is a crucial issue, especially in power-hungry monitoring missions, where continuous monitoring and transmission are inevitable. Various energy-aware mechanisms have been reported in the literature to address the energy efficiency problem in drones. For example, an approach is to utilize multiple cooperative drones to allow a single drone to temporarily leave the network for energy replenishment [173]. Storage constraint is another major concern, e.g., in monitoring missions, where drones must store a large amount of data. This motivates the investigation of novel forwarding and compression schemes to efficiently handle this huge amount of data.
- *Collision Avoidance:* Buildings and large obstacles represent a major hazard to drones, so they must be addressed thoroughly in order to avoid collisions to objects in the surrounding environment. A way to address this problem is to restrict the drone flying zones to limited areas. However, this will increase the interference between multiple drones and lead to higher collision probability [343]. Therefore, there is a need for efficient collision avoidance schemes to enable drones dynamically adjust their trajectories to minimize collision probability.
- *Channel Modeling:* Efficient implementation of cooperative aerial networks requires accurate characterization of communication links to ensure reliable and safe operation of air-to-air and air-to-ground links. In flying ad-hoc network architectures, drone communications require the development of robust theoretical framework to model air-to-air and air-to-ground links. While there have been reported works on link characteristics of aerial networks in different frequency bands [344]–[346], there are still not enough results to characterize the channel models, particularly for cooperative (relaying) scenarios [347]. Although the communication link characteristics of drone-based systems are unique, some terrestrial channel models, such as two-ray and Rician models, were

shown to be a good fit for drone environments; however, more experimental and real-time tests are required in order to verify the accuracy of such models and properly select their parameters. More importantly, further research efforts must be dedicated to verify the validity of these models in different frequency bands, such as 433 MHz, 1575.42 MHz, and 2.4 GHz bands [347].

F. BACKSCATTER COMMUNICATIONS AND ENERGY HARVESTING

- *Security and Jamming:* BackCom systems typically suffer from potential security and jamming attacks, owing to their simple modulation and coding schemes. The key issue is that the limited resources in backscatter systems are not able to support the implementation of conventional security solutions that include encryption and digital signatures [243]. This calls for the development of simple, yet highly efficient security solutions to realize secure BackCom systems.
- *Interference to Licensed Systems:* Data transmission in ambient BackCom is based on reflecting ambient signals received from licensed sources. Therefore, interference imposed on licensed users is inevitable, which calls for the need to develop communication protocols that guarantee no or minimal interference. Recent research efforts have focused on interference modeling and development of compensation schemes [227].
- *Full-Duplex Ambient Backscatter:* Full-duplex BackCom systems are proposed to enable simultaneous communication between multiple ambient backscatter nodes. In such cases, the same antenna is used by a backscatter receiver to transmit and receive signals. As a result, a significant amount of self-interference exists between different components of the BackCom transceiver. This calls for the development of self-interference mitigation schemes and constitutes an open research issue towards addressing this challenge [244], [348].

G. TACTILE INTERNET

Although TI is considered as a new paradigm envisioned to generate a plethora of new applications, several open research challenges exist and need to be fully addressed for the successful realization of this enabling technology.

- *Haptic Devices:* Haptic devices, such as sensors and actuators, enable users to feel, touch, and manipulate objects in real or virtual environments. Although haptic devices have already been commercialized, they still fall short in terms of degrees of freedom as well as the cost effectiveness. Additionally, in order to realize the envisioned applications, haptic devices have to offer kinesthetic and tactile control simultaneously [349].
- *Data Compression:* Bandwidth-limited networks represent a major challenge for haptic communications, which requires a paradigm shift towards the development of innovative solutions that would enhance system

reliability and user experience. In this regard, several haptic data compression techniques have been thoroughly investigated in the literature, to realize the full potential of TI. However, further investigations towards haptic codec design for TI are required. This might include the proposal of a new set of kinesthetic and tactile codec solutions that will lead to highly efficient data compression techniques.

- **Integration of Multi-Modal Sensory:** One of the key challenging aspects in enabling haptic feedback is multi-modal sensory, where visual, haptic, and auditory feedback are integrated simultaneously. However, these different modalities vary in terms of their latency, sampling, and transmission rate. Subsequently, novel multiplexing schemes have to be studied in order to temporally integrate multiple modalities with different priorities.
- **Ultra-Reliability:** Since TI is expected to disrupt major attributes in the society, ultra-reliable network connectivity is necessary to minimize the packet losses and reduce the outage to 10^{-7} [349]. A highly lossy environment in haptic communications leads to erroneous sensations and directly interrupts the user's activity. There are several factors that impact the reliability of TI applications. This includes uncontrollable interference, lack of resources, equipment failure, and reduced signal strength. This will require the investigation of efficient reliability enhancement mechanisms to achieve ultra-high reliability in real-time operations [350].
- **Ultra-Low Latency:** As stated earlier, TI requires sub-ms end-to-end latency. Therefore, it is essential to understand the latency budget between sensors and actuators in order to investigate the impact of each contributing factor in the chain. In general, the end-to-end latency is dominated by air-interface, backhaul, and core latencies. To cater to the critical latency requirements, innovative latency optimization mechanisms are necessary in addition to effective protocol stack and hardware designs.

V. CONCLUSION

Although the glory of 5G networks is at its peak, initial implementation and testing phase of 5G networks along with the emergence of a plethora of new applications, such as bio-interface applications, are revealing new challenges and limitations of the upcoming wireless networks, including but not limited to, ultra-high reliability, extremely high data rates and ultra-low latency. Accordingly, this spots the lights on the fundamental question: *Will the forthcoming 5G wireless networks be able to accommodate the newly emerged applications with the concurrent stringent requirements, necessary for realizing fully autonomous and intelligent systems?* To answer this question, in this paper, we sketched out the roadmap into the future hypothetical vision of B5G networks. Particularly, we focused on exploring expected new technologies for 6G networks, such as mmWave communications, THz communications, OWC, metasurfaces, aerial

networks, BackCom, and TI, along with their potential applications and inherent challenges. The technical challenges associated with these technologies call for a deeper investigation, which will potentially accelerate the development of innovative solutions as well as standardization efforts for 6G.

REFERENCES

- [1] *IMT Traffic Estimates for the Years 2020 to 2030*, document ITU-R M.2370-0, 2015.
- [2] A. Yadav and O. A. Dobre, "All technologies work together for good: A glance at future mobile networks," *IEEE Wireless Commun.*, vol. 25, no. 4, pp. 10–16, Aug. 2018.
- [3] M. Mohammadkarimi, M. A. Raza, and O. A. Dobre, "Signature-based nonorthogonal massive multiple access for future wireless networks: Uplink massive connectivity for machine-type communications," *IEEE Veh. Technol. Mag.*, vol. 13, no. 4, pp. 40–50, Dec. 2018.
- [4] G. I. Tsiropoulos, A. Yadav, M. Zeng, and O. A. Dobre, "Cooperation in 5G HetNets: Advanced spectrum access and D2D assisted communications," *IEEE Wireless Commun.*, vol. 24, no. 5, pp. 110–117, Oct. 2017.
- [5] D. Kreutz, F. M. V. Ramos, P. E. Verissimo, C. E. Rothenberg, S. Azodolmolky, and S. Uhlig, "Software-defined networking: A comprehensive survey," *Proc. IEEE*, vol. 103, no. 1, pp. 14–76, Jan. 2015.
- [6] B. Han, V. Gopalakrishnan, L. Ji, and S. Lee, "Network function virtualization: Challenges and opportunities for innovations," *IEEE Commun. Mag.*, vol. 53, no. 2, pp. 90–97, Feb. 2015.
- [7] A. Gupta and R. K. Jha, "A survey of 5G network: Architecture and emerging technologies," *IEEE Access*, vol. 3, pp. 1206–1232, Jul. 2015.
- [8] S. M. R. Islam, N. Avazov, O. A. Dobre, and K.-S. Kwak, "Power-domain non-orthogonal multiple access (NOMA) in 5G systems: Potentials and challenges," *IEEE Commun. Surveys Tuts.*, vol. 19, no. 2, pp. 721–742, 2nd Quart., 2017.
- [9] F. Tariq, M. Khandaker, K.-K. Wong, M. Imran, M. Bennis, and M. Debbah, "A speculative study on 6G," 2019, *arXiv:1902.06700*. [Online]. Available: <http://arxiv.org/abs/1902.06700>
- [10] W. Saad, M. Bennis, and M. Chen, "A vision of 6G wireless systems: Applications, trends, technologies, and open research problems," *IEEE Netw.*, vol. 34, no. 3, pp. 134–142, May 2020.
- [11] M. Giordani, M. Polese, M. Mezzavilla, S. Rangan, and M. Zorzi, "Towards 6G networks: Use cases and technologies," Mar. 2019, *arXiv:1903.12216*. [Online]. Available: <http://arxiv.org/abs/1903.12216>
- [12] K. B. Letaief, W. Chen, Y. Shi, J. Zhang, and Y.-J.-A. Zhang, "The roadmap to 6G: AI empowered wireless networks," *IEEE Commun. Mag.*, vol. 57, no. 8, pp. 84–90, Aug. 2019.
- [13] E. C. Strinati, S. Barbarossa, J. L. Gonzalez-Jimenez, D. Ktenas, N. Cassiau, L. Maret, and C. Dehos, "6G: The next frontier: From holographic messaging to artificial intelligence using subterahertz and visible light communication," *IEEE Veh. Technol. Mag.*, vol. 14, no. 3, pp. 42–50, Sep. 2019.
- [14] M. Katz, M. Matinmikko-Blue, and M. Latva-Aho, "6Genesis flagship program: Building the bridges towards 6G-enabled wireless smart society and ecosystem," in *Proc. IEEE 10th Latin-American Conf. Commun. (LATINCOM)*, Nov. 2018, pp. 1–9.
- [15] E. Peltonen, M. Bennis, M. Capobianco, M. Debbah, A. Ding, F. Gil-Castiñeira, M. Jurnu, T. Karvonen, M. Kelanti, A. Kliks, T. Leppänen, L. Lovén, T. Mikkonen, A. Rao, S. Samarakoon, K. Seppänen, P. Sroka, S. Tarkoma, and T. Yang, "6G white paper on edge intelligence," 2020, *arXiv:2004.14850*. [Online]. Available: <http://arxiv.org/abs/2004.14850>
- [16] K. David and H. Berndt, "6G vision and requirements: Is there any need for beyond 5G?" *IEEE Veh. Technol. Mag.*, vol. 13, no. 3, pp. 72–80, Sep. 2018.
- [17] S. Zhang, C. Xiang, and S. Xu, "6G: Connecting everything by 1000 times price reduction," 2020, *arXiv:2004.00853*. [Online]. Available: <http://arxiv.org/abs/2004.00853>
- [18] H. Viswanathan and P. E. Mogensen, "Communications in the 6G era," *IEEE Access*, vol. 8, pp. 57063–57074, Mar. 2020.
- [19] K. Samdanis and T. Taleb, "The road beyond 5G: A vision and insight of the key technologies," *IEEE Netw.*, vol. 34, no. 2, pp. 135–141, Mar. 2020.

- [20] S. Chen, Y.-C. Liang, S. Sun, S. Kang, W. Cheng, and M. Peng, "Vision, requirements, and technology trend of 6G: How to tackle the challenges of system coverage, capacity, User data-rate and movement speed," Feb. 2020, *arXiv:2002.04929*. [Online]. Available: <http://arxiv.org/abs/2002.04929>
- [21] S. Dang, O. Amin, B. Shihada, and M.-S. Alouini, "What should 6G be?" *Nat. Electron.*, vol. 3, p. 20–29, Jan. 2020.
- [22] H. Saarnisaari et al., "A 6G white paper on connectivity for remote areas," Apr. 2020, *arXiv:2004.14699*. [Online]. Available: <http://arxiv.org/abs/2004.14699>
- [23] M. Xiao, S. Mumtaz, Y. Huang, L. Dai, Y. Li, M. Matthaiou, G. K. Karagiannidis, E. Björnson, K. Yang, C.-L. I, and A. Ghosh, "Millimeter wave communications for future mobile networks," *IEEE J. Sel. Areas Commun.*, vol. 35, no. 9, pp. 1909–1935, Sep. 2017.
- [24] O. Semiari, W. Saad, M. Bennis, and M. Debbah, "Integrated millimeter wave and sub-6 GHz wireless networks: A roadmap for joint mobile broadband and ultra-reliable low-latency communications," *IEEE Wireless Commun.*, vol. 26, no. 2, pp. 109–115, Apr. 2019.
- [25] L. Zhang, H. Zhao, S. Hou, Z. Zhao, H. Xu, X. Wu, Q. Wu, and R. Zhang, "A survey on 5G millimeter wave communications for UAV-assisted wireless networks," *IEEE Access*, vol. 7, pp. 117460–117504, Jul. 2019.
- [26] Y. Niu, Y. Li, D. Jin, L. Su, and A. V. Vasilakos, "A survey of millimeter wave (mmWave) communications for 5G: Opportunities and challenges," Feb. 2015, *arXiv:1502.07228*. [Online]. Available: <http://arxiv.org/abs/1502.07228>
- [27] X. Wang, L. Kong, F. Kong, F. Qiu, M. Xia, S. Arnon, and G. Chen, "Millimeter wave communication: A comprehensive survey," *IEEE Commun. Surveys Tuts.*, vol. 20, no. 3, pp. 1616–1653, 3rd Quart., 2018.
- [28] Y. Niu, Y. Li, D. Jin, L. Su, and D. Wu, "Blockage robust and efficient scheduling for directional mmWave WPANs," *IEEE Trans. Veh. Technol.*, vol. 64, no. 2, pp. 728–742, Feb. 2015.
- [29] Y. Oguma, R. Arai, T. Nishio, K. Yamamoto, and M. Morikura, "Proactive base station selection based on human blockage prediction using RGB-D cameras for mmWave communications," in *Proc. IEEE Global Commun. Conf. (GLOBECOM)*, San Diego, CA, USA, Dec. 2014, pp. 1–6.
- [30] S. Singh, F. Ziliotto, U. Madhoo, E. Belding, and M. Rodwell, "Blockage and directivity in 60 GHz wireless personal area networks: From cross-layer model to multihop MAC design," *IEEE J. Sel. Areas Commun.*, vol. 27, no. 8, pp. 1400–1413, Oct. 2009.
- [31] D. Ramirez, L. Huang, Y. Wang, and B. Aazhang, "On opportunistic mmWave networks with blockage," *IEEE J. Sel. Areas Commun.*, vol. 35, no. 9, pp. 2137–2147, Sep. 2017.
- [32] Y. M. Tsang and A. S. Y. Poon, "Detecting human blockage and device movement in mmWave communication system," in *Proc. IEEE Global Telecommun. Conf. (GLOBECOM)*, Houston, TX, USA, Dec. 2011, pp. 1–6.
- [33] F. Zhao, W. Hao, L. Shen, G. Sun, Y. Zhou, and Y. Wang, "Secure energy efficiency transmission for mmWave-NOMA system," *IEEE Syst. J.*, early access, Mar. 30, 2020, doi: [10.1109/JSYST.2020.2979818](https://doi.org/10.1109/JSYST.2020.2979818).
- [34] Y. Yapici, N. Rupasinghe, I. Guvenc, H. Dai, and A. Bhuyan, "Physical layer security for NOMA transmission in mmWave drone networks," Jan. 2020, *arXiv:2001.04863*. [Online]. Available: <http://arxiv.org/abs/2001.04863>
- [35] J. Cui, Z. Ding, P. Fan, and N. Al-Dhahir, "Unsupervised machine learning-based user clustering in Millimeter-Wave-NOMA systems," *IEEE Trans. Wireless Commun.*, vol. 17, no. 11, pp. 7425–7440, Nov. 2018.
- [36] D. Marasinghe, N. Jayaweera, N. Rajatheva, and M. Latva-Aho, "Hierarchical user clustering for mmWave-NOMA systems," Feb. 2020, *arXiv:2002.07452*. [Online]. Available: <http://arxiv.org/abs/2002.07452>
- [37] B. Wang, R. Shi, F. Shi, and J. Hu, "MmWave-NOMA-based low-latency and high-reliable communications for enhancement of V2X services," *IEEE Access*, vol. 8, pp. 57049–57062, Mar. 2020.
- [38] J. Kaur and M. L. Singh, "User assisted cooperative relaying in beamspace massive MIMO NOMA based systems for millimeter wave communications," *China Commun.*, vol. 16, no. 6, pp. 103–113, Jun. 2019.
- [39] L. Dai, B. Wang, M. Peng, and S. Chen, "Hybrid precoding-based millimeter-wave massive MIMO-NOMA with simultaneous wireless information and power transfer," *IEEE J. Sel. Areas Commun.*, vol. 37, no. 1, pp. 131–141, Jan. 2019.
- [40] T. Lv, Y. Ma, J. Zeng, and P. T. Mathiopoulos, "Millimeter-wave NOMA transmission in cellular M2M communications for Internet of Things," *IEEE Internet Things J.*, vol. 5, no. 3, pp. 1989–2000, Jun. 2018.
- [41] M. Zeng, W. Hao, O. A. Dobre, and H. V. Poor, "Energy-efficient power allocation in uplink mmWave massive MIMO with NOMA," *IEEE Trans. Veh. Technol.*, vol. 68, no. 3, pp. 3000–3004, Mar. 2019.
- [42] W. Hao, M. Zeng, G. Sun, O. Muta, O. A. Dobre, S. Yang, and H. Gacanin, "Codebook-based Max–Min energy-efficient resource allocation for uplink mmWave MIMO-NOMA systems," *IEEE Trans. Commun.*, vol. 67, no. 12, pp. 8303–8314, Dec. 2019.
- [43] N. Iqbal, J. Luo, R. Muller, G. Steinbock, C. Schneider, D. A. Dupleich, S. Hafner, and R. S. Thoma, "Multipath cluster fading statistics and modeling in millimeter-wave radio channels," *IEEE Trans. Antennas Propag.*, vol. 67, no. 4, pp. 2622–2632, Apr. 2019.
- [44] I. A. Hemadeh, K. Satyanarayana, M. El-Hajjar, and L. Hanzo, "Millimeter-wave communications: Physical channel models, design considerations, antenna constructions, and link-budget," *IEEE Commun. Surveys Tuts.*, vol. 20, no. 2, pp. 870–913, 2nd Quart., 2018.
- [45] S. Hur, S. Baek, B. Kim, Y. Chang, A. F. Molisch, T. S. Rappaport, K. Haneda, and J. Park, "Proposal on millimeter-wave channel modeling for 5G cellular system," *IEEE J. Sel. Topics Signal Process.*, vol. 10, no. 3, pp. 454–469, Apr. 2016.
- [46] M. K. Samimi and T. S. Rappaport, "3-D millimeter-wave statistical channel model for 5G wireless system design," *IEEE Trans. Microw. Theory Techn.*, vol. 64, no. 7, pp. 2207–2225, Jul. 2016.
- [47] T. S. Rappaport, G. R. MacCartney, M. K. Samimi, and S. Sun, "Wideband millimeter-wave propagation measurements and channel models for future wireless communication system design," *IEEE Trans. Commun.*, vol. 63, no. 9, pp. 3029–3056, Sep. 2015.
- [48] L. N. Ribeiro, S. Schwarz, and A. L. F. De Almeida, "Double-sided massive MIMO transceivers for mmWave communications," *IEEE Access*, vol. 7, pp. 157667–157679, Oct. 2019.
- [49] C. G. Tsinos, S. Chatzinotas, and B. Ottersten, "Hybrid analog-digital transceiver designs for multi-user MIMO mmWave cognitive radio systems," *IEEE Trans. Cognit. Commun. Netw.*, vol. 6, no. 1, pp. 310–324, Mar. 2020.
- [50] K. Satyanarayana, M. El-Hajjar, P.-H. Kuo, A. A. M. Mourad, and L. Hanzo, "Adaptive transceiver design for C-RAN in mmWave communications," *IEEE Access*, vol. 6, pp. 16770–16782, Nov. 2018.
- [51] P. Xia, R. W. Heath, Jr., and N. Gonzalez-Prelicic, "Robust analog precoding designs for millimeter wave MIMO transceivers with frequency and time division duplexing," *IEEE Trans. Commun.*, vol. 64, no. 11, pp. 4622–4634, Nov. 2016.
- [52] K. Satyanarayana, M. El-Hajjar, A. A. M. Mourad, and L. Hanzo, "Multi-user full duplex transceiver design for mmWave systems using learning-aided channel prediction," *IEEE Access*, vol. 7, pp. 66068–66083, May 2019.
- [53] H. Chen, Y. Shao, Y. Zhang, C. Zhang, and Z. Zhang, "A low-profile broadband circularly polarized mmWave antenna with special-shaped ring slot," *IEEE Antennas Wireless Propag. Lett.*, vol. 18, no. 7, pp. 1492–1496, Jul. 2019.
- [54] K. Gulur Sadananda, M. P. Abegaonkar, and S. K. Koul, "Gain equalized shared-aperture antenna using dual-polarized ZIM for mmWave 5G base stations," *IEEE Antennas Wireless Propag. Lett.*, vol. 18, no. 6, pp. 1100–1104, Jun. 2019.
- [55] C. Shu, J. Wang, S. Hu, Y. Yao, J. Yu, Y. Alfadhil, and X. Chen, "A wideband dual-circular-polarization horn antenna for mmWave wireless communications," *IEEE Antennas Wireless Propag. Lett.*, vol. 18, no. 9, pp. 1726–1730, Sep. 2019.
- [56] S. Zhu, H. Liu, Z. Chen, and P. Wen, "A compact gain-enhanced vivaldi antenna array with suppressed mutual coupling for 5G mmWave application," *IEEE Antennas Wireless Propag. Lett.*, vol. 17, no. 5, pp. 776–779, May 2018.
- [57] Q. Wu, J. Hirokawa, J. Yin, C. Yu, H. Wang, and W. Hong, "Millimeter-wave multibeam endfire dual-circularly polarized antenna array for 5G wireless applications," *IEEE Trans. Antennas Propag.*, vol. 66, no. 9, pp. 4930–4935, Sep. 2018.
- [58] H. Kaouach and A. Kabashi, "Simple tri-layer linearly polarized discrete lens antenna with high-efficiency for mmWave applications," *IEEE Antennas Wireless Propag. Lett.*, vol. 15, pp. 259–262, Jun. 2016.
- [59] K. Tekbiyik, A. Ekti, G. Kurt, and A. Gorcin, "Terahertz band communication systems: Challenges, novelties and standardization efforts," *Phys. Commun.*, vol. 35, pp. 1–18, Aug. 2019.

- [60] T. Wen, D. Zhang, Q. Wen, Y. Liao, C. Zhang, J. Li, W. Tian, Y. Li, H. Zhang, Y. Li, Q. Yang, and Z. Zhong, "Enhanced optical modulation depth of terahertz waves by self-assembled monolayer of plasmonic gold nanoparticles," *Adv. Opt. Mater.*, vol. 4, no. 12, pp. 1974–1980, Sep. 2016.
- [61] W. Lai, P. Huang, B. Pelaz, P. D. Pino, and Q. Zhang, "Enhanced all-optical modulation of terahertz waves on the basis of manganese ferrite nanoparticles," *J. Phys. Chem. C*, vol. 121, no. 39, pp. 21634–21640, Sep. 2017.
- [62] T. A. P. Tran and P. H. Bolivar, "Terahertz modulator based on vertically coupled fano metamaterial," *IEEE Trans. THz Sci. Technol.*, vol. 8, no. 5, pp. 502–508, Sep. 2018.
- [63] S. Yamasaki, A. Yasui, T. Amemiya, K. Furusawa, S. Hara, I. Watanabe, A. Kanno, N. Sekine, Z. Gu, N. Nishiyama, A. Kasamatsu, and S. Arai, "Optically driven terahertz wave modulator using ring-shaped microstripline with GaInAs photoconductive mesa structure," *IEEE J. Sel. Topics Quantum Electron.*, vol. 23, no. 4, pp. 1–8, Jul. 2017.
- [64] L. Xiong, B. Zhang, H. Ji, W. Wang, X. Liu, S. He, and J. Shen, "Active optically controlled broadband Terahertz modulator based on Fe₃O₄Nanoparticles," *IEEE Trans. THz Sci. Technol.*, vol. 8, no. 5, pp. 535–540, Sep. 2018.
- [65] L. Jiu-sheng, L. Shao-he, and Z. Le, "Terahertz modulator using 4-N,N-Dimethylamino-4'-N'-methyl-stilbazolium tosylate (DAST)/Si hybrid structure," *IEEE Photon. J.*, vol. 10, no. 2, pp. 1–6, Apr. 2018.
- [66] C. Yi, S. H. Choi, M. Urteaga, and M. Kim, "20-Gb/s ON-OFF-Keying modulators using 0.25- μ m InP DHBT switches at 290 GHz," *IEEE Microw. Wireless Compon. Lett.*, vol. 29, no. 5, pp. 360–362, May 2019.
- [67] G. Isic, G. Sinatkas, D. C. Zografopoulos, B. Vasic, A. Ferraro, R. Beccherelli, E. E. Kriezis, and M. Belic, "Electrically tunable metal-semiconductor-metal terahertz metasurface modulators," *IEEE J. Sel. Topics Quantum Electron.*, vol. 25, no. 3, pp. 1–8, May 2019.
- [68] Y. Wu, X. Qiu, H. Liu, J. Liu, Y. Chen, L. Ke, and H. Yang, "Tunable Terahertz reflection of graphene via ionic liquid gating," *Nanotechnol.*, vol. 28, no. 9, pp. 1–5, Jan. 2017.
- [69] O. Ozdemir, A. M. Aygar, O. Balci, C. Kocabas, H. Caglayan, and E. Ozbay, "Enhanced tunability of V-shaped plasmonic structures using ionic liquid gating and graphene," *Carbon*, vol. 108, pp. 515–520, Nov. 2016.
- [70] H.-J. Song and T. Nagatsuma, "Present and future of terahertz communications," *IEEE Trans. THz Sci. Technol.*, vol. 1, no. 1, pp. 256–263, Sep. 2011.
- [71] Q. Yu, J. Gu, Q. Yang, Y. Zhang, Y. Li, Z. Tian, C. Ouyang, J. Han, J. F. Ohara, and W. Zhang, "All-dielectric meta-lens designed for photoconductive terahertz antennas," *IEEE Photon. J.*, vol. 9, no. 4, pp. 1–9, Aug. 2017.
- [72] Z. Shen, X. Ji, Y. Liao, K. Wang, B. Jin, and F. Yan, "Resonant polysilicon antenna for terahertz detection," *IEEE Photon. J.*, vol. 11, no. 4, pp. 1–8, Aug. 2019.
- [73] Z.-C. Hao, J. Wang, Q. Yuan, and W. Hong, "Development of a low-cost THz metallic lens antenna," *IEEE Antennas Wireless Propag. Lett.*, vol. 16, pp. 1751–1754, Feb. 2017.
- [74] K. Fan, Z.-C. Hao, Q. Yuan, and W. Hong, "Development of a high gain 325–500 GHz antenna using quasi-planar reflectors," *IEEE Trans. Antennas Propag.*, vol. 65, no. 7, pp. 3384–3391, Jul. 2017.
- [75] S. Bhardwaj and J. L. Volakis, "Hexagonal waveguide based circularly polarized horn antennas for Sub-mm-Wave/terahertz band," *IEEE Trans. Antennas Propag.*, vol. 66, no. 7, pp. 3366–3374, Jul. 2018.
- [76] G. Rana, A. Bhattacharya, A. Gupta, D. Ghindani, R. Jain, S. P. Duttagupta, and S. S. Prabhu, "A polarization-resolved study of nanopatterned photoconductive antenna for enhanced terahertz emission," *IEEE Trans. THz Sci. Technol.*, vol. 9, no. 2, pp. 193–199, Mar. 2019.
- [77] G. P. Szakmany, A. O. Orlov, G. H. Bernstein, and W. Porod, "THz wave detection by antenna-coupled nanoscale thermoelectric converters," *IEEE Trans. THz Sci. Technol.*, vol. 7, no. 5, pp. 582–585, Sep. 2017.
- [78] N. M. Burford, M. J. Evans, and M. O. El-Shenawee, "Plasmonic nanodisk thin-film terahertz photoconductive antenna," *IEEE Trans. THz Sci. Technol.*, vol. 8, no. 2, pp. 237–247, Mar. 2018.
- [79] J. Al-Eryani, H. Knapp, J. Kammerer, K. Aufinger, H. Li, and L. Maurer, "Fully integrated single-chip 305–375-GHz transceiver with on-chip antennas in SiGe BiCMOS," *IEEE Trans. THz Sci. Technol.*, vol. 8, no. 3, pp. 329–339, May 2018.
- [80] C. Jiang, A. Mostajeran, R. Han, M. Emadi, H. Sherry, A. Cathelin, and E. Afshari, "A fully integrated 320 GHz coherent imaging transceiver in 130 nm SiGe BiCMOS," *IEEE J. Solid-State Circuits*, vol. 51, no. 11, pp. 2596–2609, Nov. 2016.
- [81] B. Blazquez, K. B. Cooper, and N. Llobert, "Time-delay multiplexing with linear arrays of THz radar transceivers," *IEEE Trans. THz Sci. Technol.*, vol. 4, no. 2, pp. 232–239, Mar. 2014.
- [82] T. Bryllert, V. Drakinskiy, K. B. Cooper, and J. Stake, "Integrated 200–240-GHz FMCW radar transceiver module," *IEEE Trans. Microw. Theory Techn.*, vol. 61, no. 10, pp. 3808–3815, Oct. 2013.
- [83] T. Gobel, D. Schoenherr, C. Sydlo, M. Feiginov, P. Meissner, and H. L. Hartnagel, "Continuous-wave single-sampling-point characterisation of optoelectronic on-chip terahertz transceiver," *Electron. Lett.*, vol. 45, no. 23, pp. 1171–1172, Nov. 2009.
- [84] S. Moghadami, F. Hajilou, P. Agrawal, and S. Ardalan, "A 210 GHz fully-integrated OOK transceiver for short-range wireless Chip-to-Chip communication in 40 nm CMOS technology," *IEEE Trans. THz Sci. Technol.*, vol. 5, no. 5, pp. 737–741, Sep. 2015.
- [85] C. Lin and G. Y. Li, "Indoor terahertz communications: How many antenna arrays are needed?" *IEEE Trans. Wireless Commun.*, vol. 14, no. 6, pp. 3097–3107, Jun. 2015.
- [86] C. Han, A. O. Bicen, and I. F. Akyildiz, "Multiray channel modeling and wideband characterization for wireless communications in the terahertz band," *IEEE Trans. Wireless Commun.*, vol. 14, no. 5, pp. 2402–2412, May 2015.
- [87] D. He, K. Guan, B. Ai, A. Fricke, R. He, Z. Zhong, A. Kasamatsu, I. Hosako, and T. Kurner, "Channel modeling for kiosk downloading communication system at 300 GHz," in *Proc. 11th Eur. Conf. Antennas Propag. (EUCAP)*, Mar. 2017, pp. 1331–1335.
- [88] C. Han and I. F. Akyildiz, "Three-dimensional end-to-end modeling and analysis for graphene-enabled terahertz band communications," *IEEE Trans. Veh. Technol.*, vol. 66, no. 7, pp. 5626–5634, Jul. 2017.
- [89] C. Zhang, C. Han, and I. F. Akyildiz, "Three dimensional end-to-end modeling and directivity analysis for graphene-based antennas in the terahertz band," in *Proc. IEEE Global Commun. Conf. (GLOBECOM)*, San Diego, CA, USA, Dec. 2014, pp. 1–6.
- [90] D. He, K. Guan, A. Fricke, B. Ai, R. He, Z. Zhong, A. Kasamatsu, I. Hosako, and T. Kurner, "Stochastic channel modeling for kiosk applications in the terahertz band," *IEEE Trans. THz Sci. Technol.*, vol. 7, no. 5, pp. 502–513, Sep. 2017.
- [91] S. Kim and A. Zajic, "Statistical modeling and simulation of short-range device-to-device communication channels at sub-THz frequencies," *IEEE Trans. Wireless Commun.*, vol. 15, no. 9, pp. 6423–6433, Sep. 2016.
- [92] K. Tekbiyik, E. Ulusoy, A. R. Ekti, S. Yarkan, T. Baykas, A. Gorcin, and G. K. Kurt, "Statistical channel modeling for short range line-of-sight terahertz communication," in *Proc. IEEE 30th Annu. Int. Symp. Pers., Indoor Mobile Radio Commun. (PIMRC)*, Sep. 2019, pp. 1–5.
- [93] R. Piesiewicz, T. Kleine-Ostmann, N. Krumbholz, D. Mittleman, M. Koch, and T. Kurner, "Terahertz characterisation of building materials," *Electron. Lett.*, vol. 41, no. 18, pp. 1002–1004, Sep. 2005.
- [94] C. Jansen, R. Piesiewicz, D. Mittleman, T. Kurner, and M. Koch, "The impact of reflections from stratified building materials on the wave propagation in future indoor terahertz communication systems," *IEEE Trans. Antennas Propag.*, vol. 56, no. 5, pp. 1413–1419, May 2008.
- [95] H. Zhao, L. Wei, M. Jarrahi, and G. J. Pottie, "Extending spatial and temporal characterization of indoor wireless channels from 350 to 650 GHz," *IEEE Trans. THz Sci. Technol.*, vol. 9, no. 3, pp. 243–252, May 2019.
- [96] K. Guan, B. Peng, D. He, J. M. Eckhardt, S. Rey, B. Ai, Z. Zhong, and T. Kurner, "Measurement, simulation, and characterization of train-to-infrastructure inside-station channel at the terahertz band," *IEEE Trans. THz Sci. Technol.*, vol. 9, no. 3, pp. 291–306, May 2019.
- [97] X. Gao, L. Dai, Y. Zhang, T. Xie, X. Dai, and Z. Wang, "Fast channel tracking for terahertz beamspace massive MIMO systems," *IEEE Trans. Veh. Technol.*, vol. 66, no. 7, pp. 5689–5696, Jul. 2017.
- [98] K. Tsujimura, K. Umebayashi, J. Kokkonen, J. Lehtomaki, and Y. Suzuki, "A causal channel model for the terahertz band," *IEEE Trans. THz Sci. Technol.*, vol. 8, no. 1, pp. 52–62, Jan. 2018.
- [99] B. Peng and T. Kurner, "Three-dimensional angle of arrival estimation in dynamic indoor terahertz channels using a forward-backward algorithm," *IEEE Trans. Veh. Technol.*, vol. 66, no. 5, pp. 3798–3811, May 2017.

- [100] J. Park, S. Choi, J. J. Kim, Y. Kim, M. Lee, H. Kim, B. Bae, H. Song, K. Cho, S. Lee, H. Lee, and J. Kim, "A novel stochastic model-based eye-diagram estimation method for 8B/10B and TMDS-encoded high-speed channels," *IEEE Trans. Electromagn. Compat.*, vol. 60, no. 5, pp. 1510–1519, Oct. 2018.
- [101] M. Uysal and H. Nouri, "Optical wireless communications-an emerging technology," in *Proc. Int. Conf. Transparent Opt. Netw. (ICTON)*, Graz, Austria, Jul. 2014, pp. 1–7.
- [102] M. Z. Chowdhury, M. Shahjalal, M. K. Hasan, and Y. M. Jang, "The role of optical wireless communication technologies in 5G/6G and IoT solutions: Prospects, directions, and challenges," *Appl. Sci.*, vol. 9, no. 20, p. 4367, Oct. 2019, doi: 10.3390/app9204367.
- [103] P. H. Pathak, X. Feng, P. Hu, and P. Mohapatra, "Visible light communication, networking, and sensing: A survey, potential and challenges," *IEEE Commun. Surveys Tuts.*, vol. 17, no. 4, pp. 2047–2077, 4th Quart., 2015.
- [104] A. R. Ndjiongue, T. M. N. Ngatched, O. A. Dobre, and A. G. Armada, "VLC-based networking: Feasibility and challenges," *IEEE Netw.*, vol. 34, no. 4, pp. 158–165, Jul./Aug. 2020.
- [105] P. S. S. Kumar, "A comprehensive survey of visible light communication: Potential and challenges," *Wireless Pers. Commun.*, vol. 109, pp. 1357–1375, Nov. 2019.
- [106] H. Haas, L. Yin, C. Chen, S. Videv, D. Parol, E. Poves, H. Alshaer, and M. S. Islam, "Introduction to indoor networking concepts and challenges in LiFi," *J. Opt. Commun. Netw.*, vol. 12, no. 2, pp. A190–A203, Feb. 2020.
- [107] H. Haas, L. Yin, Y. Wang, and C. Chen, "What is LiFi?" *J. Lightw. Technol.*, vol. 34, no. 6, pp. 1533–1544, Mar. 15, 2016.
- [108] N. Saha, N. T. Le, M. S. Iftekhar, and Y. M. Jang, "Survey on optical camera communications: Challenges and opportunities," *IET Optoelectron.*, vol. 9, no. 5, pp. 172–183, Oct. 2015.
- [109] T. Nguyen, A. Islam, T. Hossan, and Y. M. Jang, "Current status and performance analysis of optical camera communication technologies for 5G networks," *IEEE Access*, vol. 5, pp. 4574–4594, Mar. 2017.
- [110] M. Z. Chowdhury, M. T. Hossan, A. Islam, and Y. M. Jang, "A comparative survey of optical wireless technologies: Architectures and applications," *IEEE Access*, vol. 6, pp. 9819–9840, Jan. 2018.
- [111] F. Demers, H. Yanikomeroglu, and M. St-Hilaire, "A survey of opportunities for free space optics in next generation cellular networks," in *Proc. 9th Annu. Commun. Netw. Services Res. Conf.*, May 2011, pp. 210–216.
- [112] M. A. Khalighi and M. Uysal, "Survey on free space optical communication: A communication theory perspective," *IEEE Commun. Surveys Tuts.*, vol. 16, no. 4, pp. 2231–2258, 4th Quart., 2014.
- [113] A. C. Boucouvalas, "Ambient light noise and its effect on receiver design for indoor wireless optical links," in *Proc. ICC/SUPERCOMM Int. Conf. Commun.*, Dallas, TX, USA, vol. 3, Jun. 1996, pp. 1472–1476.
- [114] A. C. Boucouvalas, "Indoor ambient light noise and its effect on wireless optical links," *IEE Proc.-Optoelectron.*, vol. 143, no. 6, pp. 334–338, Dec. 1996.
- [115] S. Verma, A. Shandilya, and A. Singh, "A model for reducing the effect of ambient light source in VLC system," in *Proc. IEEE Int. Advance Comput. Conf. (IACC)*, Gurgaon, Feb. 2014, pp. 186–188.
- [116] X. Li, B. Hussain, L. Wang, J. Jiang, and C. P. Yue, "Design of a 2.2-mW 24-Mb/s CMOS VLC receiver SoC with ambient light rejection and post-equalization for li-fi applications," *J. Lightw. Technol.*, vol. 36, no. 12, pp. 2366–2375, Jun. 15, 2018.
- [117] C.-L. Lin, P.-S. Chen, C.-H. Chang, J.-S. Yu, C. Chang, and Y.-H. Tseng, "A hydrogenated amorphous silicon thin-film transistor optical pixel sensor for ameliorating influences of ambient light and reflected light," *IEEE J. Electron Devices Soc.*, vol. 5, no. 4, pp. 262–265, Jul. 2017.
- [118] S.-H. Lee, "Reducing the effects of ambient noise light in an indoor optical wireless system using polarizers," *Microw. Opt. Technol. Lett.*, vol. 40, no. 3, pp. 228–231, Dec. 2004.
- [119] T. Adiono, A. Pradana, R. V. W. Putra, and S. Fuada, "Analog filters design in VLC analog front-end receiver for reducing indoor ambient light noise," in *Proc. IEEE Asia Pacific Conf. Circuits Syst. (APCCAS)*, Jeju, South Korea, Oct. 2016, pp. 581–584.
- [120] S. B. Lynch and S. P. Hotelling, "Ambient light interference reduction for optical input devices," U.S. Patent 2010001978 A1, Jan. 23, 2010.
- [121] S. Arnon, "Effects of atmospheric turbulence and building sway on optical wireless-communication systems," *Opt. Lett.*, vol. 28, no. 2, pp. 129–131, Dec. 2003.
- [122] X. Song and J. Cheng, "Optical communication using subcarrier intensity modulation in strong atmospheric turbulence," *J. Lightw. Technol.*, vol. 30, no. 22, pp. 3484–3493, Nov. 15, 2012.
- [123] X. Song and J. Cheng, "Subcarrier intensity modulated MIMO optical communications in atmospheric turbulence," *IEEE/OSA J. Opt. Commun. Netw.*, vol. 5, no. 9, pp. 1001–1009, Sep. 2013.
- [124] A. Jaiswal, M. R. Bhatnagar, P. Soni, and V. K. Jain, "Differential optical spatial modulation over atmospheric turbulence," *IEEE J. Sel. Topics Signal Process.*, vol. 13, no. 6, pp. 1417–1432, Oct. 2019.
- [125] S. Arya and Y. H. Chung, "A novel blind spectrum sensing technique for multi-user ultraviolet communications in atmospheric turbulence channel," *IEEE Access*, vol. 7, pp. 58314–58323, May 2019.
- [126] M. Aggarwal, P. Garg, and P. Puri, "Exact capacity of Amplify-and-Forward relayed optical wireless communication systems," *IEEE Photon. Technol. Lett.*, vol. 27, no. 8, pp. 903–906, Apr. 15, 2015.
- [127] M. Gebhart, E. Leitgeb, and J. Bregerer, "Atmospheric effects on optical wireless links," in *Proc. Int. Conf. Telecommun. (ConTEL)*, Zagreb, Croatia, vol. 2, Jun. 2003, pp. 395–401.
- [128] Y. Ata, Y. Baykal, and M. C. Gökçe, "Error performance of optical wireless communication systems exercising BPSK subcarrier intensity modulation in non-Kolmogorov turbulent atmosphere," *Opt. Commun.*, vol. 436, pp. 108–112, Apr. 2019.
- [129] J. Latal, J. Vitasek, L. Hajek, A. Vanderka, R. Martinek, and V. Vasinek, "Influence of simulated atmospheric effect combined with modulation formats on FSO systems," *Opt. Switching Netw.*, vol. 33, pp. 184–193, Jul. 2019.
- [130] Y. Baykal, "BER of asymmetrical optical beams in oceanic and marine atmospheric media," *Opt. Commun.*, vol. 393, pp. 29–33, Jun. 2017.
- [131] D. Kedar and S. Arnon, "Urban optical wireless communication networks: The main challenges and possible solutions," *IEEE Commun. Mag.*, vol. 42, no. 5, pp. S2–S7, May 2004.
- [132] H. G. Sandalidis, T. A. Tsiftsis, and G. K. Karagiannidis, "Optical wireless communications with heterodyne detection over turbulence channels with pointing errors," *J. Lightw. Technol.*, vol. 27, no. 20, pp. 4440–4445, Oct. 15, 2009.
- [133] M. Smilic, Z. Nikolic, D. Milic, P. Spalevic, and S. Panic, "Comparison of adaptive algorithms for free space optical transmission in Malaga atmospheric turbulence channel with pointing errors," *IET Commun.*, vol. 13, no. 11, pp. 1578–1585, Jul. 2019.
- [134] S. E. Tsvlakis, A.-A.-A. Boulogeorgos, and G. K. Karagiannidis, "Outage performance of transdermal optical wireless links in the presence of pointing errors," in *Proc. IEEE 19th Int. Workshop Signal Process. Adv. Wireless Commun. (SPAWC)*, Kalamata, Greece, Jun. 2018, pp. 1–5.
- [135] A. Jaiswal, M. R. Bhatnagar, and V. K. Jain, "Performance of optical space shift keying over Gamma-Gamma fading with pointing error," *IEEE Photon. J.*, vol. 9, no. 2, pp. 1–16, Apr. 2017.
- [136] I. S. Ansari, F. Yilmaz, and M. Alouini, "Performance analysis of free-space optical links over Malaga (M) turbulence channels with pointing errors," *IEEE Trans. Wireless Commun.*, vol. 15, no. 1, pp. 91–102, Jan. 2016.
- [137] L. Yang, X. Gao, and M.-S. Alouini, "Performance analysis of relay-assisted all-optical FSO networks over strong atmospheric turbulence channels with pointing errors," *J. Lightw. Technol.*, vol. 32, no. 23, pp. 4613–4620, Dec. 1, 2014.
- [138] I. S. Ansari, M.-S. Alouini, and J. Cheng, "Ergodic capacity analysis of free-space optical links with nonzero boresight pointing errors," *IEEE Trans. Wireless Commun.*, vol. 14, no. 8, pp. 4248–4264, Aug. 2015.
- [139] M. D. Renzo, M. Debbah, D.-T. Phan-Huy, A. Zappone, M.-S. Alouini, C. Yuen, V. Sciancalepore, G. C. Alexandropoulos, J. Hoydis, H. Gacanin, J. D. Rosny, A. Bounceur, G. Lerosey, and M. Fink, "Smart radio environments empowered by reconfigurable AI meta-surfaces: An idea whose time has come," *EURASIP J. Wireless Commun. Netw.*, vol. 2019, no. 1, pp. 1–20, May 2019.
- [140] C. Liaskos, S. Nie, A. Tsioliaridou, A. Pitsillides, S. Ioannidis, and I. Akyildiz, "A new wireless communication paradigm through software-controlled metasurfaces," *IEEE Commun. Mag.*, vol. 56, no. 9, pp. 162–169, Sep. 2018.
- [141] *Realizing Wireless Communication Through Software-Defined HyperSurface Environments*, Chania, Greece, Jun. 2018.
- [142] C. Liaskos, S. Nie, A. Tsioliaridou, A. Pitsillides, S. Ioannidis, and I. Akyildiz, "A novel communication paradigm for high capacity and security via programmable indoor wireless environments in next generation wireless systems," *Ad Hoc Netw.*, vol. 87, pp. 1–16, May 2019.
- [143] S. Abadal, T.-J. Cui, T. Low, and J. Georgiou, "Programmable metamaterials for software-defined electromagnetic control: Circuits, systems, and architectures," *IEEE J. Emerg. Sel. Topics Circuits Syst.*, vol. 10, no. 1, pp. 6–19, Mar. 2020.

- [144] L. Mohjazi, A. Zoha, L. Bariah, S. Muhaidat, P. C. Sofotasios, M. Ali Imran, and O. A. Dobre, "An outlook on the interplay of AI and software-defined metasurfaces," 2020, *arXiv:2004.00365*. [Online]. Available: <http://arxiv.org/abs/2004.00365>
- [145] C. Huang, G. C. Alexandropoulos, C. Yuen, and M. Debbah, "Indoor signal focusing with deep learning designed reconfigurable intelligent surfaces," in *Proc. IEEE 20th Int. Workshop Signal Process. Adv. Wireless Commun. (SPAWC)*, Cannes, France, 2019, pp. 1–5, doi: [10.1109/SPAWC.2019.8815412](https://doi.org/10.1109/SPAWC.2019.8815412).
- [146] C. Liaskos, A. Tsioliaridou, S. Nie, A. Pitsillides, S. Ioannidis, and I. Akyildiz, "An interpretable neural network for configuring programmable wireless environments," in *Proc. IEEE 20th Int. Workshop Signal Process. Adv. Wireless Commun. (SPAWC)*, Jul. 2019, pp. 1–5.
- [147] T. Shan, X. Pan, M. Li, S. Xu, and F. Yang, "Coding programmable metasurfaces based on deep learning techniques," *IEEE J. Emerg. Sel. Topics Circuits Syst.*, vol. 10, no. 1, pp. 114–125, Mar. 2020.
- [148] L. Li, H. Ruan, C. Liu, Y. Li, Y. Shuang, A. Alù, C.-W. Qiu, and T. J. Cui, "Machine-learning reprogrammable metasurface imager," *Nature Commun.*, vol. 10, no. 1, pp. 1–8, Mar. 2019.
- [149] J. Zhao, X. Yang, J. Y. Dai, Q. Cheng, X. Li, N. H. Qi, J. C. Ke, G. D. Bai, S. Liu, S. Jin, A. Alù, and T. J. Cui, "Programmable time-domain digital-coding metasurface for non-linear harmonic manipulation and new wireless communication systems," *Nat. Sci. Rev.*, vol. 6, no. 2, pp. 231–238, Mar. 2019.
- [150] W. Tang, X. Li, J. Y. Dai, S. Jin, Y. Zeng, Q. Cheng, and T. J. Cui, "Wireless communications with programmable metasurface: Transceiver design and experimental results," *China Commun.*, vol. 16, no. 5, pp. 46–61, May 2019.
- [151] L. Zhang, X. Q. Chen, S. Liu, Q. Zhang, J. Zhao, J. Y. Dai, G. D. Bai, X. Wan, Q. Cheng, and G. Castaldi, "Space-time-coding digital metasurfaces," *Nature Commun.*, vol. 9, no. 4334, pp. 1–11, Oct. 2018.
- [152] M. Wang, H. F. Ma, L. W. Wu, S. Sun, W. X. Tang, and T. J. Cui, "Hybrid digital coding metasurface for independent control of propagating surface and spatial waves," *Adv. Opt. Mater.*, vol. 7, no. 13, pp. 1–8, May 2019.
- [153] E. Basar, "Reconfigurable intelligent surface-based index modulation: A new beyond MIMO paradigm for 6G," 2019, *arXiv:1904.06704*. [Online]. Available: <http://arxiv.org/abs/1904.06704>
- [154] X. Guan, Q. Wu, and R. Zhang, "Intelligent reflecting surface assisted secrecy communication: Is artificial noise helpful or not?" *IEEE Wireless Commun. Lett.*, vol. 9, no. 6, pp. 778–782, Jun. 2020.
- [155] X. Yu, D. Xu, and R. Schober, "Enabling secure wireless communications via intelligent reflecting surfaces," 2019, *arXiv:1904.09573*. [Online]. Available: <http://arxiv.org/abs/1904.09573>
- [156] H. Shen, W. Xu, S. Gong, Z. He, and C. Zhao, "Secrecy rate maximization for intelligent reflecting surface assisted multi-antenna communications," *IEEE Commun. Lett.*, vol. 23, no. 9, pp. 1488–1492, Sep. 2019.
- [157] J. Chen, Y.-C. Liang, Y. Pei, and H. Guo, "Intelligent reflecting surface: A programmable wireless environment for physical layer security," *IEEE Access*, vol. 7, pp. 82599–82612, Jun. 2019.
- [158] Q. Wu and R. Zhang, "Intelligent reflecting surface enhanced wireless network: Joint active and passive beamforming design," in *Proc. IEEE Global Commun. Conf. (GLOBECOM)*, Abu Dhabi, Dec. 2018, pp. 1–6.
- [159] L. Li, H. Liu, H. Zhang, and W. Xue, "Efficient wireless power transfer system integrating with metasurface for biological applications," *IEEE Trans. Ind. Electron.*, vol. 65, no. 4, pp. 3230–3239, Apr. 2018.
- [160] M. Song, P. Kapitanova, I. Iorsh, and P. Belov, "Metamaterials for wireless power transfer," in *Proc. Days Diffraction (DD)*, St. Petersburg, Russia, May 2015, pp. 1–4.
- [161] A. Taha, M. Alrabeiah, and A. Alkhateeb, "Enabling large intelligent surfaces with compressive sensing and deep learning," 2019, *arXiv:1904.10136*. [Online]. Available: <http://arxiv.org/abs/1904.10136>
- [162] P. del Hougne, M. F. Imani, A. V. Diebold, R. Horstmeyer, and D. R. Smith, "Artificial neural network with physical dynamic metasurface layer for optimal sensing," 2019, *arXiv:1906.10251*. [Online]. Available: <http://arxiv.org/abs/1906.10251>
- [163] C. Huang, G. C. Alexandropoulos, C. Yuen, and M. Debbah, "Indoor signal focusing with deep learning designed reconfigurable intelligent surfaces," in *Proc. IEEE 20th Int. Workshop Signal Process. Adv. Wireless Commun. (SPAWC)*, Cannes, France, Jul. 2019, pp. 1–5.
- [164] C. Kyrkou, S. Timotheou, P. Kolios, T. Theoharides, and C. Panayiotou, "Drones: Augmenting our quality of life," *IEEE Potentials*, vol. 38, no. 1, pp. 30–36, Jan. 2019.
- [165] M. Alzenad and H. Yanikomeroglu, "Coverage and rate analysis for vertical heterogeneous networks (VHetNets)," *IEEE Trans. Wireless Commun.*, vol. 18, no. 12, pp. 5643–5657, Dec. 2019.
- [166] I. Bor-Yaliniz, M. Salem, G. Senerath, and H. Yanikomeroglu, "Is 5G ready for drones: A look into contemporary and prospective wireless networks from a standardization perspective," *IEEE Wireless Commun.*, vol. 26, no. 1, pp. 18–27, Feb. 2019.
- [167] G. Sachs. (Mar. 2019). *DRONES Reporting for Work*. [Online]. Available: <https://www.goldmansachs.com/insights/technology-driving-innovation/drones/>
- [168] C. D'Andrea, A. Garcia-Rodriguez, G. Geraci, L. G. Giordano, and S. Buzzi, "Cell-free massive MIMO for UAV communications," in *Proc. IEEE Int. Conf. Commun. Workshops (ICC Workshops)*, Shanghai, China, May 2019, pp. 1–6.
- [169] H. Q. Ngo, A. Ashikhmin, H. Yang, E. G. Larsson, and T. L. Marzetta, "Cell-free massive MIMO versus small cells," *IEEE Trans. Wireless Commun.*, vol. 16, no. 3, pp. 1834–1850, Mar. 2017.
- [170] C. D'Andrea, A. Garcia-Rodriguez, G. Geraci, L. G. Giordano, and S. Buzzi, "Analysis of UAV communications in cell-free massive MIMO systems," *IEEE Open J. Commun. Soc.*, vol. 1, pp. 133–147, 2020.
- [171] M. Mozaffari, W. Saad, M. Bennis, Y.-H. Nam, and M. Debbah, "A tutorial on UAVs for wireless networks: Applications, challenges, and open problems," *IEEE Commun. Surveys Tuts.*, vol. 21, no. 3, pp. 2334–2360, 3rd Quart., 2019.
- [172] M. Alzenad, A. El-Keyi, F. Lagum, and H. Yanikomeroglu, "3-D placement of an unmanned aerial vehicle base station (UAV-BS) for energy-efficient maximal coverage," *IEEE Wireless Commun. Lett.*, vol. 6, no. 4, pp. 434–437, Aug. 2017.
- [173] Y. Zeng, R. Zhang, and T. J. Lim, "Wireless communications with unmanned aerial vehicles: Opportunities and challenges," *IEEE Commun. Mag.*, vol. 54, no. 5, pp. 36–42, May 2016.
- [174] S. Hayat, E. Yanmaz, and R. Muzaffar, "Survey on unmanned aerial vehicle networks for civil applications: A communications viewpoint," *IEEE Commun. Surveys Tuts.*, vol. 18, no. 4, pp. 2624–2661, 4th Quart., 2016.
- [175] U. Siddique, H. Tabassum, E. Hossain, and D. I. Kim, "Wireless backhauling of 5G small cells: Challenges and solution approaches," *IEEE Wireless Commun.*, vol. 22, no. 5, pp. 22–31, Oct. 2015.
- [176] U. Challita and W. Saad, "Network formation in the sky: Unmanned aerial vehicles for multi-hop wireless backhauling," in *Proc. IEEE Global Commun. Conf. (GLOBECOM)*, Singapore, Dec. 2017, pp. 1–6.
- [177] M. Mozaffari, A. Taleb Zadeh Kasgari, W. Saad, M. Bennis, and M. Debbah, "Beyond 5G with UAVs: Foundations of a 3D wireless cellular network," *IEEE Trans. Wireless Commun.*, vol. 18, no. 1, pp. 357–372, Jan. 2019.
- [178] A. A. Al-Habob, A. Ibrahim, O. A. Dobre, and A. G. Armada, "Collision-free sequential task offloading for mobile edge computing," *IEEE Commun. Lett.*, vol. 24, no. 1, pp. 71–75, Jan. 2020.
- [179] A. A. Al-Habob and O. A. Dobre, "Mobile edge computing and artificial intelligence: A mutually-beneficial relationship," in *Proc. IEEE ComSoc Technical Committees Newslett.*, Nov. 2019.
- [180] M. Gharibi, R. Boutaba, and S. L. Waslander, "Internet of Drones," *IEEE Access*, vol. 4, pp. 1148–1162, Mar. 2016.
- [181] N. Chen, Y. Chen, Y. You, H. Ling, P. Liang, and R. Zimmermann, "Dynamic urban surveillance video stream processing using fog computing," in *Proc. IEEE 2nd Int. Conf. Multimedia Big Data (BigMM)*, Taipei, Taiwan, Apr. 2016, pp. 105–112.
- [182] A. Koubaa, B. Qureshi, M.-F. Sriti, Y. Javed, and E. Tovar, "A service-oriented cloud-based management system for the Internet-of-Drones," in *Proc. IEEE Int. Conf. Auto. Robot Syst. Competitions (ICARSC)*, Coimbra, Portugal, Apr. 2017, pp. 329–335.
- [183] Y. Zeng and R. Zhang, "Energy-efficient UAV communication with trajectory optimization," *IEEE Trans. Wireless Commun.*, vol. 16, no. 6, pp. 3747–3760, Jun. 2017.
- [184] D. Yang, Q. Wu, Y. Zeng, and R. Zhang, "Energy tradeoff in ground-to-UAV communication via trajectory design," *IEEE Trans. Veh. Technol.*, vol. 67, no. 7, pp. 6721–6726, Jul. 2018.
- [185] C. Zhan, Y. Zeng, and R. Zhang, "Energy-efficient data collection in UAV enabled wireless sensor network," *IEEE Wireless Commun. Lett.*, vol. 7, no. 3, pp. 328–331, Jun. 2018.
- [186] W. Wang, X. Li, M. Zhang, K. Cumanan, D. W. Kwan Ng, G. Zhang, J. Tang, and O. A. Dobre, "Energy-constrained UAV-assisted secure communications with position optimization and cooperative jamming," *IEEE Trans. Commun.*, vol. 68, no. 7, pp. 4476–4489, Jul. 2020.
- [187] S. Yin, Y. Zhao, L. Li, and F. R. Yu, "UAV-assisted cooperative communications with time-sharing information and power transfer," *IEEE Trans. Veh. Technol.*, vol. 69, no. 2, pp. 1554–1567, Feb. 2020.

- [188] M. T. Mamaghani and Y. Hong, "On the performance of low-altitude UAV-enabled secure AF relaying with cooperative jamming and SWIPT," *IEEE Access*, vol. 7, pp. 153060–153073, Jun. 2019.
- [189] F. Huang, J. Chen, H. Wang, G. Ding, Y. Gong, and Y. Yang, "Multiple-UAV-assisted SWIPT in Internet of Things: User association and power allocation," *IEEE Access*, vol. 7, pp. 124244–124255, Aug. 2019.
- [190] X. Sun, W. Yang, Y. Cai, R. Ma, and L. Tao, "Physical layer security in millimeter wave SWIPT UAV-based relay networks," *IEEE Access*, vol. 7, pp. 35851–35862, Mar. 2019.
- [191] X. Sun, W. Yang, Y. Cai, Z. Xiang, and X. Tang, "Secure transmissions in millimeter wave SWIPT UAV-based relay networks," *IEEE Wireless Commun. Lett.*, vol. 8, no. 3, pp. 785–788, Jun. 2019.
- [192] X. Hong, P. Liu, F. Zhou, S. Guo, and Z. Chu, "Resource allocation for secure UAV-assisted SWIPT systems," *IEEE Access*, vol. 7, pp. 24248–24257, Feb. 2019.
- [193] M. Wazid, A. K. Das, N. Kumar, A. V. Vasilakos, and J. J. P. C. Rodrigues, "Design and analysis of secure lightweight remote user authentication and key agreement scheme in Internet of Drones deployment," *IEEE Internet Things J.*, vol. 6, no. 2, pp. 3572–3584, Apr. 2019.
- [194] S. P. Arteaga, L. A. M. Hernandez, G. S. Perez, A. L. S. Orozco, and L. J. G. Villalba, "Analysis of the GPS spoofing vulnerability in the drone 3DR solo," *IEEE Access*, vol. 7, pp. 51782–51789, Apr. 2019.
- [195] Y.-J. Chen and L.-C. Wang, "Privacy protection for Internet of Drones: A network coding approach," *IEEE Internet Things J.*, vol. 6, no. 2, pp. 1719–1730, Apr. 2019.
- [196] S. H. Alsamhi, O. Ma, M. S. Ansari, and F. A. Almkali, "Survey on collaborative smart drones and Internet of Things for improving smartness of smart cities," *IEEE Access*, vol. 7, pp. 128125–128152, Aug. 2019.
- [197] D. Solomitckii, M. Gapeyenko, V. Semkin, S. Andreev, and Y. Koucheryavy, "Technologies for efficient amateur drone detection in 5G millimeter-wave cellular infrastructure," *IEEE Commun. Mag.*, vol. 56, no. 1, pp. 43–50, Jan. 2018.
- [198] C. Lin, D. He, N. Kumar, K.-K.-R. Choo, A. Vinel, and X. Huang, "Security and privacy for the Internet of Drones: Challenges and solutions," *IEEE Commun. Mag.*, vol. 56, no. 1, pp. 64–69, Jan. 2018.
- [199] I. Guvenc, F. Koohifar, S. Singh, M. L. Sichertiu, and D. Matolak, "Detection, tracking, and interdiction for amateur drones," *IEEE Commun. Mag.*, vol. 56, no. 4, pp. 75–81, Apr. 2018.
- [200] V. Sharma, D. N. K. Jayakody, I. You, R. Kumar, and J. Li, "Secure and efficient context-aware localization of drones in urban scenarios," *IEEE Commun. Mag.*, vol. 56, no. 4, pp. 120–128, Apr. 2018.
- [201] X. Yue, Y. Liu, J. Wang, H. Song, and H. Cao, "Software defined radio and wireless acoustic networking for amateur drone surveillance," *IEEE Commun. Mag.*, vol. 56, no. 4, pp. 90–97, Apr. 2018.
- [202] J. H. Cheon, K. Han, S.-M. Hong, H. J. Kim, J. Kim, S. Kim, H. Seo, H. Shim, and Y. Song, "Toward a secure drone system: Flying with real-time homomorphic authenticated encryption," *IEEE Access*, vol. 6, pp. 24325–24339, Mar. 2018.
- [203] A. Fotouhi, H. Qiang, M. Ding, M. Hassan, L. G. Giordano, A. Garcia-Rodriguez, and J. Yuan, "Survey on UAV cellular communications: Practical aspects, standardization advancements, regulation, and security challenges," *IEEE Commun. Surveys Tuts.*, vol. 21, no. 4, pp. 3417–3442, 4th Quart., 2019.
- [204] L. Wang, B. Hu, and S. Chen, "Energy efficient placement of a drone base station for minimum required transmit power," *IEEE Wireless Commun. Lett.*, early access, Feb. 23, 2018, doi: 10.1109/LWC.2018.2808957.
- [205] T. Long, M. Ozger, O. Cetinkaya, and O. B. Akan, "Energy neutral Internet of Drones," *IEEE Commun. Mag.*, vol. 56, no. 1, pp. 22–28, Jan. 2018.
- [206] P. Yang, X. Cao, X. Xi, W. Du, Z. Xiao, and D. Wu, "Three-dimensional continuous movement control of drone cells for energy-efficient communication coverage," *IEEE Trans. Veh. Technol.*, vol. 68, no. 7, pp. 6535–6546, Jul. 2019.
- [207] A. Alsharoa, H. Ghazzai, A. Kadri, and A. E. Kamal, "Spatial and temporal management of cellular HetNets with multiple solar powered drones," *IEEE Trans. Mobile Comput.*, vol. 19, no. 4, pp. 954–968, Apr. 2020.
- [208] J. Yao and N. Ansari, "QoS-aware power control in Internet of Drones for data collection service," *IEEE Trans. Veh. Technol.*, vol. 68, no. 7, pp. 6649–6656, Jul. 2019.
- [209] M. B. Ghorbel, D. Rodriguez-Duarte, H. Ghazzai, M. J. Hossain, and H. Menouar, "Joint position and travel path optimization for energy efficient wireless data gathering using unmanned aerial vehicles," *IEEE Trans. Veh. Technol.*, vol. 68, no. 3, pp. 2165–2175, Mar. 2019.
- [210] J. M. Arteaga, S. Aldaher, G. Kkelis, C. Kwan, D. C. Yates, and P. D. Mitcheson, "Dynamic capabilities of multi-MHz inductive power transfer systems demonstrated with batteryless drones," *IEEE Trans. Power Electron.*, vol. 34, no. 6, pp. 5093–5104, Jun. 2019.
- [211] A. M. Jawad, H. M. Jawad, R. Nordin, S. K. Gharghan, N. F. Abdullah, and M. J. Abu-Alshaeer, "Wireless power transfer with magnetic resonator coupling and Sleep/Active strategy for a drone charging station in smart agriculture," *IEEE Access*, vol. 7, pp. 139839–139851, Sep. 2019.
- [212] W. Shi, H. Zhou, J. Li, W. Xu, N. Zhang, and X. Shen, "Drone assisted vehicular networks: Architecture, challenges and opportunities," *IEEE Netw.*, vol. 32, no. 3, pp. 130–137, May 2018.
- [213] S. Sekander, H. Tabassum, and E. Hossain, "Multi-tier drone architecture for 5G/B5G cellular networks: Challenges, trends, and prospects," *IEEE Commun. Mag.*, vol. 56, no. 3, pp. 96–103, Mar. 2018.
- [214] I. Bor-Yaliniz and H. Yanikomeroglu, "The new frontier in RAN heterogeneity: Multi-tier drone-cells," *IEEE Commun. Mag.*, vol. 54, no. 11, pp. 48–55, Nov. 2016.
- [215] P. Horstrand, R. Guerra, A. Rodriguez, M. Diaz, S. Lopez, and J. F. Lopez, "A UAV platform based on a hyperspectral sensor for image capturing and on-board processing," *IEEE Access*, vol. 7, pp. 66919–66938, Apr. 2019.
- [216] M. Haris, T. Watanabe, L. Fan, M. R. Widyanto, and H. Nobuhara, "Superresolution for UAV images via adaptive multiple sparse representation and its application to 3-D reconstruction," *IEEE Trans. Geosci. Remote Sens.*, vol. 55, no. 7, pp. 4047–4058, Jul. 2017.
- [217] N. Yamamoto and N. Uchida, "Improvement of image processing for a collaborative security flight control system with multiple drones," in *Proc. 32nd Int. Conf. Adv. Inf. Netw. Appl. Workshops (WAINA)*, Kraków, Poland, May 2018, pp. 199–202.
- [218] A. Fouda, A. S. Ibrahim, I. Guvenc, and M. Ghosh, "Interference management in UAV-assisted integrated access and backhaul cellular networks," *IEEE Access*, vol. 7, pp. 104553–104566, Jul. 2019.
- [219] Z. Zhang, L. Li, W. Liang, X. Li, A. Gao, W. Chen, and Z. Han, "Downlink interference management in dense drone small cells networks using mean-field game theory," in *Proc. 10th Int. Conf. Wireless Commun. Signal Process. (WCSP)*, Hangzhou, China, Oct. 2018, pp. 1–6.
- [220] K. Yoshikawa, S. Yamashita, K. Yamamoto, T. Nishio, and M. Morikura, "Resource allocation for 3D drone networks sharing spectrum bands," in *Proc. IEEE 86th Veh. Technol. Conf. (VTC-Fall)*, Toronto, ON, Canada, Sep. 2017, pp. 1–5.
- [221] S.-H. Cheng, Y.-S. Chao, L.-C. Wang, and A.-H. Tsai, "Affinity propagation clustering for interference management in aerial small cells," in *Proc. IEEE VTS Asia Pacific Wireless Commun. Symp. (APWCS)*, Singapore, Aug. 2019, pp. 1–5.
- [222] C. Zhang and W. Zhang, "Spectrum sharing for drone networks," *IEEE J. Sel. Areas Commun.*, vol. 35, no. 1, pp. 136–144, Jan. 2017.
- [223] U. Challita, W. Saad, and C. Bettstetter, "Interference management for cellular-connected UAVs: A deep reinforcement learning approach," *IEEE Trans. Wireless Commun.*, vol. 18, no. 4, pp. 2125–2140, Apr. 2019.
- [224] E. Belyaev and S. Forchhammer, "An efficient storage of infrared video of drone inspections via iterative aerial map construction," *IEEE Signal Process. Lett.*, vol. 26, no. 8, pp. 1157–1161, Aug. 2019.
- [225] V. Sharma, I. You, D. N. K. Jayakody, D. G. Reina, and K.-K.-R. Choo, "Neural-blockchain-based ultrareliable caching for edge-enabled UAV networks," *IEEE Trans. Ind. Informat.*, vol. 15, no. 10, pp. 5723–5736, Oct. 2019.
- [226] P. Kamalnejad, C. Mahapatra, Z. Sheng, S. Mirabbasi, V. C. M. Leung, and Y. L. Guan, "Wireless energy harvesting for the Internet of Things," *IEEE Commun. Mag.*, vol. 53, no. 6, pp. 102–108, Jun. 2015.
- [227] N. Van Huynh, D. T. Hoang, X. Lu, D. Niyato, P. Wang, and D. I. Kim, "Ambient backscatter communications: A contemporary survey," *IEEE Commun. Surveys Tuts.*, vol. 20, no. 4, pp. 2889–2922, 4th Quart., 2018.
- [228] D. Niyato, D. I. Kim, M. Maso, and Z. Han, "Wireless powered communication networks: Research directions and technological approaches," *IEEE Wireless Commun.*, vol. 24, no. 6, pp. 88–97, Dec. 2017.
- [229] D. Niyato, E. Hossain, D. I. Kim, V. Bhargava, and L. Shafai, *Wireless-Powered Communication Networks: Architectures, Protocols, and Applications*, 1st ed. Cambridge, U.K: Cambridge Univ. Press, 2016.
- [230] C.-H. Loo, K. Elmahgoub, F. Yang, A. Z. Elsherbeni, D. Kajfez, A. A. Kishk, T. Elsherbeni, L. Ukkonen, L. Sydanheimo, M. Kivikoski, S. Merilampi, and P. Ruuskanen, "Chip impedance matching for UHF RFID tag antenna design," *Prog. Electromagn. Res.*, vol. 81, pp. 359–370, Jan. 2008.

- [231] J. Zhang, G. Tian, A. Marindra, A. Sunny, and A. Zhao, "A review of passive RFID tag antenna-based sensors and systems for structural health monitoring applications," *Sensors*, vol. 17, no. 2, p. 265, Jan. 2017.
- [232] J. Li, A. Liu, G. Shen, L. Li, C. Sun, and F. Zhao, "Retro - VLC: Enabling battery-free duplex visible light communication for mobile and IoT applications," in *Proc. Int. Workshop Mobile Comput. Syst. Appl.*, Santa Fe New Mexico, Feb. 2015, pp. 21–26.
- [233] S. Shao, A. Khreishah, and H. Elgala, "Pixelated VLC-backscattering for self-charging indoor IoT devices," *IEEE Photon. Technol. Lett.*, vol. 29, no. 2, pp. 177–180, Jan. 15, 2017.
- [234] R. Di Candia, R. Jantti, R. Duan, J. Lietzen, H. Khalifa, and K. Ruttik, "Quantum backscatter communication: A new paradigm," in *Proc. 15th Int. Symp. Wireless Commun. Syst. (ISWCS)*, Lisbon, Portugal, Aug. 2018, pp. 1–6.
- [235] F. Huo, P. Mitran, and G. Gong, "Analysis and validation of active eavesdropping attacks in passive FHSS RFID systems," *IEEE Trans. Inf. Forensics Security*, vol. 11, no. 7, pp. 1528–1541, Jul. 2016.
- [236] K. Fukuda, J. Heidemann, and A. Qadeer, "Detecting malicious activity with DNS backscatter over time," *IEEE/ACM Trans. Netw.*, vol. 25, no. 5, pp. 3203–3218, Oct. 2017.
- [237] Y. Zhang, F. Gao, L. Fan, X. Lei, and G. K. Karagiannidis, "Secure communications for multi-tag backscatter systems," *IEEE Wireless Commun. Lett.*, vol. 8, no. 4, pp. 1146–1149, Aug. 2019.
- [238] G. Yao, J. Bi, and A. V. Vasilakos, "Passive IP traceback: Disclosing the locations of IP spoofer from path backscatter," *IEEE Trans. Inf. Forensics Security*, vol. 10, no. 3, pp. 471–484, Mar. 2015.
- [239] X. Wang, G. Wang, and Z. Su, "Relay selection for secure backscatter wireless communications," *Electron. Lett.*, vol. 51, no. 12, pp. 951–952, Jun. 2015.
- [240] Q. Yang, H.-M. Wang, Y. Zhang, and Z. Han, "Physical layer security in MIMO backscatter wireless systems," *IEEE Trans. Wireless Commun.*, vol. 15, no. 11, pp. 7547–7560, Nov. 2016.
- [241] H. Park, J. Yu, H. Roh, and W. Lee, "SCBF: Exploiting a collision for authentication in backscatter networks," *IEEE Commun. Lett.*, vol. 21, no. 6, pp. 1413–1416, Jun. 2017.
- [242] W. Saad, X. Zhou, Z. Han, and H. V. Poor, "On the physical layer security of backscatter wireless systems," *IEEE Trans. Wireless Commun.*, vol. 13, no. 6, pp. 3442–3451, Jun. 2014.
- [243] S. G. Hong, Y. M. Hwang, S. Y. Lee, Y. Shin, D. I. Kim, and J. Y. Kim, "Game-theoretic modeling of backscatter wireless sensor networks under smart interference," *IEEE Commun. Lett.*, vol. 22, no. 4, pp. 804–807, Apr. 2018.
- [244] W. Liu, K. Huang, X. Zhou, and S. Durrani, "Full-duplex backscatter interference networks based on time-hopping spread spectrum," *IEEE Trans. Wireless Commun.*, vol. 16, no. 7, pp. 4361–4377, Jul. 2017.
- [245] S. Ebrahimi-Asl, M. T. A. Ghasr, and M. Zawodniok, "Cooperative interference control in neighboring passive scattering antennas," *IEEE J. Radio Freq. Identif.*, vol. 2, no. 3, pp. 152–158, Sep. 2018.
- [246] A. Bekkali, S. Zou, A. Kadri, M. Crisp, and R. Penty, "Performance analysis of passive UHF RFID systems under cascaded fading channels and interference effects," *IEEE Trans. Wireless Commun.*, vol. 14, no. 3, pp. 1421–1433, Mar. 2015.
- [247] A. L. T. B. da Fonseca, F. L. Cabrera, and F. R. de Sousa, "CMOS fully integrated quasi-circulator with self-interference cancellation technique," *Electron. Lett.*, vol. 55, no. 6, pp. 329–331, Mar. 2019.
- [248] W. Gong, H. Liu, J. Liu, X. Fan, K. Liu, Q. Ma, and X. Ji, "Channel-aware rate adaptation for backscatter networks," *IEEE/ACM Trans. Netw.*, vol. 26, no. 2, pp. 751–764, Apr. 2018.
- [249] Q. Yao, J. Ma, R. Li, X. Li, J. Li, and J. Liu, "Energy-aware RFID authentication in edge computing," *IEEE Access*, vol. 7, pp. 77964–77980, Jun. 2019.
- [250] S. H. Kim and D. I. Kim, "Traffic-aware backscatter communications in wireless-powered heterogeneous networks," *IEEE Trans. Mobile Comput.*, vol. 19, no. 7, pp. 1731–1744, Jul. 2020.
- [251] L. Bariah, S. Muhaidat, and A. Al-Dweik, "Error probability analysis of non-orthogonal multiple access over Nakagami- m fading channels," *IEEE Trans. Commun.*, vol. 67, no. 2, pp. 1586–1599, Feb. 2019.
- [252] C. Zheng, W. Cheng, and H. Zhang, "Optimal resource allocation for two-user and single-DF-relay network with ambient backscatter," *IEEE Access*, vol. 7, pp. 91375–91389, Jul. 2019.
- [253] G. Yang, X. Xu, and Y.-C. Liang, "Resource allocation in NOMA-enhanced backscatter communication networks for wireless powered IoT," *IEEE Wireless Commun. Lett.*, vol. 9, no. 1, pp. 117–120, Jan. 2020.
- [254] C.-B. Le and D.-T. Do, "Outage performance of backscatter NOMA relaying systems equipping with multiple antennas," *Electron. Lett.*, vol. 55, no. 19, pp. 1066–1067, Sep. 2019.
- [255] Q. Zhang, L. Zhang, Y.-C. Liang, and P.-Y. Kam, "Backscatter-NOMA: A symbiotic system of cellular and Internet-of-Things networks," *IEEE Access*, vol. 7, pp. 20000–20013, Feb. 2019.
- [256] J. Guo, X. Zhou, S. Durrani, and H. Yanikomeroglu, "Design of non-orthogonal multiple access enhanced backscatter communication," *IEEE Trans. Wireless Commun.*, vol. 17, no. 10, pp. 6837–6852, Oct. 2018.
- [257] X. Hui and E. C. Kan, "Collaborative reader code division multiple access in the harmonic RFID system," *IEEE J. Radio Freq. Identificat.*, vol. 2, no. 2, pp. 86–92, Jun. 2018.
- [258] X. Hui, Y. Ma, and E. C. Kan, "Code division multiple access in centimeter accuracy harmonic RFID locating system," *IEEE J. Radio Freq. Identificat.*, vol. 1, no. 1, pp. 51–58, Mar. 2017.
- [259] C.-H. Kang, W.-S. Lee, Y.-H. You, and H.-K. Song, "Signal detection scheme in ambient backscatter system with multiple antennas," *IEEE Access*, vol. 5, pp. 14543–14547, Jul. 2017.
- [260] W. Liu, Y.-C. Liang, Y. Li, and B. Vucetic, "Backscatter multiplicative multiple-access systems: Fundamental limits and practical design," *IEEE Trans. Wireless Commun.*, vol. 17, no. 9, pp. 5713–5728, Sep. 2018.
- [261] S. Ma, G. Wang, R. Fan, and C. Tellambura, "Blind channel estimation for ambient backscatter communication systems," *IEEE Commun. Lett.*, vol. 22, no. 6, pp. 1296–1299, Jun. 2018.
- [262] D. Mishra and E. G. Larsson, "Optimal channel estimation for reciprocity-based backscattering with a full-duplex MIMO reader," *IEEE Trans. Signal Process.*, vol. 67, no. 6, pp. 1662–1677, Mar. 2019.
- [263] W. Zhao, G. Wang, S. Atapattu, R. He, and Y.-C. Liang, "Channel estimation for ambient backscatter communication systems with massive-antenna reader," *IEEE Trans. Veh. Technol.*, vol. 68, no. 8, pp. 8254–8258, Aug. 2019.
- [264] A. Guerra, F. Guidi, D. Dardari, A. Clemente, and R. D'Errico, "A millimeter-wave indoor backscattering channel model for environment mapping," *IEEE Trans. Antennas Propag.*, vol. 65, no. 9, pp. 4935–4940, Sep. 2017.
- [265] Y. Zhang, F. Gao, L. Fan, X. Lei, and G. K. Karagiannidis, "Backscatter communications over correlated Nakagami- m fading channels," *IEEE Trans. Commun.*, vol. 67, no. 2, pp. 1693–1704, Feb. 2019.
- [266] D. Darsena, G. Gelli, and F. Verde, "Modeling and performance analysis of wireless networks with ambient backscatter devices," *IEEE Trans. Commun.*, vol. 65, no. 4, pp. 1797–1814, Apr. 2017.
- [267] Y. Ye, L. Shi, R. Qingyang Hu, and G. Lu, "Energy-efficient resource allocation for wirelessly powered backscatter communications," *IEEE Commun. Lett.*, vol. 23, no. 8, pp. 1418–1422, Aug. 2019.
- [268] G. Yang, D. Yuan, Y.-C. Liang, R. Zhang, and V. C. M. Leung, "Optimal resource allocation in full-duplex ambient backscatter communication networks for wireless-powered IoT," *IEEE Internet Things J.*, vol. 6, no. 2, pp. 2612–2625, Apr. 2019.
- [269] S. Xiao, H. Guo, and Y.-C. Liang, "Resource allocation for full-duplex-enabled cognitive backscatter networks," *IEEE Trans. Wireless Commun.*, vol. 18, no. 6, pp. 3222–3235, Jun. 2019.
- [270] S. T. Shah, K. W. Choi, T.-J. Lee, and M. Y. Chung, "Outage probability and throughput analysis of SWIPT enabled cognitive relay network with ambient backscatter," *IEEE Internet Things J.*, vol. 5, no. 4, pp. 3198–3208, Aug. 2018.
- [271] T.-H. Lin, J. Bito, J. G. D. Hester, J. Kimionis, R. A. Bahr, and M. M. Tentzeris, "On-body long-range wireless backscattering sensing system using Inkjet-3-D-printed flexible ambient RF energy harvesters capable of simultaneous DC and harmonics generation," *IEEE Trans. Microw. Theory Techn.*, vol. 65, no. 12, pp. 5389–5400, Dec. 2017.
- [272] N. Van Huynh, D. T. Hoang, D. Niyato, P. Wang, and D. I. Kim, "Optimal time scheduling for wireless-powered backscatter communication networks," *IEEE Wireless Commun. Lett.*, vol. 7, no. 5, pp. 820–823, Oct. 2018.
- [273] S. H. Kim and D. I. Kim, "Hybrid backscatter communication for wireless-powered heterogeneous networks," *IEEE Trans. Wireless Commun.*, vol. 16, no. 10, pp. 6557–6570, Oct. 2017.
- [274] J. C. Kwan and A. O. Fapojuwo, "Sum-throughput maximization in wireless sensor networks with radio frequency energy harvesting and backscatter communication," *IEEE Sensors J.*, vol. 18, no. 17, pp. 7325–7339, Sep. 2018.
- [275] D. Li, W. Peng, and Y.-C. Liang, "Hybrid ambient backscatter communication systems with Harvest-Then-Transmit protocols," *IEEE Access*, vol. 6, pp. 45288–45298, Aug. 2018.

- [276] X. Liu, Y. Gao, and F. Hu, "Optimal time scheduling scheme for wireless powered ambient backscatter communications in IoT networks," *IEEE Internet Things J.*, vol. 6, no. 2, pp. 2264–2272, Apr. 2019.
- [277] D. Van Den Berg, R. Glans, D. De Koning, F. A. Kuipers, J. Lugtenburg, K. Polachan, P. T. Venkata, C. Singh, B. Turkovic, and B. Van Wijk, "Challenges in haptic communications over the tactile Internet," *IEEE Access*, vol. 5, pp. 23502–23518, Oct. 2017.
- [278] Y. Yuan, "Paving the road for virtual and augmented reality," *IEEE Consum. Electron. Mag.*, vol. 7, no. 1, pp. 117–128, Jan. 2018.
- [279] D. You, B.-S. Seo, E. Jeong, and D. H. Kim, "Internet of Things (IoT) for seamless virtual reality space: Challenges and perspectives," *IEEE Access*, vol. 6, pp. 40439–40449, Apr. 2018.
- [280] Y. Yuan, "Changing the world with virtualaugmented reality technologies," *IEEE Consum. Electron. Mag.*, vol. 6, no. 1, pp. 40–41, Jan. 2017.
- [281] F. El Jamiy and R. Marsh, "Survey on depth perception in head mounted displays: Distance estimation in virtual reality, augmented reality, and mixed reality," *IET Image Process.*, vol. 13, no. 5, pp. 707–712, Apr. 2019.
- [282] F. J. Detmer, J. Hettig, D. Schindele, M. Schostak, and C. Hansen, "Virtual and augmented reality systems for renal interventions: A systematic review," *IEEE Rev. Biomed. Eng.*, vol. 10, pp. 78–94, Sep. 2017.
- [283] D. Wang, K. Ohnishi, and W. Xu, "Multimodal haptic display for virtual reality: A survey," *IEEE Trans. Ind. Electron.*, vol. 67, no. 1, pp. 610–623, Jan. 2020.
- [284] J. Tan, G. Cheung, and R. Ma, "360-degree virtual-reality cameras for the masses," *IEEE MultimediaMag.*, vol. 25, no. 1, pp. 87–94, Jan. 2018.
- [285] J. Yu, "A light-field journey to virtual reality," *IEEE MultimediaMag.*, vol. 24, no. 2, pp. 104–112, Apr. 2017.
- [286] G. M. N. Taira, A. C. Sementille, and S. R. R. Sanches, "Influence of the camera viewpoint on augmented reality interaction," *IEEE Latin Amer. Trans.*, vol. 16, no. 1, pp. 260–264, Jan. 2018.
- [287] B. Bach, R. Sicat, J. Beyer, M. Cordeil, and H. Pfister, "The hologram in my hand: How effective is interactive exploration of 3D visualizations in immersive tangible augmented reality?" *IEEE Trans. Vis. Comput. Graphics*, vol. 24, no. 1, pp. 457–467, Jan. 2018.
- [288] B. K. Wiederhold, I. T. Miller, and M. D. Wiederhold, "Using virtual reality to mobilize health care: Mobile virtual reality technology for attenuation of anxiety and pain," *IEEE Consum. Electron. Mag.*, vol. 7, no. 1, pp. 106–109, Jan. 2018.
- [289] J. Ryu, M. S. Heo, and H. C. Kim, "Development of portable breast self-examination device using enhanced tactile feedback," *Electron. Lett.*, vol. 46, no. 25, pp. 1651–1653, Dec. 2010.
- [290] K. B. Chen, M. E. Sesto, K. Ponto, J. Leonard, A. Mason, G. Vanderheiden, J. Williams, and R. G. Radwin, "Use of virtual reality feedback for patients with chronic neck pain and Kinesophobia," *IEEE Trans. Neural Syst. Rehabil. Eng.*, vol. 25, no. 8, pp. 1240–1248, Aug. 2017.
- [291] J. Orlosky, Y. Itoh, M. Ranchet, K. Kiyokawa, J. Morgan, and H. Devos, "Emulation of physician tasks in eye-tracked virtual reality for remote diagnosis of neurodegenerative disease," *IEEE Trans. Vis. Comput. Graphics*, vol. 23, no. 4, pp. 1302–1311, Apr. 2017.
- [292] J. Torner, S. Skouras, J. L. Molinuevo, J. D. Gispert, and F. Alpiste, "Multipurpose virtual reality environment for biomedical and health applications," *IEEE Trans. Neural Syst. Rehabil. Eng.*, vol. 27, no. 8, pp. 1511–1520, Aug. 2019.
- [293] D. Rojo, J. Mayor, J. J. G. Rueda, L. Raya, and M. Potel, "A virtual reality training application for adults with Asperger's syndrome," *IEEE Comput. Graph. Appl.*, vol. 39, no. 2, pp. 104–111, Mar. 2019.
- [294] W. Si, X. Liao, Y. Qian, and Q. Wang, "Mixed reality guided radiofrequency needle placement: A pilot study," *IEEE Access*, vol. 6, pp. 31493–31502, Jun. 2018.
- [295] K. Murphy and M. Darrah, "Haptics-based apps for middle school students with visual impairments," *IEEE Trans. Haptics*, vol. 8, no. 3, pp. 318–326, Jul. 2015.
- [296] A. A. Ali, G. A. Dafoulas, and J. C. Augusto, "Collaborative educational environments incorporating mixed reality technologies: A systematic mapping study," *IEEE Trans. Learn. Technol.*, vol. 12, no. 3, pp. 321–332, Jul. 2019.
- [297] S. Matsutomo, T. Manabe, V. Cingoski, and S. Noguchi, "A computer aided education system based on augmented reality by immersion to 3-D magnetic field," *IEEE Trans. Magn.*, vol. 53, no. 6, pp. 1–4, Jun. 2017.
- [298] N. Drljevic, L. H. Wong, and I. Boticki, "Where does my augmented reality learning experience (ARLE) belong? A student and teacher perspective to positioning ARLEs," *IEEE Trans. Learn. Technol.*, vol. 10, no. 4, pp. 419–435, Oct. 2017.
- [299] M.-B. Ibanez, A. Di-Serio, D. Villaran-Molina, and C. Delgado-Kloos, "Support for augmented reality simulation systems: The effects of scaffolding on learning outcomes and behavior patterns," *IEEE Trans. Learn. Technol.*, vol. 9, no. 1, pp. 46–56, Jan. 2016.
- [300] Y. Sheng, "Scalable intelligence-enabled networking with traffic engineering in 5G scenarios for future audio-visual-tactile Internet," *IEEE Access*, vol. 6, pp. 30378–30391, Jun. 2018.
- [301] A. Benloucif, A.-T. Nguyen, C. Sentouh, and J.-C. Popieul, "Cooperative trajectory planning for haptic shared control between driver and automation in highway driving," *IEEE Trans. Ind. Electron.*, vol. 66, no. 12, pp. 9846–9857, Dec. 2019.
- [302] M. Corno, L. D'Avico, G. Panzani, and S. M. Savaresi, "A haptic-based, safety-oriented, braking assistance system for road bicycles," in *Proc. IEEE Intell. Vehicles Symp. (IV)*, Los Angeles, CA, USA, Jun. 2017, pp. 1189–1194.
- [303] M. Mulder, D. A. Abbink, M. M. van Paassen, and M. Mulder, "Design of a haptic gas pedal for active car-following support," *IEEE Trans. Intell. Transp. Syst.*, vol. 12, no. 1, pp. 268–279, Mar. 2011.
- [304] P.-V. Mekikis, K. Ramantas, A. Antonopoulos, E. Kartsakli, L. Sanabria-Russo, J. Serra, D. Pubill, and C. Verikoukis, "NFV-enabled experimental platform for 5G tactile Internet support in industrial environments," *IEEE Trans. Ind. Informat.*, vol. 16, no. 3, pp. 1895–1903, Mar. 2020.
- [305] A. Aijaz and M. Sooriyabandara, "The tactile Internet for industries: A review," *Proc. IEEE*, vol. 107, no. 2, pp. 414–435, Feb. 2019.
- [306] O. Blanco-Novoa, T. M. Fernandez-Carames, P. Fraga-Lamas, and M. A. Vilar-Montesinos, "A practical evaluation of commercial industrial augmented reality systems in an industry 4.0 shipyard," *IEEE Access*, vol. 6, pp. 8201–8218, Feb. 2018.
- [307] J. M. Jacinto-Villegas, M. Satler, A. Filippeschi, M. Bergamasco, M. Ragaglia, A. Argiolas, M. Niccolini, and C. A. Avizzano, "A novel wearable haptic controller for teleoperating robotic platforms," *IEEE Robot. Autom. Lett.*, vol. 2, no. 4, pp. 2072–2079, Oct. 2017.
- [308] M. Dohler, T. Mahmoodi, M. A. Lema, M. Condoluci, F. Sardis, K. Antonakoglou, and H. Aghvami, "Internet of skills, where robotics meets AI, 5G and the tactile Internet," in *Proc. Eur. Conf. Netw. Commun. (EuCNC)*, Oulu, Finland, Jun. 2017, pp. 1–5.
- [309] A. Ebrahimzadeh, M. Chowdhury, and M. Maier, "Human-agent-robot task coordination in FiWi-based tactile Internet infrastructures using context- and self-awareness," *IEEE Trans. Netw. Service Manage.*, vol. 16, no. 3, pp. 1127–1142, Sep. 2019.
- [310] M. Chowdhury and M. Maier, "Collaborative computing for advanced tactile Internet human-to-Robot (H2R) communications in integrated FiWi multirobot infrastructures," *IEEE Internet Things J.*, vol. 4, no. 6, pp. 2142–2158, Dec. 2017.
- [311] S. Haddadin, L. Johannsmeier, and F. D. Ledezma, "Tactile robots as a central embodiment of the tactile Internet," *Proc. IEEE*, vol. 107, no. 2, pp. 471–487, Feb. 2019.
- [312] C. Reardon, H. Zhang, R. Wright, and L. E. Parker, "Robots can teach students with intellectual disabilities: Educational benefits of using robotic and augmented reality applications," *IEEE Robot. Autom. Mag.*, vol. 26, no. 2, pp. 79–93, Jun. 2019.
- [313] F. Brizzi, L. Peppoloni, A. Graziano, E. D. Stefano, C. A. Avizzano, and E. Ruffaldi, "Effects of augmented reality on the performance of teleoperated industrial assembly tasks in a robotic embodiment," *IEEE Trans. Human-Machine Syst.*, vol. 48, no. 2, pp. 197–206, Apr. 2018.
- [314] Z. Gao, L. Dai, D. Mi, Z. Wang, M. A. Imran, and M. Z. Shaker, "MmWave massive-MIMO-based wireless backhaul for the 5G ultra-dense network," *IEEE Wireless Commun.*, vol. 22, no. 5, pp. 13–21, Oct. 2015.
- [315] S. Hur, T. Kim, D. J. Love, J. V. Krogmeier, T. A. Thomas, and A. Ghosh, "Millimeter wave beamforming for wireless backhaul and access in small cell networks," *IEEE Trans. Commun.*, vol. 61, no. 10, pp. 4391–4403, Oct. 2013.
- [316] K. Venugopal and R. W. Heath, "Millimeter wave networked wearables in dense indoor environments," *IEEE Access*, vol. 4, pp. 1205–1221, Mar. 2016.
- [317] Z. Chen, X. Ma, B. Zhang, Y. X. Zhang, Z. Niu, N. Kuang, W. Chen, L. Li, and S. Li, "A survey on terahertz communications," *China Commun.*, vol. 16, no. 2, pp. 1–35, Feb. 2019.
- [318] T. Kürner and S. Priebe, "Towards THz communications—Status in research, standardization and regulation," *J. Infr., Millim., THz Waves*, vol. 35, no. 1, pp. 53–62, Jan. 2014.

- [319] S. Mollahasani and E. Onur, "Evaluation of Terahertz channel in data centers," in *Proc. IEEE/IFIP Netw. Oper. Manage. Symp.*, Istanbul, Turkey, Apr. 2016, pp. 727–730.
- [320] B. Peng and T. Kurner, "A stochastic channel model for future wireless THz data centers," in *Proc. Int. Symp. Wireless Commun. Syst.*, Brussels, Belgium, Aug. 2015, pp. 741–745.
- [321] H. Sameddeen, N. Saeed, T. Y. Al-Naffouri, and M.-S. Alouini, "Next generation terahertz communications: A rendezvous of sensing, imaging, and localization," 2019, *arXiv:1909.10462*. [Online]. Available: <http://arxiv.org/abs/1909.10462>.
- [322] I. F. Akyildiz, J. M. Jornet, and C. Han, "Terahertz band: Next frontier for wireless communications," *Phys. Commun.*, vol. 12, pp. 16–32, Sep. 2014.
- [323] D. M. Barbu. (2015). *The Effects of Radiation on the Eye in Industrial Environments*. [Online]. Available: <https://imt.uoradea.ro/auo.fmte/>
- [324] T. Yamazato, I. Takai, H. Okada, T. Fujii, T. Yendo, S. Arai, M. Andoh, T. Harada, K. Yasutomi, K. Kagawa, and S. Kawahito, "Image-sensor-based visible light communication for automotive applications," *IEEE Commun. Mag.*, vol. 52, no. 7, pp. 88–97, Jul. 2014.
- [325] R. Perez-Jimenez, J. Rufo, C. Quintana, J. Rabadan, and F. J. Lopez-Hernandez, "Visible light communication systems for passenger in-flight data networking," in *Proc. IEEE Int. Conf. Consum. Electron. (ICCE)*, Las Vegas, NV, USA, Jan. 2011, pp. 445–446.
- [326] D. Iturralde, C. Azurdia-Meza, N. Krommenacker, I. Soto, Z. Ghassemlooy, and N. Becerra, "A new location system for an underground mining environment using visible light communications," in *Proc. 9th Int. Symp. Commun. Syst., Netw. Digit. Sign. (CSNDSP)*, Manchester, Jul. 2014, pp. 1165–1169.
- [327] N. Lawrentschuk and D. Bolton, "Mobile phone interference with medical equipment and its clinical relevance: A systematic review," *Med. J. Aust.*, vol. 181, no. 3, pp. 154–159, Aug. 2004.
- [328] D. R. Dhatchayeny, A. Sawaiwar, S. V. Tiwari, and Y. H. Chung, "Experimental biomedical EEG signal transmission using VLC," *IEEE Sensors J.*, vol. 15, no. 10, pp. 5386–5387, Oct. 2015.
- [329] M. Song, K. Baryshnikova, A. Markvart, P. Belov, E. Nenasheva, C. Simovski, and P. Kapitanova, "Smart table based on a metasurface for wireless power transfer," *Phys. Rev. A, Gen. Phys. Appl.*, vol. 11, no. 5, pp. 1–9, May 2019.
- [330] X. Tian, P. M. Lee, Y. J. Tan, T. L. Y. Wu, H. Yao, M. Zhang, Z. Li, K. A. Ng, B. C. K. Tee, and J. S. Ho, "Wireless body sensor networks based on metamaterial textiles," *Nature Electron.*, vol. 2, no. 6, pp. 243–251, Jun. 2019.
- [331] M. Hassanalian and A. Abdelkefi, "Classifications, applications, and design challenges of drones: A review," *Prog. Aerosp. Sci.*, vol. 91, pp. 99–131, May 2017.
- [332] D. Gross. (2013). *Amazon's Drone Delivery: How Would it Work?* [Online]. Available: <http://www.cnn.com/2013/12/02/tech/innovation/amazon-drones-questions/>
- [333] L. P. Koh and S. A. Wich, "Dawn of drone ecology: Low-cost autonomous aerial vehicles for conservation," *Tropical Conservation Sci.*, vol. 5, no. 2, pp. 121–132, Jun. 2012.
- [334] A. Gudipati, D. Perry, L. E. Li, and S. Katti, "SoftRAN: Software defined radio access network," in *Proc. 2nd ACM SIGCOMM Workshop Hot Topics Softw. Defined Netw.*, Hong Kong, Aug. 2013, pp. 25–30.
- [335] A.-A.-A. Boulougorgos, A. Alexiou, T. Merkle, C. Schubert, R. Elschner, A. Katsiotis, P. Stavrianos, D. Kritharidis, P.-K. Chartsias, J. Kokkonimi, M. Juntti, J. Lehtomaki, A. Teixeira, and F. Rodrigues, "Terahertz technologies to deliver optical network quality of experience in wireless systems beyond 5G," *IEEE Commun. Mag.*, vol. 56, no. 6, pp. 144–151, Jun. 2018.
- [336] C. Han, A. O. Bicen, and I. F. Akyildiz, "Multi-ray channel modeling and wideband characterization for wireless communications in the terahertz band," *IEEE Trans. Wireless Commun.*, vol. 14, no. 5, pp. 2402–2412, May 2015.
- [337] M. Obeed, A. M. Salhab, M.-S. Alouini, and S. A. Zummo, "Survey on physical layer security in optical wireless communication systems," in *Proc. 7th Int. Conf. Commun. Netw. (ComNet)*, Hammamet, Tunisia, Nov. 2018, pp. 1–5.
- [338] S. Naser, L. Bariah, W. Jaafar, S. Muhaidat, P. C. Sofotasios, M. Al-Qutayri, and O. A. Dobre, "Optical rate-splitting multiple access for visible light communications," Feb. 2020, *arXiv:2002.07583*. [Online]. Available: <http://arxiv.org/abs/2002.07583>
- [339] M. Najafi, B. Schmauss, and R. Schober, "Intelligent reconfigurable reflecting surfaces for free space optical communications," May 2020, *arXiv:2005.04499*. [Online]. Available: <http://arxiv.org/abs/2005.04499>
- [340] L. Yang, W. Guo, and I. S. Ansari, "Mixed dual-hop FSO-RF communication systems through reconfigurable intelligent surface," *IEEE Commun. Lett.*, vol. 24, no. 7, pp. 1558–1562, Jul. 2020.
- [341] H. Wang, Z. Zhang, B. Zhu, J. Dang, L. Wu, L. Wang, K. Zhang, and Y. Zhang, "Performance of wireless optical communication with reconfigurable intelligent surfaces and random obstacles," Jan. 2020, *arXiv:2001.05715*. [Online]. Available: <http://arxiv.org/abs/2001.05715>
- [342] H. Yang, X. Cao, F. Yang, J. Gao, S. Xu, M. Li, X. Chen, Y. Zhao, Y. Zheng, and S. Li, "A programmable metasurface with dynamic polarization, scattering and focusing control," *Sci. Rep.*, vol. 6, no. 1, pp. 1–11, Oct. 2016.
- [343] R. J. Hall, "An Internet of Drones," *IEEE Internet Comput.*, vol. 20, no. 3, pp. 68–73, May 2016.
- [344] W. Khawaja, O. Ozdemir, and I. Guvenc, "UAV air-to-ground channel characterization for mmWave systems," in *Proc. IEEE 86th Veh. Technol. Conf. (VTC)*, Toronto, ON, Canada, Sep. 2017, pp. 1–5.
- [345] D. W. Matolak and R. Sun, "Air-ground channel characterization for unmanned aircraft systems—Part I: Methods, measurements, and models for over-water settings," *IEEE Trans. Veh. Technol.*, vol. 66, no. 1, pp. 26–44, Jan. 2017.
- [346] W. Khawaja, I. Guvenc, and D. Matolak, "UWB channel sounding and modeling for UAV air-to-ground propagation channels," in *Proc. IEEE Global Commun. Conf. (GLOBECOM)*, Washington, DC, USA, Dec. 2016, pp. 1–7.
- [347] Z. Kaleem and M. H. Rehmani, "Amateur drone monitoring: State-of-the-art architectures, key enabling technologies, and future research directions," *IEEE Wireless Commun.*, vol. 25, no. 2, pp. 150–159, Apr. 2018.
- [348] V. Liu, V. Talla, and S. Gollakota, "Enabling instantaneous feedback with full-duplex backscatter," in *Proc. Int. Conf. Mobile Comput. Netw.*, Maui, Hawaii, Sep. 2014, pp. 67–78.
- [349] A. Aijaz, M. Dohler, A. H. Aghvami, V. Friderikos, and M. Frodigh, "Realizing the tactile Internet: Haptic communications over next generation 5G cellular networks," *IEEE Wireless Commun.*, vol. 24, no. 2, pp. 82–89, Apr. 2017.
- [350] K. Antonakoglou, X. Xu, E. Steinbach, T. Mahmoodi, and M. Dohler, "Toward haptic communications over the 5G tactile Internet," *IEEE Commun. Surveys Tuts.*, vol. 20, no. 4, pp. 3034–3059, 4th Quart., 2018.



LINA BARIAH (Member, IEEE) received the M.Sc. and Ph.D. degrees in communications engineering from Khalifa University, Abu Dhabi, United Arab Emirates, in 2015 and 2018, respectively. She was a Visiting Researcher with the Department of Systems and Computer Engineering, Carleton University, Ottawa, ON, Canada, in Summer 2019. She is currently a Postdoctoral Fellow with the KU Center for Cyber-Physical Systems (C2PS), Khalifa University. Her research interests include advanced digital signal processing techniques for communications, channel estimation, cooperative communications, non-orthogonal multiple access, cognitive radios, reconfigurable intelligent surfaces, underwater wireless communications, and visible light communications. She was a member of the technical program committee of the numerous IEEE conferences, such as ICC and Globecom.



LINA MOHJAZI (Senior Member, IEEE) received the B.Sc. degree (Hons.) in electrical and electronic engineering from United Arab Emirates University, United Arab Emirates, in 2008, the M.Sc. degree in electrical and electronic engineering from Khalifa University (KU), United Arab Emirates, in 2012, and the Ph.D. degree in electrical and electronic engineering from the University of Surrey, U.K., in 2018. She is currently a Lecturer with the School of Engineering, University of Glasgow, U.K. Her main research interests include beyond 5G wireless technologies, physical layer optimization and performance analysis, wireless power transfer,

machine learning for future wireless systems, reconfigurable intelligent surfaces, information theory, and signal processing. She serves as an Active Reviewer for more than 20 multidisciplinary journals and conferences. She serves as a Review Editor for *Frontiers in Communications and Networks* and an Editor for *Physical Communication* (Elsevier).



SAMI MUHAIDAT (Senior Member, IEEE) received the Ph.D. degree in electrical and computer engineering from the University of Waterloo, Waterloo, ON, USA, in 2006. From 2007 to 2008, he was an NSERC Postdoctoral Fellow with the Department of Electrical and Computer Engineering, University of Toronto, Canada. From 2008 to 2012, he was an Assistant Professor with the School of Engineering Science, Simon Fraser University, Burnaby, BC, Canada. He is currently a Professor with Khalifa University. His research interests include wireless communications, 5G and beyond, optical communications, the IoT with emphasis on battery-less devices, and machine learning. He served as a Senior Editor for the IEEE COMMUNICATIONS LETTERS, an Editor for the IEEE TRANSACTIONS ON COMMUNICATIONS, and an Associate Editor for the IEEE TRANSACTIONS ON VEHICULAR TECHNOLOGY. He serves as an Area Editor for the IEEE TRANSACTIONS ON COMMUNICATIONS.



PASCHALIS C. SOFOTASIOS (Senior Member, IEEE) received the M.Eng. degree from Newcastle University, U.K., in 2004, the M.Sc. degree from the University of Surrey, U.K., in 2006, and the Ph.D. degree from the University of Leeds, U.K., in 2011. His M.Sc. studies were funded by a scholarship from UK-EPSC and the Ph.D. studies were sponsored by UK-EPSC and Pace plc. He held academic positions with the University of Leeds, the University of California, Los Angeles, CA, USA, the Aristotle University of Thessaloniki, Greece, the Tampere University of Technology, Finland, and Khalifa University, where he is currently an Assistant Professor with the Department of Electrical and Computer Engineering. His research interests include digital and optical wireless communications and topics relating to mathematics and statistics. He is a member of the technical program committee for the numerous IEEE conferences. He received the Exemplary Reviewer Award from the IEEE COMMUNICATIONS LETTERS, in 2012 and the IEEE TRANSACTIONS ON COMMUNICATIONS, in 2015 and 2016, respectively. He was a co-recipient of the Best Paper Award from ICUFN, in 2013. He has served as an Associate Editor for the IEEE COMMUNICATIONS LETTERS. He currently serves as a Guest Editor for the IEEE OPEN JOURNAL OF THE COMMUNICATIONS SOCIETY and an Associate Editor for *Frontiers in Communications and Networks*.



GUNES KARABULUT KURT (Senior Member, IEEE) received the B.S. degree (Hons.) in electronics and electrical engineering from Bogazici University, Istanbul, Turkey, in 2000, and the M.A.Sc. and Ph.D. degrees in electrical engineering from the University of Ottawa, Ottawa, ON, Canada, in 2002 and 2006, respectively. She was a Research Assistant with the CASP Group, from 2000 to 2005. From 2005 to 2006, she was with TenXc Wireless, where she researched on location estimation and radio frequency identification systems. From 2006 to 2008, she was with Edgewater Computer Systems Inc., where she researched on high-bandwidth networking in aircraft and priority-based signaling methodologies. From 2008 to 2010, she was with Turkcell Research and Development Applied Research and Technology, Istanbul. Since 2010, she has been with Istanbul Technical University. She has authored numerous publications and international patents. She was involved in various research projects, including STREP, EUREKA, and ITEA-2 projects on wireless networks. She is a Marie Curie Fellow and the Project REALMARS with the European Commission Research Executive Agency. She was a Management Committee Member of the COST Action 1104.



HALIM YANIKOMEROGLU (Fellow, IEEE) was born in Giresun, Turkey, in 1968. He received the B.Sc. degree in electrical and electronics engineering from Middle East Technical University, Ankara, Turkey, in 1990, and the M.A.Sc. and Ph.D. degrees in electrical and computer engineering from the University of Toronto, Canada, in 1992 and 1998, respectively. Since 1998, he has been with the Department of Systems and Computer Engineering, Carleton University, Ottawa, ON, Canada, where he is currently a Full Professor. He has supervised 28 M.A.Sc. and 25 Ph.D. students (theses). His Ph.D. students received various medals. He was one of the most frequent tutorial presenters with the leading international IEEE conferences. He has extensive collaboration with the Canadian and International Industry. From 2012 to 2016, he led one of the largest academic-industrial collaborative research projects on pre-standards 5G wireless networks. His collaborations with industry and holds 37 granted patents. His research interest includes wireless technologies. He is a Fellow of the Engineering Institute of Canada (EIC) and the Canadian Academy for Engineering (CAE). He was a recipient of the IEEE Communications Society Wireless Communications Technical Committee Recognition Award in 2018, the IEEE Ottawa Section Outstanding Service Award in 2018, the IEEE Ottawa Section Outstanding Educator Award in 2014, the Carleton University Faculty Graduate Mentoring Award in 2010, the Carleton University Graduate Students Association Excellence Award in Graduate Teaching in 2010, and the Carleton University Research Achievement Award in 2009 and 2018, respectively. He served as the General Chair for VTC2017-Fall Toronto and VTC2010-Fall Ottawa and the Technical Program Chair for WCNC, Istanbul, in 2014, WCNC, Las Vegas, in 2008, and WCNC, Atlanta 2004, for the several major international IEEE conferences. He served as the Chair for the IEEE Technical Committee on Personal Communications. He serves as the Steering Committee Chair for the IEEE's Flagship Wireless Communications and Networking Conference (WCNC). He served on the Editorial Boards for the IEEE TRANSACTIONS ON COMMUNICATIONS, the IEEE TRANSACTIONS ON WIRELESS COMMUNICATIONS, and the IEEE COMMUNICATIONS SURVEYS AND TUTORIALS. He also served as a Guest Editor for the various IEEE journal special issues. He is a Distinguished Speaker of the IEEE Communications Society and the IEEE Vehicular Technology Society. He is a Registered Professional Engineer.



OCTAVIA A. DOBRE (Fellow, IEEE) received the Dipl.Ing. and Ph.D. degrees from the Politehnica University of Bucharest (Polytechnic Institute of Bucharest), Bucharest, Romania, in 1991 and 2000, respectively. From 2002 to 2005, she was with the New Jersey Institute of Technology, Newark, NJ, USA, and the Politehnica University of Bucharest. She was a Visiting Professor with the Massachusetts Institute of Technology, Cambridge, MA, USA, and the Université de Bretagne Occidentale, Brest, France. In 2005, she joined Memorial University, St. John's, NL, Canada, where she is currently a Professor and the Research Chair. She has authored or coauthored over 250 refereed articles in these areas. Her research interests include machine learning for communications, enabling technologies for beyond 5G, blind signal identification and parameter estimation techniques, and optical and underwater communications. She received the Best Paper Awards at various conferences, including the IEEE ICC and the IEEE WCNC. She served as the General Chair, the Technical Program Co-Chair, the Tutorial Co-Chair, and the Technical Co-Chair for symposia at numerous conferences, including the IEEE ICC and the IEEE Globecom. She was a Royal Society Scholar in 2000 and a Fulbright Scholar in 2001. She served as a Senior Editor, an Editor, and a Guest Editor for various prestigious journals and magazines. She also served as an EiC for the IEEE COMMUNICATIONS LETTERS. She serves as the Editor-in-Chief (EiC) for the IEEE OPEN JOURNAL OF THE COMMUNICATIONS SOCIETY, and an Editor for the IEEE COMMUNICATIONS SURVEYS AND TUTORIALS, the *IEEE Vehicular Communications Magazine*, and the IEEE SYSTEMS. She is a Distinguished Lecturer of the IEEE Communications Society and a Fellow of the Engineering Institute of Canada.

• • •