

Received October 3, 2020, accepted October 16, 2020, date of publication October 20, 2020, date of current version October 30, 2020.

Digital Object Identifier 10.1109/ACCESS.2020.3032380

Discrimination of Genuine and Acted Emotional Expressions Using EEG Signal and Machine Learning

MEERA ALEX®^{[1](https://orcid.org/0000-0002-8244-2165)}, U[SM](https://orcid.org/0000-0002-5792-8032)AN TARIQ^{®1,2}, (Member, IEEE), FARES AL-SHARGIE^{®1,2}, ([Me](https://orcid.org/0000-0002-9685-4937)mber, IEEE), HASAN S. MIR^{1,2}, (Senior Member, IEEE),

AND HASAN AL NASHASH^{101,2}, (Senior Member, IEEE)
¹Biomedical Engineering Graduate Program, American University of Sharjah, Sharjah, United Arab Emirates

²Department of Electrical Engineering, American University of Sharjah, Sharjah, United Arab Emirates

Corresponding author: Fares Al-Shargie (fyahya@aus.edu)

This work was supported in part by the Biosciences and Bioengineering Research Institute (BBRI) Grant EN0275-BBRI18-06, Enhanced Faculty Research Grant EFRG18-BBR-CEN-02/ EN0, and by the Department of Electrical Engineering, American University of Sharjah, United Arab Emirates.

ABSTRACT We present here one of the first studies that attempt to differentiate between genuine and acted emotional expressions, using EEG data. We present the first EEG dataset (available here) with recordings of subjects with genuine and fake emotional expressions. We build our experimental paradigm for classification of smiles; genuine smiles, fake/acted smiles and neutral expression. We propose multiple methods to extract intrinsic features from three EEG emotional expressions; genuine, neutral, and fake/acted smile. We extracted EEG features using three time-frequency analysis methods: discrete wavelet transforms (DWT), empirical mode decomposition (EMD), and incorporating DWT into EMD (DWT-EMD) at three frequency bands. We then evaluated the proposed methods using several classifiers including, k-nearest neighbors (KNN), support vector machine (SVM), and artificial neural network (ANN). We carried out an experimental paradigm on 28-subjects underwent three types of emotional expressions, genuine, neutral and fake/acted. The results showed that incorporating DWT into EMD extracted more hidden features than sole DWT or sole EMD method. The power spectral feature extracted by DWT, EMD, and DWT-EMD showed different neural patterns across the three emotional expressions at all the frequency bands. We performed binary classification experiments and achieved acceptable accuracy reaching a maximum of 84% in all type of emotions, classifiers and bands using sole DWT or EMD. Meanwhile, a combination of DWT-EMD achieved the highest classification accuracy with ANN in classifying true emotional expressions from fake expressions in the alpha and beta bands with an average accuracy of 94.3% and 84.1%, respectively. Our results suggest combining DWT-EMD for future emotion studies and highlight the association of alpha and beta frequency bands with emotions.

INDEX TERMS Emotion recognition, electroencephalogram (EEG), discrete wavelet transforms (DWT), empirical mode decomposition (EMD), classification.

I. INTRODUCTION

Emotions are mental processes that are triggered by conscious or unconscious experiences [1]. Researchers have suggested that emotions and their dynamics influence cognition and behavior [2]. In particular, emotions tend to profoundly influence both the physical and psychological behavior of an individual [2]. Thus, emotion recognition is a critical factor for several domains such as human robot interaction, characterizing the level of interest on learning, measuring

The associate editor coordinating the [revi](https://orcid.org/0000-0001-5859-3724)ew of this manuscript and approving it for publication was Gang Wang

happiness and satisfaction, identifying the level of vigilance in road and safety, quantifying stress, and detecting patient's mental and physical states [1], [3]. Several methods have been proposed in the literature to evaluate emotions [4]–[7]. Self-reporting may be the most straightforward approach to assess emotions and emotional behavior. Such methods remain subjective and require the full attention of the user. Some more objective measures are facial expression, speech analysis, and analysis of physiological responses. In our day to day interactions with computers or people; we express our feelings in the form of various emotional behaviors. Our expressive spontaneous behavior tells a lot about how

we feel. Facial expressions and speech tone analysis are the most widely used non-physiological signals for emotion detection. Hoque and his colleagues [8] have investigated automated facial expression analysis to discriminate between frustrated and delighted smiles. They were able to distinguish smiles under frustration and delighted stimuli with 92% accuracy. However, at times social circumstances may intimidate people into concealing the felt emotion. Thus, interpreting emotions from facial expressions or audio signatures may fail to reveal the true natural mental state of people [9]. In particular, false alarms are likely to occur, since these facial attributes are not always accompanied by emotions. Besides, fixing a camera is required to analyze facial expressions and a microphone to analyze audio signatures, which raises privacy concerns. Some studies have used multimodal approaches that combine speech, facial and physiological signals for emotion recognition [10], [6], [11], [12]. One thing to note is that facial and audio expressions may not reflect the intrinsic mental state of human beings whereas physiological signals reflect real emotions. In particular, changes in physiological signals related to emotional states are involuntary, and people are often unaware of them. One may argue that accurate measurement of felt emotions would need a more reliable assessment method. The question that arises here is whether we can differentiate between actual and acted emotional expressions using other objective means?

Basic human interactions rely upon expressional behaviors. For instance, smiling behavior implies happiness in general. However, a smiling person may not be happy. According to Hoque *et al* [8], smiling may even signify frustration. In particular, a smile expression is a universal and multifaceted expression. Analysis of emotions underlying expressions like smiling needs to be explored. Modalities that can recognize human emotional states in a more in-depth and accurate level help us to build better and more reliable human-computer interface systems. In this study, we attempt to use Electroencephalography (EEG) modality to find out whether an acted emotion can be differentiated from a genuine one. EEG is one of the most commonly used techniques to study brain functions and conditions with temporal resolution at millisecond.

In the literature, there has been many datasets used for emotion recognition studies. Publicly available emotion databases are SEED [13], DEAP [14], MAHANOBI-HCI [15], and MPED [9]. Many studies have analyzed EEG data from these datasets to identify and classify positive, neutral, negative, pleasant, and unpleasant emotions. However, analyzing EEG signals to obtain the most discriminative features in representing different emotions remain a challenging problem for emotion recognition systems.

There are many techniques to analyze EEG signals. Previous studies have used feature extraction techniques like time domain, frequency domain, time-frequency domain, and functional connectivity network to analyze EEG data [16]–[18]. Amongst the signal analysis methods used for studying the primary rhythms in the signals, spectral analysis

is the most popular mode of analysis. EEG signals are highly non-stationary. Traditional methods like Fourier transforms fail to accommodate this non-stationary characteristic of EEG signal. One can explain that it is due to the global assumption of harmonic components while analyzing real-life signals. This, in turn, results in the broader Fourier spectrum and misleading energy frequency distribution [19]. Signal analysis using time-frequency space may aid to capture the fast dynamic changes in the neural spectra, unlike spectrum analysis methods.

Several research groups have reported various techniques for classifying emotions using EEG time-frequency methods. Discrete wavelet transform (DWT) and empirical mode decomposition (EMD) have been used to analyze EEG data in many works in the literature [2], [20]. DWT particularly is useful for capturing neural-specific domains in signals with regular frequency change [19], [21]. Emotion recognition based on the EMD method has not been investigated much even though it has been widely used for seizure detection and motor imagery classification. One recent study for emotion recognition from multidimensional information in EMD evaluated the performance on the Dataset for Emotion Analysis (DEAP) database [22]. The results showed that EMD outperforms time-domain methods benefiting from higher frequency content information [22]. One of the significant challenges in the application of EMD based methods in building a human-computer interface is its high computational time requirements [18]. Sweeney-Reed *et al.* [18] suggested that formulating a mathematical basis for EMD could give new insights into the underlying neural processes present in the EEG signal. They have pointed out that the frequency of oscillations related to particular cognitive behavior varies over time. This implies that EMD is useful in reflecting the underlying physiological process specific to the study of emotions.

It may be noted that, direct application of EMD to the raw EEG data may lead to intermittencies [23]. Besides, results from previous studies suggested that a combination of EMD and DWT methods can retrieve useful characteristics presented in nonlinear signals [24]. The use of wavelet transform prior to EMD on the a EEG signal is advantageous as it can detect and characterize singularities [23]. Munoz *et al.* [21] reported that EMD techniques resulted in signal softening and noise reduction [21]. Thus EMD can suppress noise accumulated from wavelet transformation [23]. The lack of adaptability from wavelet analysis can be compensated by incorporating EMD analysis. Ji *et al.* [25] used DWT and EMD based techniques for extracting non-linear features to improve the classification accuracy of motor imagery from EEG signals and showed promising results.

In the present work, we aim at studying the emotional expressions using EEG signals and machine learning approaches. Thus, we developed a novel protocol to induce genuine and acted emotional expressions within the two dimensional model of emotions; arousal and valence. Then, we analyzed these emotional expressions using three different

feature extraction methods by utilizing DWT, EMD and incorporating DWT into EMD (DWT-EMD). Data analysis presented in this study involves the higher three frequency bands; theta, alpha and beta due to their highest associations with emotions. Furthermore, we assessed the feasibility of applicable emotional expressions detection through three different classifiers: K-nearest neighbors (KNN), Support vector machines (SVM), and artificial neural network (ANN). To the best of our knowledge, this is the first work on discriminating acted from the actual expressions using three time-frequency feature analysis methods on EEG data. Hence, our key contributions in this work are as follows:

- Using EEG signal to differentiate genuine from acted emotional expressions.
- Experimental protocol and design to achieve the above.
- Introduction of a new database that contains EEG recordings of 28-subjects with acted and genuine smiles that can be used by other researchers in the area.

The rest of the paper is organized as follows. In section II, we describe our experimental stimuli, data-collection and preprocessing methods. Section III presents the proposed features extraction methods, statistical analysis and classification models. Section IV presents the results and classification analysis. Section V discusses the results and provides suggestions for future research work. Finally, Section VI concludes this study.

II. MATERIALS AND METHODS

A. SUBJECTS

Twenty-eight healthy students (20 males and 8 females; age $20±2$) participated in this study. All participants had normal or corrected to normal vision. They had no history of neurological or psychiatric illnesses. The study procedures were explained to the participants and they signed an informed consent form prior to the experiment. All methods performed followed the Declaration of Helsinki. The experimental protocol was approved by the institutional review board, (IRB) of the American University of Sharjah.

B. EXPERIMENT PROTOCOL

In this study, the emotion eliciting stimuli comprised of 246 still images obtained from two online public image datasets. These include the Open Affective Standardized Image Set (OASIS) [26], and the Geneva Affective Picture Database (GAPED) [27]. Three types of image sets were chosen to conduct this study (116-funny images, 70-neutral images, and 60-one-plain image). Funny pictures involved pictures of human and animal babies; neutral pictures include pictures of nature, and the plain-images mainly depicted a picture of a plain book. All images used in this study were based on the valence-arousal scale [26], [27]. Images were displayed and presented on 19 inch LCD screen that was kept 50 cm away from the participant. Images presentation order was semi-randomized, with the condition that no currently viewed picture belonged to the same category as the previously rated one. Three different event markers were sent to mark the epochs/trials of each type of image stimuli.

FIGURE 1. Experiment stimuli and task sequence.

The participants were instructed to pose an acted smile once the target image (plain-image) appeared on the screen and to hit a respective keyboard response (i.e. 'Q'). This was in order to invoke acted/fake emotion in the subject. In addition, all participants were asked to hit letter "P" or "N" once and only whenever they felt their feeling had changed and have to act to certain emotional expressions in the form of a true smile (hitting the letter 'P') and neutral expression by (hitting the letter 'N'), respectively. There were a total of 246 trials in this experiment as shown in FIGURE 1. Each trial has a one-second drift check followed by two-seconds of emotion stimulating image. This entire experiment lasted about 13 minutes, and the number of trials varied between subjects depending on their response speed. All the trials were labeled according to the response from the participant and only successful trials that induced genuine and acted smiles were considered for the analysis.

C. DATA ACQUISITION AND PREPROCESSING

The EEG data was recorded using 64 Ag/AgCl scalp electrodes arranged according to the standard 10–20 system (ANT waveguard system and ASA Lab 4.9.2 acquisition software, ANT Neuro, the Netherlands). The EEG data was sampled at 500 Hz. The impedances of all EEG electrodes were maintained below 10 k Ω , and were referenced to the left and right mastoids, M1 and M2. FIGURE 2 shows an example of the experimental setup and data acquisition layout.

The acquired EEG data was preprocessed using the EEGLAB toolboxes (9.0.4)[28] with custom scripts developed in [29],[30]. The eye blinks were detected through visual inspection and were discarded manually and using independent components analysis (ICA) method available in EEGLAB. The components representing artifacts, such as eye blinks, eye movements, and muscular activities were removed, and the remaining components were used to reconstruct the clean EEG signals. Typically, only one or two independent components relevant to eye blinks or eye movements were removed for each subject. All EEG signals were bandpass filtered using a finite impulse response (FIR) filter with 0.1 Hz to 40 Hz bandwidth. The power line interference was removed using a 50 Hz notch filter. The EEG data was re-referenced to the computed average reference. The data mean subtraction was performed to remove baseline

FIGURE 2. Experiment setup and data acquisition layout.

FIGURE 3. Framework for feature extraction and classification.

and DC offset. The clean signals were then segmented into epochs with a length of 1100 ms. This resulted in 230 epochs corresponding to three types of image stimuli. For all the three types of emotion, features were extracted using an equal number of epochs (we used 60 epochs per type of emotion with a total of 180 epochs).

III. FEATURE EXTRACTION

In this work, we propose to utilize three different algorithms for feature extractions. The methods are (1)-Discrete Wavelet Transform (DWT), (2)-Empirical Mode Decomposition (EMD) and [\(3\)](#page-4-0)-combination of Discrete Wavelet Transform and Empirical Mode Decomposition (DWT-EMD). The following subsections describe the implementation of the methods for feature extraction. To study the cognitive processes, we analyze oscillatory activity between the frequency range 4-30 Hz (i.e. theta, alpha and, beta bands). EEG frequency components are found to reflect changes in their power spectra. FIGURE 3 shows the proposed framework for feature extraction and emotion classification.

1) DISCRETE WAVELET TRANSFORM (DWT)

The clean EEG signals were decomposed into seven levels using discrete wavelet transform (DWT). The Daubechies 4 (Db4) wavelet family was employed in this study due to its near-optimal time-frequency localization and similarity to the EEG signal waveform [31]. At each level, the signal is down sampled by a factor of two.

The subset of wavelet coefficients corresponding to theta (DWT decomposition level 6), alpha (DWT decomposition level 5), and beta bands (DWT decomposition level 4), were used for feature extraction. The mean power of EEG signals in the three frequency bands for each electrode was computed using a moving time-window of 1.1 seconds, according to (1) as suggested by [30]:

$$
P_j = \frac{1}{N} \sum_{n=1}^{N} |x_j(n)|^2, j = 1, 2, 3
$$
 (1)

where P_j is the EEG mean power, $x_j(n)$ represents the segmented EEG signals in theta band at $j = 1$, alpha band at $j = 2j = 2$, and beta band at $j = 3$ and N is the length of the EEG signal. This gives a total of 11160 features per subject (corresponding to 60-epoch∗62-electrode∗3-frequencybands). The significant features in each frequency band were then used as an input to the machine learning classifiers.

2) EMPIRICAL MODE DECOMPOSITION

EMD is used to decompose the clean EEG signals into a finite number of intrinsic mode functions (IMFs) without any prior definitions, unlike predictive methods [20]. The EMD technique is based on direct energy extraction in time scale. Each IMF represents different frequency components of original signals and satisfies two conditions:

- The difference between the number of extrema and the number of zero crossings is at most one
- Given any point, the mean value of the envelope defined by the local maxima and local minima is zero.

Once the iterative processes of EMD satisfy the two conditions, the final function of EMD is represented in the time domain as given in (2). The local energy and the instantaneous frequency derived from the IMF through the Hilbert transform gives the full energy distribution of the data. This is ideal for nonlinear and non-stationary data analysis [19].

EMD of the EEG signal *X* for each frequency band (theta, alpha, and beta) is given as follow.

$$
X(n) = \sum_{i=1}^{N} c_i(n) + r(n)
$$
 (2)

where c_i is the ith IMF component repeated *N* times and *r* is the residue component.

3) DWT-EMD MODE

In this method, prior to EMD, the EEG data was first subjected to wavelet transformation to split them into a set of narrowband signals. Then appropriate subband signal is selected to be decomposed into an intrinsic mode function with a frequency that is more concentrated [32].

The use of wavelet transform prior to EMD on a clean EEG signal is advantageous as it can detect and characterize singularities [24]. In line with this, we used Daubechies 4 (Db4) wavelet to decompose the clean EEG signal into levels corresponding to three frequency bands such as theta, alpha and beta. Then we applied EMD on the three decomposed frequency bands to obtain their IMFs components, as

demonstrated in (2). From the first three IMFs components, we then extracted the mean power features using a time-window of 1.1 second, similar to (1). This resulted in 11160 features per subject (corresponding to 60-epoch[∗] 62-electrode∗3-frequency-bands). Significant features were then used as an input to the machine learning classifiers to distinguish between the three types of emotion. Meanwhile, the averages of all features across subjects were then represented in the form of topography covering the scalp at 62 electrodes.

A. FEATURE DIMENSION REDUCTION

Feature dimension reduction is used to select the most applicable features from the feature set. This is usually used prior to machine learning classifiers to achieve optimum performance. A variety of feature dimension reduction methods have been introduced in the literature, such as paired-sample t-test, Fisher distance and mutual information [33], [34].

In our study, the paired-sample t-test is used as the feature dimension reduction technique. The paired-sample t-test was performed to test the significance of the power features in EEG signals between true, neutral and fake emotions. Before conducting the t-test, we used the Kolmogorov-Smirnov test to check if the data is normally distributed [35]. The p-value of paired-sample t-test indicates the significant difference in two sample groups. We used the p-values of less than 0.05 to select the features for emotion recognition.

B. CLASSIFICATION AND PERFORMANCE ANALYSIS

To distinguish between the three emotions, we employed multiple classifiers. According to literature [36], the most commonly applied classifier techniques when PSD features serve as the input is SVM. Hence we used SVM as one of the methods to classify emotions. However, study in [37] applied artificial neural networks (ANN) to recognize positive, neutral, and negative emotions yielded higher accuracies than SVM and KNN techniques. Thus, we chose to deploy all the three classifier techniques KNN [38], SVM [39], and ANN [40] and test which technique works best for our EEG dataset. The parameters used for each classifier are summarized in TABLE 1. These parameters were obtained with validation on the training dataset. At this level, we classified true smile from fake smile, true smile from neutral expression and fake smile from neutral expression. In each classifier, we performed subject dependent classification with 5-fold cross-validation. The selected features in each subject were randomly split into five equally size subsets. For each of the subsets, we trained the classifiers using four subsets while the testing was done using the rest one-subset. To obtain all samples predicting labels, we repeated this procedure 5 times so that each subset is used for validation. We used the following metrics for evaluating the performance of the classifiers: accuracy, sensitivity, and specificity. The classification accuracy was calculated as the percentage ratio of correctly predicted samples to all samples in the data set. The sensitivity calculates the percentage of true positive (TP) cases that are correctly predicted out of all the true positives

and false negatives and the specificity is the percentage of true negatives (TN) that are predicted out of all the true negatives and false positives. The mathematical expressions of the accuracy, sensitivity and specificity are given in the following equations 3-5:

$$
Accuracy = \frac{TP + TN}{TP + TN + FP + FN}
$$
 (3)

$$
Sensitivity = \frac{TP}{TP + FN}
$$
 (4)

$$
Specificity = \frac{TN}{TN + FP}
$$
 (5)

IV. RESULTS

A. EMOTIONAL ACTIVATIONAL PATTERNS

The mean power distributions of all subjects corresponding to the three expressions are presented in the form of topographical maps shown in FIGURES 4, 5 and 6. The topographical map contains 62 electrodes in which electrodes of M1 and M2 were excluded from the analysis because of poor surfaceto-skin contact for most subjects. The main observations from the cortical activation patterns attained using discrete wavelet transform in FIGURE 4 across the three different emotions are summarized below:-

True emotion- Beta, alpha and theta bands show similar activation over the right frontal, right temporal, right central parietal and left parietal regions.

Neutral Emotion-Beta, alpha, and theta frequency bands show similar activation across the central and right parietal regions. Occipital regions show the lowest activations in the entire scalp in all the three frequency bands.

Fake Emotion-The topographical maps for fake emotion show a very lower cortical activation pattern compared to the true and neutral emotions. Nevertheless, higher activation is observed in the right prefrontal, right temporal and left parietal.

By using features from the EMD method, the observations from the corresponding topographical maps in FIGURE 5 are as follows:

True emotion- In beta band, most of the electrodes in the right hemisphere show higher activation compared to the one across the left hemisphere. Specifically, the right parietal and right occipital. Meanwhile, the alpha band shows high activation on the right hemisphere and left prefrontal electrodes. The higher activation in alpha band is located in the prefrontal areas. For theta band, only a few electrodes

IEEE Access®

FIGURE 4. Mean power distributions using the DWT method in different emotions and frequency bands.

FIGURE 5. Mean power distributions using EMD method in different emotions and frequency bands.

show the highest activations located at the right frontal and right parietal regions.

Neutral Emotion- In the beta band, the right hemisphere and central parietal electrodes show higher activations compared to other regions. In alpha band, the left prefrontal and right parietal and central electrodes show higher activations. In theta band, right frontal and left front-temporal show high activations compared to other regions.

Fake Emotion- Across the beta band, only right parietal and occipital electrodes show higher activation energy. In the alpha band, left prefrontal and right temporal electrodes demonstrate higher activation energy. Moreover, in the theta

FIGURE 6. Mean power distributions using DWT-EMD method in different emotions and frequency bands.

band, right central, parietal and occipital electrodes were highly active compared to other regions.

Finally, topographical maps of the power features extracted from DWT-EMD method are shown in FIGURE 6. The summary of observed results is as follows:-

True emotion- In the beta band, prefrontal, right parietal and left prefrontal show higher activation patterns compared to the other regions. In alpha band, prefrontal electrodes and right and left parietal show higher activations. In the theta band, frontal, left central/parietal as well as right parietal regions show high activations compared to the other regions.

Neutral Emotion- In beta band, only mid-central, right prefrontal and left parietal show high activations. Meanwhile, in the alpha band, the right frontal, right, and left temporal, right occipital and left central-parietal regions show high activations. Moreover, in the theta band, right frontal and left parietal and central regions show higher cortical activity.

Fake Emotion- For the beta band, left central and right prefrontal and right parietal show higher energy activations. However, in alpha and theta band most of the electrodes located at the frontal, central parietal and occipital show the highest activations.

The overall result from the three feature extraction methods is that, the DWT-EMD showed higher activations in all types of emotion and frequency bands compared to the sole DWT or EMD methods. These higher activations demonstrated by DWTEMD indicate that, the method extracted more hidden features that cannot be extracted by sole DWT or EMD methods. It was also shown that, the cortical activations shifted between brain regions with type of emotions indicating the effectiveness of image stimuli in inducing different emotions. The higher cortical activations within the type of emotions and frequency bands are consistent across the three methods of analysis.

TABLE 2. Subject dependent classification performance averaged across all subjects (%).

B. CLASSIFICATION PERFORMANCE

We evaluated the performance of the three proposed feature extraction methods using KNN, SVM, and ANN. The mean classification accuracy, sensitivity and specificity with the standard deviation across subjects in all the frequency bands and type of emotions are summarized in TABLE 2. As mentioned earlier, we conducted binary classification across three cases (case 1: true smiles vs. fake smiles, case 2: true smiles vs. neutral expression and case 3: fake smile vs. neutral expression). The features extracted by DWT technique exhibited maximum accuracy in classifying true smile from fake one with ANN classifier at the beta band (accuracy 68.6%, sensitivity 68.5%, and specificity 68.7%). Meanwhile, the highest performance accuracy attained from empirical mode decomposition method was in the case 1 with SVM classifier in the beta frequency band (accuracy 84.1%, sensitivity 81.3%, and specificity 86.8%). And finally, it can be seen that the application of discrete wavelet transform prior to empirical mode decomposition has significantly improved the classification performance. Maximum accuracy was found in the case 1 itself using ANN classifier in the alpha band (accuracy 94.3%, sensitivity 92.9%, and specificity 95.6%).

The results of the classifier performance across the three methods was validated statistically by comparing the (i) DWT to EMD, (ii) DWT to DWT-EMD method, (iii) EMD to DWT-EMD method. It was found that the DWT-EMD significantly outperforms the sole DWT and sole EMD methods, $(p<0.01)$ in most bands and classifiers.

Besides, EMD outperformed DWT in most of the classifiers and bands as shown in TABLE 2. Looking at the type of classifiers, the ANN classifier performed better than the other classifiers and the highest accuracy was observed in the alpha frequency band. It should be noted that the emotion recognition is mostly associated with higher frequency bands like alpha and beta which is why the performance accuracy was high in the alpha band. It is worth noting that the ANN classifier performs better compared to SVM or KNN due to sufficient training data as suggested in [16]. This may be one of the reasons why ANN classifier outperformed the other classifiers in this study.

V. DISCUSSIONS

The goal of this study was to discriminate genuine and acted expressions using EEG signals. For this purpose, an experimental paradigm was designed to acquire the brain signals

associated with three emotional expressions: - true, fake, and neutral. Emotion-specific studies greatly rely on the choice of emotional stimuli. Thus, we chose static images as visual stimuli. The induced emotional expressions were investigated by extracting features using three different time-frequency analysis methods from the acquired EEG signals. Moreover, how well these emotions could be distinguished was evaluated using machine learning with multiple classifiers. The achieved results predict that it is possible to distinguish between true, neutral, and fake emotional expressions using EEG signals. To the best of our knowledge, this is the first study investigating emotions in the form of smile expressions using EEG signals and machine learning approaches.

In this paper, we reported the neural activation patterns associated with three different emotional expressions represented by their topographical maps. This kind of distribution maps has been plotted to give clear idea of active EEG electrodes under each type of emotions.

Besides, we performed subject dependent classification between the three emotions using ANN, SVM and KNN. The topographical maps in FIGURES 4 to 6 reveal that there exists a specific neural pattern associated with each type of emotional expressions. Our results showed that the mental process and cognition activities to emotional stimuli were related to prefrontal region of the brain. In particular, we found that the topographical maps showed higher frontal and parietal activity for true emotion. Our findings agree with the results obtained from the previous emotion studies that highlighted the associations of specific neural patterns with different emotions [22], [13], [41]. This is also inline with previous functional magnetic resonance imaging (fMRI) and positron emission tomography (PET) studies, which demonstrated that remembering happy events is primarily associated with the activation of many areas, including anterior cingulate cortex, and prefrontal cortex [42].

It was also noted that across all the time-frequency analysis methods utilized for feature extraction, the maximum classification accuracy was achieved in the case of true smile versus a fake smile. This indicates that the type of image stimuli significantly modulated brain responses. By analyzing the classification performance across the three EEG frequency bands, it can be noted that classifiers performed slightly better in the alpha and beta frequency band, compared to the theta band. This is consistent with previous studies which revealed that emotional process were better reflected in the high frequency bands [13], [43].

Looking closely at the three-feature extraction methods employed, the DWT-EMD method has yielded the highest classification accuracy in the alpha band, with 94.3%, 92.4% and 83.8% for classifying true emotional expression from fake one using ANN, SVM, and KNN, respectively. Likewise, DWT-EMD in beta band showed comparable accuracy in classifying neutral emotional expressions from true and fake emotions. Meanwhile, DWT-EMD in theta band obtained the highest accuracy when classifying true from fake

Another noteworthy point is that there were significant improvements in the classification accuracies when incorporating DWT transform method prior to the EMD method. The features extracted by applying a discrete wavelet transform followed by empirical mode decomposition yielded better results compared to the application of EMD alone or DWT alone. In alpha band, we found that DWT-EMD outperformed DWT by 27.9%, 19.7%, and 24.7% using ANN, KNN and SVM, respectively. Similar improvements were also found across beta and theta frequency bands. Likewise, we found that DWT-EMD outperformed EMD at alpha band by 13.2%, 14.1%, and 12.9% using ANN, KNN and SVM, respectively. According to [45], applying DWT before decomposing the signal into IMFs helps to get devoid of wide frequency band coverage experienced while using EMD technique to the nonstationary signals like EEG. This may be one of the reasons for the performance enhancement for the classi?cation of EEG signals in our work. Thus, it can be inferred that indeed the application of DWT prior to EMD enhances the classifier performance and useful method for feature extraction using EEG signals.

This study has improved the emotion recognition rate significantly with DWT-EMD method. However, there are some limitations to it. First, our analysis is completely based on static images. Many previous works have used multiple stimuli for emotion recognition. Incorporation of different types of stimuli could provide a better understanding of the emotional expressions. Second, this study has been done in a single session. The possibility of monitoring the stability of EEG responses over different sessions should be explored. This would provide more insight of emotion recognition. Third, the feature dimensionality reduction /selection method used in this study was based on simple statistical analysis of t-test. The method is a univariate test and it does not consider multiple variables together and their possible interactions. Future studies should consider more robust feature selection methods such as correlation-based channel selection [46], bispectrum-based [47] and internal feature selection method of common spatial pattern [48]. In addition, to further improve the classification accuracy, researchers may combine multiple modalities such as EEG with eye tracking, EEG with functional near infrared spectroscopy or combination of the three modalities. These modalities contain complementary information and can be integrated to construct a more robust emotion estimation model. Finally, our study focused on positive emotions, the application of DWT-EMD method on other types of emotions like sadness, amusement etc. can be evaluated in future studies.

VI. CONCLUSION

In this study, we attempt to differentiate between acted versus actual emotions using EEG signals. We developed an experimental paradigm to elicit three different emotional expressions: - true, fake/acted and neutral. To extract useful information to distinguish between these three types of expressions, we used time-frequency based techniques on EEG signals. And further applied machine learning algorithms:- ANN, SVM, and KNN. The attained results from the classification performance and power distribution suggest that there exists a difference in the way humans express genuine and acted expressions. The prefrontal, electrodes exhibited higher activation patterns in the power distribution map. We achieved a maximum classification accuracy of 94.3% using ANN classifier in the alpha frequency band using DWT-EMD method. From the three used classifier techniques for emotion recognition in our study, it was found that ANN and KNN classifiers yield best results. In short, we present the first work of its kind on differentiating fake from genuine expressions using EEG signals. We designed human subjective experiments and also collected a very valuable dataset that can be used by other researchers to advance the state-of-art in this new area.

ACKNOWLEDGMENT

The authors would like to thank the Research Office, American University of Sharjah, for their sponsorship of this open access publication.

REFERENCES

- [1] R. Alazrai, R. Homoud, H. Alwanni, and M. Daoud, ''EEG-based emotion recognition using quadratic time-frequency distribution,'' *Sensors*, vol. 18, no. 8, p. 2739, Aug. 2018.
- [2] B. Garcia-Martinez, A. Martinez-Rodrigo, R. Alcaraz, and A. Fernandez-Caballero, ''A review on nonlinear methods using electroencephalographic recordings for emotion recognition,' *IEEE Trans. Affect. Comput.*, early access, Jan. 1, 2019, doi: [10.1109/TAFFC.2018.2890636.](http://dx.doi.org/10.1109/TAFFC.2018.2890636)
- [3] F. Al-Shargie, U. Tariq, M. Alex, H. Mir, and H. Al-Nashash, ''Emotion recognition based on fusion of local cortical activations and dynamic functional networks connectivity: An EEG study,'' *IEEE Access*, vol. 7, pp. 143550–143562, 2019.
- [4] R. A. Khalil, E. Jones, M. I. Babar, T. Jan, M. H. Zafar, and T. Alhussain, ''Speech emotion recognition using deep learning techniques: A review,'' *IEEE Access*, vol. 7, pp. 117327–117345, Aug. 2019.
- [5] R. Shah, H. Thaker, S. Shettigar, M. Thakar, and C. Bhadane, ''Audio tagging for emotion recognition: A review,'' in *Advanced Computing Technologies and Applications*. Singapore: Springer, 2020, pp. 573–578.
- [6] J. Zhang, Z. Yin, P. Chen, and S. Nichele, ''Emotion recognition using multi-modal data and machine learning techniques: A tutorial and review,'' *Inf. Fusion*, vol. 59, pp. 103–126, Jul. 2020.
- [7] A. Dzedzickis, A. Kaklauskas, and V. Bucinskas, ''Human emotion recognition: Review of sensors and methods,'' *Sensors*, vol. 20, no. 3, p. 592, Jan. 2020.
- [8] M. E. Hoque, D. J. McDuff, and R. W. Picard, "Exploring temporal patterns in classifying frustrated and delighted smiles,'' *IEEE Trans. Affect. Comput.*, vol. 3, no. 3, pp. 323–334, Jul. 2012.
- [9] T. Song, W. Zheng, C. Lu, Y. Zong, X. Zhang, and Z. Cui, ''MPED: A multi-modal physiological emotion database for discrete emotion recognition,'' *IEEE Access*, vol. 7, pp. 12177–12191, 2019.
- [10] S. Koelstra and I. Patras, "Fusion of facial expressions and EEG for implicit affective tagging,'' *Image Vis. Comput.*, vol. 31, no. 2, pp. 164–174, Feb. 2013.
- [11] S. Paszkiel, "Using neural networks for classification of the changes in the EEG signal based on facial expressions,'' in *Studies in Computational Intelligence*, vol. 852. New York, NY, USA: Springer-Verlag, 2020, pp. 41–69.
- [12] M. Soleymani, S. Asghari-Esfeden, Y. Fu, and M. Pantic, "Analysis of EEG signals and facial expressions for continuous emotion detection,'' *IEEE Trans. Affect. Comput.*, vol. 7, no. 1, pp. 17–28, Jan. 2016.
- [13] W.-L. Zheng and B.-L. Lu, "Investigating critical frequency bands and channels for EEG-based emotion recognition with deep neural networks,'' *IEEE Trans. Auto. Mental Develop.*, vol. 7, no. 3, pp. 162–175, Sep. 2015.
- [14] S. Koelstra, C. Muhl, M. Soleymani, J.-S. Lee, A. Yazdani, T. Ebrahimi, T. Pun, A. Nijholt, and I. Patras, ''DEAP: A database for emotion analysis; using physiological signals,'' *IEEE Trans. Affect. Comput.*, vol. 3, no. 1, pp. 18–31, Jan. 2012.
- [15] M. Soleymani, J. Lichtenauer, T. Pun, and M. Pantic, ''A multimodal database for affect recognition and implicit tagging,'' *IEEE Trans. Affect. Comput.*, vol. 3, no. 1, pp. 42–55, Jan. 2012.
- [16] H. Becker, J. Fleureau, P. Guillotel, F. Wendling, I. Merlet, and L. Albera, ''Emotion recognition based on high-resolution EEG recordings and reconstructed brain sources,'' *IEEE Trans. Affect. Comput.*, vol. 11, no. 2, pp. 244–257, Apr. 2020.
- [17] B. J. Roach and D. H. Mathalon, "Event-related EEG time-frequency analysis: An overview of measures and an analysis of early gamma band phase locking in schizophrenia,'' *Schizophrenia Bull.*, vol. 34, no. 5, pp. 907–926, Jul. 2008.
- [18] C. M. Sweeney-Reed, S. J. Nasuto, M. F. Vieira, and A. O. Andrade, ''Empirical mode decomposition and its extensions applied to EEG analysis: A review,'' *Adv. Data Sci. Adapt. Anal.*, vol. 10, pp. 1–35, Apr. 2018.
- [19] N. E. Huang, Z. Shen, S. R. Long, M. C. Wu, H. H. Shih, Q. Zheng, N.-C. Yen, C. C. Tung, and H. H. Liu, ''The empirical mode decomposition and the Hubert spectrum for nonlinear and non-stationary time series analysis,'' *Proc. R. Soc. A Math. Phys. Eng. Sci.*, vol. 454, no. 1971, pp. 903–995, 1998.
- [20] A. C. Yang, C.-K. Peng, and N. E. Huang, "Causal decomposition in the mutual causation system,'' *Nature Commun.*, vol. 9, no. 1, pp. 1–10, Dec. 2018.
- [21] R. Munoz, R. Olivares, C. Taramasco, R. Villarroel, R. Soto, T. S. Barcelos, E. Merino, and M. F. Alonso-Sánchez, ''Using black hole algorithm to improve EEG-based emotion recognition,'' *Comput. Intell. Neurosci.*, vol. 2018, pp. 1–21, Jun. 2018.
- [22] N. Zhuang, Y. Zeng, L. Tong, C. Zhang, H. Zhang, and B. Yan, ''Emotion recognition from EEG signals using multidimensional information in EMD domain,'' *BioMed Res. Int.*, vol. 2017, pp. 1–9, 2017.
- [23] Q. Pinle, L. Yan, and C. Ming, "Empirical mode decomposition method based on wavelet with translation invariance,'' *EURASIP J. Adv. Signal Process.*, vol. 2008, no. 1, p. 1, Dec. 2008.
- [24] G. Zhi-Qiang, Z. Ming-Wei, G. Xin-Quan, and D. Wen-Jie, ''On the difference between empirical mode decomposition and wavelet decomposition in the nonlinear time series,'' *Acta Physica Sinica*, vol. 54, no. 8, pp. 3947–3957, 2005.
- [25] Ji, Ma, Dong, and Zhang, "EEG signals feature extraction based on DWT and EMD combined with approximate entropy,'' *Brain Sci.*, vol. 9, no. 8, p. 201, Aug. 2019.
- [26] B. Kurdi, S. Lozano, and M. R. Banaji, "Introducing the open affective standardized image set (OASIS),'' *Behav. Res. Methods*, vol. 49, no. 2, pp. 457–470, Apr. 2017.
- [27] E. S. Dan-Glauser and K. R. Scherer, ''The Geneva affective picture database (GAPED): A new 730-picture database focusing on valence and normative significance,'' *Behav. Res. Methods*, vol. 43, no. 2, pp. 468–477, Jun. 2011.
- [28] A. Delorme and S. Makeig, "EEGLAB: An open source toolbox for analysis of single-trial EEG dynamics including independent component analysis,'' *J. Neurosci. Methods*, vol. 134, no. 1, pp. 9–21, 2004.
- [29] F. Al-Shargie, T. B. Tang, and M. Kiguchi, ''Stress assessment based on decision fusion of EEG and fNIRS signals,'' *IEEE Access*, vol. 5, pp. 19889–19896, Sep. 2017.
- [30] F. Al-Shargie, M. Kiguchi, N. Badruddin, S. C. Dass, A. F. M. Hani, and T. B. Tang, ''Mental stress assessment using simultaneous measurement of EEG and fNIRS,'' *Biomed. Opt. Express*, vol. 7, no. 10, p. 3882, Oct. 2016.
- [31] M. Murugappan, M. Rizon, R. Nagarajan, S. Yaacob, I. Zunaidi, and D. Hazry, ''EEG feature extraction for classifying emotions using FCM and FKM,'' *Int. J. Comput. Commun.*, vol. 1, no. 2, pp. 21–25, 2007.
- [32] E. Abdalsalam Mohamed, M. Zuki Yusoff, I. Khalil Adam, E. Ali Hamid, F. Al-Shargie, and M. Muzammel, ''Enhancing EEG signals in brain computer interface using intrinsic time-scale decomposition,'' *J. Phys., Conf.*, vol. 1123, Nov. 2018, Art. no. 012004.
- [33] F. M. Al-Shargie, T. B. Tang, N. Badruddin, and M. Kiguchi, ''Mental stress quantification using EEG signals,'' in *Proc. IFMBE*, vol. 56, 2016, pp. 15–19.
- [34] R. Jenke, A. Peer, and M. Buss, "Feature extraction and selection for emotion recognition from EEG,'' *IEEE Trans. Affect. Comput.*, vol. 5, no. 3, pp. 327–339, Jul. 2014.
- [35] H. W. Lilliefors, "On the Kolmogorov-Smirnov test for normality with mean and variance unknown,'' *J. Amer. Stat. Assoc.*, vol. 62, no. 318, pp. 399–402, Jun. 1967.
- [36] A. Al-Nafjan, M. Hosny, Y. Al-Ohali, and A. Al-Wabil, "Review and classification of emotion recognition based on EEG brain-computer interface system research: A systematic review,'' *Appl. Sci.*, vol. 7, no. 12, p. 1239, Dec. 2017.
- [37] W.-L. Zheng and B.-L. Lu, ''Investigating critical frequency bands and channels for EEG-based emotion recognition with deep neural networks,'' *IEEE Trans. Auto. Mental Develop.*, vol. 7, no. 3, pp. 162–175, Sep. 2015.
- [38] A. M. Bhatti, M. Majid, S. M. Anwar, and B. Khan, ''Human emotion recognition and analysis in response to audio music using brain signals,'' *Comput. Hum. Behav.*, vol. 65, pp. 267–275, Dec. 2016.
- [39] F. Al-shargie, T. B. Tang, N. Badruddin, and M. Kiguchi, ''Towards multilevel mental stress assessment using SVM with ECOC: An EEG approach,'' *Med. Biol. Eng. Comput.*, vol. 56, no. 1, pp. 125–136, Jan. 2018.
- [40] V. Meza-Kubo, A. L. Morán, I. Carrillo, G. Galindo, and E. García-Canseco, ''Assessing the user experience of older adults using a neural network trained to recognize emotions from brain signals,'' *J. Biomed. Informat.*, vol. 62, pp. 202–209, Aug. 2016.
- [41] N. Zhuang, Y. Zeng, K. Yang, C. Zhang, L. Tong, and B. Yan, ''Investigating patterns for self-induced emotion recognition from EEG signals,'' *Sensors*, vol. 18, no. 3, p. 841, Mar. 2018.
- [42] A. Suardi, I. Sotgiu, T. Costa, F. Cauda, and M. Rusconi, ''The neural correlates of happiness: A review of PET and fMRI studies using autobiographical recall methods,'' *Cognit., Affect., Behav. Neurosci.*, vol. 16, no. 3, pp. 383–392, Jun. 2016.
- [43] C. Pan, C. Shi, H. Mu, J. Li, and X. Gao, "EEG-based emotion recognition using logistic regression with Gaussian kernel and Laplacian prior and investigation of critical frequency bands,'' *Appl. Sci.*, vol. 10, no. 5, p. 1619, Feb. 2020.
- [44] N. Jatupaiboon, S. Pan-ngum, and P. Israsena, ''Real-time EEG-based happiness detection system," *Sci. World J.*, vol. 2013, p. 12, 2013, Art. no. 618649.
- [45] Ji, Ma, Dong, and Zhang, "EEG signals feature extraction based on DWT and EMD combined with approximate entropy,'' *Brain Sci.*, vol. 9, no. 8, p. 201, Aug. 2019.
- [46] J. Jin, Y. Miao, I. Daly, C. Zuo, D. Hu, and A. Cichocki, "Correlationbased channel selection and regularized feature optimization for MI-based BCI,'' *Neural Netw.*, vol. 118, pp. 262–270, Oct. 2019.
- [47] J. Jin, C. Liu, I. M. Y. Daly, S. Li, X. Wang, and A. Cichocki, ''Bispectrum-based channel selection for motor imagery based braincomputer interfacing,'' *IEEE Trans. Neural Syst. Rehabil. Eng.*, vol. 28, no. 10, pp. 2153–2163, Oct. 2020, doi: [10.1109/TNSRE.2020.3020975.](http://dx.doi.org/10.1109/TNSRE.2020.3020975)
- [48] J. Jin, R. Xiao, I. Daly, Y. Miao, X. Wang, and A. Cichocki, ''Internal feature selection method of CSP based on L1-norm and dempster-shafer theory,'' *IEEE Trans. Neural Netw. Learn. Syst.*, early access, Aug. 24, 2020, doi: [10.1109/TNNLS.2020.3015505.](http://dx.doi.org/10.1109/TNNLS.2020.3015505)

MEERA ALEX was born in India, in 1993. She received the B.S. degree in biomedical engineering from the University of Calicut, India. She is currently pursuing the master's degree in biomedical engineering with the American University of Sharjah, United Arab Emirates.

USMAN TARIQ (Member, IEEE) received the M.S. and Ph.D. degrees from the Electrical and Computer Engineering Department, University of Illinois at Urbana-Champaign (UIUC), in 2009 and 2013, respectively. He was a Research Scientist with the Xerox Research Center Europe, Computer Vision Group, France. He is currently a Faculty Member with the Department of Electrical Engineering, American University of Sharjah (AUS), United Arab Emirates. His research inter-

ests include computer vision, image processing, and machine learning in general while facial expression recognition and face biometrics in particular.

FARES AL-SHARGIE (Member, IEEE) received the B.S. and M.S. degrees in biomedical engineering from Multimedia University, Malaysia, and the Ph.D. degree in biomedical engineering from Universiti Teknologi Petronas, Malaysia. He was with several biomedical engineering departments and companies, including the Research and Development Group, Hitachi Ltd., Japan. He is the first author in more than 30 journal and conference papers, one book, and one book chapter.

His current research interests include assessment of mental stress, vigilance decrement, and emotions via EEG, fNIRS neuroimaging modalities, and eye tracking. He is a member of the Society of Functional Near-Infrared Spectroscopy.

HASAN S. MIR (Senior Member, IEEE) received the B.S. *(cum laude)*, M.S., and Ph.D. degrees in electrical engineering from the University of Washington, Seattle, in 2000, 2001, and 2005, respectively. He was with the MIT Lincoln Laboratory, Air Defense Technology Group, Lexington, MA, USA, from 2005 to 2009, where he was involved in several projects related to airborne and maritime radar systems. Since 2009, he has been with the Department of Electrical Engineering, American University of Sharjah, where he is currently a Professor. His research interests include radar signal processing, adaptive beamforming, and direction-of-arrival estimation. He serves as an Associate Editor for IEEE ACCESS, the IEEE TRANSACTIONS ON AEROSPACE AND ELECTRONIC SYSTEMS, *IET Microwaves, Antennas, and Propagation*, and *IET Signal Processing*.

HASAN AL NASHASH (Senior Member, IEEE) was with several biomedical engineering departments and hospitals, including the National University of Singapore, Johns Hopkins University, and the Rashid Hospital, Dubai. He is currently a Professor, an Interim Director with the Biosciences and Bioengineering Research Institute, and a Former Chair with the Department of Electrical Engineering, American University of Sharjah. He has designed and developed several electronic

instruments to measure various biodynamic parameters. He led the effort to establish the M.S. Graduate Program in biomedical engineering. He has played an active role in organizing several biomedical and electrical engineering conferences. He is leading the effort to establish the Biosciences and Bioengineering Research Institute, AUS. He is the author of more than 100 journal and conference papers and five book chapters. He holds two issued U.S. patents. His main research interests include neuroengineering, signal processing, and microelectronics. He is a Senior Member of the former Middle East and Africa Representative with the IEEE-EMBS Administrative Committee.