

Received November 9, 2020, accepted November 16, 2020, date of publication November 19, 2020, date of current version December 3, 2020.

Digital Object Identifier 10.1109/ACCESS.2020.3039276

User Clustering in mmWave-NOMA Systems With User Decoding Capability Constraints for B5G Networks

ADITYA S. RAJASEKARAN^{1,3}, (Member, IEEE), OMAR MARAQA²,
HAMZA UMIT SOKUN³, HALIM YANIKOMEROGU¹, (Fellow, IEEE),
AND SAAD AL-AHMADI²

¹Department of Systems and Computer Engineering, Carleton University, Ottawa, ON K1S 5B6, Canada

²Department of Electrical Engineering, King Fahd University of Petroleum & Minerals, Dhahran 31261, Saudi Arabia

³Ericsson Canada, Inc., Ottawa, ON K2K 2V6, Canada

Corresponding author: Aditya S. Rajasekaran (aditya.sriram.rajasekaran@ericsson.com)

This work was supported in part by the Discovery Grant of the Natural Sciences and Engineering Research Council of Canada and in part by the King Fahd University of Petroleum & Minerals (KFUPM) under Grant SB191049. The work of Aditya S. Rajasekaran was supported by Ericsson Canada, Inc..

ABSTRACT This article proposes a millimeter wave-NOMA (mmWave-NOMA) system that takes into account the end-user signal processing capabilities, an important practical consideration. The implementation of NOMA in the downlink (DL) direction requires successive interference cancellation (SIC) to be performed at the user terminals, which comes at the cost of additional complexity. In NOMA, the weakest user only has to decode its own signal, while the strongest user has to decode the signals of all other users in the SIC procedure. Hence, the additional implementation complexity required of the user to perform SIC for DL NOMA depends on its position in the SIC decoding order. Beyond fifth-generation (B5G) communication systems are expected to support a wide variety of end-user devices, each with their own processing capabilities. We envision a system where users report their SIC decoding capability to the base station (BS), i.e., the number of other users signals a user is capable of decoding in the SIC procedure. We investigate the rate maximization problem in such a system, by breaking it down into a user clustering and ordering problem (UCOP), followed by a power allocation problem. We propose a NOMA-minimum exact cover (NOMA-MEC) heuristic algorithm that converts the UCOP into a cluster minimization problem from a derived set of valid cluster combinations after factoring in the SIC decoding capability. The complexity of NOMA-MEC is analyzed for various algorithm and system parameters. For a homogeneous system of users that all have the same decoding capabilities, we show that this equates to a simple maximum number of users per cluster constraint and propose a lower complexity NOMA-best beam (NOMA-BB) algorithm. Simulation results demonstrate the performance superiority in terms of sum rate compared to orthogonal multiple access (OMA) and traditional NOMA clustering schemes that do not incorporate individual users' SIC decoding capability constraints.

INDEX TERMS Non-orthogonal multiple access (NOMA), millimeter-wave (mmWave), user clustering (UC), successive interference cancellation (SIC), minimum exact cover (MEC) problem.

I. INTRODUCTION

Beyond fifth-generation (B5G) communication systems are expected to support a large number of connected users at a time, each with different processing capabilities and require-

The associate editor coordinating the review of this manuscript and approving it for publication was Kezhi Wang.

ments. The massive machine-type connectivity (mMTC), also called the Internet of Things (IoT), as well as the ultra-reliable low latency communication (URLLC) use-cases, are expected to bring many different types of connected users into the system compared to traditional mobile broadband users [1]. Thus, B5G systems need to support a very large number of low-cost devices for the IoT connections in addition to the

traditional high data rate mobile broadband connections that are also growing exponentially. The latest Ericsson mobility report [2] estimates upwards of 30 billion connected users by 2023, with more than 50% coming from IoT connections. This puts enormous spectral efficiency requirements on the B5G wireless communication systems.

The mmWave spectrum offers a large amount of bandwidth to scale up the capacity from the cellular networks that operate today in the sub-6 GHz range. Further, non-orthogonal multiple access (NOMA) techniques offer a way to serve multiple users in the same orthogonal resource, e.g., time, frequency, orthogonal frequency division multiplexing (OFDM) resource block (RB), etc., by separating the users in the power domain instead (PD-NOMA). Hence, when combined, mmWave-NOMA has the potential to serve the high rates and massive connectivity demands of B5G networks. Additionally, the high level of correlation amongst users channels in mmWave, makes them ideal for the formation of user clusters to be served by a single beam and separated in the power domain through NOMA [3]–[5].

The survey in [6] shows that the key aspects of achieving a good performance in NOMA systems are user clustering, user ordering, beamforming, and power allocation. User clustering refers to the selection of users to serve in a NOMA cluster, typically in a beam via beamforming techniques. User ordering refers to the order in which successive interference cancellation (SIC) is applied at the users in the downlink. Power allocation techniques are then used to allocate the right amount of power to each user in the cluster, so that SIC decoding can be successful and each users target rates are met. The focus of this article is user clustering and user ordering.

As we group users in NOMA clusters, the weakest user only has to decode its own signal, while the strongest user has to decode the signals of all other users in the SIC procedure. The decoding of other users' signals requires significant additional processing capability, in terms of hardware capability, energy consumption, etc. [7], [8]. The authors in [9] identified this SIC decoding complexity as the first major practical implementation issue for NOMA. NOMA is expected to support a wide variety of end-user devices in B5G systems, each with different signal processing capabilities [9], [10]. Hence, each user has its own limitations on the number of other users signals that it can decode. We term this the SIC decoding capability of the user. For NOMA, this SIC decoding capability translates to the number of other users signals a DL user can decode before decoding its own signal. This SIC decoding capability can be easily communicated to the BS during connection setup. For IoT devices, this could be as low as zero or one, while for high-end smartphones this can be a much higher value due to the differences in hardware processing capability. Hence, when implementing NOMA in the DL, the BS needs to respect this SIC decoding capability limit of the user when it orders users to be served in a NOMA cluster as we discuss further in the motivation in Section I-B.

A. RELATED WORK

In [11], the authors highlight the tight coupling between user clustering, cluster sizes, and user ordering on the performance of NOMA systems. In typical NOMA works from the literature, the user pairing or user clustering schemes have been designed to group two users per cluster [12], [13], or some fixed number of users per cluster [14], respectively. In [14], the optimum cluster sizes from a performance perspective is analyzed. However, in this article, we focus on the cluster size as a constraint. More importantly, it is not just a generic constraint that limits the number of users in the cluster, but there is a constraint from each user in the cluster on how many other users signals it can decode in the SIC decoding order. When it comes to the SIC decoding order within a cluster, as highlighted in [15], users are typically ordered either based on their effective channel gains, i.e., channel gains after considering the beamforming weights, or based on their quality of service (QoS) using a cognitive radio concept. In this article, we focus on the effective channel gain strategy as we assume all users have the same QoS.

Unlike multi-user MIMO (MU-MIMO), where correlated users are difficult to separate by individual beams, such correlated users can easily be grouped together in a NOMA cluster [6]. In mmWave systems, the users' channels are highly correlated due to the highly directional nature of mmWave transmission [16], [17]. The user clustering schemes in mmWave-NOMA systems typically exploit the high correlation amongst users channels to cluster correlated users together, e.g., [3], [18]. In [19], the authors use an angle-domain NOMA scheme that schedules one cell-center and one cell-edge user in a NOMA pair, for each beam in each cell. Recent works in mmWave-NOMA systems have also used machine learning clustering techniques to identify correlated users and group them in NOMA clusters [5], [20], [21]. Further, in mmWave systems, since it is often infeasible to scale up the number of transceivers with the number of antennas, studies in mmWave-NOMA systems often use either analog beamforming (BF) with a single RF chain [16], [22], [23] or a hybrid BF design with a reduced number of RF chains [24], [25].

B. MOTIVATION AND CONTRIBUTIONS

In practical deployments, the typical clustering approaches described above in the related work in mmWave-NOMA have two important limitations. First, they can lead to arbitrarily large and uneven cluster sizes. If we have a system model where one cluster is served on one channel, this could lead to over-use on one channel and under-use on other channels. More than the imbalance in resource usage, large cluster sizes mean the users at the end of the SIC decoding orders need to decode a very large number of users. This is particularly an issue in dense deployments, where large clusters of correlated users can exist. The second important limitation with these algorithms is there is no flexibility incorporated to account for the SIC decoding capability limitations of each individual

user. Concretely, just finding groups of correlated users, can lead to cluster formations where the individual user decoding capability limits of some users are not respected, i.e., users are placed in SIC decoding positions in a cluster that require them to decode the signals of a greater number of users than their indicated SIC decoding capability.

The clustering schemes from the mmWave-NOMA literature that focus on finding correlated users, e.g., [5], can be modified to arbitrarily divide the groups of correlated users the algorithm identified into different clusters, served on different channels. Users then need to be decoded in the order of their decoding capabilities, rather than the effective channel gains. Even when users are decoded in the order of SIC decoding capability, further orthogonal channels might be needed if some users' constraints are not met. All such workarounds to meet the practical SIC decoding capability constraints of users in real deployments would erode the gains from the clustering algorithms that strived to find good sets of correlated users, with sufficient separation between the clusters. Instead, if the clustering algorithm was able to consider the user decoding capability requirements as part of its input, it would be better able to construct clusters that maximize the overall spectral efficiency, while taking into account these individual user decoding capability constraints. This is the motivation for the work presented in this article.

Against this background, in this article, we investigate a rate maximization problem for a mmWave-NOMA system that takes into consideration the SIC decoding capability of each individual user in the system. We break down the problem into a user clustering and ordering problem (UCOP), which is the focus of this article, followed by a power allocation (PA) problem. We consider a single-cell mmWave-NOMA equipped base station (BS) that applies analog beamforming (ABF) in a fixed set of directions uniformly distributed around the cell coverage area. A NOMA cluster of users will be served on an orthogonal channel, e.g., a time channel or OFDM resource block, using one of these pre-defined beams. In this way, the UCOP can be framed as a cluster minimization problem in order to minimize the number of orthogonal channels used to serve the required number of users, while respecting each individual user's SIC decoding capability constraints. We propose two algorithms to solve this UCOP. The first one we term NOMA-minimum exact cover (NOMA-MEC), as we decompose the problem into a MEC problem, a known NP-complete problem [26]. For a homogeneous system where all users have the same SIC decoding capability, we propose a less complex NOMA-best beam (NOMA-BB) algorithm. The key aspects of the two algorithms are outlined next.

In both algorithms, the BS uses the cosine similarity metric that aligns a user's channel with the set of possible beam directions to rank the best beams for each user. The BS then chooses the best beams to form a candidate beam list for each user, with the number of beams in this list a configurable parameter that can be tuned for a complexity-performance trade-off as we discuss in-depth in this article. This step

identifies users that can potentially cluster with each other. User ordering in any cluster is done in the order of the effective channel gains. NOMA-MEC then takes the SIC decoding capability of the users into account, and builds a list of valid cluster combinations such that the SIC decoding is done in the order of the users' channel gains and each user SIC decoding capability is respected. Using this candidate list, NOMA-MEC is able to frame the problem as a MEC problem where the goal is to serve all the users in the least number of channels from the designed set of valid cluster combinations.

In a homogeneous system, the user decoding capability constraints of the users translate to limiting the number of users per cluster, as any user ordering within that cluster will satisfy each user's decoding constraints since they are all equal. Such a homogeneous system with a restriction on the maximum number of users per cluster is what is typically considered in user clustering algorithms in the literature, e.g., [14]. In our case, the homogeneous system is just a special case of the heterogeneous system where all users have the same SIC decoding capabilities, and so the NOMA-MEC algorithm can still be run. However, for this simpler homogeneous system, we also propose a simpler NOMA-best beam (NOMA-BB) algorithm that demonstrates comparable performance to NOMA-MEC when we have the special setting of all users having the same decoding capability. Finally, we demonstrate the performance superiority of NOMA-MEC compared to orthogonal multiple access (OMA) as well as the additional flexibility the NOMA-MEC scheme offers in heterogeneous systems compared to other NOMA clustering schemes like NOMA-BB that target a fixed number of users per cluster.

Our contributions can thus be summarized as follows:

- We design a joint user-clustering, user ordering, and beamforming scheme in a mmWave-NOMA ABF system with a fixed set of candidate beams that minimizes the number of clusters required to serve all the users, subject to each individual users decoding capability and beamforming constraints. Each NOMA cluster is served on one orthogonal channel, so minimizing the number of clusters also minimizes the number of channel uses. Together with a power allocation scheme per cluster, we maximize the sum rate of the system.
- To the best of the authors' knowledge, this is the first NOMA work that considers the individual SIC decoding capability of each user when doing NOMA clustering and ordering. The proposed scheme is ideally suited for a mmWave-NOMA deployment involving a low-cost small-cell BS with only one RF chain, supporting a large number and variety of connected users, from low-cost IoT devices with limited processing capabilities to high-end smartphones with much larger processing capabilities. From the perspective of NOMA in the downlink, the processing capability of the user primarily impacts the SIC decoding capability, i.e., the number of other users signals a user can decode every channel use.

TABLE 1. List of Parameters.

Notation	Description
$h_u, \alpha_u, L, r_u^\eta$	mmWave channel parameters
$\mathbf{a}(\theta_u), \phi_u, D, \lambda$	Antenna array related parameters
M	Number of antennas at BS
N	Total number of users in the system
K	Number of clusters
$C = \{C_1, \dots, C_K\}$	The set of K clusters
$(B, \bar{\theta})$	Coverage area θ is divided into B parts, which the BS uses to generate $B + 1$ candidate beams
$B_c = \{\text{Beam-0}, \dots, \text{Beam-}B\}$	The set of $B + 1$ candidate beams
$W_c = \{\mathbf{w}_0, \dots, \mathbf{w}_B\}$	The set of $B + 1$ candidate precoding vectors
B_u, b	User-beam set for user- u containing b beams
B_u^*	Best beam in B_u , i.e., B_u with $b = 1$
$(C_k, N_{C_k}, b_k, \mathbf{w}_{b_k})$	The cluster C_k , containing N_{C_k} users, served on beam- b_k with a precoding vector \mathbf{w}_{b_k}
s_k	The transmitted signal to cluster- k
y_u	The received signal at user- u
p_u	The power allocated to user- u
P	The power available per channel
ξ_u	The noise at user- u
σ^2	The noise power
$\pi_k(j)$	The user index for the j -th decoded user in the k -th cluster
$\Gamma_{\pi_k(j)}^{\pi_k(j')}$	The SINR when decoding user $\pi_k(j)$ at user $\pi_k(j')$, where $j' > j$
$\Gamma_{\pi_k(u)}^{\pi_k(u)}$	The SINR when decoding user $\pi_k(u)$ own signal
$R_{\text{sum}} / R_{\text{OMA}}$	The effective sum rate of the system that adopted NOMA/OMA scheme
R_k	The sum rate of the users within cluster- k
Γ_{min}	Users minimum QoS SINR
d_{max}	The maximum decoding capability among the N users in the system
d_u	Decoding capability of user- u , in the range $[0, d_{\text{max}}]$
m	A NOMA-BB algorithm parameter between 1 and d_{max}
$d_{\pi_k(j)}$	The decoding capability of the j -th decoded user in the k -th cluster
C_v	A list of viable candidate cluster options
n_b	The number of users that have beam- b in their user-beam set
b_{th}	User is in the coverage area of b_{th} beams from the list of candidate beams in B_c
I_1	Number of iterations examined in step-1 of NOMA-MEC
I_2	Number of possible combinations for step-2 of NOMA-MEC to examine, i.e., number of elements in C_v
$u_{i,k}, z_{u,c}, x_c$	Binary variables defined as part of NOMA-MEC algorithm
$l, c_s, C_t, C_{\text{sorted}}$	Variables defined as part of NOMA-MEC algorithm
$(\cdot)^T, (\cdot)^H$	Transpose and Hermitian transpose
$\lceil \cdot \rceil$	Ceiling function

C. PAPER ORGANIZATION

The rest of this article is organized as follows. In Section II, the system model and problem formulation that aims to minimize the number of clusters required to serve the given

users are presented. In Section III, we detail the proposed NOMA-MEC and NOMA-BB algorithms. Detailed simulation results for the proposed algorithms, including a complexity analysis for different algorithm parameters, are presented




FIGURE 1. The ABF scheme used by the BS is illustrated on the left with a fixed set of $B + 1$ precoding weights, creating $B + 1$ candidate beam directions to choose from when serving a NOMA cluster of users in one orthogonal channel. On the right, the N users, each with their own SIC decoding capability, is illustrated.

in Section IV. Finally, concluding remarks are provided in Section V. Table 1 lists the notations used in this article.

II. SYSTEM MODEL AND PROBLEM FORMULATION

Consider a mmWave-NOMA single-cell BS equipped with M antennas serving N single-antenna users, each with a minimum QoS constraint. We use the single path mmWave channel model used in several mmWave-NOMA papers [3], [5], [17] to model the mmWave channel between the BS and user- u as follows:

$$h_u = a(\theta_u) \frac{\alpha_u}{\sqrt{L}(1 + r_u^\eta)}, \tag{1}$$

where L denotes the number of paths, r_u denotes the distance between the BS and user- u , η denotes the path loss exponent and α_u denotes the complex channel gain for user- u . The parameter θ_u represents the physical angle of departure and for a uniform linear array (ULA), the normalized angle is defined as $\phi_u = 2\frac{D}{\lambda} \sin(\theta_u)$, where D is the separation between elements of the antenna and λ is the wavelength of the carrier signal [17]. The term $a(\theta_u)$ represents the steering vector and for a ULA can be represented as

$$a(\theta_u) = [1, e^{-j2\pi \frac{D}{\lambda} \sin(\theta_u)}, \dots, e^{-j2\pi (M-1) \frac{D}{\lambda} \sin(\theta_u)}]^T \\ = [1, e^{-j\pi \phi_u}, \dots, e^{-j\pi (M-1) \phi_u}]^T. \tag{2}$$

Analog beamforming is used since only one radio frequency (RF) chain is available at the BS, typical of small-cell deployments where low hardware cost and power consumption is essential, e.g., [17], [22]. Hence, only one beam can be transmitted at a time, which we equate to forming

one beam to serve one cluster of NOMA users per channel use. Since we use ABF that can only generate one beam at a time, we use a time-division strategy to alternate between the different clusters.

As the left part of Fig. 1 illustrates, the entire coverage region, $\bar{\theta}$, from $-\pi/2$ to $\pi/2$ is covered by a set of $B + 1$ candidate beams, with significant overlap between the candidate beams. A NOMA cluster of users will be served on an orthogonal channel using one of these candidate beams. Each beam- b in this candidate list has the following precoding vector,

$$w_b = a(\bar{\theta}_b), \quad \forall b \in [0, B] \tag{3}$$

where the parameter $\bar{\theta}_b$ is

$$\bar{\theta}_b = -\pi/2 + (b \times \pi/B). \tag{4}$$

In this way, we uniformly divide this entire coverage region, $\bar{\theta}$, into B equal angles, effectively forming a set of $B + 1$ candidate beams, as illustrated in the left part of Fig. 1. The $B + 1$ beams can be thought of as a choice of $B + 1$ different precoding vectors based on (3), such that collectively, the steering vectors of the B candidate precoding vectors uniformly cover the entire region of $\bar{\theta} = -\pi/2$ to $\pi/2$ or $\bar{\phi} = -1$ to 1. We let B_c represent this list of candidate beams, such that $B_c = \{\text{Beam-0}, \dots, \text{Beam-B}\}$, with their respective list of candidate precoding vectors being $W_c = \{w_0, \dots, w_B\}$, as illustrated in Fig.1.

A NOMA cluster of users will be served on an orthogonal channel using one of the $B + 1$ precoding vectors in the candidate list. In our system model, the orthogonal channel is a time slice, hence each cluster will be served in one time slice. A total of K such clusters are formed to serve the N users. This equates to requiring K channel uses, i.e., K time-slices, to serve the N users, $K \leq N$. Let $C = \{C_1, \dots, C_K\}$ represent the K clusters required to serve the N users, where C_k refers to the N_{C_k} users, $N_{C_k} \leq N$, selected to serve in the cluster with index- k . For each cluster C_k , a beam- b_k with a precoding vector w_{b_k} is selected from the set of $B + 1$ possible beam options in B_c .

We exploit the high correlation in the mmWave channels as follows. We assume the BS has access to the full channel state information (CSI) vector of each user, h_u , from (1) [4], [5]. Additionally, the BS knows the precoding vectors of each beam, w_b , in the candidate set. The BS can use the cosine similarity metric between the user’s channel vector and the precoding vector of each beam to determine the level of correlation between the user and the beam. This metric has been used in several mmWave-NOMA works for user clustering to determine the correlation between users in [5], [20], and between users and random beams in [17]. Using similar steps as these works, we can derive the cosine similarity between a user- u with channel h_u and a beam- b with precoding vector w_b here as follows:

$$\cos(h_u, w_b) = \frac{|a(\phi_u)^H a(\phi_b)|}{M}$$

$$\begin{aligned}
 &= \left| \frac{\sum_{i=0}^{M-1} e^{-j\pi i(\phi_u - \phi_b)}}{M} \right| \\
 &= \left| \frac{\sin\left(\frac{\pi M(\phi_u - \phi_b)}{2}\right)}{M \sin\left(\frac{\pi(\phi_u - \phi_b)}{2}\right)} \right| \\
 &= F_M(\pi[\phi_u - \phi_b]), \tag{5}
 \end{aligned}$$

where ϕ_u and ϕ_b are the normalized directions of the user and beam respectively, H represents the Hermitian transpose and F_M represents the Fejer Kernel, whose properties dictate that as $|\phi_u - \phi_b|$ increases, $\cos(\mathbf{h}_u, \mathbf{w}_b) \rightarrow 0$. In other words, if the beam and users directions are well aligned, the cosine similarity metric is high and it reflects that it is suitable to schedule the user on a cluster served by the beam- b . In this way, the BS builds a user-beam set, B_u , for each user- u . This user-beam set, B_u consists of b beams each, by selecting the best b beams for each user using the cosine similarity metric from (5). The parameter b is a tunable parameter, as we discuss later in Section III. We note that based on the choice of M and B , the beams are highly overlapping in nature and so a single user can be served by more than one beam, while still benefiting from a good beamforming gain. Alternatively, the user can select its best beams using the typical ABF approach for the mmWave in new radio (NR) standard [27], but that is beyond the scope of this article and is a topic for future work. It is also worth mentioning that our BF scheme is different from the random BF scheme in [17], where a random beam is generated with precoding vector $\mathbf{w} = \mathbf{a}(\theta)$, $\theta \in [-\pi/2, \pi/2]$ and all users with a high cosine similarity with that beam are then scheduled. In our scheme, while also ABF with a similar precoding vector, we are not randomly generating the beams, but instead selectively choosing an appropriate beam for a NOMA cluster from a given set of candidate options, B_c .

For cluster C_k , the BS applies superposition coding (SC) for the selected N_{C_k} users as follows:

$$s_k = \sum_{u=1}^{N_{C_k}} \sqrt{p_u} s_{k,u}, \tag{6}$$

where p_u represents the power allocated to user- u with $\sum_{u=1}^{N_{C_k}} p_u \leq P$, where P denotes the power available to the BS per-channel use. The received signal at user- u in cluster C_k is

$$\begin{aligned}
 y_u &= \mathbf{h}_u^H \mathbf{w}_{b_k} s_k + \xi_u, \\
 &= \underbrace{\mathbf{h}_u^H \mathbf{w}_{b_k} \sqrt{p_u} s_{k,u}}_{\text{Desired signal}} + \underbrace{\mathbf{h}_u^H \mathbf{w}_{b_k} \sum_{u \neq v, v=1}^{n_k} \sqrt{p_v} s_{k,v}}_{\text{Inter-user interference}} + \underbrace{\xi_u}_{\text{Noise}}. \tag{7}
 \end{aligned}$$

In the SIC procedure, let $\pi_k(j)$ denote the user index for the j -th decoded user in the cluster C_k serving N_{C_k} users, $j \leq N_{C_k}$. This j -th user then needs to decode and subtract all the messages for all users $\{\pi_k(1), \dots, \pi_k(j)\}$. The signal-to-interference-plus-noise ratio (SINR) when decoding user

$\pi_k(j)$ at user $\pi_k(j')$, $j' > j$ can be represented as

$$\Gamma_{\pi_k(j')}^{\pi_k(j)} = \frac{p_j |\mathbf{h}_{(j')}^H \mathbf{w}_{b_k}|^2}{|\mathbf{h}_{(j')}^H \mathbf{w}_{b_k}|^2 \sum_{v>j}^{N_{C_k}} p_v + \sigma^2}, \tag{8}$$

where σ^2 represents the noise power. Let R_k denote the rate achieved in NOMA cluster C_k . The effective sum rate of the system, R_{sum} can then be expressed as the sum of the rates, R_k , achieved in each of the K clusters over which all N users are served divided by the number of clusters, since each cluster is served by one channel. The effective sum rate can thus be represented as

$$\begin{aligned}
 R_{\text{sum}} &= \frac{\sum_{k=1}^K R_k}{K} \\
 &= \frac{\sum_{k=1}^K \sum_{u \in C_k} \log_2(1 + \Gamma_{\pi_k(u)}^{\pi_k(u)})}{K}, \tag{9}
 \end{aligned}$$

expressed in bits per second (bps) per channel-use and the term $\Gamma_{\pi_k(u)}^{\pi_k(u)}$ refers to the SINR when decoding the u -th user's own signal in the SIC decoding procedure. For OMA, where each user has to be served in an individual channel, K channels are required to serve the N users, i.e., $K = N$. Each user will be served in its best beam from B_u with a precoding vector \mathbf{w}_u . This gives us an effective sum rate of

$$R_{\text{OMA}} = \frac{\sum_{u=1}^N \log_2(1 + \frac{P|\mathbf{h}_u^H \mathbf{w}_u|^2}{\sigma^2})}{N}, \tag{10}$$

where P is the power available per channel. For NOMA, since one cluster is formed per channel, P represents the power available per cluster as we describe later in this section.

To model the user decoding capability constraints, we consider that each user- u is associated with a decoding capability constraint d , represented as d_u . To illustrate the decoding capability constraint, the right side of Fig.1 shows the distribution of N users to be served by the BS. Using the cosine similarity metric, each user will find the b beams it is best aligned with, forming the user-beam set, B_u , for the user. As Fig.1 then highlights, each user has its SIC decoding capability associated with it. For example, user-1 with SIC capability of 0 ($d_1 = 0$) indicates it needs to be either served as an OMA user in an orthogonal channel of its own or in a NOMA cluster as the weakest user where it is not required to decode any other users' signals. User-4 with SIC decoding capability of 4 ($d_4 = 4$) indicates it is capable of decoding four other users' signals. This means that if user-4 is scheduled in cluster- k at position j , then the maximum value of j is 5 for this user since that would involve decoding 4 other users' signals, i.e., $\max(j) = 5$.

Let $d_{\text{max}} = \max(d_u), \forall u = [1, \dots, N]$, represent the maximum decoding capability among the N users in the system. If all users have the same decoding capability, i.e., $d_u = d_{\text{max}}, \forall u = [1, \dots, N]$, we refer to this as homogeneous user decoding capabilities, or just a homogeneous system for short. In a homogeneous system, since any user- u has the same decoding capability $d_u = d_{\text{max}}$, this is equivalent

to designing a user clustering scheme such that there are a maximum of d_{\max} users per cluster. On the other hand, in a heterogeneous system, user clustering must be done in tandem with user ordering, such that each user in the cluster needs to decode at most d other user's signals, where each user has its own value of d , $1 \leq d \leq d_{\max}$. This means that for every user- u with decoding capability d_u at SIC decoding position j in cluster C_k , i.e., $\pi_k(j)$, it must satisfy that $d \geq j - 1$. Using our nomenclature, $d_{\pi_k(j)}$ denotes the decoding capability of the j -th user in the k -th cluster.

In this article, the objective is to utilize NOMA to maximize the effective sum-rate of the system, such that each user's QoS is met and all user decoding capability constraints are satisfied. Let Γ_{\min} denote the minimum SINR with which each user needs to be served, i.e., $\Gamma_{\pi_k(u)}^{\pi_k(u)} \geq \Gamma_{\min}$, $\forall u = [1, \dots, N]$. The overall objective function to maximize R_{sum} can be stated as

$$\max_{\{C_k\}, \{w_{b_k}\}, \{\pi_k\}, \{p_u\}} R_{\text{sum}}, \quad (11a)$$

$$\text{s.t. } R_u \geq \log_2(1 + \Gamma_{\min}), \quad \forall u = 1, \dots, N \quad (11b)$$

$$d_{\pi_k(j)} \geq j - 1, \quad j = \{1, \dots, N_{C_k}\}, \quad \forall k = 1, \dots, K, \quad (11c)$$

$$\sum_{i=1}^{N_{C_k}} p_i \leq P, \quad \forall k = 1, \dots, K, \quad (11d)$$

where (11b) represents the QoS constraint, (11c) represents the decoding capability constraint, and (11d) represents the power per channel constraint.

In order to solve the optimization problem in (11a), we break down the problem into two steps. First, we jointly tackle the user clustering, user ordering, and beamforming aspects, where we aim to minimize the number of clusters required to serve all the users while satisfying the beamforming and user decoding constraints. Second, once we have clusters of users, we do a power allocation step for the users in each cluster. We describe each of these steps next.

In the first step, the goal is two-fold: a) to build clusters of SIC ordered users that satisfy the SIC decoding constraints and b) to identify which beam each of these clusters will be served by, such that the selected beam is in the user-beam set of each of the users selected to be in the cluster. The objective in this step is to serve all the users in the minimum number of clusters, while respecting the aforementioned constraints. Since each cluster is served on one orthogonal channel, the N users being served on K clusters, is equivalent to requiring K orthogonal channel uses to serve the N users. Hence, reducing K improves the channel re-use, and in doing so, in general, contributes to an increased spectral efficiency. This is illustrated in equation (9), where R_{sum} is inversely proportional to the number of clusters, K . However, R_{sum} also depends on the SINR for each user in (9). This SINR for each user is affected by the other users they are clustered with, the order in which the users are decoded and finally the beamforming gain from the choice of beam from B_c to serve each cluster with. Along

with this, each users SIC decoding capability constraints need to be respected. Hence, we tackle these aspects jointly as a cluster minimization problem subject to several constraints as discussed in what follows next.

For a single-cell NOMA deployment with no inter-cluster interference to consider since each cluster is served in an orthogonal channel, it is known that NOMA performance is significantly improved by decoding users in the order of their channel gains [11], [28]. Hence, given that we have the full CSI of each user along with the precoding vectors, for every cluster C_k , we only allow the users to be decoded in the order of their effective channel gains. This means that the SIC decoding position- j of user- u with decoding capability d_u in cluster- k , $\pi_k(j)$, is determined by the effective channel gain of the user- u in relation to other users also selected to be in cluster C_k . Since we have the constraint that $d_{\pi_k(j)} \geq j - 1$, we need to design clusters such that the users when ordered according to their effective channel gains, satisfy their SIC decoding constraints. Formally, the user clustering, user ordering, and BF optimization problem can be written as follows. Let $C = \{C_1, \dots, C_K\}$ represent the K clusters required to serve the N users. At most, each user is served in its own cluster or channel (equivalent to OMA), hence $K \leq N$. Each cluster C_k in C represents a set of users ordered according to their effective channel gains when served by beam- b_k from B_c with precoding vector w_{b_k} . Let $u_{i,k}$ be a binary variable that represents whether user- i belongs to cluster- C_k , served by beam- b_k . Let $d_{\pi_k(j)}$ represents the user decoding capability of the j^{th} decoded user in cluster- C_k . The objective of our user clustering, ordering, and BF scheme is to minimize K , as follows:

$$\min_{\{u_{i,k}\}, \{b_k\}, \{\pi_k\}} K, \quad (12a)$$

$$\text{s.t. } \sum_{k=1}^K u_{i,k} = 1, \quad \forall i = 1, \dots, N, \quad (12b)$$

$$b_k \in B_u, \quad u_{i,k} = 1, \quad \forall k = 1, \dots, K, \quad (12c)$$

$$d_{\pi_k(j)} \geq j - 1, \quad j = \{1, \dots, N_{C_k}\}, \quad \forall k = 1, \dots, K, \quad (12d)$$

$$u_{i,k} \in \{0, 1\}, \quad (12e)$$

$$b_k \in B_c, \quad \forall k = 1, \dots, K, \quad (12f)$$

where constraint (12b) ensures each user is placed in exactly one cluster. Constraint (12c) is to ensure that the beam- b_k chosen for cluster- C_k in C belongs to the user-beam list of each of the users selected to be served in that NOMA cluster. Constraint (12d) ensures the decoding capability constraints of each user in the system is adhered to. For the homogeneous system, since all users have the same decoding capability, we only need to limit the number of users per cluster. In other words, for a homogeneous system, within a cluster- k of size N_{C_k} , if $N_{C_k} \leq d_{\max}$, then any decoding order within that cluster is feasible since all users have the same decoding capability of $d_u = d_{\max}$. Hence, for a homogeneous system,

constraint (12d) can be simplified down to:

$$\sum_{i=1}^N u_{i,k} \leq d_{\max}, \quad \forall k = 1, \dots, K. \quad (13)$$

The second step is power allocation (PA), which is not the focus of this article but briefly described here for completeness. Since only one cluster is served on one channel in our model, the channel power budget, P , is equivalent to the cluster power budget. Hence, the goal is to divide the power P , among the N_{C_k} users in each cluster $C_k \in C$. The objective in this step is to maximize the rate R_k in each cluster. Since the users in the cluster are already ordered based on their effective channel gains, we iterate through the first $j = \{1, \dots, N_{C_k} - 1\}$ users in the cluster at position $\pi_k(j)$ and assign it as much power as it needs to satisfy Γ_{\min} and ensure successful SIC decoding, based on (8). The strongest user is assigned the remaining power. We assume P is always sufficient to meet each user's QoS, including the remaining power left over for the strongest user. This is similar to the QoS-based PA schemes described in [29].

III. PROPOSED ALGORITHM(S)

In this section, we outline our two proposed algorithms, namely, the NOMA-MEC algorithm for heterogeneous systems in Algorithm 1 and the NOMA-BB algorithm for homogeneous systems in Algorithm 2.

We begin with the NOMA-MEC algorithm to solve the cluster minimization problem in (12a) for heterogeneous systems in Algorithm 1. The goal is to minimize the number of clusters used while respecting the beamforming and user decoding capability constraints of each user in each cluster, as captured in (12c) and (12d), respectively. To do this, we break down the NOMA-MEC into two steps. In step-1, we find all possible valid cluster combinations, C_v , that respect both the constraints, (12c) and (12d). We refer to C_v , which is a set of valid user combinations, as the candidate list of clusters. Then, in step-2, from C_v , we find the minimum number of clusters that cover all the users exactly once. This is a MEC problem [26], hence we term the algorithm NOMA-MEC.

Step-1 of NOMA-MEC begins by building a list of users that can potentially be served on a NOMA cluster by each of the $B + 1$ candidate beams in B_c . This is obtained by iterating through the user-beam set, B_u , of all users, $u = \{1, \dots, N\}$. Through this step, we get a list of users that can potentially cluster with each other. Let n_b represent the number of users that have beam- b in their user-beam set. Clusters can be of size $l = \{2, \dots, d_{\max}\}$. We treat clusters of one separately as described later in this section. Hence, we form all $\binom{n_b}{l}$ groups of users, for all $B + 1$ beams. These are all potential clusters to be served in an orthogonal channel with a beam using precoding vector, w_b . Along with w_b , each user's channel vectors are known. Thus, we can order the users according to their effective channel gains from smallest to largest in each of these potential clusters. Since we only allow users to be

Algorithm 1: NOMA-MEC

Input: Beam-list B_u of b beams for user u with channel h_u and decoding capability d_u , $\forall u = [1, \dots, N]$. Also, precoding vectors of candidate beams, w_b , $\forall b = [1, \dots, B]$.

Output: K clusters of ordered users such that each user- u , is served in cluster- k (with beam b_k) at position- j , such that $d_{\pi_k(j)} \geq j - 1$ and $b_k \in B_u$, $k = [1, \dots, K]$, $\forall u = [1, \dots, N]$

- 1 **Step-1:** Build candidate list C_v ;
- 2 **for** (beam- $b : B_c$) **do**
- 3 Find all n_b users that have beam- b in B_u ;
- 4 Form set C_l by computing all possible $\binom{n_b}{l}$ combinations, $\forall l = [2, \dots, d_{\max}]$;
- 5 **for** ($c : C_l$) **do**
- 6 Order the users in c according to the effective channel gains, creating set of ordered users in c as $\{u_1, \dots, u_n\}$, such that $|w_b^H h_1|^2 \leq \dots \leq |w_b^H h_n|^2$
- 7 **for** u_1 to u_n **do**
- 8 **if** $d_{\pi_c(j)} < j - 1$ **then**
- 9 combination c is invalid, skip it.
- 10 **break;** (outer for loop)
- 11 **end**
- 12 **end**
- 13 Add c to candidate list C_v . (If we did not break, combination c satisfies $d \geq j - 1$ for all users in c).
- 14 **end**
- 15 **end**
- 16 Add each users- u , as a cluster of one with their best beam from B_u to candidate list C , $\forall u = [1, \dots, N]$;
- 17 **Step-2:** Run greedy MEC on C_v to obtain C ;
- 18 $C_{\text{sorted}} = \text{sort } C_v$ in descending order;
- 19 $x_c = 0 \forall c \in C_v$;
- 20 $C = \{\}$, $K = 0$;
- 21 **for** $c_s : C_{\text{sorted}}$ **do**
- 22 **if** $z_{u,c} x_c \neq 0, \forall c \in C$ **then**
- 23 $C = \{C, c_s\}$;
- 24 $K = K + 1$;
- 25 **end**
- 26 **end**
- 27 return K, C ;

decoded in this order, if any cluster has a user at position $\pi(j)$, such that $d_{\pi(j)} < j - 1$, that cluster is invalid. Only those clusters that satisfy the decoding capability constraint (12d) for all the users in the cluster are added to the candidate list, C_v . Finally, all users can be in a cluster of their own and be served like they would be with OMA. Hence, we add N elements to C , each being a cluster of one where user- u is served on its best beam from B_u , $u = \{1, \dots, N\}$.

In step-2 of NOMA-MEC, from the list of viable candidate cluster options in C_v , we want to select the minimum number

Algorithm 2: NOMA-BB

Input: Best beam B_u^* for user u with channel h_u
 $\forall u = [1, \dots, N]$, common decoding capability
 d_{\max} for all users, precoding vectors w_b ,
 $\forall b = [1, \dots, B]$.

Output: K clusters of ordered users such that each user- u , is placed in a cluster served by its best beam, B_u^* and $N_{C_k} \leq d_{\max}, \forall k = [1, \dots, K]$.

- 1 $C = \{\}, K = 0;$
- 2 $m = d_{\max};$
- 3 **for** (beam- $b : B_c$) **do**
- 4 Find all n_b users that have $B_u^* = b$ and group them in
 set $c : \{u_1, \dots, u_{n_b}\};$
- 5 **if** $n_b > m$ **then**
- 6 **for** $i = 1 : \lceil \frac{n_b}{m} \rceil$ **do**
- 7 $j = \min(m \times (i + 1), n_b);$
- 8 $C = \{C, \{u_{m \times i}, \dots, u_j\}\};$
- 9 $K = K + 1;$
- 10 **end**
- 11 **end**
- 12 **else**
- 13 $C = \{C, c\};$
- 14 $K = K + 1;$
- 15 **end**
- 16 **end**
- 17 **return** $K, C;$

of elements that would cover every user exactly once. Since we added clusters of one for each user in the last part of step-1, we are guaranteed the existence of a solution. Let x_c be a binary variable that represents if element- c from set C_v is selected and $z_{u,c}$ be a binary variable that represents if user- u belongs to element- c in C_v . The optimization problem can be stated as follows:

$$\min_{x_c} \sum_{c: C_v} x_c, \quad (14a)$$

$$\text{s.t.} \sum_{u=1}^N z_{u,c} x_c = 1, \quad \forall c : C_v \quad (14b)$$

$$x_c, z_{u,c} \in [0, 1], \quad (14c)$$

where (14a) represents the objective of the problem that minimizes the number of clusters and constraint (14b) ensures that all users occur exactly once in the final cluster set. This is a minimum exact cover problem, a known NP-complete problem [26]. We solve this problem using a greedy algorithm as follows. The first step is to sort the clusters in C_v in descending order of the number of users they contain, since using clusters in C_v that cover the most number of users allows us to minimize the number of clusters we need to cover all the users. We then go through the list of cluster combinations, adding cluster- c to C only if all users in the cluster have not been covered by clusters already in C . The

algorithm stops when all users have been covered exactly once, as highlighted in Algorithm 1.

The complexity of the algorithm is influenced by the following parameters - 1) the number of beams each user picks in its beam set, b , which is an algorithm specific parameter, 2) the number of candidate beams, B , which is a system level design parameter that we can control and 3) the number of users, N , that need to be served along with their respective decoding capabilities, $d_u, u \in [1, N]$. In step-1 of NOMA-MEC, building C_v involves the construction of I_1 clusters as follows:

$$I_1 = \binom{n_b}{l} \times (B + 1), \quad (15)$$

where $l = \{2, \dots, d_{\max}\}$. In each of these I_1 clusters, the users have to be ordered and then analyzed to check whether each users decoding capability criteria are satisfied. The parameter n_b , the number of users that have beam- b in their user-beam set, scales with N and b . The second step is the minimum exact cover problem. Let I_2 represent the number of valid combinations in C_v that the greedy algorithm in MEC needs to explore to find C . In a homogeneous system, all the Z clusters are valid clusters, which means $I_2 = I_1$. Thus, a homogeneous system represents the worst-case complexity for the MEC part of the NOMA-MEC algorithm. However, in general, a large number of the original cluster combinations will be rejected due to them being unable to meet the user decoding capabilities, resulting in $I_2 \ll I_1$. This in turn controls the complexity of the MEC part of the algorithm. This is discussed further in Section IV, supported by simulation figures.

The choice of b is the most important design parameter for the NOMA-MEC algorithm. From a performance perspective, a larger b gives the algorithm the ability to find a larger number of cluster combinations that satisfy the decoding capability constraint. So, strictly from the perspective of minimizing K in (12a), a large b is good. However, as b increases, we add beams that are less and less aligned with the user direction to the user-beam set B_u , reducing the beamforming gain with each increment of b . Due to the overlapping nature of the beams as seen in Fig. 1, there is a value of b such that the user is within the coverage area of all of its best b beams in B_u . Let this value of b be b_{th} . However, as b is further increased beyond b_{th} , the user gets out of the coverage area of the beam- $(b_{\text{th}} + 1)$ and if NOMA-MEC schedules the user on beam- $(b_{\text{th}} + 1)$, it will have poor spectral efficiency, R_u , bringing down the overall spectral efficiency, R_{sum} , in the process. The exact value of b_{th} depends on system-level parameters M and B . The number of antennas, M , determines the width of the beam and together with the number of candidate beams, $B + 1$, determines the level of overlap between the beams and hence also determines the value of b_{th} . Additionally, b is also an important parameter to control the complexity of NOMA-MEC. If the number of users is large or d is large for most users, b can be reduced to lower I_1 . For a homogeneous system with a large d_{\max} , the number of combinations can be

TABLE 2. Simulation Parameters.

Parameter name, notation	Value
Number of paths, L	1 [3], [5], [17]
Path loss exponent, η	2 [5]
$\frac{\text{BS antenna spacing}}{\text{Wavelength of the carrier signal}}, \frac{D}{\lambda}$	$\frac{1}{2}$ [5]
Noise power, σ^2	7.962×10^{-11} [5]
Users minimum QoS SINR, Γ_{\min}	0.02 [5]
Number of antennas at BS, M	[2, 4, 8, 16, 32]
Number of candidate beams, B	[10, 20, 30, 40]
Number of users in the system, N	[50, 100, 150, 200]
Max. user decoding capability, d_{\max}	[0, 10]
User distribution	Randomly distributed around 5 meters radius from BS. [3]

very large and so we need to scale back b . If $b = 1$, it is equivalent to having each user pick its best beam. Hence, for the homogeneous system with large d_{\max} , we propose a low-complexity clustering algorithm called NOMA-best beam (NOMA-BB) that has each user served by its best beam in B_u , as we outline next.

In the NOMA-BB algorithm, like NOMA-MEC, we iterate through each beam and build the list of n_b users that picked each beam- b . However, compared to NOMA-MEC, the difference is that in this case, users have to belong to that beam since we follow the best beam strategy where each user picked only one beam in their user-beam set. Hence, these groups of users are effectively our clusters except that we might have beams that have more than d_{\max} users in it, leading to some users needing to decode more than d_{\max} users signals, which violates the SIC decoding capability constraint. Hence, for all beams where $n_b > d_{\max}$, we break up the one cluster of n_b users into $\lceil \frac{n_b}{m} \rceil$ clusters, where m is an integer between 1 and d_{\max} , i.e., $m \in [1, d_{\max}]$, that controls the maximum number of users per cluster and $\lceil \cdot \rceil$ is the ceiling function. Since the goal is to minimize the number of clusters, we set $m = d_{\max}$. Setting $m = d_{\max}$ is feasible because all users have the same decoding capability, $d = d_{\max}$, and so any user ordering among the N_{C_k} users in some cluster- C_k formed by NOMA-BB would be valid, as long as $N_{C_k} \leq d_{\max}$. In this article, when we need to split n_b users in a beam into multiple clusters, i.e., when $n_b > d_{\max}$, we arbitrarily split the users into different clusters. As a future work, a more advanced NOMA-BB clustering schemes could aim to maximize the channel disparity between the users in the cluster when doing this split, a condition known to improve the rate in NOMA systems [30].

IV. SIMULATION RESULTS AND DISCUSSION

The performance of the proposed NOMA-MEC and NOMA-BB algorithms are evaluated using MATLAB simulations, with the system parameters described in Table 2. The mmWave channel model in (1) is considered, where $L = 1$,





FIGURE 2. Performance of NOMA-BB for a homogeneous system where each users SIC decoding capability constraint $d = d_{\max}$, effectively making d_{\max} the maximum number of users that can be placed in a cluster. (a) Overall spectral efficiency compared to OMA (b) Number of clusters, K , required to serve the N users.

$\eta = 2$ and $D/\lambda = 1/2$ for the ULA steering vector. The BS is equipped with $M = 8$ antennas, unless specified otherwise. The noise power is $\sigma^2 = -174 + 10\log_{10}(W) + N_f$ dBm, where $W = 2$ GHz is the system bandwidth and the noise floor $N_f = 10$ dB. The users are randomly distributed around the BS within a 5 meter radius, i.e., $r_u \leq 5$. We consider the minimum user QoS to be an average of $N \times \Gamma_{\min}$ bps per channel-use. Since the users are scheduled in $K \leq N$ channels (K NOMA clusters), we can simplify this requirement by just considering a minimum user rate of Γ_{\min} for each user in every cluster. In the simulations, $\Gamma_{\min} = 0.02$. Finally, the number of candidate beams is $B = 20$. In the simulations for heterogeneous systems, we set $d_{\max} = 5$ and generate each user's decoding capability, d , as a random integer in the range $[0, d_{\max}]$. For the homogeneous systems, we vary d_{\max} from 1 to 10.

We start by evaluating the NOMA-BB algorithm for a homogeneous system, where each users decoding capability is $d = d_{\max}$ that we vary from 1 to 10 in this simulation.

In Fig. 2a, we compare the spectral efficiency, measured in bps per channel use, for the NOMA-BB algorithm against OMA for a system with 50, 100, 150, and 200 users. OMA is not influenced by the value of d_{\max} as it has to serve one user per cluster, irrespective. As seen in Fig. 2a, a NOMA setting with $d_{\max} = 1$ is equivalent to OMA. As d_{\max} increases beyond one, we start to see the gain of NOMA. A higher value of d_{\max} means all users are capable of decoding more number of other users signals, i.e., we can serve more users per-cluster. Looking at the NOMA-BB algorithm, for each beam- b , we split the n_b users who picked beam- b into $\lceil \frac{n_b}{m} \rceil$ clusters, where $m = d_{\max}$. Clearly, as d_{\max} increases, m increases, and so NOMA-BB needs to form fewer clusters in this splitting step. This is illustrated in Fig. 2b, where the number of clusters, K required to serve the N users decreases as d_{\max} increases. Further, as the number of users in the system, N , increases, the likelihood of having beams with more than d_{\max} users increases in the first step of the NOMA-BB algorithm. As a result, for higher N , we see the number of clusters decrease in Fig. 2b by increasing d_{\max} for longer before it starts to flatten out. Correspondingly, the rate in Fig. 2a increases with d_{\max} for longer when N is larger.

We now move to heterogeneous systems and evaluate the performance of our proposed NOMA-MEC algorithm, compared against OMA and NOMA-BB with slight modifications to account for the heterogeneous decoding capability constraints. We note that there are no direct user clustering schemes in the literature that considers individual user decoding capabilities for us to compare against. NOMA-BB is fairly typical of most NOMA clustering schemes in the literature that do not have individual restrictions on each user’s SIC decoding position, and so offers good insights for us to compare our proposed NOMA-MEC against. However, to run NOMA-BB in a heterogeneous system, we cannot set $m = d_{\max}$ like we could for a homogeneous system, since each user has its own decoding capability constraint and so not all clusters will result in feasible decoding order combinations, even if the cluster size is capped at d_{\max} . To make NOMA-BB work for a heterogeneous system, we need to separate out all users with $d < m$, for any $m \in [1, d_{\max})$, and then divide the remaining users into $\lceil \frac{n}{m} \rceil$ clusters. This would ensure that the arbitrary user ordering done by the NOMA-BB scheme does not violate any user’s SIC decoding capability constraint. A larger m means we can form larger clusters but will have to exclude more users with the extreme case of $m = d_{\max}$ equivalent to OMA and so we exclude it, while a smaller m means we will form smaller clusters, but exclude less users. We term this modified version of NOMA-BB for heterogeneous systems as NOMA-BB-Het and run it with all possible values of $m \in [1, d_{\max})$, $d_{\max} = 5$, for the simulations in Fig. 3 which we discuss next.

Analyzing the performance of NOMA-MEC from Fig. 3, we see that despite the restrictions put in place by the heterogeneous user decoding capabilities, we still see a significant performance gain over OMA. It also outperformed NOMA-BB-Het for all values of m , because NOMA-BB-Het and




FIGURE 3. Performance of NOMA-MEC for a heterogeneous system where each user has its own decoding capability constraints. NOMA-MEC is compared against OMA and NOMA-BB-Het, a modified version of NOMA-BB to account for the heterogeneous user decoding capabilities.




FIGURE 4. NOMA-MEC run in a heterogeneous system with users having their SIC decoding capability, d , randomly distributed in $[0, d_{\max}]$, is compared against NOMA-BB and NOMA-MEC run for a homogeneous system where all users have $d = d_{\max}$ ($d_{\max} = 5$).

other such clustering algorithms from the literature do not consider restrictions on each individual user’s capabilities while clustering. In Fig. 4, the NOMA-MEC heterogeneous scheme running in a heterogeneous system with all users having a random value of d in the range $[0, d_{\max}]$, is compared against a hypothetical homogeneous system where all users have $d = d_{\max}$. For the hypothetical homogeneous system, the original NOMA-BB and NOMA-MEC that assumes homogeneous user decoding capability with $m = d_{\max}$ is run. We note that the NOMA-MEC algorithm can easily be run for a homogeneous system, with all users having $d = d_{\max}$. We see that the NOMA-MEC algorithm for the heterogeneous deployment closely shadows, but always trails, the NOMA-MEC run for the homogeneous deployment. The flexibility of the proposed NOMA-MEC algorithm is highlighted by this observation since it says that even though each user is posing its own decoding restrictions of $d \leq d_{\max}$,






FIGURE 5. Analyzing NOMA-MEC in terms of the number of clusters, K , outputted by the algorithm, as the number of heterogeneous users in the system increases for different values of b .

we are still able to achieve close to the performance we could if there was a simple maximum users per cluster constraint of $d = d_{max}$. The hypothetical homogeneous deployment is still better because in the NOMA-MEC for the homogeneous deployment, all I_1 cluster combinations examined is step-1 of NOMA-MEC are valid and entered into C_v for the MEC algorithm to choose from. However, the NOMA-MEC for heterogeneous systems strips a large chunk of these I_1 combinations away due to not satisfying the user decoding capability constraints and so gives fewer pairing options in C_v for the greedy MEC algorithm to work with when trying to minimize K . Looking at just the homogeneous curves in Fig. 4, NOMA-MEC (Hom.) with $b \in [2, 4]$ outperforms NOMA-BB. This is expected as the NOMA-MEC algorithm is more advanced, allowing users to pick multiple candidate beams for clustering, giving more clustering opportunities..

Additionally, analyzing the trends of NOMA-MEC in both Fig. 3 and Fig. 4, we see the rate increase at first as b increases, but then starts to drop-off as we increase b further. This is a consequence of the trade-off between a larger search space to reduce K and the beamforming gain from allowing users to be served on their stronger beams, as discussed in Section III. A larger choice of b implies a larger candidate cluster list C_v , in the NOMA-MEC algorithm, allowing the MEC part of the algorithm to find solutions with a lower number of clusters, K . This is illustrated in Fig. 5, where for any number of users in the system, the number of clusters required to serve the N users, i.e., K , decreases as b increases. However, as b increases beyond the b_{th} , users are adding beams to their user-beam-set, B_u , that they are less aligned with in terms of the cosine similarity metric. In other words, \forall beam- b in $B_u, b > b_{th}$, NOMA-MEC can potentially schedule the user in a cluster served by beam- b , even though the user is out of the coverage area of beam- b . As seen in Fig. 3 and Fig. 4, at first as b goes from one to two, the extra clustering opportunities allow us to reduce K as well as not incur too much of a penalty in terms of the beamforming gain.



(a)



(b)

FIGURE 6. Analyzing the impact of b on the performance of NOMA-MEC as system parameters B and M vary.

However, as b increases further, the penalty from sacrificing the beamforming gain outweighs the further cluster reduction we are able to achieve and hence we see the spectral efficiency start to drop off after that. The exact value of b at which this reversal occurs depends on the number of candidate beams, B and the width of these candidate beams, which is a consequence of the number of transmit antennas, M . Next, we discuss the impact of B and M on the choice of b from a performance perspective.

The simulations in Fig. 6 were conducted to understand the impact of parameters B and M respectively on the performance of NOMA-MEC. In particular, we are focused on the trend where we first see a performance improvement as b increases, but then a decline as b is further increased. In Fig. 6a, we vary M while keeping B fixed, $B = 20$. As the number of transmit antennas at the BS, M , increases, the BS is able to form more narrow beams. For a fixed value of B , as M increases, the amount of overlap between the candidate beams decreases. This means that a user is located in the coverage area of a smaller number of beams, i.e., b needs to be smaller to realize the beamforming gain. Conversely,

as M decreases for a fixed B , the overlap between the beams increases, as we have the same number of wider beams. This allows for a user to be located in the coverage area of more number of beams, i.e., a larger b can be chosen. The same analysis can be done for a fixed M and varying B in Fig. 6b. In this case, the beam width is fixed since M is fixed. However, as B increases, the overlap increases as we have more candidate beams covering the same coverage area, $\bar{\phi}$. As a result, we see the performance gain from increasing b for longer in Fig. 6b for larger values of B . We see that with every increase of $B = 10$, the drop-off starts to occur $b = 1$ later. Hence, irrespective of the values of B and M , the trend is the same - we first see a gain from increasing b , but then the performance starts to drop off once we start to lose the beamforming gain as b is further increased. For a small value of M and a large value of B , the value of b before the drop-off starts to occur is larger than if we had a small B or large M . Hence, from a performance perspective, b needs to be selectively tuned as a function of B and M . We discuss the impact of parameter b on the complexity of the algorithm next.

As described in Section III, the NOMA-MEC algorithm presented in Algorithm 1 consists of two steps. The first is the formation of candidate list C_v by iterating through each beam in the list of candidate beams, looking for all valid combinations of users who could be scheduled together in a cluster served by the beam. Each possible combination requires users to be ordered by their effective channel gain and then the decoding capability of each user has to be checked to see if the combination is valid or not. The second part of the algorithm involves taking the candidate list, C_v , and running the greedy algorithm to solve the minimum exact cover problem. Simulation runs to present the number of iterations required at both steps of the NOMA-MEC algorithm, I_1 and I_2 respectively, are presented in Fig. 7a and Fig. 7b respectively.

The number of iterations in step-1 of NOMA-MEC, I_1 , is determined by n_b , l and B as equation (15) shows. The term n_b , which corresponds to the number of users that contain each beam- b in their user-beam-set, is influenced by the number of users in the system N and the number of beams per user set, b . Since NOMA-MEC iterates through $\binom{n_b}{l}$, $l = \{2, \dots, d_{\max}\}$, combinations to check for valid cluster combinations based on the user decoding capability, the impact of l on I_1 is entirely determined by d_{\max} . The complexity of step-2 depends entirely on the size of set C_v , i.e., the number of valid combinations found after step-1, i.e., I_2 . If I_1 is large, I_2 is likely to be large too and so the same factors that influence I_1 in step-1 also affect the complexity of step-2. However, since a large number of combinations examined in step-1 are deemed invalid and not added to C_v in step-1 due to the SIC decoding capability restrictions, the size of C_v will still be small. This is illustrated in Fig. 7b, where we see a significant reduction in the candidate cluster list size, C_v compared to the number of cluster combinations examined in Fig. 7a. As discussed in Section III, if NOMA-MEC were run on a homogeneous system, $I_2 = I_1$, leading




FIGURE 7. Impact of the number of beams per user set, b , on the complexity of NOMA-MEC in terms of (a) I_1 which represents the number of cluster combinations examined in step-1 of NOMA-MEC and (b) I_2 , which represents the number of valid combinations in C_v to be considered by the greedy algorithm to solve the MEC problem.

quickly to a prohibitively high complexity for the greedy algorithm to solve the MEC problem. On the other end of the spectrum, if a large number of combinations examined in step-1 are deemed invalid due to the SIC decoding capability constraints, the size of C_v will still be small. This is likely in deployments where the majority of users are IoT users with $d \in [0, 1]$ and there are only a handful of users with a larger value of d , e.g., cellular users. In such a case, the complexity of step-1 will be high since $d_{\max} = \max(d)$ is still large. However, if most users have $d \in [0, 1]$, then most examined combinations in step-1 will be deemed invalid, still leaving a manageable size of C_v for the greedy algorithm in step-2 to work with. However, in the simulations in Fig. 7, we only considered the case where the users' decoding capabilities, d , are randomly generated from $[0, d_{\max}]$. In future works, we will consider more skewed distributions of d and explore how the complexity of step-1 of the NOMA-MEC algorithm can be reduced by exploiting advanced knowledge of the distribution of the users' decoding capabilities.

Finally, it is worth mentioning that the parameter b in the NOMA-MEC algorithm can be set by considering the performance-complexity tradeoff as follows. We have seen that increasing b improves performance up to $b = b_{th}$, but then the performance declines as b is increased any further. Depending on system parameters B and M , we can find the value of b_{th} at which the performance gains from increasing b peaks. After that, the complexity aspect can be considered. If the complexity is acceptable at b_{th} , that would be a logical choice for b . However, for systems with a large N or d_{max} , setting $b = b_{th}$ could result in a prohibitively high algorithm complexity as seen in Fig. 7. In such settings, b can be reduced to bring down the complexity as seen from Fig. 7, at the expense of performance.

V. CONCLUSION

In this article, we proposed a joint user clustering and user ordering scheme, namely, NOMA-MEC, for an ABF mmWave-NOMA system that can serve a set of users that each have their own SIC decoding capability constraints. By using the reported SIC decoding capability constraint from each user to set the maximum position in the SIC decoding order for clusters that are always decoded in the order of their effective channel gains, we framed the problem as a minimum exact cover optimization problem. Despite each user posing individual conditions on how many other users' signals it can decode in the SIC decoding order, simulation results demonstrated that the proposed algorithm still offers significant spectral efficiency gains over OMA as well as over other NOMA clustering algorithms that do not have the flexibility to accommodate for such user decoding requirements. We provided a detailed analysis of the performance-complexity trade-off from the setting of parameters related to the NOMA-MEC algorithm as well as system-level parameters. Finally, for a homogeneous system where all users have the same decoding capability requirements, we showed that this boils down to a simpler condition of restricting the number of users per cluster. We proposed a simpler NOMA-BB algorithm for the homogeneous system and also evaluated its performance through simulations.

REFERENCES

- [1] A. Ghosh, A. Maeder, M. Baker, and D. Chandramouli, "5G evolution: A view on 5G cellular technology beyond 3GPP release 15," *IEEE Access*, vol. 7, pp. 127639–127651, 2019.
- [2] P. Cerwall. (Nov. 2019). *Ericsson Mobility Report*. [Online]. Available: <http://www.ericsson.com/en/mobility-report/reports>
- [3] J. Cui, Y. Liu, Z. Ding, P. Fan, and A. Nallanathan, "Optimal user scheduling and power allocation for millimeter wave NOMA systems," *IEEE Trans. Wireless Commun.*, vol. 17, no. 3, pp. 1502–1517, Mar. 2018.
- [4] L. Zhu, J. Zhang, Z. Xiao, X. Cao, D. O. Wu, and X.-G. Xia, "Millimeter-wave NOMA with user grouping, power allocation and hybrid beamforming," *IEEE Trans. Wireless Commun.*, vol. 18, no. 11, pp. 5065–5079, Nov. 2019.
- [5] J. Cui, Z. Ding, P. Fan, and N. Al-Dhahir, "Unsupervised machine learning-based user clustering in Millimeter-Wave-NOMA systems," *IEEE Trans. Wireless Commun.*, vol. 17, no. 11, pp. 7425–7440, Nov. 2018.
- [6] O. Maraqa, A. S. Rajasekaran, S. Al-Ahmadi, H. Yanikomeroglu, and S. M. Sait, "A survey of rate-optimal power domain NOMA with enabling technologies of future wireless networks," *IEEE Commun. Surveys Tuts.*, early access, Aug. 3, 2020, doi: 10.1109/COMST.2020.3013514.
- [7] D. Tse and P. Viswanath, *Fundamentals Wireless Communication*. Cambridge, U.K.: Cambridge Univ. Press, 2005.
- [8] H. Tabassum, M. S. Ali, E. Hossain, M. J. Hossain, and D. I. Kim, "Uplink Vs. Downlink NOMA in cellular networks: Challenges and research directions," in *Proc. IEEE 85th Veh. Technol. Conf. (VTC Spring)*, Jun. 2017, pp. 1–7.
- [9] S. M. R. Islam, N. Avazov, O. A. Dobre, and K.-S. Kwak, "Power-domain non-orthogonal multiple access (NOMA) in 5G systems: Potentials and challenges," *IEEE Commun. Surveys Tuts.*, vol. 19, no. 2, pp. 721–742, 2nd Quart., 2017.
- [10] W. Saad, M. Bennis, and M. Chen, "A vision of 6G wireless systems: Applications, trends, technologies, and open research problems," *IEEE Netw.*, vol. 34, no. 3, pp. 134–142, May 2020.
- [11] K. Shaukat Ali, M.-S. Alouini, E. Hossain, and M. Jahangir Hossain, "On clustering and channel disparity in non-orthogonal multiple access (NOMA)," 2019, *arXiv:1905.02337*. [Online]. Available: <http://arxiv.org/abs/1905.02337>
- [12] W. Hao, M. Zeng, Z. Chu, and S. Yang, "Energy-efficient power allocation in millimeter wave massive MIMO with non-orthogonal multiple access," *IEEE Wireless Commun. Lett.*, vol. 6, no. 6, pp. 782–785, Dec. 2017.
- [13] X. Chen, F.-K. Gong, G. Li, H. Zhang, and P. Song, "User pairing and pair scheduling in massive MIMO-NOMA systems," *IEEE Commun. Lett.*, vol. 22, no. 4, pp. 788–791, Apr. 2018.
- [14] K. S. Ali, M. Haenggi, H. ElSawy, A. Chaaban, and M.-S. Alouini, "Downlink non-orthogonal multiple access (NOMA) in Poisson networks," *IEEE Trans. Commun.*, vol. 67, no. 2, pp. 1613–1628, Feb. 2019.
- [15] Z. Ding, R. Schober, and H. V. Poor, "Unveiling the importance of SIC in NOMA systems: Part I - state of the art and recent findings," 2020, *arXiv:2005.10215*. [Online]. Available: <http://arxiv.org/abs/2005.10215>
- [16] Z. Xiao, L. Zhu, J. Choi, P. Xia, and X.-G. Xia, "Joint power allocation and beamforming for non-orthogonal multiple access (NOMA) in 5G millimeter wave communications," *IEEE Trans. Wireless Commun.*, vol. 17, no. 5, pp. 2961–2974, May 2018.
- [17] Z. Ding, P. Fan, and H. V. Poor, "Random beamforming in millimeter-wave NOMA networks," *IEEE Access*, vol. 5, pp. 7667–7681, 2017.
- [18] K. Wang, J. Cui, Z. Ding, and P. Fan, "Stackelberg game for user clustering and power allocation in millimeter wave-NOMA systems," *IEEE Trans. Wireless Commun.*, vol. 18, no. 5, pp. 2842–2857, May 2019.
- [19] W. Shao, S. Zhang, H. Li, N. Zhao, and O. A. Dobre, "Angle-domain NOMA over multicell millimeter wave massive MIMO networks," *IEEE Trans. Commun.*, vol. 68, no. 4, pp. 2277–2292, Apr. 2020.
- [20] D. Marasinghe, N. Jayaweera, N. Rajatheva, and M. Latva-Aho, "Hierarchical user clustering for mmWave-NOMA systems," in *Proc. 2nd 6G Wireless Summit*, Mar. 2020, pp. 1–5.
- [21] J. Ren, Z. Wang, M. Xu, F. Fang, and Z. Ding, "An EM-based user clustering method in non-orthogonal multiple access," *IEEE Trans. Commun.*, vol. 67, no. 12, pp. 8422–8434, Dec. 2019.
- [22] Z. Xiao, L. Zhu, Z. Gao, D. O. Wu, and X.-G. Xia, "User fairness non-orthogonal multiple access (NOMA) for millimeter-wave communications with analog beamforming," *IEEE Trans. Wireless Commun.*, vol. 18, no. 7, pp. 3411–3423, Jul. 2019.
- [23] A. N. Uwaechia and N. M. Mahyuddin, "Spectrum and energy efficiency optimization for hybrid precoding-based SWIPT-enabled mmwave mMIMO-NOMA systems," *IEEE Access*, vol. 8, pp. 139994–140007, 2020.
- [24] L. Dai, B. Wang, M. Peng, and S. Chen, "Hybrid precoding-based millimeter-wave massive MIMO-NOMA with simultaneous wireless information and power transfer," *IEEE J. Sel. Areas Commun.*, vol. 37, no. 1, pp. 131–141, Jan. 2019.
- [25] D. Fan, F. Gao, G. Wang, Z. Zhong, and A. Nallanathan, "Channel estimation and transmission strategy for hybrid mmWave NOMA systems," *IEEE J. Sel. Topics Signal Process.*, vol. 13, no. 3, pp. 584–596, Jun. 2019.
- [26] C. Lund and M. Yannakakis, "On the hardness of approximating minimization problems," *J. ACM*, vol. 41, no. 5, pp. 960–981, Sep. 1994.
- [27] B. Mondal, A. Sengupta, G. Ermolaev, V. Sergeev, A. Davydov, and E. Kwon, "Impact of analog beamforming on 5G-NR mmWave system performance," in *Proc. IEEE 88th Veh. Technol. Conf. (VTC-Fall)*, Aug. 2018, pp. 1–5.

- [28] M. Vaezi, R. Schober, Z. Ding, and H. V. Poor, "Non-orthogonal multiple access: Common myths and critical questions," *IEEE Wireless Commun.*, vol. 26, no. 5, pp. 174–180, Oct. 2019.
- [29] M. M. El-Sayed, A. S. Ibrahim, and M. M. Khairy, "Power allocation strategies for non-orthogonal multiple access," in *Proc. Int. Conf. Sel. Topics Mobile Wireless Networking (MoWNeT)*, Apr. 2016, pp. 1–6.
- [30] K. Higuchi and A. Benjebbour, "Non-orthogonal multiple access (NOMA) with successive interference cancellation for future radio access," *IEICE Trans. Commun.*, vol. E98.B, no. 3, pp. 403–414, 2015.



ADITYA S. RAJASEKARAN (Member, IEEE) received the B.Eng. (Hons.) and M.Eng. degrees in systems and computer engineering from Carleton University, Ottawa, ON, Canada, in 2014 and 2017, respectively. He is currently pursuing the Ph.D. degree in systems and computer engineering with Carleton University.

He is also with Ericsson Canada, Inc., where he has been a Software Developer since 2014. He is currently involved in the physical layer development work for Ericsson's 5G New Radio (NR) solutions. His research interest includes wireless technology solutions aimed towards 5G and beyond cellular networks, including non-orthogonal multiple access solutions.



OMAR MARAQA received the B.S. degree in electrical engineering from Palestine Polytechnic University, Palestine, in 2011, and the M.S. degree in computer engineering from the King Fahd University of Petroleum & Minerals (KFUPM), Dhahran, Saudi Arabia, in 2016, where he is currently pursuing the Ph.D. degree in electrical engineering. His research interests include performance analysis and the optimization of wireless communications systems.



and machine learning.

HAMZA UMIT SOKUN received the B.Sc. degree (Hons.) in electronics engineering from Kadir Has University, Istanbul, Turkey, in 2010, the M.Sc. degree in electrical engineering from Özyeğin University, Istanbul, in 2012, and the Ph.D. degree in electrical engineering from Carleton University, Ottawa, ON, Canada, in 2017. Since 2017, he has been with Ericsson Canada, Inc., Ottawa, ON, Canada. His research interests include wireless communication and networks, signal processing,



HALIM YANIKOMEROGLU (Fellow, IEEE) led one of the largest academic-industrial collaborative research projects on pre-standards 5G wireless, sponsored by the Ontario Government and the industry, from 2012 to 2016. He is currently a Professor of Carleton University, Canada. He has been one of the most frequent tutorial presenters in the leading international IEEE conferences. He has had extensive collaboration with industry which resulted in 37 granted patents (plus more than a dozen applied). He supervised 26 Ph.D. students (all completed with theses). His research interest includes communications technologies with emphasis on wireless networks. He is a Fellow of the Engineering Institute of Canada (EIC) and of the Canadian Academy of Engineering. He served as the general chair and technical program chair for several major international IEEE conferences. He is currently serving as the Chair for the Steering Board of the IEEE's Flagship Wireless Conference and Wireless Communications and Networking Conference (WCNC). He is a Distinguished Speaker of the IEEE Communications Society and of the IEEE Vehicular Technology Society.



SAAD AL-AHMADI received the M.Sc. degree in electrical engineering from the King Fahd University of Petroleum & Minerals (KFUPM), Dhahran, Saudi Arabia, in 2002, and the Ph.D. degree in electrical and computer engineering from the Ottawa-Carleton Institute for ECE (OCIECE), Ottawa, Canada, in 2010. He is currently an Associate Professor with the Department of Electrical Engineering, KFUPM. His current research interest includes the channel characterization, design, and performance analysis of wireless communications systems and networks.

...