

Received May 18, 2021, accepted June 18, 2021, date of publication June 24, 2021, date of current version July 5, 2021.

Digital Object Identifier 10.1109/ACCESS.2021.3092074

# Highly Accurate Prediction Model for Daily Runoff in Semi-Arid Basin Exploiting Metaheuristic Learning Algorithms

YAMINA AOULMI<sup>1,2</sup>, NADIR MAROUF<sup>1,2</sup>, MOHAMED AMIRECHE<sup>1,2</sup>,  
OZGUR KISI<sup>3</sup>, RAED M. SHUBAIR<sup>4</sup>, AND BEHROOZ KESHTEGAR<sup>5</sup>

<sup>1</sup>Department of Hydraulic, Faculty of Sciences and Applied Sciences, University of Larbi Ben M'hidi, Oum El Bouaghi 04000, Algeria

<sup>2</sup>Laboratory of Ecology and Environment, University of Larbi Ben M'hidi, Oum El Bouaghi 04000, Algeria

<sup>3</sup>School of Technology, Ilia State University, 0162 Tbilisi, Georgia

<sup>4</sup>Department of Electrical and Computer Engineering, New York University Abu Dhabi (NYU), Abu Dhabi, United Arab Emirates

<sup>5</sup>Department of Civil Engineering, Faculty of Engineering, Zabol University, Zabol 35856-98613, Iran

Corresponding author: Yamina Aoulmi (yamina.aoulmi@univ-oeb.dz)

**ABSTRACT** Developing trustworthy rainfall-runoff (R-R) models can offer serviceable information for planning and managing water resources. Use of artificial neural network (ANN) in adopting such models and predicting changes in runoff has become popular among many hydrologists from a long time. However, since the optimization is the most significant phase in ANN training, researchers' attentiveness has been attracted to the ANN's biggest problem, i.e. its susceptibility of being blocked in local minima. Consequently, use of genetic algorithms (GA), particle swarm optimization (PSO), firefly algorithm (FFA) and improved particle swarm optimization (IPSO) approaches to increase the performance of ANN, have gained remarkable interest among distinct modern heuristic optimization approaches. In this paper, the capability of four improved ANN methods, hybrid GA-based ANN, PSO-based ANN, FFA-based ANN and IPSO-based ANN in modeling rainfall-runoff (R-R) is investigated. IPSO has been used in order to increase the ability of PSO, where the new positions of particles are dynamically adjusted using two procedures which is given form the velocity obtained by PSO and proposed velocity in IPSO. The random normal graded number with a dynamical scale factor is used to compute the new position of the best particles in proposed velocity. Daily R-R data from six stations distributed in the Seybouse watershed located in semi-arid region in Algeria were used in models' development. The selection of the input data sets was carried out using the autocorrelation, partial autocorrelation and cross correlation functions. The results of the four hybrid models were compared via performance metrics, viz., Root Mean Square Error (RMSE), Pearson's correlation coefficient (R), Nash Sutcliffe Efficiency coefficient (NSE), and via graphical analysis (scatter plots, time series and Taylor diagram). Outcomes of the analysis at all study stations disclosed that all the ANN models enhanced with IPSO overachieved the GA-based ANN, PSO-based ANN and FFA-based ANN models in estimating runoff for both training and testing periods. The outcomes of the study indicate that the IPSO hybrid metaheuristic algorithm is the best technique in improving ANN capability in modeling daily R-R.

**INDEX TERMS** Rainfall-runoff models, artificial neural network (ANN), genetic algorithms (GA), particle swarm optimization (PSO), firefly algorithm (FFA), improved particle swarm optimization (IPSO), Seybouse watershed, semi-arid region.

## I. INTRODUCTION

Since the dawn of time, water has been a predominant factor in the socio-economic development of human beings.

The associate editor coordinating the review of this manuscript and approving it for publication was Bo Pu <sup>1</sup>.

It intervenes in the whole functioning of the natural environment and represents a main life resource for many plants and animals. However, with the demographic explosion, the industrial growth and the various forms of life in several areas worldwide, water requirements have considerably increased; this has caused a mismatch between water demand

and water supply; therefore, the problems of water availability became amplified and water resources become under high pressure. As a result, appropriate management of these resources becomes a major concern in order to minimize this pressure or to bridge the hiatus between water availability and demand [1]–[3]. In order to be eligible to arrange some water management tactics to make it obtainable anytime, a prediction of the interrelationship between the two main components of the hydrological cycle rainfall and runoff is necessary [4], [5]. Also, developing accurate models to simulate rainfall-runoff process can help to manage water scarcity problems. However, the rainfall to runoff conversion is mightily nonlinear, stochastic and strongly complex process [6], as there are several meteorological parameters and other various subprocesses influence this complicated system [7], [8]. Therefore, hydrologists and researchers have developed various rainfall-runoff (R-R) models in order to capture and represent this intricate phenomenon, where the model selection has to be made according to its ability and levels of complexity [9]. Generally, these models are categorized into (i) the physics-based technique that offers better understandability, but their accuracy is poor, and (ii) the empirical or data driven technique based on measured data that provides highly accurate results [10].

The artificial neural network (ANN) is one of these data-driven approaches which was utilized in diverse fields such as hydrology and water resources, it's become advocated due to its capability of tackling, modeling and forecasting the problems that are nonlinear or stochastic within the R-R system [11]–[17]. Since ANNs cannot represent the internal structure of the catchment or even manage the environmental data distributed related to the physical characteristics of the basin, they do not replace conceptual watershed modeling. However, they have been recognized as a applicable alternative to conceptual models for input-output forecasting, due to several advantages among which their computational speed in simulation and forecasting [18] and their capacity of making models easy to use and more accurate from complex natural systems with large inputs [19]. The ANN is found to be a very novel and useful model applied to problem-solving and machine learning. As well as it has shown its power and capacity to simulate the hydrological phenomena. Therefore, ANN models are recommended for R-R modeling; due to their simple structures and precision which help us to solve problems related to water resources management.

As there are many apprenticeship algorithms that can be applied to enhance ANN, it still leaves a large scope of probabilities. Although extremely renowned in flood prediction, there is no obvious conclusions declared regarding to which model perform better in a given application [13]. Most of the researches have applied feed-forward and backpropagation (FFBP) network in ANN model development. In the last few years, several optimization tools have been used to enhance the potential of the backpropagation algorithm including the gradient descent (GD) which is commonly applied in backpropagation stage of the neural network

training process [20] and it's formulated as reducing the error between measured and predicted output at every iteration. Nevertheless, the GD may suffer from convergence issues, training method deceleration, stocking within local minima and overfitting; if the model structure is intricate and the parameter set is large, this results in poor performance of ANN models [7], [10], [21]. Recently, several conventional heuristic tools have been created to beat the deficiency of gradient-based techniques and to facilitate the solution of difficult optimization problems and obtain the optimal ANN parameters in training; in order to enhancing its efficiency. Among these tools: artificial bee colony algorithm (ABC), biogeography-based optimization (BBO), differential evolution (DE), grey wolf optimizer (GWO), genetic algorithm (GA), particle swarm optimization (PSO) and firefly algorithm (FFA) etc. [22]. Even though the standard ANN method is old, its hybrid versions with these metaheuristic algorithms have been commonly used these days to solve complex problems in various fields such as: modelling solar energy system, injection molding process, rock engineering field, rock fragmentation [23]–[26].

Genetic algorithms are among the most popular evolutionary algorithms that are suitable for research, adaptability and learning in a miscellaneous of application areas, particularly for problems where nonlinear data and model intricacy conduce to unworthy results. This algorithm has been widely revealed to offer precise optimization solutions for research difficulties through simulation development. Conjointly with intelligence techniques, the GA has become a powerful method of modeling and optimizing complex processes [27]–[29], it is used as an enhancer of ANN parameters to ameliorate the model's efficiency [30], [31]. In addition, GAs is population-based, and many modern evolutionary algorithms are directly based on genetic algorithms or have strong similarities. There are several studies on the applicability of GA in the hydrological sciences. [32] utilized real code GAs for training (ANN) R-R models, in order to anticipate the quotidian flow which is more precise than the backpropagation technique-based ANN models. [33] suggested an intelligent hybrid model that is a combination of methods of data preprocessing, genetic algorithms and Levenberg–Marquardt (LM) algorithm to train feed-forward NN for runoff prediction.

In the other hand, PSO has become one of the most widely used swarm intelligence-based algorithms due to its simplicity and flexibility. Rather than using mutation / crossover, it uses real number chance and global communication between particles in the swarm. Therefore, it is easier to implement than GAs. It could also be used to optimize irregular, non-linear systems and solve complex problems and it has a high speed of convergence towards the ideal solution on a certain iterations number. Moreover, PSO could be involved as a training algorithm for ANN model [21], [34]. At this stage, satisfactory results in various studies have also been obtained in the problems linked to hydrology. [35] suggested a PSO-based perceptron approach to forecast

water stage in the Shing Mun River in Hong Kong. [7] proposed a new hybrid metaheuristic algorithm combining biogeography-based optimization (BBO), particle swarm optimization (PSO) and grey wolf optimizer (GWO) integrated with ANN and ANFIS (adaptive neuro-fuzzy inference systems) for modeling R-R process in the watershed Fal at Tregony. [36], proposed three optimization algorithms integrated with ANFIS, i.e. particle swarm optimization (ANFIS-PSO), genetic algorithm (ANFIS-GA) and differential evolution algorithm (ANFIS-DE) for forecasting monthly streamflow of Pahang River, located in a tropical climatic region of Peninsular Malaysia. [10] applied PSO for training ANN R-R model in Jardin river basin etc.

The swarm-based firefly algorithm (FFA) is receiving considerable research attention, with a number of studies reporting favorable improvement in their modeling accuracy [37], [38]. It is indeed a relatively newer optimization approach that is straightforward with a strong potential to converge quicker to optimum solutions than other intelligent techniques [39]; because the global and local optima of the predictor data can be solved simultaneously and efficiently [40]–[43]. In such optimization problems, it was experimentally seen to surpass PSO. Lately [44] examined its validity to ANN training in classification issues and compared its reliability with GA and ABC. [45] developed an integrated adaptive neuro fuzzy inference system with firefly algorithm (ANFIS-FFA) to forecast monthly rainfall in Pahang River catchment, Malaysia. [46] adopted a novel simulation approach called multilayer perceptron-firefly algorithm (MLP-FFA) for monthly streamflow forecasting at Ajichay watershed, East Azerbaijani. [47] adopted a novel approach based on the integration of support vector regression (SVR) and FFA for rainfall predicting at two stations situated in a semi-arid area, Iran.

Finally, a new version of the PSO algorithm which is Improved PSO (IPSO) could solve multi-objective combination optimization problems in many researches. where it can restrict the position change of original and new particles in the iteration process and accelerate the convergence speed of the algorithm [48]. [49] applied an improved PSO to train artificial neural network (ANN) for water level prediction in the Heshui Watershed in China. [50] introduced a new prediction model for solar radiation, the model was essentially based on an improved support vector regression (SVR) integrated with IPSO, its application showed its superiority over the other models (multivariate adaptive regression 'MARS', genetic programming 'GP', SVR-PSO, SVR-GA, SVR-FFA and M5 tree model).

As these algorithms have different advantages and specific processes in the modeling of complex phenomena and, as their studies in hydrology, in particular R-R modeling, are still at an early stage, and little research has been done on these models to solve hydrological problems and real-time flow forecasting, investigating these models in hydrology and comparing them are highly recommended. On the other hand, the capacity of evolutionary IPSO and FFA in improving

ANN efficiency in modeling R-R as well a study that groups together all the algorithms mentioned above to model this phenomenon has not been previously investigated. This gave us impetus to prepare this research.

The principle aim of the present article is to investigate the capability of ANN-IPSO in modeling R-R so as to provide an efficient method for solving such a complex hydrological problem. In order to assess the viability of the IPSO in improving ANN efficiency, this method was compared with the other three commonly used evolutionary metaheuristic optimizers, GA, PSO and FFA inspired by nature by integrating into ANN as a training algorithm for R-R modeling in the Seybouse Basin situated in a semi-arid region. Autocorrelation and cross-correlation functions were applied to define the optimal model input scenario. Daily actual R-R datasets have been utilized to train and test the hybrid models (ANN-GA, ANN-PSO, ANN-FFA and ANN-IPSO). For the purpose of identifying the most powerful ANN training algorithm, the accuracy of the hybrid models was evaluated and compared using performance metrics: Root Mean Square Error (RMSE), Pearson's correlation coefficient (R), Nash Sutcliffe Efficiency (NSE) and graphical analysis: scatter plots, time series and Taylor diagram. The recent advancement of this research is to investigate the feasibility of a new structure for an ANN model that is integrated with Improved PSO and FFA as optimizers for R-R modeling.

The computer codes for all models' combinations as well the selection process of their architectures, were programmed in MATLAB language ('MATLAB R2018b' purchased with its complete platform and its licenses).

## II. STUDY BASIN AND DATA ACQUISITION

### A. STUDY ZONE

The Seybouse watershed is situated in Algeria's North - East, one of the constituents of the large hydrographic basin named CONSTANTINOIS-SEYBOUSE-MELLEQUE [47]; it presents a significant latitudinal extension, where it occupies an area of 6,471 km<sup>2</sup>. The main river, Oued Seybouse, that drains this watershed, has a total length of 240 km, it originates in the high plains of Heractas and Sellaoua and ends in the coastal plain of Annaba to flow into the Mediterranean. It is formed by the confluence of the wadis Cherf and Bouhamdane at the level of Madjez Amar and receives two other tributaries of unequal importance: the Oued Mellah and the Oued Ressoul. A set of dams were erected on all the wadis of Seybouse Watershed, intended mainly for irrigation and water supply. These dams include Hammam-Debagh on Wadi Bouhamdane, Foum El Khanga on Wadi Cherf upstream, Koudiat Harricha in Cherf downstream, Koudiat Mahcha in basse Seybouse part and other small dams built on Wadi Cherf upstream (Tiffech, Sedrata), Ben Badis on the El Heria wadi which is a small tributary of the Bouhamdane wadi, and M'djez El Bgar in the downstream Cherf. Overall, the water resources of this basin are vital to support most economic activities in the region. Figure 1 displays the location map of

**TABLE 1. Runoff stations’ details for Seybouse Catchment.**

Runoff station	Location		River	Area (km <sup>2</sup> )	Available data period
	X	Y			
Moulin Rochefort	7,224093	36,374004	Cherf	1710	1974 to 1994
Medjez-AmarII	7,310283	36,444445	Moyenne Seybouse	1105	1981 to 2002
Bordj-Sabath	7,037219	36,418058	Bouhandan e	304	1980 to 2015
Bouchehouf	7,709725	36,45944	Melah	550	1980 to 1995
Mirebek	7,750935	36,583701	Seybouse	5950	1981 to 1995
Ain Berda	7,596389	36,691941	Ressoul	102	1977 to 1997

**TABLE 2. Statistical characteristics of daily datasets for the six runoff study stations.**

Station	Data set	data points	Max (m <sup>3</sup> /s)	Min (m <sup>3</sup> /s)	Mean (m <sup>3</sup> /s)
Moulin Rochefort	Training (80 %)	5210	3.062	0	0.024
	Testing (20 %)	1303	1.103	0	0.020
	Total (100%)	6513	3.062	0	0.023
Medjez-AmarII	Training (80 %)	5601	60.821	0	0.182
	Testing (20 %)	1401	0.719	0.006	0.301
	Total (100%)	7002	60.821	0	0.206
Bordj-Sabath	Training (80 %)	9512	100.03	0	0.169
	Testing (20 %)	2379	54.59	0	0.149
	Total (100%)	11891	100.03	0	0.165
Bouchehouf	Training (80 %)	3784	30.223	0	0.225
	Testing (20 %)	947	10.267	0.002	0.184
	Total (100%)	4731	30.223	0	0.225
Mirebek	Training (80 %)	3703	14.608	0	0.106
	Testing (20 %)	926	4.156	0	0.123
	Total (100%)	4629	14.608	0	0.110
Ain Berda	Training (80 %)	5328	42.582	0	0.301
	Testing (20 %)	1333	37.238	0	0.262
	Total (100%)	6661	42.582	0	0.294


Seybouse Watershed as well as the distribution of the various hydrometric and rainfall stations in the six-sub basin used in this study.

**B. DATA ACQUISITION**

The most measured components of the hydrological cycle are precipitation and river flow, they are crucial for any hydrological modeling [52], [53]. Thus, the database compiled of these two parameters in the six stations spread throughout the catchment area of Seybouse at different periods for each one (due to the unavailability of data at these stations for the same duration), were applied to simulate the R-R relationship. Further information about these stations is given in Table 1 and 2, while their locations are represented in Figure 1.

In the aim of evolving the model, the primary stage is to divide data into various categories for the model effectiveness training and testing. The principal goal of such a stage is for assuring that the model is functioning with a constant degree of accuracy; in case it knows invisible data instead of training. According to [54], the best results are attained if we allocate 20-30% of the original data points for testing, and use the remaining 80-70% for training. For this division, we get accuracy estimates which are:

- valid – in the sense that they do not overestimate the accuracy (i.e., do not underestimate the approximation error), and



**FIGURE 1. The case study site location, Seybouse Catchment located in Algeria.**

- are the more accurate among the valid estimates – i.e., their overestimation of the approximation error is the smallest possible.

In this context, the data used in this research was categorized into two main parts; the first to train the models with 80% of the data collected and the second to test the calibrated models with 20% of the data to examine the model performance. The entry dataset  $x^*$  was normalized in the scope [0.1, 0.9], Eq. (1):

$$0.1 + \frac{0.8(x - x_{min})}{(x_{max} - x_{min})} \tag{1}$$

where:  $x$  is the historical data,  $x_{min}$  and  $x_{max}$  are the minimum and maximum values, respectively. All these data were acquired from the National Water Resources Agency (ANRH) of Algiers.

Where, Max, Min and Mean are the maximum, minimum and average value of the observation series in training and testing phases for each runoff station.

As shown in table 2, we have enough data points for the six study stations, because more data points we use for the models, the more precise the model estimates.

In fact, the accuracy also depends upon the model data requirement, the quality of this data (which must be good) and model setup equation that which type of is that either lump or distributed all model have their own set of equations and input requirements to run up that model. The best way is that do adjust the model parameters until calibration and validation results come better.

**III. METHODOLOGY**

**A. ANN, GA, PSO, FFA and IPSO**

1) ARTIFICIAL NEURAL NETWORK (ANN)

In recent years, the ANN-method has drawn considerable interest from scientists for prediction of the systems that are nonlinear; due to its highly learning potential without any physical acquaintance of the process to be modeled [55].

The primary principle of data handling ANNs is inspired by the nervous biological system [56]. ANNs comprise of a countless number of nodes that are linked together to address multiple issues.

In the present study, the ANN is based on the multi-layer perceptron structure (MLP). MLP typically composes of three layers (input layer, hidden or intermediate layer, and output layer) Figure 2 [57]. Every layer may contain different neurons' numbers that bind to each other with the links named weights ( $w$ ). the input layer nodes transmit the input signal values to the intermediate layer nodes. Similarly, the intermediate layer nodes transmit the signal values to the output layer nodes. Eventually, the output layer displays the results that have been simulated. Eq. (2) determines the output of each layer:

$$y = \sum_{i=1}^n y_i w_i + b \tag{2}$$

where  $y$ : the layer's output,  $y_i$ : the input of a layer;  $w_i$ : weights; and  $b$ : bias.




FIGURE 2. ANN architecture.

The logistic sigmoid and tangent functions are the more ordinarily transfer functions used. [58] pointed that the training with tangent function is not only quicker than the training with logistic sigmoid transfer function, but also the forecasts found through tangent networks are marginally better than those with logistic sigmoid transfer functions. [59] indicated that it is more difficult to train ANNs with the sigmoid logistic function than ANNs with the tangent function. [60] found that in outflow estimation, the tangent sigmoid function worked much better than the logistic sigmoid function.

As a result, the adopted activation function employed in this study was the hyperbolic tangent sigmoid function, Eq. (3)

$$f(S) = \frac{2}{(1 + e^{-2S})} - 1 \tag{3}$$

In this paper, the ANN was adopted to predict the rainfall-runoff process over several time horizons. Three algorithms, termed genetic algorithm, particle swarm optimization and firefly algorithm were applied to determine the improved set of ANN variables. Further explanation of these techniques is given in the following sections.

## 2) GENETIC ALGORITHM (GA)

The Genetic Algorithm (GA), was first created by John Henry Holland. This metaheuristic algorithm is a machine learning model, that originates its behavior and habits from a description of evolutionary systems in nature, it has been utilized to enhance the parameters of the control process that are complicated and hard to fix by traditional optimization techniques. This act is achieved by introducing by a computer, a sample of individuals demonstrated by chromosomes (similar to the chromosomes contained in human DNA) [61]. In nature, the genetic information coding generally outcomes in offspring genetically similar to the parent. Sexual proliferation makes it possible to create genetically radically dissimilar offspring of the same general organisms. Straightforwardly, a couple of chromosomes conflict at the molecular scale, exchange set of genetic knowledge and separate each other. This is named the recombination operation, that is called in GA crossover duo to the manner in which the genetic information goes from one chromosome to the other. Other operators with bio-inspiration including mutation and regeneration. In the regeneration operator, two arbitrary nominees are chosen and when the weak one is removed, the other is doubled. In the mutation, a nominee will be silenced and therefore an extremely low mutation rate can lead to genetic deviation [62].

Because ANNs and GAs are popular methods that have been used by various researchers to optimize nonlinear problems such as modeling and forecasting the rainfall-runoff systems, a conjunction model between these two methods is introduced (ANN-GA). This procedure adjusts artificial neural network variables like momentum term and number of intermediate layers' neurons. However, this method may take time in the training procedure, but the use of the genetic algorithm tries to reduce error and inaccuracy considerably. Consequently, this technique appears meaningful. In various ANN structures, the GA technique improves the various components of ANN such as neurons number in the hidden layers; which is formed by the Levenberg-Marquardt training method.

## 3) PARTICLE SWARM OPTIMIZATION (PSO)

PSO was first defined by Eberhart and Kennedy (1995). Its idea stemmed from the social behavior of creatures in a horde or swarm. Though it is originally created as a mechanism for simulating social behavior, the PSO technique has been identified as a computational intelligence algorithm closely linked to meta-heuristic evolutionary search optimization algorithm [63]. The evolutionary methodology acquired using Eq. (4) and (5) is the main feature of PSO which differentiates it from other improvement algorithms.

$$\vec{v}_{new} = \vec{v} + r_1 c_1 * (\vec{p}_{best} - \vec{p}) + r_2 c_2 * (\vec{g}_{best} - \vec{p}) \tag{4}$$

$$\vec{p}_{new} = \vec{p} + \vec{v}_{new} \tag{5}$$

where  $v_{new}$ ,  $v$ ,  $p_{new}$ , and  $p$  signify the new velocity, current velocity, new position, and current position, respectively, of a

specific particle;  $c_1$  and  $c_2$  denote cognition and social coefficient respectively;  $p_{best}$  symbolizes the ideal or best position of this particle,  $g_{best}$  is the best position that the swarm knows;  $r_1$  and  $r_2$  are random numbers between 0 and 1 [64].

The introduction of certain arbitrary chosen particles is the initial phase to solve optimization issues utilizing PSO (initialize the ANN weights). Every particle (i.e. weight ANN) is designated an arbitrary position and velocity. A repeated process is applied over the next phase to figure out the best possible solution; the  $p_{best}$  and  $g_{best}$  values of each particle were registered in other verses throughout each interaction. Therefore, utilizing equations 3 and 4, the positions of the particles vary based on their expertise and that of other particles. Particle positions are updated until the best solution is obtained [64].

As ANNs can be stocked in local minima, the integration of hybrid methods like ANNs based on PSOs becomes encouraging. The PSO constituent of this kind of hybrid model is capable of finding an overall minimum and further research. Therefore, a hybrid ANN model based on PSO has the benefits of these two techniques: in the quest field, PSO will look for all the minimums and ANN will need them to come up with the optimal solution. In ANN-PSO, every particle (the ANN weight) is a frontrunner solution to reduce the error. The enhanced weights are utilized for the network training after improving the problem. In fact, the aim of introducing the PSO to the ANN is to strengthen the training process of the ANN.

#### 4) FIREFLY ALGORITHM (FFA)

The firefly algorithm (FFA) is a new nature inspired meta-heuristic process, established by Xin-She Yang in 2008 for solving various optimization problems. The concept behind FFA is that fireflies emit or produce light generated by chemical processes, for mating purposes, the light-flashing activity draws fireflies to each other [65]. It is important to note that, the bright fireflies attract readily the less bright fireflies. This mechanism could be generated as an enhancement algorithm as the flashing-light can be programmed to be synchronized with the optimized fitness function. Three rules are followed by the firefly algorithm:

- All the fireflies are unisex.
- The less bright ones will move towards the brighter ones. But, when a brighter one is no visible, fireflies will move arbitrarily.
- A firefly's brightness or light intensity is defined by the land scape of the optimized objective function.

By knowing these rules, the firefly's brightness and light intensity form the fundamental basis of the FFA model's function. Eq. (6) and (7) signify the firefly's intensity and attractiveness, since each firefly demonstrates its particular attractiveness, reflecting its attractive prowess in the swarm [66].

$$I = I_0 e^{-\gamma r^2} \tag{6}$$

$$\beta(r) = \beta_0 e^{-\gamma r^2} \tag{7}$$

At distance  $r$ ,  $I$  denote the light intensity and  $\beta(r)$  the attractiveness. At distance  $r=0$ , the light intensity becomes  $I_0$  and the attractiveness  $\beta_0$ .  $\gamma$  is the light absorption coefficient  $0.1 < \gamma < 10$ . The Cartesian distance between any two fireflies is defined as:

$$r_{ij} = \|x_i - x_j\| = \sqrt{\sum_{k=1}^d (x_{i,k} - x_{j,k})^2} \tag{8}$$

where  $d$  denotes problem dimensionality,  $x_i$  and  $x_j$  are the fireflies' positions, and  $x_{i,k}$  and  $x_{j,k}$  are the  $k$ th component of spatial coordinate. As already noted, fireflies are enticed to each other, therefore, the next movement of firefly  $i$  can be expressed in formula (9).

$$x_i^{t+1} = x_i^t + \beta_0 e^{-\gamma r_{ij}^2} (x_j - x_i) + \alpha (\text{rand} - \frac{1}{2}) \tag{9}$$

where  $x_i^t$  is the solution vector or actual position of the firefly  $i$ , the second term is due to attraction to a brighter firefly  $j$ , and  $\alpha(\text{rand}-1/2)$  represents the firefly's arbitrary walk with the randomization parameter  $\alpha \in [0,1]$  [67].

As with PSO, firefly can readily be used to train ANN. To optimize the ANN model weights, to achieve the optimum parameter settings for ANN training and to reduce the error ratio. Each firefly is employed to represent a candidate solution to the ANN training problem (i.e. a vector of all the weights and biases of an ANN). First, the population size of candidate solutions is created for the problem in question (the ANN's weights). After this, the fireflies' light intensity is calculated and the attractive firefly (best candidate) is found within the population. Afterwards, to move all fireflies towards the attractive one in the search area, calculate for each firefly the attractiveness and distance. Eventually, in the search area, the attractive firefly moves arbitrarily. This procedure is replicated until a termination criterion is reached (the maximum number of generations is achieved) [68].

#### 5) IMPROVED PSO

In improved PSO, the particles are randomly adjusted using a generated number by normal standard distribution (*Normrand*) as follows:

$$p_{new} = p + v_{new}^I$$

$$v_{new}^I = r_3 [g_{best} - p] + \text{Normrand}(0, 1) \times \gamma_k \tag{10}$$

where,  $v_{new}^I$  is the improved velocity which are adjusted for new positions.  $v_{new}^I$  is determined based on best position of particle ( $g_{best}$ ) and a random number generated by a normal distribution with mean of 1 and STD of 0 (*Normrand*(0, 1)). The normal random part is scaled using factor  $\gamma_k$  which is determined by the following relation [69], [70]:

$$\gamma_k = \sqrt{1 - \frac{k}{NI}} \tag{11}$$

Factor  $\gamma_k$  is tended to 1 at first iterations and 0 at fill iterations  $\gamma_k \in [0, 1]$ . As seen from the improved velocity,

the new positions of particles are adjusted using random normal process. Thus, the new and the best particles have not the same positions. Consequently, it is reduced the chance to the local optimum by compared to original PSO by this presented optimization approach. The formulation of IPSO is presented in Eq. (12) by using two random adjusting procedures given by improved velocity presented in Eq. (10).

$$P_{new}^I = \begin{cases} p + v_{new}^I & r \leq P_k \\ p + v_{new} & r > P_k \end{cases} \quad (12)$$

where,  $r \in [0,1]$  is a random number gendered by uniform distribution between 0 and 1. In IPSO, the initial velocity and its parameters are randomly determined as well as PSO.

$P_k$  is named as adjusting particle rate, which is computed as follows:

$$P_k = 0.2 + 0.8\sqrt{\frac{k}{NI}} \quad (13)$$

$P_k$  is randomly provided a pattern for adjusting the new particle using two formulations of PSO and IPSO. By increasing  $P_k$ , the chance of applying improved velocity for determining the new positions for particles is increased. We commonly used this formula presented in Eq. (10) at final iterations. Thus, it is a local search on the best position for computing the global optimum results at final iterations.

As see in Eq. (12), it is applied two velocity terms for adjusting the positions of the new particles while in the PSO, we apply the velocity of particles using Eq. (4) which is determined by using  $p_{best}$  and  $g_{best}$ ; and this is the main differences of PSO and IPSO.

**B. INPUT COMBINATION AND MODEL DEVELOPMENT**

**1) INPUT COMBINATION**

The input combination selection is considered as one of the major factors effecting the model’s effectiveness. Therefore, a proper input selection is essential before applying the ANN models. For this study, an input scenario was created and studied for the four hybrid ANN models based on the autocorrelation function (ACF), the partial autocorrelation function (PACF) and simple cross-correlation function (CCF) which have been used to identify the number of effective lags of antecedent rainfall and runoff. This method was proposed by the several researches [36], [71]–[74] to determining the optimal inputs for data driven methods.


The Table 3 is listing the CCF and PACF values of the six stations studied, a representation example of these functions (ACF, PACF and CCF) for one of the stations (station ‘Medjez-Amar II’ of the sub basin 3) is shown in Figure 3.

The CCF indicates that the precipitation at time t and one lag are considerably effective on runoff compared to the precipitation for two and three lags, while the other lags have fallen within the confidence limit. Therefore,  $R_{t-1}$  was considered as one of the parameters included in the input scenario used in the developed models. In addition, the PACF in all the stations indicates that the first lag of runoff has considerable effect, and that the second and third lags are very

**TABLE 3. Partial autocorrelation and cross-correlation values of the used data.**

Variable sets	Time series	Whole data set for the different runoff stations					
		S1	S2	S3	S4	S5	S6
Partial autocorrelation	$Q_t\_Q_{t-1}$	0.38	0.58	0.46	0.57	0.52	0.48
	$Q_t\_Q_{t-2}$	0.09	-0.07	*	-0.01	0.20	0.17
	$Q_t\_Q_{t-3}$	0.08	-0.05	*	0.17	0.14	*
Cross-correlation	$Q_t\_R_{t-1}$	0.22	0.42	0.28	0.36	0.25	0.31
	$Q_t\_R_{t-2}$	0.1	0.21	0.13	0.19	0.14	0.19
	$Q_t\_R_{t-3}$	0.08	0.07	0.05	0.17	0.13	0.1

S1: Moulin Rechefort, S2: Medjez-Amar II, S3: Bordj-Sabath, S4: Boucheougouf, S5: Mirebek, S6: Ain Berda



**FIGURE 3. The autocorrelation (ACF), the partial autocorrelation (PACF) functions of the runoff time series and cross-correlation function (CCF) between runoff ( $Q_t$ ) and rainfall at various lags with the 95% confidence limit for ‘Medjez-Amar II’ Station.**

near to the confidence limit (but in ‘Bordj-Sabath’ and ‘Ain Berda’ stations, the lags  $Q_{t-2}$ ,  $Q_{t-3}$  and  $Q_{t-3}$  respectively are within the confidence limit \*). Therefore, these two entries were ignored.

As the precipitation beyond the 2<sup>nd</sup> lag doesn’t really affect the runoff at time t, as well as the runoff is not effective

beyond the same lag. Therefore, the input combination considered for the scenario used in this research to model the rainfall-runoff process is made up of  $R_t$ ,  $R_{t-1}$  and  $Q_{t-1}$  to simulate the output  $Q_t$ .

## 2) MODEL DEVELOPMENT

In the present study, four ANN models have been created and compared with each other for modeling rainfall/runoff task. The first model utilizing the (GA) for its training was termed as ANN-GA, the second utilizing the PSO algorithm was named ANN-PSO, the third using the (FFA), was called ANN-FFA and the last using (IPSO) referred to ANN-IPSO. In fact, since the efficiency of every model generally depends on the appropriate variable's determination, these three optimization techniques have been combined with ANN model to improve the calibration of its variables (optimize its weights and biases).

The choice of the hidden layers' numbers as well as the neurons number was decided after performing different combinations. Indeed, we have been able to observe, through several tests, that the rise in the number of intermediate layers or that of neurons did not lead to an improvement in the results, on the contrary it made the network more difficult to stall and its training time longer. As well, a higher probability of converging to a local minima can be introduced, so there is no notional justification for using more than two intermediate layers [75], [76]. On the other side, the use of too few nodes in the intermediate layers compared to the intricacy of the problem data, will leads to the *underfitting* and using too many neurons might result *overfitting* which occurs when unnecessarily more neurons are presented into the network [77], [78]. In this work, the use of a single hidden layer was found to be enough to have simulation results of the model with good convergence and performance [79], [80]. The ideal number of nodes in the intermediate layer has been defined following a trial and error method (forward approach) by changing the intermediate-layer neurons number [46], [81]–[84], in this case, we start from an architecture with 2 nodes in the intermediate layer, after that, train and test the ANN, then constantly increase the hidden neurons number. We repeated the above procedure until training and testing improved, then we retain the architecture which gives the minimum of the error on the test base [76]. As a result, the best ANN-GA, ANN-PSO, ANN-FFA and ANN-IPSO architectures obtained were with one hidden layer and 10 neurons.

The four computer programs that show the development process of the hybrid models were developed in MATLAB. The Figure 4 depicts the procedure of how the GA, PSO, FFA and IPSO algorithms optimize the ANN parameters.

During the application of GA, PSO, FFA and IPSO, several parameters must be specified. A suitable selection of parameters influences the algorithm convergence rate. Table 4 displays the parameters values utilized for the four optimization algorithms.




FIGURE 4. Flowchart of the suggested hybrid algorithms (a) ANN-GA, (b) ANN-PSO, (c) ANN-FFA and (d) ANN-IPSO.

TABLE 4. Parameters utilized for the four evolutionary algorithms.

GA parameters	PSO and IPSO parameters	FFA parameters
Population size: 160	Swarm size: 200	Swarm size: 150
MaxIt: 50	MaxIt: 35	MaxIt=50
Crossover type: arithmetic (50%)	C1, C2 = 2	$\gamma=1$
Mutation: 35%	$w_{max}=0.9$	$\beta_0=2$
Recombination: 15%	$w_{min}=0.6$	$\alpha=0.2$

The parameters of IPSO and PSO are given a same in the optimization process. however, the new position of particles is determined with novel velocity relation which is computed using the global best of particle and a normal random generated approach.

In IPSO, the improved velocity of particles is deceptively combined with the velocity given from original PSO with a self-adaptive random process as presented in Eq. (12).

## 3) STATISTICAL PERFORMANCE INDICATORS

The effectiveness of different predictive models is evaluated through graphical interpretation (line, scatter and Taylor diagram) and through performance indicators: Pearson's correlation coefficient (R), Nash Sutcliffe Efficiency coefficient (NSE) and Root Mean Square Error (RMSE). R varying



from  $-1$  to  $1$ , evaluates the linear correlation between predicted and observed values, its values of  $1$  and  $0$  signify an ideal fit and no statistical correlation between the data and the line drawn across them, respectively. The NSE is utilized to analyze the predictive accuracy of the hydrological models (varies from  $-\infty$  to  $1$ ). The RMSE is used to estimate predicting precision, which produces a positive value by squaring the errors. The RMSE rises from zero for perfect predictions to large positive values as the discrepancies between predictions and observations become significantly large. Usually, the best model forecasts are obtained when R, NSE, and RMSE are close to  $1$ ,  $1$ , and  $0$ , respectively. The formulation of these three-performance metrics could be defined as:

$$R = \frac{\sum_1^n (Q_{o,i} - \hat{Q}_o)(Q_{p,i} - \hat{Q}_p)}{\sqrt{\sum_1^n (Q_{o,i} - \hat{Q}_o)^2 \sum_1^n (Q_{p,i} - \hat{Q}_p)^2}} \quad (14)$$

$$NSE = 1 - \frac{\sum_1^n (Q_{o,i} - Q_{p,i})^2}{\sum_1^n (Q_{o,i} - \hat{Q}_o)^2} \quad (15)$$

$$RMSE = \sqrt{\frac{\sum_1^n (Q_{p,i} - Q_{o,i})^2}{n}} \quad (16)$$

where  $n$  is the data number,  $Q_{o,i}$  is the observed runoff,  $Q_{p,i}$  is predicted runoff,  $\hat{Q}_o$  is the average value of the observed runoff and  $\hat{Q}_p$  is the average value of the predicted runoff [7].

#### IV. RESULTS, ANALYSIS AND DISCUSSION

In this chapter, a thorough assessment of ANN-GA, ANN-PSO, ANN-FFA and ANN-IPSO hybrid models in simulating the output  $Q_t$  using defined scenario ( $R_t, R_{t-1}$  and  $Q_{t-1}$ ) is presented and their efficiency in terms of numerous statistical indicators during training and testing for the various study stations is demonstrated in Table 5.

In the training stage (Table 5), it can be observed that for all the hydrometric stations that are distributed in the study basin, the ANN-IPSO model offers greater approximations or simulated runoff values than the ANN-GA, ANN-PSO and ANN-FFA models; by way of illustration, for ‘Medjez-Amar II’ Station in the sub-basin B3, the ANN model trained by the genetic algorithm (GA) gave a strong correlation coefficient R (0.823), a good efficiency coefficient NSE (0.666) and a low root mean squared error RMSE (0.744). Whereas, the ANN which used particle swarm optimization as training algorithm (PSO) has further improved these performance statistics, where R became very strong (0.941), NSE very good (0.868) and RMSE low (0.466). And for the hybrid model ANN-FFA, the performance indicators became more important (R = 0.961, NSE = 0.916 and RMSE = 0.425). However, the ANN trained by Improved PSO performed as the best model for R-R modeling, where R = 0.993, NSE = 0.985 and RMSE = 0.177. Also, the application of ANN-GA

**TABLE 5. Performance indicators of optimal ANN-GA, ANN-PSO, ANN-FFA and ANN-IPSO over training and testing periods.**

Station	Model	Training (80%)			Testing (20%)		
		R	NSE	RMSE	R	NSE	RMSE
Moulin Rochefort	ANN-GA	0.782	0.590	0.046	0.805	0.643	0.047
	ANN-PSO	0.850	0.715	0.039	0.878	0.764	0.039
	ANN-FFA	0.869	0.743	0.039	0.908	0.765	0.028
	ANN-IPSO	<b>0.904</b>	<b>0.813</b>	<b>0.034</b>	<b>0.919</b>	<b>0.839</b>	<b>0.023</b>
Medjez-Amar II	ANN-GA	0.823	0.666	0.744	0.916	0.814	0.621
	ANN-PSO	0.941	0.868	0.466	0.975	0.926	0.394
	ANN-FFA	0.961	0.916	0.425	0.986	0.942	0.341
	ANN-IPSO	<b>0.993</b>	<b>0.985</b>	<b>0.177</b>	<b>0.987</b>	<b>0.943</b>	<b>0.052</b>
Bordj-Sabath	ANN-GA	0.798	0.622	0.948	0.831	0.675	0.971
	ANN-PSO	0.918	0.818	0.554	0.971	0.842	0.947
	ANN-FFA	0.927	0.850	0.640	0.978	0.896	0.395
	ANN-IPSO	<b>0.961</b>	<b>0.923</b>	<b>0.459</b>	<b>0.980</b>	<b>0.960</b>	<b>0.245</b>
Bouche gouf	ANN-GA	0.808	0.627	0.615	0.837	0.697	0.389
	ANN-PSO	0.875	0.743	0.513	0.926	0.857	0.253
	ANN-FFA	0.920	0.842	0.405	0.962	0.847	0.249
	ANN-IPSO	<b>0.970</b>	<b>0.939</b>	<b>0.252</b>	<b>0.965</b>	<b>0.929</b>	<b>0.170</b>
Mirebek	ANN-GA	0.810	0.656	0.207	0.821	0.65	0.176
	ANN-PSO	0.821	0.670	0.156	0.965	0.859	0.203
	ANN-FFA	0.863	0.720	0.183	0.972	0.895	0.108
	ANN-IPSO	<b>0.940</b>	<b>0.882</b>	<b>0.119</b>	<b>0.975</b>	<b>0.950</b>	<b>0.075</b>
Ain Berda	ANN-GA	0.807	0.638	0.862	0.831	0.666	0.905
	ANN-PSO	0.843	0.707	0.811	0.902	0.806	0.572
	ANN-FFA	0.870	0.745	0.743	0.912	0.812	0.614
	ANN-IPSO	<b>0.957</b>	<b>0.915</b>	<b>0.428</b>	<b>0.944</b>	<b>0.891</b>	<b>0.467</b>

model in the 2nd station ‘Bordj-Sabath’, provided values of R (0.798), NSE (0.622) and RMSE (0.948) which are worse compared to those provided by ANN-PSO where R, NSE and RMSE are 0.918, 0.818 and 0.554, respectively. The ANN model trained by the firefly algorithm (FFA) gave as well good results compared to president models (R = 0.927, NSE = 0.85 and RMSE = 0.64). Whereas, the ANN-IPSO offered better performance values (R = 0.961, NSE = 0.923 and RMSE = 0.459).

The same remarks for exceeding the excellence of the ANN model that utilizes IPSO as a training algorithm on the ANN model that employs GA, PSO and FFA for the training, are valid for the remaining stations (sub-basin B2 ‘Moulin Rochefort’ Station, sub-basin B5 ‘Bouche gouf’ Station, sub-basin B6 ‘Mirebek and Ain Berda’ stations).

On the one hand, the disproportion of performance between the two models of neural networks trained by GA and PSO separately can be due to several reasons: The implementation of GA is usually an intricate process that involves evolutionary operations such as selection, crossover and mutation. Also, the convergence velocity could be considerably decreased if the size of the sample is big. However, the PSO algorithm is easier to implement, and unlike GA, it achieves its final variables values in lesser generations (see Table 5), it converges faster, it has fewer parameters, and it doesn’t have complex evolutionary operators like crossover and mutation. Another important point was noted during the simulation, which is the calculation time for GA is relatively small contrasted to the PSO enhancer tool, even though it rises proportionally to the number of PSO and GA generations. Therefore, the bigger calculation time for PSO is resulting to the interaction among the particles. On the other hand,

the FFA has shown a more interesting ability than PSO and GA to model this intricate phenomenon, so it has proven to be an encouraging optimization algorithm; due to the influence of the attractiveness function that is specific to the firefly behavior. However, PSO is preferable than firefly with regards to the time needed for the optimum value to be produced.

Same results obtained by [65], where he found that particle swarm frequently exceeds conventional algorithms like genetic algorithms, whereas in terms of effectiveness and success ratio, the modern firefly algorithm is superior to both PSO and GA.

While, the IPSO has potentially demonstrated that it is a more powerful favorable optimization tool than FFA in solving optimization problems which are complex and non-linear.

An identical tendency is also noticed for the testing phase, where the ANN-IPSO performed much better than the ANN-GA, ANN-PSO and ANN-FFA models in terms of all effectiveness indicators. Keeping the same example of the stations as in the training stage, applying the ANN-GA model in the 'Medjez-Amar II' Station of the sub-basin B3 gave a very strong correlation coefficient  $R$  (0.916), an NSE (0.814) and an RMSE of 0.621, whereas the use of the ANN-PSO model improved these indices better where the value of  $R$  increased further to 0.975, NSE to 0.926 and RMSE became lower (0.394). Also, the ANN-FFA enhanced more the performances indices to ( $R = 0.986$ ,  $NSE = 0.942$  and  $RMSE = 0.341$ ). However, the ANN-IPSO provided the highest performance value ( $R = 0.987$ ,  $NSE = 0.943$  and  $RMSE = 0.052$ ); these values confirm the excellence of this model. For the 'Bordj-Sabath' Station of the same sub-basin B3, the ANN-IPSO provided a correlation coefficient of 0.98 and an NSE of 0.96 and an RMSE of 0.245 which are much better than the  $R$  (0.978), NSE (0.896) and RMSE (0.395) obtained by the ANN-FFA and largely higher than those provided by the ANN-PSO ( $R = 0.971$ ,  $NSE = 0.842$  and  $RMSE = 0.947$ ) and ANN-GA ( $R = 0.831$ ,  $NSE = 0.675$  and  $RMSE = 0.971$ ). All the observations discussed above about the efficiency of ANN-IPSO model compared to ANN-GA, ANN-PSO and ANN-FFA in testing period for the sub-basin B3, remain virtuous for the remaining sub-basin stations. Compared to ANN-GA, the ANN-IPSO improved the R-R modeling accuracy by 51%, 92%, 75%, 56%, 57% and 48% with respect to RMSE for the Moulin Rochefort, Medjez-Amar II, Bordj-Sabath, Bouchegouf, Mirebek and Ain Berda stations, respectively. The corresponding percentages compared to ANN-FFA are 18%, 85%, 38%, 32% and 24% for the Moulin Rochefort, Medjez-Amar II, Bordj-Sabath, Bouchegouf and Mirebek stations, respectively. All these clearly prove the superiority of the ANN-IPSO to the other alternatives in modeling R-R.

After analyzing and discussing the results obtained from the two phases of the applied models, an important remark can be deduced is that, the reliabilities of the models in the training phase are significantly lower than that during the testing phase (look at the  $R$  and NSE values in Table 5).

Perhaps the principal cause is that the more complicated training data structure; that has a more distribution curve, which include peaks of runoff and precipitation much higher than the testing dataset.

The scatter plots for predicted and observed daily flow values for the six study stations during testing period provided by the four hybrid models, are indicated in Figure 5. As clearly observed, the linear trend of the ANN-IPSO is the nearest to the line  $y=x$  compared to those of ANN-GA, ANN-PSO and ANN-FFA. Similarly, the predicted flow's time series utilizing ANN-IPSO are compared with the observed ones through the testing period (see Figure 6). A good fit and a decent agreement are noticed between the observed and predicted flow by the ANN-IPSO model.


### The Taylor diagram

The Taylor diagram [85] were used to provide a visual understanding of effectiveness measurements that plots for the modeling results a set of points on a polar plot, the diagram was used for demonstrating the spatial variation of the expected flow by the ANN-GA, ANN-PSO, ANN-FFA and ANN-IPSO over the observed value during testing period for the six study stations. The standard deviation (SD) between expected and observed values is defined by Taylor diagram along the radial intervals with roots, and  $R$  values are defined as angles of direction. The assumption is that on the Taylor diagram, the observed values have an independent display and the nearer the performance indicators of predictions to the observed values, the stronger the model performance. As illustrated in Figure 7, the results found by ANN-IPSO are nearer to the observed one in comparison with ANN-GA, ANN-PSO and ANN-FFA, which indicates higher accuracy of this model as mentioned previously considering Table 5, Figures 5-6.


The standard ANN method is successfully used in water resources management issues. For example, estimation and/or forecasting runoff and provide data for early warning systems against the possible floods. As also mentioned in the introduction section, standard ANN however has some drawbacks such as training method deceleration, stocking within local minima and overfitting. So, new metaheuristics algorithms are needed to solve this issue and improve standard ANN efficiency. This has been confirmed by the results found in this study after applying the hybrid models of ANN trained separately by GA, PSO, FFA and IPSO, where they revealed the superiority of the ANN-IPSO over the ANN-FFA, ANN-PSO and ANN-GA in both training and testing phases for the six stations distributed in the study basin. As a result, the IPSO algorithm was able to improve the resolution capabilities of this complex problem with a high convergence speed compared to FFA, PSO and GA. Also, it could be used to improve other abnormal troubles that change over time. Such models can be used as a module in general hydrological analysis models [10], [86], [87].

[88] used MLP-ANN and hybrid multilayer perceptron (MLP-FFA) to forecast monthly river flow for a set of time intervals using observed data. Their results show that


Moulin Rochefort




Medjez-Amar II




Bordj-Sabath



Bouchegouf



Mirebek



Ain Berda




FIGURE 5. Scatter plots of the observed and predicted daily runoff values during testing phase, produced by ANN-GA, ANN-PSO, ANN-FFA and ANN-IPSO for the six stations.




FIGURE 6. Time series of the observed and predicted daily runoff values during testing phase, produced by ANN-IPSO for the six stations.




FIGURE 7. Taylor diagrams displaying statistical comparison of the four models during testing period at the six study stations.

MLP-FFA model is satisfactory for monthly river flow simulation in Ajichay watershed (East Azerbaijani) in the province of East Azerbaijan.

[86] compared particle swarm optimization and genetic algorithm for daily rainfallrunoff modelling in Southeast Queensland, Australia. The results indicated that the ANN-PSO model significantly outperformed the ANN-GA model in terms of convergence speed, accuracy, and fitness function evaluation.

V. CONCLUSION

This paper developed a highly accurate prediction model based on a combined artificial neural network-improved

particle swarm optimization algorithm (ANN-IPSO) approach for a common problem in the field of hydrology involving rainfall-runoff in semiarid basin. The developed approach outperforms other existing techniques in the literature, including genetic algorithm (GA), particle swarm optimization (PSO) and firefly algorithm (FFA).

The daily rainfall and runoff data collected from Seybouse watershed, Algeria, were used to establish all the developed models. The model’s effectiveness was assessed based on different statistical measures.

Overall, the study indicated that the GA, PSO, FFA and IPSO algorithms can be employed in modeling the rainfall-runoff process. However, the optimal results from an

evolutionary standpoint, significantly proved the superiority and the capacity of ANN-IPSO over ANN-GA, ANN-PSO and ANN-FFA in terms of all statistical criteria and graphical interpretation, where the input predictors are  $R_t$ ,  $R_{t-1}$  and  $Q_{t-1}$ .

These findings unquestionably confirm the effectiveness of the IPSO algorithm in tuning the parameters of ANN model and appreciably strengthen its forecasting performance. The IPSO-based hybrid ANN model can thus be employed in different functionalities and, more especially in hydrology and its related disciplines. As a result, this study finding indicates that the ANN model optimized by IPSO is more powerful for R-R modeling and a better alternative to other three metaheuristic-based models (GA-ANN, PSO-ANN and ANN-FFA). It's hoped that future research attempts R-R modeling by testing the general potential of ANN-IPSO method using datasets from different catchments.

## ACKNOWLEDGMENT

The authors thank the staff of the National Water Resources Agency (ANRH) of Algiers for providing all the data.

## REFERENCES

- [1] A. T. Benkaci and N. Dechemi, "modelisation pluie-debit mensuelle et journaliere par les models conceptuels et les systemes neuro flous (applications aux bassins algeriens)," Ecole Nat. Polytechn., Algiers, Algeria, Tech. Rep., 2006.
- [2] Y. Tikhmarine, D. Souag-Gamane, A. N. Ahmed, S. S. Sammen, O. Kisi, Y. F. Huang, and A. El-Shafie, "Rainfall-runoff modelling using improved machine learning methods: Harris hawks optimizer vs. particle swarm optimization," *J. Hydrol.*, vol. 589, Oct. 2020, Art. no. 125133, doi: 10.1016/j.jhydrol.2020.125133.
- [3] M. S. Turgut, O. E. Turgut, H. A. Afan, and A. El-Shafie, "A novel master-slave optimization algorithm for generating an optimal release policy in case of reservoir operation," *J. Hydrol.*, vol. 577, Oct. 2019, Art. no. 123959, doi: 10.1016/j.jhydrol.2019.123959.
- [4] V. Andréassian, C. Perrin, C. Michel, I. Usart-Sanchez, and J. Lavabre, "Impact of imperfect rainfall knowledge on the efficiency and the parameters of watershed models," *J. Hydrol.*, vol. 250, no. 1, pp. 206–223, Sep. 2001, doi: 10.1016/S0022-1694(01)00437-1.
- [5] S. M. Asokan and D. Dutta, "Analysis of water resources in the Mahanadi river basin, India under projected climate conditions," *Hydrological Processes*, vol. 22, no. 18, pp. 3589–3603, Aug. 2008, doi: 10.1002/hyp.6962.
- [6] Z. Wang, N. F. Attar, K. Khalili, J. Behmanesh, S. S. Band, A. Mosavi, and K.-W. Chau, "Monthly streamflow prediction using a hybrid stochastic-deterministic approach for parsimonious non-linear time series modeling," *Eng. Appl. Comput. Fluid Mech.*, vol. 14, no. 1, pp. 1351–1372, Jan. 2020, doi: 10.1080/19942060.2020.1830858.
- [7] B. Roy and M. P. Singh, "An empirical-based rainfall-runoff modelling using optimization technique," *Int. J. River Basin Manage.*, vol. 18, no. 1, pp. 49–67, Jan. 2020, doi: 10.1080/15715124.2019.1680557.
- [8] V. K. Vidyarthi, A. Jain, and S. Chourasiya, "Modeling rainfall-runoff process using artificial neural network with emphasis on parameter sensitivity," *Model. Earth Syst. Environ.*, vol. 6, no. 4, pp. 2177–2188, Dec. 2020, doi: 10.1007/s40808-020-00833-7.
- [9] J. Boisvert, N. El-Jabi, A. St-Hilaire, and S.-E. El Adlouni, "Parameter estimation of a distributed hydrological model using a genetic algorithm," *Open J. Mod. Hydrol.*, vol. 6, no. 3, pp. 151–167, 2016, doi: 10.4236/ojmh.2016.63013.
- [10] V. K. Vidyarthi and S. Chourasiya, "Particle swarm optimization for training artificial neural network-based rainfall-runoff model, case study: Jardine river basin," in *Micro-Electronics and Telecommunication Engineering* (Lecture Notes in Networks and Systems), vol. 106, D. K. Sharma et al., Eds. Singapore: Springer, 2020, pp. 641–647, doi: 10.1007/978-981-15-2329-8\_65.
- [11] F.-J. Chang, J.-M. Liang, and Y.-C. Chen, "Flood forecasting using radial basis function neural networks," *IEEE Trans. Syst., Man Cybern. C, Appl. Rev.*, vol. 31, no. 4, pp. 530–535, Nov. 2001, doi: 10.1109/5326.983936.
- [12] D. B. De Lima, M. D. C. E. Lima, and R. M. Saigado, "An empirical analysis of MLP neural networks applied to streamflow forecasting," *IEEE Latin Amer. Trans.*, vol. 9, no. 3, pp. 295–301, Jun. 2011, doi: 10.1109/TLA.2011.5893775.
- [13] M. R. M. Romlay, M. M. Rashid, S. F. Toha, and A. M. Ibrahim, "Rainfall-runoff model based on ANN with LM, BR and PSO as learning algorithms," *Int. J. Recent Technol. Eng.*, vol. 8, no. 3, Sep. 2019, Art. no. 3.
- [14] M. P. Rajurkar, U. C. Kothiyari, and U. C. Chaube, "Artificial neural networks for daily rainfall—Runoff modelling," *Hydrological Sci. J.*, vol. 47, no. 6, pp. 865–877, Dec. 2002, doi: 10.1080/02626660209492996.
- [15] R. S. Vilanova, S. S. Zanetti, and R. A. Cecilio, "Assessing combinations of artificial neural networks input/output parameters to better simulate daily streamflow: Case of Brazilian Atlantic rainforest watersheds," *Comput. Electron. Agricult.*, vol. 167, Dec. 2019, Art. no. 105080, doi: 10.1016/j.compag.2019.105080.
- [16] W.-C. Wang, D.-M. Xu, K.-W. Chau, and S. Chen, "Improved annual rainfall-runoff forecasting using PSO-SVM model based on EEMD," *J. Hydroinformatics*, vol. 15, no. 4, pp. 1377–1390, Oct. 2013, doi: 10.2166/hydro.2013.134.
- [17] Z. M. Yaseen, M. Fu, C. Wang, W. H. M. W. Mohtar, R. C. Deo, and A. El-Shafie, "Application of the hybrid artificial neural network coupled with rolling mechanism and grey model algorithms for streamflow forecasting over multiple time horizons," *Water Resour. Manage.*, vol. 32, no. 5, pp. 1883–1899, Mar. 2018, doi: 10.1007/s11269-018-1909-5.
- [18] G. Corani and G. Guariso, "Coupling fuzzy modeling and neural networks for river flood prediction," *IEEE Trans. Syst., Man Cybern. C, Appl. Rev.*, vol. 35, no. 3, pp. 382–390, Aug. 2005, doi: 10.1109/TSMCC.2004.843229.
- [19] O. I. Abiodun, A. Jantan, A. E. Omolara, K. V. Dada, N. A. Mohamed, and H. Arshad, "State-of-the-art in artificial neural network applications: A survey," *Heliyon*, vol. 4, no. 11, Nov. 2018, Art. no. e00938, doi: 10.1016/j.heliyon.2018.e00938.
- [20] D. Rumelhart, G. E. Hinton, and R. J. Williams. (1986). *Learning Representations by Back-Propagating Errors*. Accessed: 2020. [Online]. Available: <http://www.paper.com/Learning-representations-by-back-propagating-errors-Rumelhart-Hinton/052b1d8ce63b07fec3de9dbb583772d860b7c769>
- [21] M. Asadnia, L. H. C. Chua, X. S. Qin, and A. Talei, "Improved particle swarm optimization-based artificial neural network for rainfall-runoff modeling," *J. Hydrologic Eng.*, vol. 19, no. 7, pp. 1320–1329, Jul. 2014.
- [22] D. Devikanniga, K. Vetrivel, and N. Badrinath, "Review of meta-heuristic optimization based artificial neural networks and its applications," *J. Phys.*, vol. 1362, Nov. 2019, Art. no. 012074.
- [23] R. J. Bensingh, R. Machavaram, S. R. Boopathy, and C. Jebaraj, "Injection molding process optimization of a bi-aspheric lens using hybrid artificial neural networks (ANNs) and particle swarm optimization (PSO)," *Measurement*, vol. 134, pp. 359–374, Feb. 2019, doi: 10.1016/j.measurement.2018.10.066.
- [24] Q. Fang, H. Nguyen, X.-N. Bui, T. Nguyen-Thoi, and J. Zhou, "Modeling of rock fragmentation by firefly optimization algorithm and boosted generalized additive model," *Neural Comput. Appl.*, vol. 33, no. 8, pp. 3503–3519, Apr. 2021, doi: 10.1007/s00521-020-05197-8.
- [25] H. Tian, J. Shu, and L. Han, "The effect of ICA and PSO on ANN results in approximating elasticity modulus of rock material," *Eng. Comput.*, vol. 35, no. 1, pp. 305–314, Jan. 2019, doi: 10.1007/s00366-018-0600-z.
- [26] B. Jamali, M. Rasekh, F. Jamadi, R. Gandomkar, and F. Makiabadi, "Using PSO-GA algorithm for training artificial neural network to forecast solar space heating system parameters," *Appl. Thermal Eng.*, vol. 147, pp. 647–660, Jan. 2019, doi: 10.1016/j.applthermaleng.2018.10.070.
- [27] I. Istadi and N. A. S. Amin, "Modelling and optimization of catalytic-dielectric barrier discharge plasma reactor for methane and carbon dioxide conversion using hybrid artificial neural network—Genetic algorithm technique," *Chem. Eng. Sci.*, vol. 62, no. 23, pp. 6568–6581, Dec. 2007, doi: 10.1016/j.ces.2007.07.066.
- [28] S. Nandi, Y. Badhe, J. Lonari, U. Sridevi, B. S. Rao, S. S. Tambe, and B. D. Kulkarni, "Hybrid process modeling and optimization strategies integrating neural networks/support vector regression and genetic algorithms: Study of benzene isopropylation on Hbeta catalyst," *Chem. Eng. J.*, vol. 97, nos. 2–3, pp. 115–129, Feb. 2004, doi: 10.1016/S1385-8947(03)00150-5.

- [29] A. L. Ahmad, I. A. Azid, A. R. Yusof, and K. N. Seetharamu, "Emission control in palm oil mills using artificial neural network and genetic algorithm," *Comput. Chem. Eng.*, vol. 28, no. 12, pp. 2709–2715, Nov. 2004, doi: [10.1016/j.compchemeng.2004.07.034](https://doi.org/10.1016/j.compchemeng.2004.07.034).
- [30] A. Adib and A. Mahmoodi, "Prediction of suspended sediment load using ANN GA conjunction model with Markov chain approach at flood conditions," *KSCSE J. Civil Eng.*, vol. 21, no. 1, pp. 447–457, Jan. 2017, doi: [10.1007/s12205-016-0444-2](https://doi.org/10.1007/s12205-016-0444-2).
- [31] M. Aditya, C. Chandranath, and E. R. N. Singh, "Flood forecasting using ANN, neuro-fuzzy, and neuro-GA models," *J. Hydrologic Eng.*, vol. 14, no. 6, pp. 647–652, Jun. 2009, doi: [10.1061/\(ASCE\)HE.1943-5584.0000040](https://doi.org/10.1061/(ASCE)HE.1943-5584.0000040).
- [32] A. Jain and S. Srinivasulu, "Development of effective and efficient rainfall-runoff models using integration of deterministic, real-coded genetic algorithms and artificial neural network techniques," *Water Resour. Res.*, vol. 40, no. 4, Apr. 2004, Art. no. W04302, doi: [10.1029/2003WR002355](https://doi.org/10.1029/2003WR002355).
- [33] S. Asadi, J. Shahrabadi, P. Abbaszadeh, and S. Tabanmehr, "A new hybrid artificial neural networks for rainfall-runoff process modeling," *Neurocomputing*, vol. 121, pp. 470–480, Dec. 2013.
- [34] S. Panda and N. P. Padhy, "Comparison of particle swarm optimization and genetic algorithm for FACTS-based controller design," *Appl. Soft Comput.*, vol. 8, no. 4, pp. 1418–1427, Sep. 2008, doi: [10.1016/j.asoc.2007.10.009](https://doi.org/10.1016/j.asoc.2007.10.009).
- [35] K. W. Chau, "Particle swarm optimization training algorithm for ANNs in stage prediction of shing mun river," *J. Hydrol.*, vol. 329, nos. 3–4, pp. 363–367, Oct. 2006.
- [36] Z. M. Yaseen, W. H. M. W. Mohtar, A. M. S. Ameen, I. Ebtehaj, S. F. M. Razali, H. Bonakdari, S. Q. Salih, N. Al-Ansari, and S. Shahid, "Implementation of univariate paradigm for streamflow simulation using hybrid data-driven model: Case study in tropical region," *IEEE Access*, vol. 7, pp. 74471–74481, 2019, doi: [10.1109/ACCESS.2019.2920916](https://doi.org/10.1109/ACCESS.2019.2920916).
- [37] I. Ebtehaj, H. Bonakdari, S. Shamsheerband, Z. Ismail, and R. Hashim, "New approach to estimate velocity at limit of deposition in storm sewers using vector machine coupled with firefly algorithm," *J. Pipeline Syst. Eng. Pract.*, vol. 8, no. 2, May 2017, Art. no. 04016018, doi: [10.1061/\(ASCE\)PS.1949-1204.0000252](https://doi.org/10.1061/(ASCE)PS.1949-1204.0000252).
- [38] I. Ebtehaj and H. Bonakdari, "A support vector regression-firefly algorithm-based model for limiting velocity prediction in sewer pipes," *Water Sci. Technol.*, vol. 73, no. 9, pp. 2244–2250, May 2016, doi: [10.2166/wst.2016.064](https://doi.org/10.2166/wst.2016.064).
- [39] F. S. Moustafa, N. M. Badra, and A. Y. Abdelaziz, "Evaluation of the performance of different firefly algorithms to the economic load dispatch problem in electrical power systems," *Int. J. Eng.*, vol. 9, no. 2, p. 14, 2017.
- [40] A. Kavousi-Fard, H. Samet, and F. Marzbani, "A new hybrid modified firefly algorithm and support vector regression model for accurate short term load forecasting," *Expert Syst. Appl.*, vol. 41, no. 13, pp. 6047–6056, Oct. 2014, doi: [10.1016/j.eswa.2014.03.053](https://doi.org/10.1016/j.eswa.2014.03.053).
- [41] S. Łukasik and S. Żak, "Firefly algorithm for continuous constrained optimization tasks," in *Computational Collective Intelligence. Semantic Web, Social Networks and Multiagent Systems*, vol. 5796, N. T. Nguyen, R. Kowalczyk, and S.-M. Chen, Eds. Berlin, Germany: Springer, 2009, pp. 97–106.
- [42] T. Xiong, Y. Bao, and Z. Hu, "Multiple-output support vector regression with a firefly algorithm for interval-valued stock price index forecasting," *Knowl.-Based Syst.*, vol. 55, pp. 87–100, Jan. 2014, doi: [10.1016/j.knsys.2013.10.012](https://doi.org/10.1016/j.knsys.2013.10.012).
- [43] X.-S. Yang, "Firefly algorithm, stochastic test functions and design optimisation," 2010, *arXiv:1003.1409*. [Online]. Available: <http://arxiv.org/abs/1003.1409>
- [44] I. Brajevic and M. Tuba, "Training feed-forward neural networks using firefly algorithm," in *Recent Advances in Knowledge Engineering and Systems Science*. Jun. 2013.
- [45] Z. M. Yaseen, M. I. Ghareb, I. Ebtehaj, H. Bonakdari, R. Siddique, S. Heddami, A. A. Yusif, and R. Deo, "Rainfall pattern forecasting using novel hybrid intelligent model based ANFIS-FFA," *Water Resour. Manage.*, vol. 32, no. 1, pp. 105–122, 2017.
- [46] S. Darbandi and F. A. Pourhosseini, "River flow simulation using a multi-layer perceptron-firefly algorithm model," *Appl. Water Sci.*, vol. 8, no. 3, p. 9, Jun. 2018.
- [47] A. D. Mehr, V. Nourani, V. K. Khosrowshahi, and M. A. Ghorbani, "A hybrid support vector regression-firefly model for monthly rainfall forecasting," *Int. J. Environ. Sci. Technol.*, vol. 16, no. 1, pp. 335–346, 2019.
- [48] M. Tao, S. Huang, Y. Li, M. Yan, and Y. Zhou, "SA-PSO based optimizing reader deployment in large-scale RFID systems," *J. Netw. Comput. Appl.*, vol. 52, pp. 90–100, Jun. 2015, doi: [10.1016/j.jnca.2015.02.011](https://doi.org/10.1016/j.jnca.2015.02.011).
- [49] M. Asadnia, L. H. C. Chua, X. S. Qin, and A. Talei, "Improved particle swarm optimization-based artificial neural network for rainfall-runoff modeling," *J. Hydrol. Eng.*, vol. 19, no. 7, pp. 1320–1329, Jun. 2014, doi: [10.1061/\(ASCE\)HE.1943-5584.0000927](https://doi.org/10.1061/(ASCE)HE.1943-5584.0000927).
- [50] H. Ghazvinian, S.-F. Mousavi, H. Karami, S. Farzin, M. Ehteram, M. S. Hossain, C. M. Fai, H. B. Hashim, V. P. Singh, F. C. Ros, A. N. Ahmed, H. A. Afan, S. H. Lai, and A. El-Shafie, "Integrated support vector regression and an improved particle swarm optimization-based model for solar radiation prediction," *PLoS ONE*, vol. 14, no. 5, May 2019, Art. no. e0217634, doi: [10.1371/journal.pone.0217634](https://doi.org/10.1371/journal.pone.0217634).
- [51] *Décret exécutif N° 96-100 du 06 Mars 1996 Portant Définition du Bassin Hydrographique et Fixant le Statut—Type des Établissements Publics de Gestion*, ABH, Beverly Hills, CA, USA, 1996.
- [52] A. S. Gebregiorgis and F. Hossain, "Understanding the dependence of satellite rainfall uncertainty on topography and climate for hydrologic model simulation," *IEEE Trans. Geosci. Remote Sens.*, vol. 51, no. 1, pp. 704–718, Jan. 2013, doi: [10.1109/TGRS.2012.2196282](https://doi.org/10.1109/TGRS.2012.2196282).
- [53] A. Tarpanelli, E. Santi, M. J. Tourian, P. Filippucci, G. Amarnath, and L. Brocca, "Daily river discharge estimates by merging satellite optical sensors and radar altimetry through artificial neural network," *IEEE Trans. Geosci. Remote Sens.*, vol. 57, no. 1, pp. 329–341, Jan. 2019, doi: [10.1109/TGRS.2018.2854625](https://doi.org/10.1109/TGRS.2018.2854625).
- [54] A. Gholamy, V. Kreinovich, and O. Kosheleva, "Why 70/30 or 80/20 relation between training and testing sets: A pedagogical explanation," Dept. Comput. Sci., Univ. Texas El Paso, El Paso, TX, USA, Feb. 2018.
- [55] M. Jalal, Z. Grasley, C. Gurganus, and J. W. Bullard, "A new nonlinear formulation-based prediction approach using artificial neural network (ANN) model for rubberized cement composite," *Eng. Comput.*, pp. 1–18, May 2020, doi: [10.1007/s00366-020-01054-3](https://doi.org/10.1007/s00366-020-01054-3).
- [56] S. S. Sammen, M. A. Ghorbani, A. Malik, Y. Tikhmarine, M. Amirrahmani, N. Al-Ansari, and K.-W. Chau, "Enhanced artificial neural network with Harris hawks optimization for predicting scour depth downstream of ski-jump spillway," *Appl. Sci.*, vol. 10, no. 15, p. 5160, Jul. 2020.
- [57] B. Raheli, M. T. Aalami, A. El-Shafie, M. A. Ghorbani, and R. C. Deo, "Uncertainty assessment of the multilayer perceptron (MLP) neural network model with implementation of the novel hybrid MLP-FFA method for prediction of biochemical oxygen demand and dissolved oxygen: A case study of Langat River," *Environ Earth Sci.*, vol. 76, p. 503, Jul. 2017.
- [58] H. R. Maier and G. C. Dandy, "The effect of internal parameters and geometry on the performance of back-propagation neural networks: An empirical study," *Environ. Model.*, vol. 13, no. 2, pp. 193–209, 1998.
- [59] W. Wang, P. H. A. J. M. Van Gelder, J. K. Vrijling, and J. Ma, "Forecasting daily streamflow using hybrid ANN models," *J. Hydrol.*, vol. 324, nos. 1–4, pp. 383–399, 2006.
- [60] M. R. Zadeh, S. Amin, D. Khalili, and V. P. Singh, "Daily Outflow prediction by multi-layer perceptron with logistic sigmoid and tangent sigmoid activation functions," *Water Resour. Manage.*, vol. 24, pp. 2673–2688, Mar. 2010.
- [61] S. A. Kalogirou, "Artificial neural networks and genetic algorithms for the modeling, simulation, and performance prediction of solar energy systems," in *Assessment and Simulation Tools for Sustainable Energy Systems: Theory and Applications*, F. Cavallaro, Ed. London, U.K.: Springer, 2013, pp. 225–245.
- [62] B. Jamali, M. Rasekh, F. Jamadi, R. Gandomkar, and F. Makiabadi, "Using PSO-GA algorithm for training artificial neural network to forecast solar space heating system parameters," *Appl. Thermal Eng.*, vol. 147, pp. 647–660, Jan. 2019, doi: [10.1016/j.applthermaleng.2018.10.070](https://doi.org/10.1016/j.applthermaleng.2018.10.070).
- [63] K. W. Chau, "A split-step particle swarm optimization algorithm in river stage forecasting," *J. Hydrol.*, vol. 346, nos. 3–4, pp. 131–135, Nov. 2007, doi: [10.1016/j.jhydrol.2007.09.004](https://doi.org/10.1016/j.jhydrol.2007.09.004).
- [64] E. T. Mohamad, D. J. Armaghani, E. Momeni, and S. V. A. N. K. Abad, "Prediction of the unconfined compressive strength of soft rocks: A PSO-based ANN approach," *Bull. Eng. Geol. Environ.*, vol. 74, no. 3, pp. 745–757, Aug. 2015, doi: [10.1007/s10064-014-0638-0](https://doi.org/10.1007/s10064-014-0638-0).
- [65] X.-S. Yang. (2010). *Firefly Algorithms for Multimodal Optimization*. Accessed: Apr. 2020. [Online]. Available: [https://link.springer.com/chapter/10.1007/978-3-642-04944-6\\_14](https://link.springer.com/chapter/10.1007/978-3-642-04944-6_14)
- [66] X. S. Yang, "Firefly algorithm, stochastic test functions and design optimisation," *Int. J. Bio-Inspired Comput.*, vol. 2, no. 2, p. 78, 2010, doi: [10.1504/IJBIC.2010.032124](https://doi.org/10.1504/IJBIC.2010.032124).

- [67] X.-S. Yang, S. S. S. Hosseini, and A. H. Gandomi, "Firefly algorithm for solving non-convex economic dispatch problems with valve loading effect," *Appl. Soft Comput.*, vol. 12, no. 3, pp. 1180–1186, Mar. 2012, doi: [10.1016/j.asoc.2011.09.017](https://doi.org/10.1016/j.asoc.2011.09.017).
- [68] M. Alweshah, "Firefly algorithm with artificial neural network for time series problems," *Res. J. Appl. Sci., Eng. Technol.*, vol. 7, no. 19, pp. 3978–3982, May 2014, doi: [10.19026/rjaset.7.757](https://doi.org/10.19026/rjaset.7.757).
- [69] B. Keshtegar, P. Hao, Y. Wang, and Y. Li, "Optimum design of aircraft panels based on adaptive dynamic harmony search," *Thin-Walled Struct.*, vol. 118, pp. 37–45, Sep. 2017, doi: [10.1016/j.tws.2017.05.004](https://doi.org/10.1016/j.tws.2017.05.004).
- [70] B. Keshtegar, T. Ozbakkaloglu, and A. Gholampour, "Modeling the behavior of FRP-confined concrete using dynamic harmony search algorithm," *Eng. Comput.*, vol. 33, no. 3, pp. 415–430, Jul. 2017, doi: [10.1007/s00366-016-0481-y](https://doi.org/10.1007/s00366-016-0481-y).
- [71] R. M. Adnan, Z. Liang, S. Heddami, M. Zounemat-Kermani, O. Kisi, and B. Li, "Least square support vector machine and multivariate adaptive regression splines for streamflow prediction in mountainous basin using hydro-meteorological data as inputs," *J. Hydrol.*, vol. 586, Jul. 2020, Art. no. 124371, doi: [10.1016/j.jhydrol.2019.124371](https://doi.org/10.1016/j.jhydrol.2019.124371).
- [72] S. J. Hadi, S. I. Abba, S. S. Sammen, S. Q. Salih, N. Al-Ansari, and Z. M. Yaseen, "Non-linear input variable selection approach integrated with non-tuned data intelligence model for streamflow pattern simulation," *IEEE Access*, vol. 7, pp. 141533–141548, 2019, doi: [10.1109/ACCESS.2019.2943515](https://doi.org/10.1109/ACCESS.2019.2943515).
- [73] Ö. Kisi, "Constructing neural network sediment estimation models using a data-driven algorithm," *Math. Comput. Simul.*, vol. 79, no. 1, pp. 94–103, Oct. 2008, doi: [10.1016/j.matcom.2007.10.005](https://doi.org/10.1016/j.matcom.2007.10.005).
- [74] K. P. Sudheer, A. K. Gosain, and K. S. Ramasastri, "A data-driven algorithm for constructing artificial neural network rainfall-runoff models," *Hydrological Processes*, vol. 16, no. 6, pp. 1325–1330, Apr. 2002, doi: [10.1002/hyp.554](https://doi.org/10.1002/hyp.554).
- [75] K. Benzineb, "Modelisation des debits de crues du bassin de oued ouahrane par Les reseaux de neurones artificiels," *J. Fundam. Appl. Sci.*, 2017. [Online]. Available: <http://www.jfas.info>
- [76] F. S. Panchal and M. Panchal, "Review on methods of selecting number of hidden nodes in artificial neural network," *Int. J. Comput. Sci. Mobile Comput.*, vol. 3, no. 11, pp. 455–464, 2014.
- [77] D.-C. Lo, C.-C. Wei, and E.-P. Tsai, "Parameter automatic calibration approach for neural-network-based cyclonic precipitation forecast models," *Water*, vol. 7, no. 12, pp. 3963–3977, Jul. 2015, doi: [10.3390/w7073963](https://doi.org/10.3390/w7073963).
- [78] G. Panchal, A. Ganatra, Y. P. Kosta, and D. Panchal, "Behaviour analysis of multilayer perceptrons with multiple hidden neurons and hidden layers," in *Proc. IJCTE*, 2011, pp. 332–337, doi: [10.7763/IJCTE.2011.V3.328](https://doi.org/10.7763/IJCTE.2011.V3.328).
- [79] S. Lallahem and J. Mania, "Evaluation and forecasting of daily groundwater outflow in a small chalky watershed," *Hydrological Processes*, vol. 17, no. 8, pp. 1561–1577, Jun. 2003, doi: [10.1002/hyp.1199](https://doi.org/10.1002/hyp.1199).
- [80] S. Riad, J. Mania, L. Bouchaou, and Y. Najjar, "Predicting catchment flow in a semi-arid region via an artificial neural network technique," *Hydrological Processes*, vol. 18, no. 13, pp. 2387–2393, Sep. 2004, doi: [10.1002/hyp.1469](https://doi.org/10.1002/hyp.1469).
- [81] M. Aqil, I. Kita, A. Yano, and S. Nishiyama, "A comparative study of artificial neural networks and neuro-fuzzy in continuous modeling of the daily and hourly behaviour of runoff," *J. Hydrol.*, vol. 337, nos. 1–2, pp. 22–34, Apr. 2007, doi: [10.1016/j.jhydrol.2007.01.013](https://doi.org/10.1016/j.jhydrol.2007.01.013).
- [82] M. Jahandideh-Tehrani, G. Jenkins, and F. Helfer, "A comparison of particle swarm optimization and genetic algorithm for daily rainfall-runoff modelling: A case study for southeast Queensland, Australia," *Optim. Eng.*, vol. 22, no. 1, pp. 29–50, Mar. 2021, doi: [10.1007/s11081-020-09538-3](https://doi.org/10.1007/s11081-020-09538-3).
- [83] A. K. Lohani, N. K. Goel, and K. K. S. Bhatia, "Comparative study of neural network, fuzzy logic and linear transfer function techniques in daily rainfall-runoff modelling under different input domains," *Hydrological Processes*, vol. 25, no. 2, pp. 175–193, Jan. 2011, doi: [10.1002/hyp.7831](https://doi.org/10.1002/hyp.7831).
- [84] V. K. Vidyarthi, A. Jain, and S. Chourasiya, "Modeling rainfall-runoff process using artificial neural network with emphasis on parameter sensitivity," *Model. Earth Syst. Environ.*, vol. 6, no. 4, pp. 2177–2188, Dec. 2020, doi: [10.1007/s40808-020-00833-7](https://doi.org/10.1007/s40808-020-00833-7).
- [85] K. E. Taylor, "Summarizing multiple aspects of model performance in a single diagram," *J. Geophys. Research: Atmos.*, vol. 106, no. D7, pp. 7183–7192, Apr. 2001, doi: [10.1029/2000JD900719](https://doi.org/10.1029/2000JD900719).
- [86] M. Jahandideh-Tehrani, G. Jenkins, and F. Helfer, "A comparison of particle swarm optimization and genetic algorithm for daily rainfall-runoff modelling: A case study for southeast Queensland, Australia," *Optim. Eng.*, vol. 22, no. 1, pp. 29–50, Mar. 2021, doi: [10.1007/s11081-020-09538-3](https://doi.org/10.1007/s11081-020-09538-3).
- [87] A. D. Mehr, V. Nourani, V. K. Khosrowshahi, and M. A. Ghorbani, "A hybrid support vector regression–firefly model for monthly rainfall forecasting," *Int. J. Environ. Sci. Technol.*, vol. 16, no. 1, pp. 335–346, Jan. 2019, doi: [10.1007/s13762-018-1674-2](https://doi.org/10.1007/s13762-018-1674-2).
- [88] S. Darbandi and F. A. Pourhosseini, "River flow simulation using a multi-layer perceptron-firefly algorithm model," *Appl. Water Sci.*, vol. 8, no. 3, p. 85, Jun. 2018, doi: [10.1007/s13201-018-0713-y](https://doi.org/10.1007/s13201-018-0713-y).



**YAMINA AOULMI** received the degree in engineering and the master's degree in hydraulics from the National Polytechnic School of Algiers, Algeria, in 2018. She is currently pursuing the Ph.D. degree with L'arbi Ben M'hidi University, Algeria. She is currently a Field Engineer with multinational company Schlumberger, Algeria. Her current research interests include water resources, hydrological modeling using artificial intelligence, optimization algorithms, and deep learning.



**NADIR MAROUF** received the degree from the Higher National School of Hydraulics (ENSH), Blida, Algeria, the Magister degree from ENSH, in 2002, and the Ph.D. degree from Biskra University, in 2012. He was promoted to a Senior Lecturer A, in 2015. He has been appointed as the Head of the Department of Hydraulic, since 2004. He is currently teaching with the Department of Hydraulic, University of Oum El Bouaghi, Algeria. He is also the chairman of scientific committee and doctoral training of department. He is the author of several scientific publications in international journals. His research interests include open channel flow, sediment transport, hydrology, modelization, and environmental analyses.



**MOHAMED AMIRECHE** received the engineer's diploma degree in hydraulics from the National Polytechnic School and the Doctorate in Science degree in civil engineering, with a focus on hydraulic structures. He is currently an Assistant Professor and the Head of the Department of Hydraulics, University Larbi Ben Mhidi, Oum El Bouaghi, Algeria. He conducted research on transient regimes in pipes under load. He is also working on the modeling of the rainfall-runoff relationship and the forecasting of floods in the Algerian basins.



**OZGUR KISI** received the B.Sc. degree from the Department of Civil Engineering, Faculty of Engineering, Çukurova University, Turkey, in 1997, the M.Sc. degree from the Hydraulics Division, Institute of Science and Technology, Erciyes University, Turkey, in 1999, and the Ph.D. degree from the Hydraulics Division, Institute of Science and Technology, Istanbul Technical University, Turkey, in 2003. He has been working as a Professor with Ilia State University. He is an active participant in numerous national research projects and supervisor of several M.Sc. and Ph.D. works. He is the author of several peer-reviewed scientific publications. He has authored more than 500 research articles, 12 chapters, and 30 discussions (Web of Science H-index = 60, Google Scholar H-index = 77; and Scopus H-index 65). He is also serving as a reviewer for more than 90 journals indexed in Science Citation Index (SCI) in the fields of hydrology, irrigation, water resources, and hydro informatics. His research fields are developing novel algorithms and methods towards the innovative solution of hydrologic forecasting and modeling; suspended sediment modeling; forecasting, estimating, spatial, and temporal analysis of hydro-climatic variables, such as precipitation, streamflow, suspended sediment, evaporation, evapotranspiration, groundwater, lake level, and water quality parameters; and hydro-informatics. He is serving as an Editorial Board Member of several reputed journals, such as *Journal of Hydrologic Engineering (ASCE)*, *Hydrology Research*, *Hydrological Sciences Journal*, *Sustainability*, and *Arabian Journal of Geosciences*. He is a Principle Member of the Turkish Academy of Science (selected in 2012, see [http://www.tuba.gov.tr/en/members/all-members/principal-members?&\\_pp=12&per\\_page=48](http://www.tuba.gov.tr/en/members/all-members/principal-members?&_pp=12&per_page=48)). He was a recipient of the 2006 International Tison Award from the International Association of Hydrological Sciences (IAHS; URL: <http://iahs.info/About-IAHS/Competition-Events/Tison-Award/Tison-Award-winners/OKisi.do>). According to Webometrics (in 2016 and 2017), his ranking in Turkey was 67 and 51, respectively ([http://yunus.hacettepe.edu.tr/~sadi/yayin/Ranking\\_Web\\_of\\_Universities\\_Turkey\\_Ocak2016.pdf](http://yunus.hacettepe.edu.tr/~sadi/yayin/Ranking_Web_of_Universities_Turkey_Ocak2016.pdf) and [http://www.ihsandag.gen.tr/index\\_dosyalar/RankingofscientistsinTurkish.pdf](http://www.ihsandag.gen.tr/index_dosyalar/RankingofscientistsinTurkish.pdf)). He had 7th rank in his field according to the database (list of top 2% scientists in the world) developed by Stanford University (<https://drive.google.com/file/d/1bUJrVurVVbBxS19eFZRSHFif7tt30-5U/view>). The details of the database preparation can be obtained from the published report (<https://journals.plos.org/plosbiology/article?id=10.1371/journal.pbio.3000918>). He has also served as a Guest Editor for Special Issues published in *Hydrological Hazards in a Changing Environment-Early Warning, Forecasting, and Impact Assessment (Advances in Meteorology)*, in 2015.



**RAED M. SHUBAIR** received the B.Sc. degree (Hons.) in electrical engineering from Kuwait University, in 1989, and the Ph.D. degree (Hons.) in electrical engineering from the University of Waterloo, in 1993.

He started his academic career as a University Professor, in 1993. His past affiliations also include visiting academic and research appointments with the University of Waterloo, Massachusetts Institute of Technology (MIT), and Harvard Medical School. He is currently a Full Professor of electrical engineering affiliated with New York University (NYU), Abu Dhabi, where he is also the Founder and the Chair of the IEEE Chapter and Adjunct Professor of engineering. Prior to his affiliation at NYU, Abu Dhabi, he was a Full Professor with Khalifa University, from 1993 to 2017. He has more than 350 publications in the form of U.S. patents, book chapters, and refereed articles in peer-reviewed journals and indexed conference proceedings. His current research interests include RF/microwave technologies, smart integrated antennas and radio systems, mm-wave/terahertz integrated technologies, nano-EM and photonics, EM in health science and biomedicine, bio-electromagnetics, medical sensing, new EM materials, wireless sensors and networks wireless communications, adaptive array processing, machine learning, and computational methods.

Dr. Shubair is a fellow of the MIT Electromagnetics Academy and a Founding Member of MIT Scholars of the Emirates. He is also a Standing Member of the editorial boards of several international journals and serves regularly on the steering, organizing, and technical committees of IEEE flagship conferences in antennas, communications, and signal processing, including several editions of IEEE AP-S/URSI, EuCAP, IEEE GlobalSIP, IEEE WCNC, and IEEE ICASSP. He is also a Founding Member of five IEEE society chapters, UAE, which are IEEE UAE Communication Society Chapter, IEEE UAE Signal Processing Society Chapter, IEEE UAE Antennas and Propagation Society Chapter, IEEE UAE Microwave Theory and Techniques Society Chapter, and IEEE UAE Engineering in Medicine and Biology Society Chapter. He is a Board Member of the European School of Antennas, the Regional Director for the IEEE Signal Processing Society in IEEE Region 8 the Middle East, and the Chair of the IEEE Antennas and Propagation Society Educational Initiatives Program. He is a Board Member of the European School of Antennas, Middle East Liaison of European Conference on Antennas and Propagation, a member of IEEE Signal Processing PROGRESS initiative, and Global Publicity Officer for IEEE ComSoc Machine Learning for Communications Emerging Technical Initiative. He is the Director of IEEE UAE Distinguished Seminar Series Program. He is also the Regional Director of the IEEE Signal Processing Society, Middle East, and the Chair of the IEEE Innovation and Research. He was a recipient of the IEEE UAE Award of the Year, in 2020. His Ph.D. thesis received the University of Waterloo's "Distinguished Doctoral Dissertation Award," in 1993. He received the "Teaching Excellence Award" and "Distinguished Service Award." He was nominated for the IEEE Distinguished Educator Award of the IEEE Antennas and Propagation Society and received the "Distinguished Service Award" from both ACES Society, USA, and from MIT Electromagnetics Academy, USA. He is also a nominee for the Regional Director-at-Large of the IEEE Signal Processing Society in IEEE Region 8 Europe, Africa, and the Middle East. He is also a nominee for the IEEE Distinguished Educator Award of the IEEE Antennas and Propagation Society. He has been honored to serve as an Invited Speaker with the prestigious U.S. National Academies of Sciences, Engineering, and Medicine. He organized and chaired numerous technical special sessions and tutorials in IEEE flagship conferences. In addition to his paper presentation at technical conferences, he delivered over 65 invited speaker seminars and technical talks in world-class universities and flagship conferences. He has served as a TPC Chair for the IEEE MMS2016 and IEEE GlobalSIP 2018 Symposium on 5G Satellite Networks. He holds several leading roles in the international professional engineering community. He is an Editor of IEEE JOURNAL OF ELECTROMAGNETICS, RF AND MICROWAVES IN MEDICINE AND BIOLOGY and IEEE OPEN JOURNAL OF ANTENNAS AND PROPAGATION.



**BEHROOZ KESHTEGAR** is currently an Associate Professor with the Department of Civil Engineering, Zabol University, Zabol, Iran. His research interests are structural reliability analysis, reliability-based design optimization, data driven-based modeling approaches, and artificial intelligent-based optimization. He has been working on different topics of structural reliability analysis, including chaos control approach, conjugate sensitivity methods and optimization method, such as harmony search and the hybrid AI methods. He established several models as predicted approach for estimation the complex engineering problems in mechanical/civil field under multi-uncertainties. He can code the numerical methods in a computer program to solve and to analysis of engineering problems in optimization, modeling, and reliability fields. These interesting fields are the novel numerical approaches, predicted models, computational frameworks, and optimization algorithms.

...