

Received August 20, 2021, accepted September 6, 2021, date of publication September 14, 2021, date of current version September 27, 2021.

Digital Object Identifier 10.1109/ACCESS.2021.3112806

OPCNN-FAKE: Optimized Convolutional Neural Network for Fake News Detection

HAGER SALEH¹, ABDULLAH ALHARBI², AND SAEED HAMOOD ALSAMHI^{3,4}

¹Faculty of Computers and Artificial Intelligence, South Valley University, Hurghada 83523, Egypt

²Department of Information Technology, College of Computers and Information Technology, Taif University, Taif 21944, Saudi Arabia

³Athlone Institute of Technology, Athlone, N37HD68 Ireland

⁴Department of Electrical Engineering, IBB University, Ibb, Yemen

Corresponding author: Hager Saleh (hager.saleh.fci@gmail.com)

This work was supported by Taif University Researchers Supporting Project, Taif University, Taif, Saudi Arabia, under Grant TURSP-2020/231.

ABSTRACT Recently, there is a rapid and wide increase in fake news, defined as provably incorrect information spread with the goal of fraud. The spread of this type of misinformation is a severe danger to social cohesiveness and well-being since it increases political polarisation and people's distrust of their leaders. Thus, fake news is a phenomenon that is having a significant impact on our social lives, particularly in politics. This paper proposes novel approaches based on Machine Learning (ML) and Deep Learning (DL) for the fake news detection system to address this phenomenon. The main aim of this paper is to find the optimal model that obtains high accuracy performance. Therefore, we propose an optimized Convolutional Neural Network model to detect fake news (OPCNN-FAKE). We compare the performance of the OPCNN-FAKE with Recurrent Neural Network (RNN), Long Short-Term Memory (LSTM), and The six regular ML techniques: Decision Tree (DT), logistic Regression (LR), K Nearest Neighbor (KNN), Random Forest (RF), Support Vector Machine (SVM), and Naive Bayes (NB) using four fake news benchmark datasets. Grid search and hyperopt optimization techniques have been used to optimize the parameters of ML and DL, respectively. In addition, N-gram and Term Frequency—Inverse Document Frequency (TF-IDF) have been used to extract features from the benchmark datasets for regular ML, while Glove word embedding has been used to represent features as a feature matrix for DL models. To evaluate the performance of the OPCNN-FAKE, accuracy, precision, recall, F1-measure were applied to validate the results. The results show that OPCNN-FAKE model has achieved the best performance for each dataset compared with other models. Furthermore, the OPCNN-FAKE has a higher performance of cross-validation results and testing results over the other models, which indicates that the OPCNN-FAKE for fake news detection is significantly better than the other models.

INDEX TERMS Fake news, machine learning, deep learning, neural network, convolutional neural network, detection, OPCNN-FAKE.

I. INTRODUCTION

In recent years, the ability of a user to write anything on online news platforms such as social media and news websites newspapers has led to the propagation of misleading information [1]. Online social media platforms (Twitter, Facebook, Instagram, YouTube, etc.) have become the primary source of news for people around the world, particularly in developing nations. Therefore, anyone from anywhere in the world can use popular social media and social networking as platforms

The associate editor coordinating the review of this manuscript and approving it for publication was Cheng Chin¹.

to publish any statement and spread fake news through various networking sites to achieve various goals, which may be illegitimate.

We are currently experiencing significant ramifications for society, business, and culture as a result of the increasing use of social media, which have the potential to be both detrimental and beneficial [2].

Fake news is widely regarded as one of the most severe dangers to global commerce, journalism, and democracy, with significant collateral harm. The stock market suffered a \$130 billion loss as a result of a false news story saying that the US President Barack Obama had been injured in an

explosion [3]. According to statistics published by Stanford University academics, 72.3 percent of fake news originates from official news outlets and online social media platforms [4]. Because of the negative impact of fake news on society, and as fake news is widely regarded as one of the most serious challenges to global commerce, media, and democracy, posing significant societal harm to them, it is critical to build effective fake news detection systems.

With the rapid advances in Artificial Intelligence (AI), a significant number of experiments are being undertaken to tackle issues that were never addressed in the framework of computer science, such as fake news detection [5]–[8]. Automatic detection approaches based on Machine Learning (ML) have been studied to combat the emergence and dissemination of false news. The majority of fake news detection systems utilize ML approaches to help consumers in filtering the content they are seeing and determining if a given news piece is misleading or not [5], [9]. Deep Learning (DL) techniques recent accomplishments in difficult natural language processing tasks make them viable for detecting fake news effectively and efficiently. Creating automatic, trustworthy, and accurate systems for identifying fake news on social media is a trending topic of research. The process of determining if a certain news item on any field, from any social media domain, is purposefully or inadvertently misleading might be characterized as fake news detection [6]–[8]. Convolutional Neural Network (CNN) has been prominent in many fields with the best performance, including computer vision [10], smart building structures [11], and natural language processing [12]. CNN uses convolution layers, pooling layers, and fully connected layers to extract more features with high-level and low-level features. Therefore, we have proposed an Optimal CNN model for Fake news detection (OPCNN-Fake) that can extract high-level and low-level features from the dataset to detect fake news, and it has registered the best performance compared with others models.

A. MOTIVATION AND CONTRIBUTION

Fake news has an effect on journalism, global commerce, and democracy, with significant collateral harm. Fake news detection is an area of artificial intelligence that has attracted the curiosity of researchers from all over the world. Unfortunately, regular ML techniques have not provided significant performance for the detection of fake news. On the other side, DL is more efficient for extracting features of fake news detection than Regular ML due to its capability to deep extraction of high and low levels. In this paper, we propose an efficient OPCNN-FAKE model based on optimized CNN for detecting fake news. Furthermore, CNN can extract more features by using different layers. The contributions of this study are as follows:

We propose the OPCNN-Fake model for detecting fake news; the proposed model uses various layers to extract high-level and low-level features. Also, we optimized OPCNN-FAKE by selecting the best values of

OPCNN-FAKE's parameters in each layer using the hyper-opt optimization technique. In addition, we utilized four benchmark datasets, where each one is divided into a 20% testing dataset and an 80% training dataset. We evaluated the performance of the OPCNN-FAKE model based on accuracy, precision, recall, F1-measure. Furthermore, we compared the performance of OPCNN-FAKE with different models, DT, RF, SVM, NB, LR, KNN, RNN, and LSTM. Then, we registered the results for cross-validation (training set) and the testing set (unseen data). The experimental results demonstrated the effectiveness of the OPCNN-FAKE significant performance compared to other models. And this shows that our OPCNN-FAKE can effectively and efficiently detect fake news with high level of accuracy.

B. PAPER ORGANIZATION

The remainder of the paper is organized as follows: Section II reviews related works on fake news detection. The proposed OPCNN-FAKE model in this paper is presented in Section III. The experimental results, as well as a comparison to the baseline categorization and discussion are presented in Section IV. Finally, Section V provides a summary of the paper.

II. RELATED WORK

This section covers a variety of machine learning algorithms for detecting fake news. Jing [13] have proposed model-based to build hidden representations that capture changes in contextual information in relevant posts over time. They conducted experiments using 5 million postings that were collected from Twitter and Sina Weibo microblogs. They made a comparison between DT, RF, SVM, LSTM and Gated Recurrent Unit (GRU), and RNN. On the same dataset, another study developed a hybrid DL model. Ruchansky *et al.*, [14] proposed a model which includes three modules: Capture, Score, and Integrate (CSI). The capture module has used LSTM and RNN to extract from particular article mundane patterns of user activity.

Score module has used a fully connected neural network layer to capture characteristics from users' behavior. Both models have integrated with the third model to classify articles as fake or not. Shu *et al.* [15] released the FakeNewsNet dataset and applied different algorithms to a dataset: SVM, LR, NB, and CNN. Salem, *et al.* [16] used the FA-KES dataset that comprises news events around the Syrian war. There are 804 news articles in the collection, 376 of which are fraudulent. Semi-supervised with a fact-checking labeling approach were used to annotations dataset. However, the dataset can be used to train machine learning models for detecting fake news. Popat *et al.* [17] introduced DeClarE, an end-to-end neural network model for debunking fake news and fraudulent claims. To support or reject a claim, it uses evidence and counter-evidence gathered from the internet. The authors trained a bi-directional LSTM model with at least four different datasets and achieved an overall classification accuracy of 80%. Ksieniewicz *et al.* [18]

TABLE 1. Summary of the comparison of the existing work.

Ref.	Highlighted	Techniques	Datasets Name	Optimization methods
[33] (2020)	FakeNewsNet description and fakeNewsNet benefits	SVM LR, CNN, NB	FakeNewsNet	No
[27] (2020)	Hybrid CNN-LSTM to classify the fake news.	hybrid CNN-LSTM model	Fake news dataset from Kaggle	No
[29] (2021)	Hybrid CNN-RNN for fake news classification	LR, SVM, NB, Stochastic Gradient Decent (SDG), Ada Boost, RNN, CNN hybrid CNN-RNN	ISOT dataset FA-KES dataset	No
[28] (2020)	FNDNet model for fake news detection which can learn the features for fake news automatically	RNN, CNN, FNDNet (deep CNN)	Dataset from Kaggle	yes
[32] (2021)	The substance of the news piece and the prevalence of echo chambers in the social network.	Deep neural network	BuzzFeed PolitiFact	No
[31] (2021)	Proposing DeepFakE model for fake news article and also echo chambers existence.	XGBoost and DeepFakE: a multi-layer deep neural network	BuzzFeed PolitiFact	No
[30] (2019)	MCNN-TFW, a multiple-level CNN-based fake news detection system in cultural communication	MCNN	Weibo NewsFN	No
Our work	OPCNN-FAKE for detecting fake news. Applying optimization method for OPCNN-FAKE, LSTM, RNN and ML modes to enhance performance. Comparing OPCNN-FAKE with ML models, RNN, and LSTM using four benchmark datasets. The performance of models was registered for cross-validation results and testing results.	OPCNN-FAKE, SVM, NB, LR, DT, RF, RNN, LSTM,	Four datasets: Dataset1 FakeNewsNet FA-KES5 ISOT	Yes

proposed decision tree ensembles diversified using the Random Subspace method to detect fake news.

Singh, *et al.* [19] proposed an Attention-based LSTM network that uses tweet text with thirteen different linguistic and user features to distinguish rumor and non-rumor tweets. They compared the Attention-based LSTM network with various conventional machines and DL models. The results showed that Attention-based LSTM network has achieved the best performance. Ahmed *et al.* [20] proposed the ISOT dataset, made comparison between six machine learning models using n-gram with two feature extraction techniques: Term Frequency (TF) and Term Frequency — Inverse Document Frequency (TF-IDF) to the ISOT dataset. Pérez-Rosas, *et al.* [21] also developed classification models using linguistic features such as lexical, syntactic, and semantic level features and a linear SVM to detect fake and real news. CNN have been utilised in a variety of computer vision in recent years, and they have improved the state-of-the-art performance of a variety of visual classification tasks, such as image processing [22], face verification [23], object recognition [24], and natural language processing tasks [25].

Yang, *et al.* [26] proposed a model using Text and Image information based CNN (TI-CNN). They compared their model with several models such as LSTM, CNN, and GRU using two datasets. Abdullah, A., *et al.* [27] used CNN and LSTM to classify the fake news articles that achieved significant performance. They conducted their experiments using one Fake news dataset from Kaggle.

To detect fake news, the authors of [28] proposed a Deep Convolutional Neural Network (FNDNet) to learn the discriminatory features for fake news detection. Furthermore, the authors of [29] introduced a hybrid deep learning model that blends CNN and RNN. for the same aim of detecting fake news articles, the authors of [27] presented CNN and LSTM to categorize fake news to produce significant results. Also, the authors of [30] developed multi-level CNN, which incorporated local and global convolutional features to collect semantic information from article texts efficiently, [31]. Also, the authors of [32] focused on the substance news piece and the presence of echo chambers in the social network. Table. 1 summaries the comparison of the existing works and our proposed work.

III. FAKE NEWS DETECTION SYSTEM

Figure 1 presents the main steps of the proposed system. It consists many steps: fake news data collection, text pre-processing, dataset splitting, features extraction methods, models training/optimization, and models evaluation. There are two approaches in the proposed system: the regular ML approach and the DL approach. In the ML approach, six ML models: DT, LR, KNN, RF, SVM, and NB are used to train and evaluate the model. Different sizes of n-gram, including uni-gram, bi-gram, tri-gram, and four-gram with TF-ID feature extraction method are used to extract features and build matrix features. Grid search with cross-validation




FIGURE 1. The architecture of the proposed system.

is used to optimize the ML models. In the DL approach, the OPCNN-FAKE model is proposed and LSTM, RNN are used to train and evaluate the model. The hyperopt optimization method is used to optimize the OPCNN-FAKE, RNN and LSTM. Word embedding is used for feature extraction. Also, we compared the OPCNN-FAKE model with RNN and LSTM. Word embedding is used to build a feature matrix. Each step is described in detail as following.

A. FAKE NEWS DATASET

We trained, optimized, and evaluated models using four datasets. Each dataset was split into 80% training dataset and 20% testing dataset (unseen data). In this section, these datasets are introduced as following.

1) DATASET1

Fake News detection was collected from Kaggle [34]. There are 3988 news articles in this dataset. In addition to the body of the text, each article includes a headline and a list of URLs. There is also a class label with the values “0” for fake news and “1” for real news. Only the article body and headline can be used in models. The 1868 articles are real news, while the remaining 2120 are fake news. The statistics of the training set and testing set for dataset1 are shown in Table 2.

2) FakeNewsNet (DATASET2)

FakeNewsNet [33] dataset includes data about two topics: gossipco and politifact. Each topic includes two files.

TABLE 2. The statistics of dataset1.

Dataset	News type	Total size
Training dataset	Real news	1494
	Fake news	1696
Testing dataset	Real news	374
	Fake news	424

There are two files in the politifact dataset: `politifact_real.csv`, includes 432 tweets and contains samples relevant to real news. `politifact_fake.csv` contains 618 tweets and samples related to fake news.

There are two files in the gossipco dataset: `gossipcop_real.csv`, which includes 5328 tweets and contains samples relevant to real news. `gossipcop_fake.csv` contains 5322 tweets and samples related to fake news.

Each file includes id, URL, title, and tweet. We created a new dataset merged between four files and added a new column; the label column consists of two values: 0 belongs to fake news and 1 belongs to real news. The total number of tweets is 44280 tweets. The FakeNewsNet has been split into 80% training set and 20% testing set. The statistics of the training set and testing set for dataset3 are shown in Table 3.

TABLE 3. The statistics of FakeNewsNet (dataset2).

Dataset	News type	Total size
Training dataset	Real news	26907
	Fake news	8517
Testing dataset	Real news	6727
	Fake news	2129

3) FA-KES5 (DATASET3)

The FAKES5 [16] dataset includes 804 article news about Syrian war. Also, it includes a set of articles labeled by 0 (fake) or 1 (real). Each article has the headline, date, location, and full body of text. The 426 articles are true, and the 376 are fake. The statistics of the training set and testing set for dataset3 are shown in Table 4.

TABLE 4. The statistics of the dataset3.

Dataset	News type	Total size
Training dataset	Real news	341
	Fake news	302
Testing dataset	Real news	85
	Fake news	76

4) THE ISOT (DATAET4)

The ISOT dataset [20] consists of 44202 news articles, the 21416 news are true and 22756 of news are fake. Real news were collected from the Reuters website, and fake news were collected from Wikipedia⁷ and from Politifact website. Each news consists of title, text, date, and subject. The dataset includes two files: fake file and real file. We created a new dataset merged between two files and added a new column; the label column consists of two values as 0 for fake news

and 1 for real news. The statistics of the training set and the testing set for dataset4 are shown in Table 5.

TABLE 5. The statistics of The ISOT (dataset4).

Dataset	News type	Total size
Training dataset	Real news	17133
	Fake news	18204
Testing dataset	Real news	4283
	Fake news	4552

B. DATA PREPROCESSING

Data preprocessing is a critical step of natural language processing, such as fake news detection, as it directly impacts the model's effectiveness to the complexity of the data. Fake news datasets consist of many links, hashtags, special symbols, etc. Therefore, we applied many steps of preprocessing to each dataset. These steps are as follows.

- **Lower casing:** The most effective kind of text preprocessing is lowercasing, which ensures correlation within the feature set and solves the sparsity problem.
- **Removal of URL's:** Irrelevant links embedded into news have been removed.
- **Removal of special symbols** such as punctuations, emojis, ,, , ' , ; #, \$, %, & etc.
- **Removal of Stop Word:** Stop words are small words in a language that are useless in text mining and are utilised to structure language grammar. These stop words have been filtered away, including articles, conjunctions, prepositions, some pronouns, and common terms like the, a, an, about, by, from, to, and so on.
- **Tokenization** Tokenization in preprocessing is the process of dividing lengthy text sequences into tokens (i.e., smaller pieces). For example, consider this sentence before tokenization: "Fake news dataset", after tokenization it comes 'Fake', 'news',' dataset'.
- **Stemming** The stemming step is the process of changing the words into their original form. For example, the words " Walking", " Walked" and "Walker" will be reduced to the word "walk".

C. DATA SPLITTING

Using a stratified technique, each dataset is divided into 80% training dataset and 20% testing dataset (unseen dataset). The training dataset is used to optimize and train the machine learning models and deep learning models, while the unseen dataset is used to evaluate the machine learning models and deep learning models.

D. FEATURE EXTRACTION METHODS

N-gram with TF-IDF are used to extract features for the ML models and build feature matrix. To describe the context of the text, we employed several sizes of N-gram approach, ranging from $n = 1$ to $n = 4$ (i.e., uni-gram, bi-gram, tri-gram, and four-gram). TF-ID assigns a weight to each word




FIGURE 2. The architecture of the proposed OPCNN-FAKE model.

representing the importance of the word in the document and corpus.

Word embedding is a technique for converting text data (words) into vectors. Every word is represented as an n -dimensional dense vector, with vectors that are comparable for similar words. We used the Golve [35] for word embedding to build embedding matrix. GloVe is an unsupervised learning technique that generates word vector representations. The resulting representations highlight intriguing linear substructures of the word vector space, which are trained using aggregated global word-word co-occurrence statistics from a corpus. We utilised glove.6B.zip, which contains vectors in four different dimensions: 25d, 50d, 100d, and 200d. The embedding matrix was constructed using 200d vectors.

E. THE PROPOSED MODEL (OPCNN-FAKE)

In this section, we describe the architecture of the proposed OPCNN-FAK model as shown in Figure 2 that is used to detect fake news. Also, we describe optimization methods to select the best values for OPCNN-FAKE's parameters. OPCNN-FAK consists of six layers: an embedding layer, dropout layer, a convolutional layer, a pooling layer, flatten layer, and an output layer.

- **In the embedding layer**, each news is embedded at the word level and is represented as a matrix with each row corresponding to a word. It is implemented in the Keras library [36]. It has three arguments: the input-dim parameter represents the vocabulary size in the dataset, the output-dim parameter describes the vector space in which words will be embedded, and the input-length parameter describes the length of input sequences. We configured the output-dim as 200 because the length of Golve is 200d vectors and input-dim as 20000, and the input-length as 32.
- **The dropout layer** is an efficient regularization technique that prevents overfitting and reduces the complexity of model [37]. It receives the output of the embedding layer. We adopted the value of dropout using optimization methods range from 0.1 to 0.9.

- **Convolutional layer** receives the output of the dropout layer to reduce the complexity of the model. It includes a convolution filter and feature map (kernel). The convolution filter is applied to the input word matrix to produce a feature map indicating valuable input data patterns. Additionally, each filter employs the Rectified Linear Unit (ReLU) activation function [38] to identify multiple features in news. We used ReLU as the activation function in our DL. It is able to remove negative values from an activation map in a given network by setting them to zero. The most significant benefit of ReLU is the non-saturation of gradient, which considerably accelerates stochastic gradient descent convergence when compared to other activation functions [38]. Furthermore, it addresses the vanishing gradient problem and is more computationally efficient than sigmoid or tanh activation functions.
- **The pooling layer** uses the max operation to reduce the features in the feature map. Choosing the highest value is to capture the most significant features while reducing the amount of computation required in the next layer.
- **The flatten layer** has converted the text into a 1-dimensional array for inputting it to the next layer.
- **The output layer** gets the flatten layer's output to produce the model's final output, in which the neural network model identifies the news as real or fake. It has one neuron that determines if the news is fake or not. The ADAM optimizer [39] was used in this layer, and the activation function is sigmoid [40].

For optimization method, a crucial aspect of DL solutions is the selection of hyper-parameters. Distributed asynchronous hyper-parameter optimization (hyperopt) [41] technique has been used to optimize RNN, LSTM, and the OPCNN-FAKE. Hyperopt has been designed to accommodate Bayesian optimization algorithms based on Gaussian processes and regression trees. For OPCNN-FAKE, we adapted sets of values for different parameters in OPCNN-FAKE: filter sizes, kernel size, pool size, dropout, batch size, and epochs. Table 6 presents the values of parameters that have been adapted for OPCNN-FAKE.




FIGURE 3. The architecture of RNN and LSTM.

TABLE 6. The values of parameters have adapted for OPCNN-FAKE.

Parameter	Values
Dropout rate	between the range of 0.1 to 0.9 rate
Filter sizes	32,64,128
Kernel size	2,3,4
Pool size	3,6
Batch size	73, 146, 219, 500, 1000, 100
Epochs.	within the range of 1 epoch to 200 epoch

F. RNN AND LSTM MODELS

We used RNN [42], LSTM [43]. Figure 3 shows architecture of RNN and LSTM models. It consists of five layers: an embedding layer, hidden layers, dropout layer, flatten layer, and an output layer.

The embedding layer is the first layer and it is a similar layer in OPCNN-FAKE. In hidden layers, RNN [13] and LSTM [44] have been used. For each model, one layer and two layers hidden layers have been used. For each hidden layer, L2 weight regularization technique [45] has been used by adopting reg_rate value for 12. Dropout layer has been used for each hidden layer. The next layer is flatten layer that converts the text into the single long feature vector. The output layer gets the flatten layer’s output to produce the model’s final output, in which the neural network model identifies the news as real or fake. It has one neuron that determines whether the news is fake or not. The ADAM optimizer was used in this layer, and the activation function is sigmoid.

For optimization of RNN and LSTM models, the hyper-opt optimization technique is used. We adapted sets of values for different parameters in RNN and LSTM: number of neurons, dropout, reg_rate, batch size, and epochs. Table 7 presents the values of parameters that have been adapted for RNN and LSTM.

Regular ML Models:

Six Regular ML models: DT [46], LR [47], KNN [48], RF [49], SVM [50], and NB [51]) were used to compare with OPCNN-Fake.

For optimization ML models, There are many ways to optimize hyper-parameters, including grid search, random search, Bayesian optimization, hyperband optimization, gradient-based optimization, and metaheuristics

TABLE 7. The values of parameters have been adapted for RNN and LSTM.

Parameter	Values
Dropout rate	between the range of 0.1 to 0.9 rate
number of neurons	10 to 200 neurons
batch_size	73, 146, 219, 500, 1000, 100
epochs.	within the range of 1 epoch to 200 epoch
reg_rate	0.01, 0.05, 0.1, .2,3,4,5
Epochs.	within the range of 1 epoch to 200 epoch

optimization. Each method has its advantages and disadvantages. For example, Hyper-parameter optimization search space is not convex and not differentiable, where it is impossible to reach the global optimum. On the other hand, grid search does an exhaustive search in the hyper-parameter’s search space. This allows the grid search to reach the best results compared to other techniques, especially when the hyper-parameters are not significant. As a result, we expected that this technique will achieve the best results. Grid search with stratified 10-fold cross-validation was used to select the best value for each parameter of regular ML models. Grid search is used to find the optimal hyper-parameters of a model that achieves the best performance of ML models. We define the set of values for each parameter of models. Then, the model tests all values for each parameter using stratified 10-fold cross-validation and selects the best values which achieved the best performance. In fold cross-validation, the dataset is split into k equal divisions, with k-1 groups utilised for training and one fold reserved for testing.

G. EVALUATING THE MODELS

The accuracy, precision, recall, and F1-score of the models were used to evaluate the models. TP stands for true positive, TN stands for true negative, FP stands for false positive, and FN stands for false negative. Equations 1-4 can be found here.

$$Accuracy = \frac{TP + TN}{TP + FP + TN + FN} \tag{1}$$

$$Precision = \frac{TP}{TP + FP} \tag{2}$$

TABLE 8. The performance of ML for dataset1.

Models	Matrix size	Cross-validation performance				Testing performance			
		Accuracy	Precision	Recall	F1-score	Accuracy	Precision	Recall	F1-score
DT	Unigram	95.63±1.29	95.77±1.12	95.67±1.37	95.65±1.24	90.0	90.03	90.0	89.99
	Bi-gram	95.02±1.34	95.11±1.33	95.01±1.18	95.01±1.26	89.95	89.99	89.95	89.93
	Tri-gram	95.07±1.4	95.02±1.35	95.09±1.26	95.04±1.21	89.96	89.99	89.96	89.95
	Four-gram	94.98±1.38	95.05±1.34	95.08±1.28	95.05±1.2	89.28	89.28	89.28	89.27
KNN	Unigram	92.68±1.38	92.73±1.38	92.68±1.38	92.68±1.38	87.39	88.26	87.39	87.39
	Bi-gram	94.49±1.27	94.52±1.26	94.49±1.27	94.49±1.27	89.37	90.01	89.37	89.38
	Tri-gram	94.94±1.28	94.97±1.27	94.94±1.28	94.93±1.29	89.81	90.45	89.81	89.81
	Four-gram	95.1±1.22	95.13±1.21	95.1±1.22	95.1±1.22	90.05	90.69	90.05	90.05
LR	Unigram	98.3±0.72	98.31±0.71	98.3±0.72	98.3±0.72	96.24	96.26	96.24	96.24
	Bi-gram	98.41±0.69	98.42±0.69	98.41±0.69	98.41±0.69	96.76	96.78	96.76	96.76
	Tri-gram	98.43±0.64	98.44±0.63	98.43±0.64	98.43±0.64	96.82	96.84	96.82	96.82
	Four-gram	98.5±0.67	98.5±0.67	98.5±0.67	98.5±0.67	96.9	96.92	96.9	96.9
RF	Unigram	98.07±0.72	98.05±0.76	98.02±0.72	98.02±0.76	94.2	94.23	94.2	94.2
	Bi-gram	98.71±0.61	98.7±0.56	98.68±0.63	98.62±0.61	95.79	95.81	95.79	95.79
	Tri-gram	98.75±0.67	98.82±0.6	98.78±0.62	98.82±0.6	96.97	97.04	96.97	96.97
	Four-gram	98.4±0.67	98.42±0.6	98.48±0.62	98.42±0.6	96.46	96.49	96.46	96.46
SVM	Unigram	98.32±0.71	98.34±0.7	98.32±0.71	98.32±0.71	95.3	95.4	95.3	95.3
	Bi-gram	98.34±0.7	98.35±0.7	98.34±0.7	98.34±0.7	95.38	95.46	95.38	95.38
	Tri-gram	98.42±0.7	98.43±0.69	98.42±0.7	98.42±0.7	96.29	96.31	96.29	96.29
	Four-gram	98.37±0.69	98.39±0.69	98.37±0.69	98.37±0.69	95.52	95.52	95.52	95.53
NB	Unigram	94.49±1.14	94.79±1.05	94.49±1.14	94.49±1.14	91.57	92.27	91.57	91.57
	Bi-gram	94.17±1.35	94.3±1.31	94.17±1.35	94.18±1.35	91.2	92.14	91.2	91.2
	Tri-gram	93.41±1.23	93.94±1.07	93.41±1.23	93.41±1.23	90.95	92.07	90.95	90.94
	Four-gram	92.92±1.17	93.6±0.97	92.92±1.17	92.92±1.18	90.44	91.74	90.44	90.42

$$Recall = \frac{TP}{TP + FN} \quad (3)$$

$$F1 = \frac{2 \cdot precision \cdot recall}{precision + recall} \quad (4)$$

IV. EXPERIMENTS RESULTS

A. EXPERIMENT SETUP

The experiments of this paper were conducted on a Google Colab RAM 25 GB, Python 3, and GPU. The Keras library implemented the OPCNN-FAKE, RNN, and LSTM. The scikit-learn package implemented the ML models. The hyperopt library and grid search have optimized DL models and ML models, respectively. To initialize the embedding layer, we used the 200-dimensional word vectors pre-trained in the Glove set. Four benchmark fake news datasets were split into 80% training datasets used to optimize the models and register cross-validation results, and the 20% testing datasets (unseen data) to evaluate the models and register the testing results. All the experiments were run 10 times separately.

B. RESULTS OF DATASET1

The performance of cross-validation and the testing results for ML models and DL models will be discussed in the two sections.

1) REGULAR ML MODELS RESULTS

Table 8 shows the performance of cross-validation and the testing validation of applying regular ML to dataset1. The performance of cross-validation and the testing results will be discussed in two sections.

1) Cross-validation results

For DT, unigram has obtained the highest performance (Accuracy = 95.63%, Precision = 95.77%, Recall = 95.67% and F1-score = 95.65%), while Four-gram has obtained the lowest performance (Accuracy = 94.98%, Precision = 95.05%, Recall = 95.08% and F1-score = 95.05%). For KNN, four-gram has obtained the highest performance (Accuracy = 95.1%, Precision = 95.13%, Recall = 95.1% and F1-score 95.1%), while unigram has obtained the lowest performance (Accuracy = 92.68%, Precision = 95.77%, Recall = 95.67% and F1-score = 95.65%). As the same, for LR, four-gram has obtained the highest performance (Accuracy = 98.5%, Precision = 98.5%, Recall = 98.5% and F1-score 98.5%), whereas unigram has obtained the lowest performance (Accuracy = 98.3%, Precision = 98.31%, Recall = 98.3% and F1-score = 98.3%). For RF, Tri-gram has obtained the highest performance (Accuracy = 98.75%, Precision = 98.82%, Recall = 98.78% and F1-score 98.8%), while unigram has obtained the lowest performance (Accuracy = 96.07%, Precision = 97.08%, Recall = 98.02% and F1-score = 96.07%). For SVM, tri-gram has obtained the highest performance (Accuracy = 98.32%, Precision = 98.34%, Recall = 32% and F1-score 98.3%), while unigram has obtained the lowest performance (Accuracy = 96.07%, Precision = 97.08%, Recall = 98.02% and F1-score = 96.07%). For NB, unigram has obtained the highest performance (Accuracy = 94.49%, Precision = 94.49%, Recall = 94.4% and F1-score 94.4%), whereas four-gram has obtained the lowest

TABLE 9. The performance of ML for dataset1.

Models	Cross-validation performance				The testing performance			
	Accuracy	Precision	Recall	F1-score	Accuracy	Precision	Recall	F1-score
OPCNN-FAKE	99.99±0.0	100.0±0.0	99.97±0.01	99.98±0.0	97.84	97.86	97.84	97.84
LSTM one layer	95.98±1.52	95.57±2.11	95.61±2.52	95.5±1.74	92.56	92.58	92.56	92.55
LSTM two layers	96.13±1.25	96.0±2.19	95.93±2.6	95.86±1.56	90.9	91.07	90.9	90.89
RNN one layer	95.85±1.52	96.05±2.08	94.95±2.78	95.38±1.71	90.64	90.72	90.64	90.63
RNN two layers	85.94±1.24	87.18±3.7	82.92±5.59	84.62±1.83	86.76	86.97	86.76	86.72

TABLE 10. The best values of OPCNN-FAKE's parameters dataset1.

Models	Filter size	Kernel size	Max pooling	Dropout	Batch size	epochs
OPCNN-FAKE	128	2	3	0.2	219	28

TABLE 11. The best values of parameters for LSTM and RNN for dataset1.

Models	Neurons	reg _{rate}	Dropout	Batch size	epochs
LSTM one layer	48	0.05	0.5	146	32
LSTM two layers	[40,41]	[0.1,0.4]	[0.4,0.4]	146	12
RNN one layer	34	0.05	0.4	73	11
RNN two layers	[5,42]	[0.3,0.1]	[0.6,0.6]	219	11

performance (Accuracy = 92.92%, Precision = 93.6%, Recall = 92.92% and F1-score = 92.9%).

2) The testing results

For DT, unigram has obtained the highest performance (Accuracy = 90.0%, Precision = 90.03%, Recall = 90.0% and F1-score = 89.99%). Four-gram has obtained the lowest performance (Accuracy = 89.28%, Precision = 89.28%, Recall = 89.28% and F1-score = 89.27%). For KNN, four-gram has obtained the highest performance (Accuracy = 90.05%, Precision = 90.69%, Recall = 90.05% and F1-score 90.05%), while unigram has obtained the lowest performance (Accuracy = 87.39%, Precision = 89.28%, Recall = 89.28% and F1-score = 89.27%). As the same, for LR, four-gram has obtained the highest performance (Accuracy = 96.9%, Precision = 96.92%, Recall = 96.9% and F1-score 96.9%), whereas Unigram has obtained the lowest performance (Accuracy = 96.24%, Precision = 96.26%, Recall = 96.24% and F1-score = 96.24%). For RF, tri-gram has obtained the highest performance (Accuracy = 96.97%, Precision = 97.04%, Recall = 96.97% and F1-score = 96.97%), while unigram has obtained the lowest performance (Accuracy = 94.2%, Precision = 94.23%, Recall = 94.2% and F1-score = 94.2%). For SVM, tri-gram has obtained the highest performance (Accuracy = 96.29%, Precision = 96.31%, Recall = 96.29% and F1-score = 96.29%), while unigram has obtained the lowest performance (Accuracy = 95.3%, Precision = 95.3%, Recall = 95.3% and F1-score = 95.3%). For NB, Unigram has obtained the highest performance (Accuracy = 91.57%, Precision = 92.27%, Recall = 91.57% and F1-score 91.57%), while four-gram has obtained the lowest performance

(Accuracy = 90.44%, Precision = 91.74%, Recall = 90.44% and F1-score = 90.42%).

Overall, RF with Tri-gram is ranked the highest performance for cross-validation results and the testing results compared with the other regular ML models.

C. DL MODELS RESULTS

Table 9 shows the cross-validation and the testing results of OPCNN-FAKE, LSTM, RNN, and for dataset1.

1) Cross-validation results

We can see that OPCNN-FAKE is ranked the highest performance (Accuracy = 99.9%, Precision = 100%, Recall = 99.97% and F1-score 95.9%), while RNN two layers is ranked the lowest performance (Accuracy = 85.94%, Precision = 87.18%, Recall = 82.92% and F1-score = 95.38%). The second highest performance has been registered by LSTM with two layers (Accuracy = 96.13%, Precision = 96.0%, Recall = 95.93% and F1-score 95.86%).

2) The testing results

We can see that OPCNN-FAKE has obtained the highest performance (Accuracy = 97.84%, Precision = 97.86%, Recall = 97.84% and F1-score 97.84%), While RNN two layers has obtained the lowest performance (Accuracy = 86.76%, Precision = 86.97%, Recall = 86.76% and F1-score = 86.72%).

Overall, **the OPCNN-FAKE** is ranked the highest performance for cross-validation results and the testing results compared with the other regular ML models, and DL models (RNN and LSTM).

TABLE 12. The performance of ML for dataset2 (FakeNewsNet).

Models	Matrix size	Cross-validation performance				Test performance			
		Accuracy	Precision	Recall	F1-score	Accuracy	Precision	Recall	F1-score
DT	Unigram	92.41±0.42	92.3±0.44	92.42±0.41	92.29±0.42	81.27	81.04	81.27	81.15
	Bi-gram	92.46±0.38	92.36±0.36	92.47±0.4	92.35±0.4	81.54	81.28	81.54	81.4
	Tri-gram	92.47±0.4	92.33±0.42	92.46±0.43	92.35±0.42	81.38	81.11	81.38	81.23
	Four-gram	92.49±0.43	92.36±0.44	92.48±0.39	92.37±0.43	81.8	81.47	81.8	81.62
KNN	Unigram	93.7±0.34	93.8±0.34	93.7±0.34	93.47±0.36	81.87	84.15	81.87	77.69
	Bi-gram	93.63±0.35	93.73±0.34	93.63±0.35	93.39±0.38	81.13	83.65	81.13	76.39
	Tri-gram	93.62±0.35	93.72±0.34	93.62±0.35	93.38±0.37	80.97	83.59	80.97	76.1
	Four-gram	93.45±0.34	93.64±0.33	93.45±0.34	93.17±0.37	80.9	83.57	80.9	75.96
LR	Unigram	87.86±0.47	87.5±0.5	87.86±0.47	87.57±0.48	84.18	83.51	84.18	83.68
	Bi-gram	87.39±0.5	87.08±0.53	87.39±0.5	87.17±0.52	83.42	83.02	83.42	83.18
	Tri-gram	87.42±0.46	87.05±0.49	87.42±0.46	87.14±0.48	83.93	83.27	83.93	83.46
	Four-gram	87.28±0.48	86.82±0.52	87.28±0.48	86.84±0.5	82.28	82.45	82.28	82.28
RF	Unigram	92.36±0.2	92.42±0.3	92.3±0.37	92.07±0.31	85.34	84.8	85.34	84.2
	Bi-gram	92.17±0.15	92.36±0.22	92.26±0.18	91.96±0.29	85.28	84.63	85.28	84.1
	Tri-gram	92.3±0.21	92.34±0.27	92.24±0.3	91.91±0.28	85.02	84.33	85.02	83.97
	Four-gram	91.28±0.39	91.38±0.44	91.31±0.41	90.83±0.46	85.00	85.04	84.63	83.26
SVM	Unigram	93.85±0.27	93.89±0.28	93.85±0.27	93.64±0.29	83.94	84.24	83.94	81.62
	Bi-gram	93.59±0.23	93.58±0.24	93.59±0.23	93.4±0.24	83.29	84.16	83.29	80.39
	Tri-gram	93.48±0.22	93.45±0.24	93.48±0.22	93.29±0.22	83.83	84.06	83.83	81.49
	Four-gram	93.44±0.22	93.41±0.24	±0.22	93.26±0.22	82.72	82.89	82.72	80.36
NB	Unigram	86.03±0.49	85.47±0.56	86.03±0.49	85.3±0.53	84.53	83.73	84.53	83.56
	Bi-gram	85.77±0.55	85.16±0.6	85.77±0.55	85.2±0.57	83.77	82.91	83.77	82.98
	Tri-gram	85.66±0.55	85.05±0.6	85.66±0.55	85.08±0.56	83.55	82.63	83.55	82.68
	Four-gram	85.66±0.54	85.04±0.6	85.66±0.54	85.07±0.56	83.52	82.59	83.52	82.63

1) THE BEST VALUES OF PARAMETERS FOR DATASET1

Table 10 shows the best values of parameters for the OPCNN-FAKE model. Table 11 presents the best values parameters for RNN and LSTM.

D. RESULTS OF DATASET2 (Fakenewsnet)

The performance of cross-validation and the testing results for ML models and DL models will be discussed in two sections.

1) REGULAR ML MODELS RESULTS

Table 12 shows the performance of cross-validation and the testing validation of applying regular ML to detest2. The performance of cross-validation and the testing results will be discussed in two sections.

1) Cross-validation results

In DT and KNN, we can see that the value of Accuracy, Precision, Recall, and F1-score for unigram, bi-gram, tri-gram and four-gram are similar. For DT, four-gram has obtained the highest performance (Accuracy = 92.49%, Precision = 92.36%, Recall = 92.48% and F1-score = 92.37%), while unigram has obtained the lowest performance (Accuracy = 92.41%, Precision = 92.3%, Recall = 92.42% and F1-score = 92.29%). For KNN, Unigram has obtained the highest performance (Accuracy = 93.7%, Precision = 93.8%, Recall = 93.7% and F1-score = 93.47%), while unigram has obtained the lowest performance (Accuracy = 93.45%, Precision = 93.64%, Recall = 93.45% and F1-score = 93.17%). For LR, Unigram has obtained the highest performance (Accuracy = 93.7%, Precision = 93.8%, Recall = 93.7% and F1-score = 93.47%), while Four-gram has

obtained the lowest performance (Accuracy = 87.28%, Precision = 86.82%, Recall = 87.28% and F1-score = 86.84%). For RF, Unigram has obtained the highest performance (Accuracy = 92.36%, Precision = 92.42%, Recall = 92.07% and F1-score = 83.68%), while Four-gram has obtained the lowest performance (Accuracy = 91.28%, Precision = 91.38%, Recall = 91.31% and F1-score = 90.83%). For SVM, Unigram has obtained the highest performance (Accuracy = 93.85%, Precision = 93.89%, Recall = 93.85% and F1-score = 93.64%), while, Four-gram has obtained the lowest performance (Accuracy = 93.44%, Precision = 93.41%, Recall = 93.44% and F1-score = 93.26%). For NB, Unigram has obtained the highest performance (Accuracy = 86.03%, Precision = 85.47%, Recall = 85.3% and F1-score = 81.26%), whereas four-gram and Tri-gram have the same performance.

2) The testing results

For DT, Four-gram has obtained the highest performance (Accuracy = 81.8%, Precision = 81.47%, Recall = 81.8% and F1-score = 81.62%), while Unigram has obtained the lowest performance (Accuracy = 81.27%, Precision = 81.04%, Recall = 81.27% and F1-score = 81.15%). For KNN, Unigram has obtained the highest performance (Accuracy = 81.87%, Precision = 84.15%, Recall = 81.87% and F1-score = 77.69%), while unigram has obtained the lowest performance (Accuracy = 80.9%, Precision = 83.57%, Recall = 80.9% and F1-score = 75.96%). For LR, Unigram has obtained the highest performance (Accuracy = 84.18%, Precision = 83.51%, Recall = 84.18% and F1-score = 83.68%), while Four-gram has obtained the lowest performance (Accuracy = 82.28%, Precision = 82.45%,

TABLE 13. The performance of deep neural networks for dataset2 (FakeNewsNet).

Models	Cross-validation performance				Testing performance			
	Accuracy	Precision	Recall	F1-score	Accuracy	Precision	Recall	F1-score
OPCNN-FAKE	98.65±0.25	99.34±0.17	98.87±0.24	99.1±0.18	95.26	95.28	95.26	95.27
LSTM one layer	83.23±0.42	85.07±1.18	94.56±1.56	89.52±0.31	83.27	82.49	83.27	81.89
LSTM two layers	85.96±0.52	87.55±1.01	95.15±1.2	91.16±0.31	86.43	85.9	86.43	85.95
RNN one layer	82.26±0.36	84.0±1.04	94.65±1.57	88.96±0.26	82.02	81.63	82.02	81.8
RNN two layers	79.49±0.57	79.51±0.8	98.32±0.63	87.89±0.27	79.84	80.23	79.84	74.91

TABLE 14. The best values of parameters’s OPCNN-FAKE for dataset2 (FakeNewsNet).

Model	Filter size	Kernel size	Max pooling	Dropout	Batch size	epochs
OPCNN-FAKE	128	4	3	0.6	219	40

TABLE 15. The best values of parameters for LSTM and RNN for dataset2 (FakeNewsNet).

Models	Neurons	reg _{rate}	Dropout	Batch size	epochs
LSTM one layer	37	0.1	0.8	500	33
LSTM two layers	[48,21]	[0.1,0.5]	[0.7,0.8]	100	58
RNN one layer	14	0.1	0.1	219	81
RNN two layers	[24,30]	[0.5,0.5]	[0.2,0.7]	500	52

TABLE 16. The performance of regular ML for dataset3.

Models	Matrix size	Cross-validation performance				Test performance			
		Accuracy	Precision	Recall	F1-score	Accuracy	Precision	Recall	F1-score
DT	Unigram	51.02±6.05	51.11±5.36	51.01±4.93	51.39±5.94	48.76	48.84	48.76	48.72
	Bi-gram	49.46±5.49	50.21±5.93	49.56±5.73	49.91±5.78	46.58	46.58	46.58	46.48
	Tri-gram	50.96±6.41	50.85±5.23	49.94±6.55	49.58±5.91	47.82	47.97	47.82	47.83
	Four-gram	50.49±5.64	50.58±5.38	50.14±5.21	50.0±5.31	48.07	48.04	48.07	47.96
KNN	Unigram	48.76±5.35	51.64±5.06	51.64±5.06	50.67±6.7	49.63	48.97	49.63	46.98
	Bi-gram	52.64±4.78	51.77±6.14	52.64±4.78	49.83±5.23	51.24	49.4	51.24	46.01
	Tri-gram	53.34±4.98	52.7±6.31	53.34±4.98	50.72±5.34	49.94	48.01	49.94	45.94
	Four-gram	53.17±4.74	52.65±5.42	53.17±4.74	51.9±4.98	51.43	49.9	51.43	48.74
LR	Unigram	49.46±5.58	50.05±5.56	50.05±5.56	49.69±5.86	47.08	46.2	47.08	46.03
	Bi-gram	51.18±5.31	51.02±5.44	51.18±5.31	50.83±5.31	50.43	50.26	50.43	50.27
	Tri-gram	51.66±5.18	51.64±5.22	51.66±5.18	51.44±5.2	51.92	51.68	51.92	51.66
	Four-gram	50.51±5.7	49.83±6.21	50.51±5.7	49.13±5.66	50.75	49.73	50.75	48.75
RF	Unigram	50.6±5.33	51.52±4.31	52.17±4.41	51.69±5.75	48.63	47.8	48.63	47.48
	Bi-gram	52.21±4.89	49.94±6.13	51.62±4.99	49.69±5.83	49.38	48.64	49.38	48.37
	Tri-gram	52.90±4.78	52.80±5.49	52.64±5.42	52.36±5.15	51.3	50.08	51.3	48.66
	Four-gram	52.72±5.5	52.18±5.7	51.69±5.09	51.97±5.08	50.0	49.3	50.0	48.50
SVM	Unigram	53.05±4.17	53.34±4.94	53.34±4.94	52.58±7.92	52.36	50.7	52.36	45.84
	Bi-gram	48.54±5.56	52.23±6.35	53.05±4.17	48.38±4.54	51.74	49.43	51.74	44.25
	Tri-gram	52.18±2.9	49.24±10.86	52.18±2.9	41.57±3.92	52.05	47.04	52.05	38.48
	Four-gram	46.96±4.94	50.05±6.77	51.57±4.59	46.96±4.94	49.32	44.09	49.32	40.94
NB	Unigram	53.37±6.11	53.93±6.08	53.93±6.08	53.7±6.32	51.68	51.52	51.68	51.54
	Bi-gram	53.28±5.84	53.22±6.0	53.28±5.84	52.96±5.85	51.49	51.31	51.49	51.32
	Tri-gram	52.34±5.66	52.11±5.93	52.34±5.66	51.87±5.7	49.19	48.8	49.19	48.76
	Four-gram	51.22±5.59	51.22±5.59	51.47±5.34	51.0±5.44	48.88	48.68	48.88	48.67

Recall = 82.28% and F1-score = 82.28%). For RF, Unigram has obtained the highest performance (Accuracy = 85.34%, Precision = 84.8%, Recall = 85.34% and F1-score = 84.2%), while Four-gram has obtained the lowest performance (Accuracy = 84.63%, Precision = 84.04%, Recall = 84.63% and F1-score = 83.26%). For SVM, Unigram has obtained the highest performance (Accuracy = 83.94%, Precision = 84.24%, Recall = 83.94% and F1-score = 81.26%) whereas Four-gram has obtained the lowest performance (Accuracy = 82.72%, Precision = 82.89%, Recall = 82.72% and F1-score = 80.36%). For NB, Unigram has obtained the highest performance (Accuracy = 84.53%,

Precision = 83.73%, Recall = 84.53% and F1-score = 83.56%), whereas Four-gram and Tri-gram have the same performance.

Overall, SVM with Unigram is ranked the highest performance for cross-validation results than the other regular ML models. And NB with Unigram is rated the highest performance for the testing results than the other regular ML models.

2) DL MODELS RESULTS

Table 13 shows the cross-validation and test results of LSTM, RNN and OPCNN-FAKE for dataset2.

1) Cross-validation result

We can see that OPCNN-FAKE has obtained the highest performance (Accuracy = 98.65%, Precision = 99.34%, Recall = 98.87% and F1-score 99.1%), while RNN two layers has obtained the lowest performance (Accuracy = 79.49%, Precision = 79.51%, Recall = 98.32% and F1-score = 87.8%). The second highest performance has been registered by LSTM with two layers (Accuracy = 85.96%, Precision = 87.55%, Recall = 95.15% and F1-score 91.16%).

2) The testing result

We can see that OPCNN-FAKE has obtained the highest performance (Accuracy = 95.26%, Precision = 95.28%, Recall = 95.26% and F1-score 97.895.274%), while RNN two layers has obtained the lowest performance (Accuracy = 79.84%, Precision = 80.23%, Recall = 79.84% and F1-score = 74.91%).

Overall, **the proposed OPCNN-FAKE** is ranked the highest performance for cross-validation results and the testing results compared with the other regular ML models and DL models (RNN and LSTM).

3) THE BEST VALUES OF PARAMETERS FOR DATASET2

(FakeNewsNet)

Table 14 shows the best values of parameters for the OPCNN-FAKE model. Table 15 presents the best values of parameters for RNN and LSTM.

E. RESULTS OF DATASET3

The performance of cross-validation and the testing results for ML models and DL models will be discussed in two sections.

1) REGULAR ML MODELS RESULTS

Table 16 shows the performance of cross-validation and the testing validation of applying regular ML to detest3. The performance of cross-validation and the testing results will be discussed in two sections.

1) Cross-validation results

For DT, Unigram has obtained the highest performance (Accuracy = 51.02%, Precision = 51.11%, Recall = 51.01% and F1-score = 51.39%), while Bi-gram has obtained the lowest performance (Accuracy = 49.46%, Precision = 50.21%, Recall = 49.56% and F1-score = 49.91%). For KNN, Four-gram has obtained the highest performance (Accuracy = 53.17%, Precision = 51.9%, Recall = 53.17% and F1-score = 48.72%), While Unigram has obtained the lowest performance (Accuracy = 48.76%, Precision = 51.64%, Recall = 51.64% and F1-score = 50.67%). For LR, Tri-gram has obtained the highest performance (Accuracy = 51.66%, Precision = 51.64%, Recall = 51.66% and F1-score = 51.44%). For RF, Four-gram has obtained the highest performance (Accuracy = 52.90%, Precision = 52.80%, Recall = 52.64% and F1-score = 52.36%), while

Unigram has obtained the lowest performance (Accuracy = 50.6%, Precision = 51.52%, Recall = 52.17% and F1-score = 51.69%). For SVM, Unigram has obtained the highest performance (Accuracy = 53.05%, Precision = 53.34%, Recall = 53.34% and F1-score = 52.58%), while Four-gram has obtained the lowest performance (Accuracy = 46.96%, Precision = 50.05%, Recall = 51.57% and F1-score = 46.96%). For NB, Unigram has obtained the highest performance (Accuracy = 53.37%, Precision = 53.93%, Recall = 53.93% and F1-score = 53.7%), whereas Four-gram has obtained the lowest performance (Accuracy = 51.22%, Precision = 51.22%, Recall = 51.47% and F1-score = 51.0%).

2) The testing results

For DT, Unigram has obtained the highest performance (Accuracy = 48.76%, Precision = 48.84%, Recall = 48.76% and F1-score = 48.72%), while Bi-gram has obtained the lowest performance (Accuracy = 46.58%, Precision = 46.58%, Recall = 46.58% and F1-score = 46.48%). For KNN, Four-gram has obtained the highest performance (Accuracy = 51.43%, Precision = 49.9%, Recall = 51.43% and F1-score = 48.74%), while Unigram has obtained the lowest performance (Accuracy = 49.63%, Precision = 48.97%, Recall = 49.63% and F1-score = 46.98%). For LR, Tri-gram has obtained the highest performance (Accuracy = 51.92%, Precision = 51.68%, Recall = 51.92% and F1-score = 51.66%). For RF, Four-gram has obtained the highest performance (Accuracy = 51.3%, Precision = 50.08%, Recall = 51.3% and F1-score = 52.36%), while Unigram has obtained the lowest performance (Accuracy = 48.63%, Precision = 47.8%, Recall = 48.63% and F1-score = 47.48%). For SVM, Unigram has obtained the highest performance (Accuracy = 52.36%, Precision = 50.7%, Recall = 52.36% and F1-score = 45.84%), while Four-gram has obtained the lowest performance (Accuracy = 49.32%, Precision = 44.09%, Recall = 49.32% and F1-score = 40.94%). For NB, Unigram has obtained the highest performance (Accuracy = 51.68%, Precision = 51.52%, Recall = 51.68% and F1-score = 51.54%), whereas Four-gram has obtained the lowest performance (Accuracy = 48.88%, Precision = 48.682%, Recall = 48.88% and F1-score = 48.67%).

2) DL MODELS RESULTS

Table 17 shows the cross-validation and the testing results of LSTM, RNN and OPCNN-FAKE for dataset3.

1) Cross-validation results

We can see that OPCNN-FAKE has obtained the highest performance (Accuracy = 97.23%, Precision = 97.37%, Recall = 97.58% and F1-score = 97.26%), while LSTM with one layer has obtained the lowest performance (Accuracy = 71.97%, Precision = 73.32%, Recall = 73.86% and F1-score = 73.85%). The second highest performance has been registered by LSTM with two

TABLE 17. The performance of deep neural networks for dataset3.

Models	Cross-validation performance				The testing performance			
	Accuracy	Precision	Recall	F1-score	Accuracy	Precision	Recall	F1-score
OPCNN-FAKE	97.23±0.26	97.37±0.24	97.58±0.36	97.26±0.21	53.99	53.86	53.91	53.99
LSTM one layer	71.97±6.26	73.32±6.62	73.86±7.21	73.85±9.13	47.64	47.44	47.71	47.64
LSTM two layers	90.67±2.35	91.55±2.46	91.42±2.88	92.53±4.04	47.26	47.17	47.32	47.26
RNN one layer	74.23±2.04	79.02±1.43	78.16±1.43	91.08±1.92	48.57	44.24	45.93	48.57
RNN two layers	78.66±2.8	80.6±2.57	78.57±2.87	83.23±3.23	47.58	47.60	47.60	47.58

layers (Accuracy = 90.67%, Precision = 91.55%, Recall = 91.55% and F1-score 92.53%).

2) The testing results

We can see that OPCNN-FAKE has obtained the highest performance (Accuracy = 53.99%, Precision = 53.86%, Recall = 53.91% and F1-score = 53.99%), while LSTM with two layers obtained the lowest performance (Accuracy = 47.26%, Precision = 47.17%, Recall = 47.32% and F1-score = 47.26%).

Overall, **OPCNN-FAKE** is ranked the highest performance for cross-validation results and the testing results compared with the other regular ML models and DL models (RNN and LSTM).

F. THE BEST VALUES OF PARAMETERS FOR DATASET3

Table 18 shows the best values of parameters for the OPCNN-FAKE model. Table 19 presents the best values of parameters for RNN and LSTM.

G. RESULTS OF DATASET4

The performance of cross-validation and the testing results for ML models and DL models will be discussed in two sections.

1) REGULAR ML MODELS RESULTS

Table 20 shows the performance of cross-validation and the testing validation of applying regular ML to detest4. The performance of cross-validation and the testing results will be discussed in two sections.

1) Cross-validation results

For DT, Bi-gram has obtained the highest performance (Accuracy = 99.58%, Precision = 99.59%, Recall = 99.58% and F1-score = 99.58%), while Four-gram and Tri-gram have the same performance. For KNN, Four-gram has obtained the highest performance (Accuracy = 91.54%, Precision = 91.52%, Recall = 91.63% and F1-score = 91.54%), while Unigram has obtained the lowest performance (Accuracy = 90.75%, Precision = 90.85%, Recall = 90.75% and F1-score = 90.74%). For LR, Tri-gram has obtained the highest performance (Accuracy = 99.44%, Precision = 99.44%, Recall = 99.44% and F1-score = 99.44%). For RF, Bi-gram has obtained the highest performance (Accuracy = 99.75%, Precision = 99.74%, Recall = 99.73% and F1-score = 99.75%). For SVM, Bi-gram has obtained the highest performance

(Accuracy = 99.65%, Precision = 99.64%, Recall = 99.63% and F1-score = 99.65%), while Four-gram has obtained the lowest performance (Accuracy = 99.23%, Precision = 99.23%, Recall = 99.23% and F1-score = 99.23%). For NB, Four-gram has obtained the highest performance (Accuracy = 95.11%, Precision = 95.11%, Recall = 95.11% and F1-score = 95.11%), while Unigram has obtained the lowest performance (Accuracy = 92.89%, Precision = 92.9%, Recall = 92.89% and F1-score = 92.89%).

2) The testing results

For DT, Bi-gram has obtained the highest performance (Accuracy = 99.40%, Precision = 99.40%, Recall = 99.40% and F1-score = 99.40%) while Unigram, Four-gram, and Tri-gram have the same performance. For KNN, Four-gram has obtained the highest performance (Accuracy = 90.72%, Precision = 90.72%, Recall = 90.93% and F1-score = 90.72%), while Unigram has obtained the lowest performance (Accuracy = 90.75%, Precision = 90.85%, Recall = 90.75% and F1-score = 90.74%). For LR, Tri-gram has obtained the highest performance (Accuracy = 98.8%, Precision = 98.8%, Recall = 98.8% and F1-score = 98.8%). For RF, Bi-gram has obtained the highest performance (Accuracy = 99.90%, Precision = 99.90%, Recall = 99.90% and F1-score = 99.90%). For SVM, Bi-gram has obtained the highest performance (Accuracy = 99.40%, Precision = 99.40%, Recall = 99.40% and F1-score = 99.40%), while Four-gram has obtained the lowest performance (Accuracy = 98.90%, Precision = 98.90%, Recall = 98.90% and F1-score = 98.90%). For NB, Four-gram has obtained the highest performance (Accuracy = 94.94%, Precision = 94.94%, Recall = 94.94% and F1-score = 94.94%), whereas Unigram has obtained the lowest performance (Accuracy = 92.9%, Precision = 92.9%, Recall = 92.9% and F1-score = 92.9%).

Overall, RF with Tri-gram is ranked the highest performance for cross-validation results than the other regular ML models. And NB with Four-gram is rated the highest performance for the testing results than the other regular ML models.

H. DL MODELS RESULTS

Table 21 shows the cross-validation and the testing results of LSTM, RNN, and OPCNN-FAKE for dataset4.

TABLE 18. The best values of parameters for OPCNN-FAKE for dataset3.

Model	Filter size	Kernel size	Max pooling	Dropout	Batch size	epochs
OPCNN-FAKE	64	4	3	0.7	219	25

TABLE 19. The best values of parameters for LSTM and RNN for dataset3.

Models	Neurons	reg _{rate}	Dropout	Batch size	epochs
LSTM one layer	37	0.4	0.8	146	40
LSTM two layers	[20,39]	[0.01,0.1]	[0.7,0.5]	219	14
RNN one layer	36	0.01	0.9	219	14
RNN two layers	[3,23]	[0.2,0.05]	[0.7,0.3]	73	14

TABLE 20. The performance of regular ML for dataset4.

Models	Matrix size	Cross validation performance				Test performance			
		Accuracy	Precision	Recall	F1-score	Accuracy	Precision	Recall	F1-score
DT	Unigram	99.44±0.11	99.43±0.13	99.44±0.12	99.44±0.12	99.22	99.22	99.22	99.22
	Bi-gram	99.58±0.12	99.59±0.11	99.58±0.11	99.58±0.11	99.40	99.40	99.40	99.40
	Tri-gram	99.48±0.12	99.47±0.12	99.48±0.12	99.48±0.12	99.2	99.2	99.2	99.2
	Four-gram	99.47±0.12	99.47±0.12	99.48±0.12	99.47±0.12	99.25	99.25	99.25	99.25
KNN	Unigram	90.75±0.41	90.85±0.4	90.75±0.41	90.74±0.41	89.54	89.83	89.54	89.54
	Bi-gram	91.31±0.41	91.43±0.41	91.31±0.41	91.3±0.41	90.44	90.65	90.44	90.44
	Tri-gram	91.5±0.4	91.48±0.4	91.61±0.39	91.5±0.4	90.71	90.71	90.91	90.71
	Four-gram	91.54±0.48	91.52±0.48	91.63±0.47	91.54±0.48	90.72	90.72	90.93	90.72
LR	Unigram	99.3±0.13	99.3±0.13	99.3±0.13	99.3±0.13	98.56	98.56	98.56	98.56
	Bi-gram	99.43±0.13	99.43±0.13	99.43±0.13	99.43±0.13	98.79	98.79	98.79	98.79
	Tri-gram	99.44±0.15	99.44±0.15	99.44±0.15	99.44±0.15	98.8	98.8	98.8	98.8
	Four-gram	99.43±0.16	99.43±0.16	99.43±0.16	99.43±0.16	98.79	98.79	98.79	98.79
RF	Unigram	99.74±0.08	99.71±0.07	99.7±0.09	99.75±0.05	99.4	99.4	99.4	99.4
	Bi-gram	99.75±0.04	99.77±0.06	99.73±0.07	99.75±0.07	99.90	99.90	99.90	99.90
	Tri-gram	99.72±0.06	99.75±0.07	99.72±0.07	99.73±0.07	99.48	99.48	99.48	99.48
	Four-gram	99.73±0.07	99.75±0.07	99.77±0.06	99.74±0.05	99.48	99.48	99.48	99.48
SVM	Unigram	99.64±0.08	99.61±0.07	99.6±0.09	99.65±0.05	99.2	99.2	99.2	99.2
	Bi-gram	99.65±0.04	99.64±0.06	99.63±0.07	99.65±0.07	99.40	99.40	99.40	99.40
	Tri-gram	99.52±0.05	99.55±0.06	99.52±0.06	99.53±0.06	99.28	99.28	99.28	99.28
	Four-gram	99.23±0.15	99.23±0.15	99.23±0.15	99.23±0.15	98.90	98.90	98.90	98.90
NB	Unigram	92.89±0.36	92.9±0.36	92.89±0.36	92.89±0.36	92.9	92.9	92.9	92.9
	Bi-gram	94.72±0.42	94.72±0.42	94.72±0.42	94.72±0.42	94.67	94.67	94.67	94.67
	Tri-gram	95.05±0.41	95.05±0.41	95.05±0.41	95.05±0.41	94.86	94.86	94.86	94.86
	Four-gram	95.11±0.4	95.11±0.4	95.11±0.4	95.11±0.4	94.94	94.94	94.94	94.94

1) Cross-validation results

We can see that OPCNN-FAKE has obtained the highest performance (Accuracy = 100%, Precision = 100%, Recall = 100% and F1-score 100%), while RNN two layers has obtained the lowest performance (Accuracy = 79.49%, Precision = 87.89%, Recall = 79.51% and F1-score = 98.32%). LSTM one layer and LSTM two layers have obtained the same performance.

2) The testing results

We can see that OPCNN-FAKE has obtained the highest performance (Accuracy = 99.99%, Precision = 99.99%, Recall = 99.99% and F1-score 99.99%), while RNN two layers has obtained the lowest performance (Accuracy = 79.84%, Precision = 74.91%, Recall = 80.23% and F1-score = 79.84%). LSTM one layer and LSTM two layers have recorded the same performance.

Overall, OPCNN-FAKE is ranked the highest performance for cross-validation results and the testing results compared with the other regular ML models, and DL models (RNN and LSTM).

1) THE BEST VALUES OF PARAMETERS FOR DATASET4

Table 22 shows the best values of parameters of the OPCNN-FAKE model. Table 23 presents the best values of parameters for RNN and LSTM.

I. DISCUSSION

1) THE BEST MODELS OF FAKE NEWS DETECTION FOR DATASET1

Figure 4 and Figure 5 illustrate the experimental results in the broad picture for the cross-validation performances and the testing performance for the best models, respectively, based on the results acquired in our experiments for dataset1. Overall, When compared to the other models, the OPCNN-FAKE model provides the largest cross-validation and the testing performance. While, NB with Unigram has achieved the worst cross-validation and the testing performance compared to the other models. For cross-validation results, the OPCNN-FAKE model has achieved the highest performance (Accuracy = 99.99%, precision = 100%, recall = 99.97%, and F1-score = 99.97%). NB with Unigram has

TABLE 21. The performance of deep neural networks for dataset4.

Models	Cross validation performance				Testing performance			
	Accuracy	F1-score	Precision	Recall	Accuracy	F1-score	Precision	Recall
OPCNN-FAKE	100.0±0.0	100.0±0.0	100.0±0.0	100.0±0.0	99.99	99.99	99.99	99.99
LSTM one layer	98.87±0.97	98.7±1.16	99.51±0.5	98.09±1.76	99.78	99.78	99.78	99.78
LSTM two layers	99.69±0.86	99.61±1.48	99.89±0.34	99.44±1.75	99.78	99.78	99.79	99.78
RNN one layer	99.46±0.16	99.44±0.17	99.51±0.4	99.37±0.28	99.6	99.6	99.6	99.6
RNN two layers	79.49±0.57	87.89±0.27	79.51±0.8	98.32±0.63	79.84	74.91	80.23	79.84

TABLE 22. The best values of parameters of OPCNN-FAKE for dataset4.

Model	Filter size	Kernel size	Max pooling	Dropout	Batch size	epochs
OPCNN-FAKE	22	4	3	0.4	500	66

TABLE 23. The best values parameters for LSTM and RNN for dataset4.

Models	Neurons	reg.ate	Dropout	Batch size	epochs
LSTM one layer	254	0.1	0.7	400	59
LSTM two layers	[39,41]	[0.4,0.5]	[0.1,0.6]	400	85
RNN one layer	44	0.5	0.2	400	44
RNN two layers	[24,30]	[0.05,0.05]	[0.2,0.7]	500	52




FIGURE 4. The best cross-validation performance models for dataset1.




FIGURE 5. The best testing performance models for dataset1.

registered the lowest performance (Accuracy = 94.49%, precision = 94.79%, recall = 94.49%, and F1-score = 94.49%). RF with Tri-gram has achieved the second best performance (Accuracy = 98.75%, precision = 98.82%, recall = 98.78%, and F1-score = 98.82%). For the testing results, the OPCNN-FAKE model has achieved the highest performance (Accuracy = 97.84%, precision = 97.86%, recall = 97.84%, and F1-score = 97.84%). NB with Unigram has registered the lowest performance (Accuracy = 91.57%, Precision = 92.27%, Recall = 91.57%, and F1-score = 91.57%). RF with Tri-gram has achieved the second best performance (Accuracy = 96.97%, precision = 97.04%, recall = 96.97%, and F1-score = 96.97%).

2) THE BEST MODELS OF FAKE NEWS DETECTION FOR DATASET2 (FakeNewsNet)

Figure 6 and Figure 7 illustrate the experimental results in the broad picture for the cross-validation performances and the testing performance for the best models,

respectively, based on the results acquired in our experiments for FakeNewsNet. Overall, When compared to the other models, the OPCNN-FAKE model provides the largest cross-validation and the testing performance. For cross-validation results, **OPCNN-FAKE model** has achieved the highest performance (Accuracy = 98.65%, precision = 99.34%, recall = 98.87%, and F1-score = 99.1%). NB with Unigram has registered the lowest performance (Accuracy = 86.03%, precision = 85.47%, recall = 86.03%, and F1-score = 85.3%). SVM with Unigram has achieved the second best performance (Accuracy = 93.85%, precision = 93.89%, recall = 93.85%, and F1-score = 93.64%). For the testing results, **OPCNN-FAKE model** has achieved the highest performance (Accuracy = 95.26%, precision = 95.28%, recall = 95.26%, and F1-score = 95.27%). DT with Four-gram has registered the lowest performance (Accuracy = 81.8%, precision = 81.47%, recall = 81.8%, and F1-score = 81.62%). RF with Unigram has achieved the second best performance




FIGURE 6. The best cross-validation performance models for dataset2 (FakeNewsNet).




FIGURE 8. The best cross-validation performance models for dataset3.




FIGURE 7. The best test performance models for dataset2.

(Accuracy = 85.34%, precision = 84.8%, recall = 85.34%, and F1-score = 84.2%).

3) THE BEST MODELS OF FAKE NEWS DETECTION FOR DATASET3

Figure 8 and Figure 9 illustrate the experimental results in the broad picture for the cross-validation performances and the testing performance for the best models, respectively, based on the results acquired in our experiments for dataset3. Overall, When compared to the other models, the OPCNN-FAKE model provides the largest cross-validation and the testing performance. For cross-validation results, OPCNN-FAKE model has achieved the highest performance (Accuracy = 97.23%, precision = 97.37%, recall = 97.58%, and F1-score = 97.26%). DT with Unigram has registered the lowest performance (Accuracy = 51.02%, precision = 51.11%, recall = 51.01%, and F1-score = 51.39%). NB with Unigram has achieved the second best performance (Accuracy = 53.37%, precision = 53.93%, recall = 53.93%, and F1-score = 53.7%). For the testing results, the OPCNN-FAKE model has achieved the highest performance (Accuracy = 99.99%, precision = 99.99%, recall = 99.99%, and F1-score = 99.99%). DT with Four-gram has registered the lowest




FIGURE 9. The best testing performance models for dataset3.

performance (Accuracy = 48.76%, precision = 48.84%, recall = 48.76%, and F1-score = 48.72%).

4) THE BEST MODELS OF FAKE NEWS DETECTION FOR DATASET4

Figure 10 and Figure 11 illustrate the experimental results in the broad picture for the cross-validation performances and the testing performance for the best models, respectively, based on the results acquired in our experiments for dataset4. Overall, When compared to the other models, the OPCNN-FAKE model provides the largest cross-validation and the testing performance. For cross-validation results, OPCNN-FAKE model has achieved the highest performance (Accuracy = 100%, precision = 100%, recall = 100%, and F1-score = 100%). KNN with Four-gram has registered the lowest performance (Accuracy = 91.54%, precision = 91.52%, recall = 91.63%, and F1-score = 91.54%). RF with Tri-gram has achieved the second best performance (Accuracy = 99.75%, precision = 99.74%, recall = 99.73%, and F1-score = 99.75%). For the testing results, the OPCNN-FAKE model has achieved the highest performance (Accuracy = 99.99%, precision = 99.99%, recall = 99.99%, and F1-score = 99.99%). DT with Four-gram has registered the lowest performance (Accuracy = 90.72%, precision = 90.72%, recall = 90.93%, and F1-score = 90.72%). RF with Tri-gram has achieved the second

TABLE 24. Results comparison with existing work.

Ref	The number of dataset	Dataset name	Models' performance
[33] (2020)	One dataset	FakeNewsNet (PolitiFact topic)	CNN Accuracy= 62.9% and F1-score =58.3%
		FakeNewsNet (GossipCop topic)	CNN Accuracy= 72.3% and F1-score =72.5%
[27] (2020)	One dataset	The dataset from Kaggle	hybrid CNN-LSTM Accuracy =97.5%
[29] (2021)	Two datasets	ISOT dataset	hybrid CNN-RNN Accuracy =100% of the training set
		FA-KES dataset	hybrid CNN-RNN Accuracy = 60% of training set
[28] (2020)	One dataset	The dataset from Kaggle	The CNN only (Accuracy of 91.50%, Precision = 90.74%, Recall = 92.07%, F1-Score = 91.40%) The FNDNet (deeper CNN) model (Accuracy of 98.36%, Precision =99.40%, Recall =96.88%, F1-Score =98.12%)
[30] (2019)	Two dataset	Weibo	Accuracy = 88.82%
		NewsFN	Accuracy=90.10%
Our work	Four datasets	Dataset from Kaggle (dataset1)	The OPCNN-FAKE model Cross-validation results (Accuracy = 99.99%, Precision = 100%, Recall = 99.97%, and F1-score = 99.97%). Testing set (Accuracy = 97.84%, Precision = 97.86%, Recall = 97.84%, and F1-score = 97.84%).
		FakeNewsNet	The OPCNN-FAKE model Cross-validation results (Accuracy = 98.65%, Precision = 99.34%, Recall = 98.87%, and F1-score = 99.1%). Testing results (Accuracy = 95.26%, Precision = 95.28%, Recall = 95.26%, and F1-score = 95.27%).
		FA-KES5	The OPCNN-FAKE model Cross-validation results (Accuracy = 97.23%, Precision = 97.37%, Recall = 97.58%, and F1-score = 97.26%) Testing results (Accuracy = 53.99%, Precision = 53.86%, Recall = 53.91%, and F1-score = 53.99%).
		ISOT	OPCNN-FAKE Cross-validation results (Accuracy = 100%, Precision = 100%, Recall = 100%, and F1-score = 100%). Testing results (Accuracy = 99.99%, Precision = 99.99%, Recall = 99.99%, and F1-score = 99.99%).

best performance (Accuracy = 99.9%, precision = 99.9%, recall = 99.9%, and F1-score = 99.9%).

Briefly, the proposed OPCNN-FAKE model has the highest performance compared to the other models based on Accuracy, Precision, Recall, f1-score. Furthermore, it indicates that the OPCNN-FAKE model for fake news detection performance is significantly better than the other existing works that have used methods based on CNN. For instance, the authors of [27] used a dataset from Kaggle and the accuracy registered was 97.5% and in [28] the performance for CNN was only (Accuracy of 91.50%, Precision = 90.74%, Recall = 92.07, F1-Score = 91.40);and the performance for the FNDNet was (Accuracy of 98.36%, Precision = 99.40, Recall = 96.88, F1-Score = 98.12), while OPCNN-Fake achieved the highest performance for cross-validation results

(Accuracy = 99.99%, Precision = 100%, Recall = 99.97%, and F1-score = 99.97%), and for the testing results (Accuracy = 97.84%, Precision = 97.86%, Recall = 97.84%, and F1-score = 97.84%).

For FakeNewsNet, the preference in [15] was (Accuracy = 62.9% and F1-score = 58.3%), while OPCNN-Fake performance for cross-validation results was (Accuracy = 98.65%, and F1-score = 99.1%), and performance for the testing results was (Accuracy = 95.26%, and F1-score = 95.27%). Furthermore, FA-KES5 was used by [29] and the performance for hybrid CNN-RNN was (Accuracy = 60% for the training set), while OPCNN-Fake performance for cross-validation results achieved (Accuracy = 97.23). For ISOT, the performance in [29] was (Accuracy = 100% for the training set), and OPCNN-Fake




FIGURE 10. The best cross-validation performance models for dataset4.




FIGURE 11. The best testing performance models for dataset4.

performance for cross-validation results was (Accuracy = 100%). Briefly, Table 24 illustrates the difference between the OPCNN-FAKE and existing work based on the dataset and performance.

V. CONCLUSION

This paper has introduced a fake news detection system using two approaches, namely, regular ML and DL. In DL, we have proposed the OPCNN-FAKE model that has achieved the best performance. The proposed OPCNN-FAKE model consists of six layers: an embedding layer, a dropout layer, a convolutional layer, a pooling layer, a flatten layer, and an output layer. Also, it has been optimized using hyperopt optimization technique; the different values of parameters for each layer have been adapted, and the best values that achieved the best performance have been selected. Also, n-gram with TF-IDF and word embedding feature extraction methods have been used for ML and DL, respectively. We compared the OPCNN-FAKE with RNN, LSTM, and the six regular ML techniques: DT, LR, KNN, RF, SVM, NB using four fake news benchmark datasets. Each dataset has been split into 80% training dataset and 20% testing dataset. The training datasets have been used to optimize and train the models, while the testing datasets were used to evaluate the models. Also, cross-validation and the testing results have been registered showing that the OPCNN-FAKE model has achieved the best performance for each dataset compared

with the other models. For dataset1, the OPCNN-FAKE model achieved the best performance for the testing results (Accuracy = 97.84%, precision = 97.86%, recall = 97.84%, and F1-score = 97.84%). For dataset2 (FakeNewsNet), in the testing results, OPCNN-FAKE model has achieved the highest performance for the testing results (Accuracy = 95.26%, precision = 95.28%, recall = 95.26%, and F1-score = 95.27%). For dataset3, OPCNN-FAKE model has achieved the highest performance for the testing results (Accuracy = 53.99%, precision = 53.86%, recall = 53.91%, and F1-score = 53.99%). For dataset4, the OPCNN-FAKE model has achieved the highest performance for the testing results (Accuracy = 99.99%, precision = 99.99%, recall = 99.99%, and F1-score = 99.99%). In future, we will use our proposed model to detect COVID-19 fake news. Also, we plan to apply multimodel-based methods with recently pre-trained word embeddings (i.e., Elmo, XLNet, etc.) to handle visual information like video and images. In addition, we may use knowledge-based and fact-based approaches to detect fake news. We will also expand our planned dataset to include data from additional languages.

REFERENCES

- [1] M. H. Goldani, R. Safabakhsh, and S. Momtazi, "Convolutional neural network with margin loss for fake news detection," *Inf. Process. Manage.*, vol. 58, no. 1, Jan. 2021, Art. no. 102418.
- [2] A. Bondielli and F. Marcelloni, "A survey on fake news and rumour detection techniques," *Inf. Sci.*, vol. 497, pp. 38–55, Sep. 2019.
- [3] K. Rapoza, "Can 'fake news' impact the stock market," *Tech. Rep.*, 2017. [Online]. Available: <https://www.forbes.com/sites/kenrapoza/2017/02/26/can-fake-news-impact-the-stock-market/?sh=187125e22fac>
- [4] H. Allcott and M. Gentzkow, "Social media and fake news in the 2016 election," *J. Econ. Perspect.*, vol. 31, no. 2, pp. 211–236, 2017.
- [5] L. Bozarth and C. Budak, "Toward a better performance evaluation framework for fake news classification," in *Proc. Int. AAAI Conf. Web Social Media*, vol. 14, 2020, pp. 60–71.
- [6] Y. Liu and Y.-F. B. Wu, "Early detection of fake news on social media through propagation path classification with recurrent and convolutional networks," in *Proc. 32nd AAAI Conf. Artif. Intell.*, Apr. 2018, pp. 354–361.
- [7] F. Monti, F. Frasca, D. Eynard, D. Mannion, and M. M. Bronstein, "Fake news detection on social media using geometric deep learning," 2019, *arXiv:1902.06673*. [Online]. Available: <http://arxiv.org/abs/1902.06673>
- [8] S. Gírgis, E. Amer, and M. Gadallah, "Deep learning algorithms for detecting fake news in online text," in *Proc. 13th Int. Conf. Comput. Eng. Syst. (ICCES)*, Dec. 2018, pp. 93–97.
- [9] S. Ghosh and C. Shah, "Towards automatic fake news classification," *Proc. Assoc. Inf. Sci. Technol.*, vol. 55, no. 1, pp. 805–807, Jan. 2018.
- [10] R. Yamashita, M. Nishio, R. K. G. Do, and K. Togashi, "Convolutional neural networks: An overview and application in radiology," *Insights Imag.*, vol. 9, pp. 611–629, Aug. 2018.
- [11] Y. Yu, C. Wang, X. Gu, and J. Li, "A novel deep learning-based method for damage identification of smart building structures," *Struct. Health Monitor.*, vol. 18, no. 1, pp. 143–163, Jan. 2019.
- [12] H. Li, "Deep learning for natural language processing: Advantages and challenges," *Nat. Sci. Rev.*, vol. 5, no. 1, pp. 24–26, Jan. 2018.
- [13] J. Ma, W. Gao, P. Mitra, S. Kwon, B. J. Jansen, K.-F. Wong, and M. Cha, "Detecting rumors from microblogs with recurrent neural networks," *Tech. Rep.*, 2016. [Online]. Available: https://ink.library.smu.edu.sg/sis_research/4630/
- [14] N. Ruchansky, S. Seo, and Y. Liu, "CSI: A hybrid deep model for fake news detection," in *Proc. ACM Conf. Inf. Knowl. Manage.*, Nov. 2017, pp. 797–806.
- [15] K. Shu, D. Mahudeswaran, S. Wang, D. Lee, and H. Liu, "FakeNewsNet: A data repository with news content, social context and spatiotemporal information for studying fake news on social media," 2018, *arXiv:1809.01286*. [Online]. Available: <http://arxiv.org/abs/1809.01286>

- [16] F. K. A. Salem, R. Al Feel, S. Elbassuoni, M. Jaber, and M. Farah, "FA-KES: A fake news dataset around the Syrian war," in *Proc. Int. AAAI Conf. Web Social Media*, vol. 13, 2019, pp. 573–582.
- [17] K. Popat, S. Mukherjee, A. Yates, and G. Weikum, "DeClarE: Debunking fake news and false claims using evidence-aware deep learning," 2018, *arXiv:1809.06416*. [Online]. Available: <http://arxiv.org/abs/1809.06416>
- [18] P. Ksieniewicz, M. Choraś, R. Kozik, and M. Woźniak, "Machine learning methods for fake news classification," in *Proc. Int. Conf. Intell. Data Eng. Automated Learn.* Guimaraes, Portugal: Springer, 2019, pp. 332–339.
- [19] J. P. Singh, A. Kumar, N. P. Rana, and Y. K. Dwivedi, "Attention-based LSTM network for rumor veracity estimation of tweets," *Inf. Syst. Frontiers*, pp. 1–16, Aug. 2020, doi: [10.1007/s10796-020-10040-5](https://doi.org/10.1007/s10796-020-10040-5).
- [20] H. Ahmed, I. Traore, and S. Saad, "Detection of online fake news using n-gram analysis and machine learning techniques," in *Proc. Int. Conf. Intell., Secure, Dependable Syst. Distrib. Cloud Environ.* Vancouver, BC, Canada: Springer, 2017, pp. 127–138.
- [21] V. Pérez-Rosas, B. Kleinberg, A. Lefevre, and R. Mihalcea, "Automatic detection of fake news," 2017, *arXiv:1708.07104*. [Online]. Available: <http://arxiv.org/abs/1708.07104>
- [22] Q. Li, W. Cai, X. Wang, Y. Zhou, D. D. Feng, and M. Chen, "Medical image classification with convolutional neural network," in *Proc. 13th Int. Conf. Control Autom. Robot. Vis. (ICARCV)*, Dec. 2014, pp. 844–848.
- [23] M. Khalil-Hani and L. S. Sung, "A convolutional neural network approach for face verification," in *Proc. Int. Conf. High Perform. Comput. Simul. (HPCS)*, Jul. 2014, pp. 707–714.
- [24] M. Liang and X. Hu, "Recurrent convolutional neural network for object recognition," in *Proc. IEEE Conf. Comput. Vis. Pattern Recognit. (CVPR)*, Jun. 2015, pp. 3367–3375.
- [25] Y. Goldberg, "Neural network methods for natural language processing," *Synth. Lect. Hum. Lang. Technol.*, vol. 10, no. 1, pp. 1–309, 2017.
- [26] Y. Yang, L. Zheng, J. Zhang, Q. Cui, Z. Li, and P. S. Yu, "TI-CNN: Convolutional neural networks for fake news detection," 2018, *arXiv:1806.00749*. [Online]. Available: <http://arxiv.org/abs/1806.00749>
- [27] A. Abdullah, M. Awan, M. Shehzad, and M. Ashraf, "Fake news classification bimodal using convolutional neural network and long short-term memory," *Int. J. Emerg. Technol. Learn.*, vol. 11, pp. 209–212, Aug. 2020.
- [28] R. K. Kaliyar, A. Goswami, P. Narang, and S. Sinha, "FNDNet—A deep convolutional neural network for fake news detection," *Cognit. Syst. Res.*, vol. 61, pp. 32–44, Jun. 2020.
- [29] J. A. Nasir, O. S. Khan, and I. Varlamis, "Fake news detection: A hybrid CNN-RNN based deep learning approach," *Int. J. Inf. Manage. Data Insights*, vol. 1, no. 1, Apr. 2021, Art. no. 100007.
- [30] Q. Li, Q. Hu, Y. Lu, Y. Yang, and J. Cheng, "Multi-level word features based on CNN for fake news detection in cultural communication," *Pers. Ubiquitous Comput.*, vol. 24, no. 2, pp. 259–272, 2019.
- [31] R. K. Kaliyar, A. Goswami, and P. Narang, "DeepFakeE: Improving fake news detection using tensor decomposition-based deep neural network," *J. Supercomput.*, vol. 77, no. 2, pp. 1015–1037, Feb. 2021.
- [32] R. K. Kaliyar, A. Goswami, and P. Narang, "EchoFakeD: Improving fake news detection in social media with an efficient deep neural network," *Neural Comput. Appl.*, pp. 1–17, Jan. 2021, doi: [10.1007/s00521-020-05611-1](https://doi.org/10.1007/s00521-020-05611-1).
- [33] K. Shu, D. Mahudeswaran, S. Wang, D. Lee, and H. Liu, "FakeNewsNet: A data repository with news content, social context, and spatiotemporal information for studying fake news on social media," *Big Data*, vol. 8, no. 3, pp. 171–188, Jun. 2020.
- [34] *Fake News Detection*.
- [35] J. Pennington, R. Socher, and C. Manning, "Glove: Global vectors for word representation," in *Proc. Conf. Empirical Methods Natural Lang. Process. (EMNLP)*, 2014, pp. 1532–1543.
- [36] F. Chollet, "Keras: The Python deep learning library," *Astrophys. Source Code Library*, to be published. [Online]. Available: <https://ui.adsabs.harvard.edu/abs/2018ascl.soft06022C/abstract>
- [37] B. Zhong, X. Xing, P. Love, X. Wang, and H. Luo, "Convolutional neural network: Deep learning-based classification of building quality problems," *Adv. Eng. Informat.*, vol. 40, pp. 46–57, Apr. 2019.
- [38] A. F. Agarap, "Deep learning using rectified linear units (ReLU)," 2018, *arXiv:1803.08375*. [Online]. Available: <http://arxiv.org/abs/1803.08375>
- [39] Z. Zhang, "Improved Adam optimizer for deep neural networks," in *Proc. IEEE/ACM 26th Int. Symp. Qual. Service (IWQoS)*, Jun. 2018, pp. 1–2.
- [40] A. Wanto, A. P. Windarto, D. Hartama, and I. Parlina, "Use of binary sigmoid function and linear identity in artificial neural networks for forecasting population density," *Int. J. Inf. Syst. Technol.*, vol. 1, no. 1, pp. 43–54, 2017.
- [41] J. Bergstra, D. Yamins, and D. Cox, "Hyperopt: Distributed asynchronous hyper-parameter optimization," *Retrieved May*, vol. 21, p. 2020, 2012.
- [42] A. Sherstinsky, "Fundamentals of recurrent neural network (RNN) and long short-term memory (LSTM) network," *Phys. D, Nonlinear Phenomena*, vol. 404, Mar. 2020, Art. no. 132306.
- [43] A. Graves, "Long short-term memory," in *Supervised Sequence Labelling With Recurrent Neural Networks*. Springer, 2012, pp. 37–45. [Online]. Available: https://link.springer.com/chapter/10.1007%2F978-3-642-24797-2_4
- [44] M. Sundermeyer, R. Schlüter, and H. Ney, "LSTM neural networks for language modeling," in *Proc. Interspeech*, Sep. 2012, pp. 1–4.
- [45] T. van Laarhoven, "L2 regularization versus batch and weight normalization," 2017, *arXiv:1706.05350*. [Online]. Available: <http://arxiv.org/abs/1706.05350>
- [46] A. Sikandar, W. Anwar, U. I. Bajwa, X. Wang, M. Sikandar, L. Yao, Z. L. Jiang, and Z. Chunkai, "Decision tree based approaches for detecting protein complex in protein protein interaction network (PPI) via link and sequence analysis," *IEEE Access*, to vol. 6, pp. 22108–22120, 2018.
- [47] J. H. Cheon, D. Kim, Y. Kim, and Y. Song, "Ensemble method for privacy-preserving logistic regression based on homomorphic encryption," *IEEE Access*, vol. 6, pp. 46938–46948, 2018.
- [48] Y. Guo, H. Cao, S. Han, Y. Sun, and Y. Bai, "Spectral-spatial hyperspectral image classification with k-nearest neighbor and guided filter," *IEEE Access*, vol. 6, pp. 18582–18591, 2018.
- [49] M. Pal, "Random forest classifier for remote sensing classification," *Int. J. Remote Sens.*, vol. 26, no. 1, pp. 217–222, 2007.
- [50] L. Auria and R. A. Moro, "Support vector machines (SVM) as a technique for solvency analysis," *IEEE Access*, 2008.
- [51] L. Li, Y. Zhang, W. Chen, S. K. Bose, M. Zukerman, and G. Shen, "Naïve Bayes classifier-assisted least loaded routing for circuit-switched networks," *IEEE Access*, vol. 7, pp. 11854–11867, 2019.

HAGER SALEH received the Ph.D. degree from the Faculty of Computers and Information, Minia University, Egypt. She is currently a Lecturer with the Faculty of Computers and Artificial Intelligence, South Valley University, Hurghada, Egypt. She is also a Research Member of the Big Data Team in Egypt. Her research interests include big data analytics, data mining, sentiment analysis, natural language processing, machine learning, deep learning, and streaming data.

ABDULLAH ALHARBI received the Ph.D. degree from the University of Technology Sydney, Australia. He is currently an Associate Professor with the Department of Information Technology, Taif University. His research interests include human-computer interaction, information systems modeling, streaming data, cybersecurity, big data analytics, AI, and data science.



SAEED HAMOOD ALSAMHI received the B.Eng. degree from the Department of Electronic Engineering (Communication Division), IBB University, Yemen, in 2009, and the M.Tech. degree in communication systems and the Ph.D. degree from the Department of Electronics Engineering, Indian Institute of Technology (Banaras Hindu University), IIT (BHU), Varanasi, India, in 2012 and 2015, respectively. In 2009, he worked as a Lecturer Assistant with the Faculty of Engineering, IBB University. He was a Postdoctoral Researcher with the School of Aerospace Engineering, Tsinghua University, Beijing, China, in optimal and smart wireless network research and its applications to enhance robotics technologies. Since 2019, he has been an Assistant Professor. He is currently a MSCA SMART 4.0 Fellow at Athlone Institute of Technology, Athlone, Ireland. He has published 30 articles in high reputation journals in IEEE, Elsevier, Springer, Wiley, and MDPI publishers. His research interests include green communication, green Internet of Things, QoS, multi-robot collaboration, block-chain technology, and space technologies (high altitude platform, drone, and tethered balloon technologies).

...