

Received February 21, 2022, accepted May 6, 2022, date of publication May 23, 2022, date of current version May 27, 2022.

Digital Object Identifier 10.1109/ACCESS.2022.3177195

Development of Bayesian Neural Network Model to Predict the Correlated Color Temperature Using Digital Camera and Macbeth ColorChecker Chart

VEDAVYASA KAMATH¹, CIJI PEARL KURIAN¹, (Senior Member, IEEE),
AND U. SUPRABHA PADIYAR¹

Department of Electrical and Electronics Engineering, Manipal Institute of Technology, Manipal Academy of Higher Education, Manipal, Karnataka 576104, India

Corresponding author: Ciji Pearl Kurian (ciji.pearl@manipal.edu)

This work was supported in part by the All India Council for Technical Education (AICTE), Research Promotional Scheme (RPS) India, funded Project, under Grant 8-T4/FDC/RPS (Policy-1) /2019-20.

ABSTRACT Information about correlated color temperature influencing the scene due to the surrounding lighting is vital, especially for circadian lighting and photography. This paper proposes a novel image-based machine learning model to predict the correlated color temperature in a scene with the help of the Macbeth ColorChecker color rendition chart and a DSLR camera. In the proposed technique, the researcher fixes the white balance setting in the camera, thereby forcing color difference in the captured image of the Macbeth ColorChecker chart placed in the scene. The Bayesian neural network model considers the color difference values of the six spectrally neutral patches of the Macbeth ColorChecker chart as inputs for CCT prediction. The color differences are calculated using the CIEDE2000 color difference formula. Four models with white balance settings in the camera as 5000 K, 6500 K, 8000 K, and 10000 K were developed and analyzed. During experimentation, the proposed model's correlated color temperature prediction error is less than five percent with the white balance setting in the DSLR camera as 10000 K. The model performed consistently under varied lighting levels and mixed CCT lighting conditions set up with LED, incandescent, and fluorescent lamps.

INDEX TERMS Computer vision, digital photography, image color analysis, neural networks, photometry.

I. INTRODUCTION

Correlated color temperature (CCT) expressed in Kelvin (K) indicates the color of the influencing light in a scene. The knowledge of the CCT value can be used to estimate the appearance of a known object in a scene. In various sectors like healthcare, industry, and corporate, circadian lighting is gaining importance, which demands color tuning of indoor artificial light [1]–[3]. This is achieved by varying CCT and intensity of the artificial light in sync with outdoor light conditions. In photography, knowledge of light source CCT is crucial in determining the color output of the photograph. The camera setting 'white balance', which can be set by the photographer, is associated with the CCT of light governing

the scene [4]. Hence, CCT information of the light source in a location is vital in human-centric lighting and photography applications.

The use of digital cameras as sensors for photometry has gained momentum due to their cost-effectiveness, measurement speed, and accuracy [5]–[7]. Techniques of using a digital single-lens reflex (DSLR) camera for luminance measurement are well explored and established [8]–[10]. This motivates us to explore further the possibility of using a digital camera to estimate photometric parameters like CCT and Color Rendering Index (CRI), which are helpful to access the qualitative aspects of lighting design.

The traditional approach of CCT measurement involves placing the artificial light source in an integrating sphere that houses a spectrometer. Handheld spectrometers are now available in the market with which CCT of the influencing

The associate editor coordinating the review of this manuscript and approving it for publication was Jeon Gwanggil¹.

light source on the work plane can be obtained. But both methods require expensive calibrated instruments. Professional photographers use standardized target surfaces to ensure color reproduction in the resulting photograph.

CIEDE2000 has been officially adopted as the color difference formula by CIE [11], [12]. Software tools are available to compute this color difference caused by the camera settings during image capture. Using standard white balance cards and ColorChecker charts for color rectification is enhanced with the help of post-processing photo editing software commercially available [13]. Though these charts help correct color in the resulting image, they do not provide the actual numerical value of CCT in the captured scene.

When a camera is used for photometric measurement, the white balance setting plays a significant role in deciding the pixel values of the resulting image. The user must carefully analyze the lighting condition in the scene and set the white balance mode. Keeping auto white balance (AWB) mode on the camera may lead to unreliable pixel data for photometry. The post-processing image manipulation algorithms of the camera also contribute to the pixel values. It must be noted that the user has limited control over these image manipulation steps. A sensor calibration method is suggested by Juan Sebastian Valencia *et al.* [14] to address the above issue. Sneha Jain *et al.* [15] photographically obtained CIE XYZ values using HDR images. McCamy's method is used to calculate CCT values from CIE XYZ values. The percentage error reported by the authors for CCT prediction is $\pm 9.54\%$. The light source in the scene was a tubular daylight device. The radiance daylight simulation tool was used to get X , Y , and Z pixel values from the HDR image.

Authors of literature [16] proposed a novel model that can predict dynamic variations of CRI and CCT due to system power variations of phosphor-coated white LED systems. Electrical, optical, spectral, thermal, and device-specific parameters were extracted from steady-state tests only. The authors claimed that the model could be used during steady-state and dynamic situations. The current article proposes a machine learning-based approach to predict the actual CCT influencing the scene with the help of Xrite ColorChecker chart pixel data.

II. PROPOSED HYPOTHESIS

This study explores the possibility of establishing a relation between the pixel data of the ColorChecker chart image and the CCT of light in the scene and proposes a machine learning-based model to predict the CCT influencing a given location.

The hypothesis statement is as follows: 'When the white balance of a digital camera is manually fixed, and an image of the ColorChecker chart is captured, the color difference of the spectrally neutral patches of the chart that result after shifting the pixel values to D50 white point can be used to predict the actual CCT of the surrounding light'.

Once the white balance value is fixed in the camera, say to 10000 K, the camera's image processor considers

TABLE 1. Reference CIE L^* , a^* , b^* values using illuminant D50 2-degree observer (for charts manufactured before november 2014).

Color patch	L^*	a^*	b^*
White	96.539	-0.425	1.186
Neutral 8	81.257	-0.638	-0.335
Neutral 6.5	66.766	-0.734	-0.504
Neutral 5	50.867	-0.153	-0.27
Neutral 3.5	35.656	-0.421	-1.231
Black	20.461	0.079	-0.973

the surrounding light condition as cool white (with CCT 10000 K). The processor then compensates by adding a yellow tint to produce an image of the scene under neutral white conditions. For example, if the actual lighting condition of the scene is warm white, say 3200 K, and the image of the scene is captured with a white balance setting as 10000 K, a considerable yellow tint appears in the resulting image. The image seems warmer than seen by the eye. This condition is due to the additional yellow tint compensation made by the camera image processor to make the image scene appear neutral. The compensation done by the camera for neutralizing the image is assumed to be directly proportional to the difference between the actual CCT of the scene and the set white balance in the camera. This process is not desired by a photographer whose aim is usually to capture a scene as seen by the human eyes. In the proposed technique, the color difference caused by the white balance setting in the resulting image from the actual scene is desired for analysis purposes.

The CIE L^* , a^* , b^* values of patches of x-rite ColorChecker chart classic manufactured before and after November 2014 are made available by the manufacturer [17]. These standard reference values are noted by illuminating the chart with a D50 illuminant, that is, standard lighting condition with a CCT value of 5003 K. The reference L^* , a^* , and b^* values of the six neutral patches used during experimentation are given in Table 1.

To compute the color difference, it is necessary that reference and measured L^* , a^* , and b^* values should have the same white point [18]. Hence, during the experimentation, the measured L^* , a^* , b^* value under a lighting condition is transformed to L^* , a^* , b^* value with D50 white point.

The following sections discuss the experimental setup to test the proposed hypothesis, model development to relate color difference values with actual CCT, and results are discussed.

III. EXPERIMENTAL SETUP

The ColorChecker chart is exposed to a wide range of CCT values from warm white to cool white lighting conditions in the experimentation. For every lighting condition, the image of the ColorChecker chart is captured using a DSLR camera, and the actual CCT value is measured using calibrated Asensetek lighting passport spectrometer. The actual

values of CCT measured from the standard meter, and the extracted RGB values of the spectrally neutral targets in the ColorChecker chart are used to develop a supervised learning-based neural network model for predicting CCT. The workflow of the data building process is shown in Fig. 1.




FIGURE 1. Workflow for developing the model.

A. SURROUNDING CONDITIONS

For gathering data for the proposed model, a dark room is used to ensure consistent lighting conditions. Experimenting in the darkroom nullifies the influence of wall surfaces and objects on the ColorChecker chart. Also, the ColorChecker chart is illuminated only by the desired sources for the research.

In the setup, four commercially available LED battens are used. The technical details of the fixture are shown in Table 2.

With the help of the android app, the CCT of the four lamps can be changed in steps of 1% simultaneously, from 2800 K to 5800 K, providing 110 unique CCT lighting conditions. The LED fixture’s spectral power distribution (SPD) when set to

TABLE 2. Light source specification.

Product	Smart LED batten
Input voltage and power	240 V, 50 Hz; 20 W
Nominal lumens	1880 lm
CCT	Cool white to warm white
Light control	Dimmable via android app or voice assistants




FIGURE 2. (a) SPD of the fixture with cool white light output and 0% dimming (b) SPD of fixture with cool white light output and 0% dimming.

cool white and warm white conditions is shown in Fig. 2. The app also facilitated the fixture’s remote operation, thereby avoiding the possible error due to light reflection from users’ clothing. Care is also taken to provide a constant voltage supply to the lighting fixtures.

The light fixtures are vertically mounted to throw light on the ColorChecker chart positioned 1.5 meters away. The ColorChecker chart (passport) is clamped to cardboard and positioned vertically. The calibrated spectrometer is mounted above the chart to capture the true CCT due to the light fixtures, as shown in Fig. 3. The spectrometer is also triggered to capture accurate data remotely through the spectrum genius mobile application. The isometric view of the light fixture set up with the camera is shown in Fig. 4.

The camera is positioned behind the lighting fixture to avoid glare on the camera lens. The image of the ColorChecker chart is captured by placing it in front of the lighting fixture.

B. CAMERA SETUP

The camera used for the experiment is a full-frame Nikon D750 with a 50 mm Nikkor F/1.8D AF prime lens. In addition to standard white balance settings like auto, cloudy, and shade, the user can manually set the color temperature



FIGURE 3. Positioning of ColorChecker chart and spectrometer.




FIGURE 4. Isometric view of the light fixture arrangement.

TABLE 3. Additional camera settings for data collection.

ISO	100
Shooting mode	Aperture priority mode
Aperture value	f/3.2
Active D-Lighting	OFF
Remote control mode	ON
Color space	sRGB
Picture control	Neutral

value of the scene in the camera. The motive behind using a prime lens is to reduce the possibility of vignetting and distortions due to the series of glasses found in telephoto lenses. Table 3 shows camera settings made during data collection.

ISO 100 camera sensor sensitivity leads to less digital noise in the resulting image. The sensor is correctly exposed (exposure compensation is zero) using aperture priority mode. Since the chart surface is parallel to the image sensor, the aperture of f/3.2 ensures the correct focus of the ColorChecker chart patches in the image. Post-processing settings like ‘active D-lighting’ and ‘picture control’ are minimized. The camera is mounted on a tripod. The center of the lens and ColorChecker chart are in the same line. The camera flash is kept OFF, and the shutter button is remotely triggered using a wireless remote.

C. IMAGE DATA EXTRACTION AND MODEL DEVELOPMENT

The proposed model should work in any lighting conditions caused by different types of light sources (LED, incandescent, fluorescent). Four models are developed using images captured with white balance as 5000 K, 6500 K, 8000 K, and 10000 K. For each white balance setting, around 110 images are analyzed. The white balance value that gives the best performing model has to be fixed as the white balance setting during the deployment of the proposed setup. In sections D, E, and F, the procedure followed to extract data from images, the statistical significance analysis, and model development are discussed.

D. DATA EXTRACTION FROM IMAGES

Data extraction from images is a laborious process without proper image processing tools. The steps to obtain the CIEDE2000 color difference value for each of the neutral patches of the ColorChecker chart are shown in Fig. 5.




FIGURE 5. Stages to calculate the color difference of a neutral color patch.

An application is developed using MATLAB App Designer to simplify data collection and tabulation. Fig. 6 shows the opening page of the application when the user chooses an image to analyze using the ‘Browse Image’ button.




FIGURE 6. Opening page of the developed GUI.

The application is used in the following steps:

1) STEP 1: BROWSE AND SELECT THE IMAGE TO BE ANALYZED

Once the user chooses the image to analyze using the ‘Browse Image’ button, camera aperture, shutter speed, ISO settings used to capture the scene, and the file name are displayed at the bottom of the application screen to facilitate the user. The EXIF data of the image file using image processing toolbox commands is used for this purpose. The user can also enter the true CCT and CRI values noted from the calibrated sensor during the capture of the scene.

2) STEP 2: COLOR CHECKER CHART IDENTIFICATION

The user must manually specify the ‘registration points’ of the ColorChecker chart, as shown in Fig. 7. This is done by moving the four blue points (labeled as 1. Black point, 2. White point, 3. Brown point, and 4. Bluish-green point) to their marker position available in the chart. Once this is done, the ‘Marker points updated’ button must be pressed.



FIGURE 7. Specifying the ColorChecker chart registration points.

On the press of the ‘Marker points updated’ button in the designed app, the following operations occur:

- 1) All the patches of the ColorChecker chart are identified, and RGB pixel values of the patches are measured. This step of chart recognition can be verified, as shown in Fig. 8.
- 2) Color differences based on the CIEDE2000 formula and CIE94 formula are computed and tabulated

The above steps occur due to ‘ColorChecker’ (function of MATLAB available since 2020b version), ‘measureColor’ (measures RGB values from the chart patches), ‘rgb2lab’ (to covert RGB color space to LAB with D50 as white point), ‘imcolordiff’ (to calculate color difference with CIEDE2000 formula). Depending upon the manufactured date of the ColorChecker chart (before/after November 2014), the reference values used in the ‘measureColor’ function are to be modified.




FIGURE 8. Identification of ColorChecker chart.

3) STEP 3: DATA SAVING

After step 2, the application user interface appears, as shown in Fig. 9.




FIGURE 9. User interface after the chart is analyzed.

The ‘Export Data’ button is enabled to export the following data to an excel file:

- RGB pixel values of ColorChecker chart patches
- LAB values of ColorChecker chart patches
- Image file name and camera exposure settings
- CIEDE2000 color difference value of all the ColorChecker chart patches
- True CCT and CRI value

The excel file can be accessed from the ‘current folder’ set in MATLAB. After the data is exported, the user can continue to analyze another image. A tracker is maintained to inform the user about the number of image files analyzed.

E. STATISTICAL ANALYSIS OF THE DATA

The data of color difference is measured for six neutral patches, and the actual CCT condition of the scene is recorded and tabulated for each white balance setting on the camera (5000 K, 6500 K, 8000 K, and 10000 K). Statistical tests are carried out to check if a statistical correlation between the




FIGURE 10. Bayesian neural network model structure.




FIGURE 11. BNN based ML model performance at 5000 K camera white balance setting (a) Error histogram (b) Regression for training data (c) Regression for test data.

tabulated color difference values of the neutral patches and the actual CCT value of the scene exists.

Table 4 shows the outcome of Pearson’s correlation test for the color difference vs. actual CCT data collected corresponding to a white balance setting of 10000 K. A negative ‘r’ value close to 1 indicates good inverse relation between the two variables supporting the possibility of a mathematical model for predicting the CCT of the scene.

In addition to the correlation test, z-score values were used to detect outliers. Measurements with z-score above and below 2.56 and -2.56 , respectively, are considered outliers.

F. TRAINING A BAYESIAN NEURAL NETWORK

The CIE2000 color difference data of the six neutral patches populated is used for training the Bayesian neural network. Four neural network models corresponding to 5000 K, 6500 K, 8000 K, and 10000 K white balance settings are




FIGURE 12. BNN based ML model performance at 6500 K camera white balance setting (a) Error histogram (b) Regression for training data (c) Regression for test data.

developed. The network structure is as shown in Fig. 10. 75% of the data is used for training, and the remaining 25% is used for testing purposes.

IV. RESULTS AND DISCUSSION

This section discusses the results obtained from the Bayesian neural network-based model for four different manual white balance settings in the camera.

Fig. 11-14 shows the error histograms, training, and testing regression plots for four different white balance settings in the camera, i.e., 5000 K, 6500 K, 8000 K, and 10000 K. Table 5 provides the Mean Square Error (MSE) of the CCT prediction models during training and testing. When the white balance is set to 5000 K, it is observed that the model is overfitting for the training data hence leading to poor generalization. At 6500 K white balance setting in the camera, the performance improves. But for cases with actual CCT values close to 6500 K, the model prediction errors lead to poor testing MSE.

It must be noted that most artificial light sources operate in the 2500 K to 6500 K range. The model’s prediction performance with a white balance setting in the camera at 8000 K and 10000 K is very encouraging.

The model’s mean square error (MSE) with a white balance of 8000 K is better than 10000 K. But prediction instances near-zero error line is more from the model developed with

TABLE 4. Statistical analysis of the correlation between neutral patches and actual CCT value using pearson’s coefficient.

Statistical parameter	Neutral patches of the ColorChecker chart					
	White	Neutral 8	Neutral 6.5	Neutral 5	Neutral 3.5	Black
r	-0.9428	-0.9817	-0.9969	-0.9888	-0.9899	-0.9942
N	120	120	120	120	120	120
t-statistic	30.71	55.95	138.12	72.05	75.82	100.45
DF	118	118	118	118	118	118
p-value	4.11E-58	8.41E-87	2.51E-132	2.15E-99	5.98E-102	3.80E-116




FIGURE 13. BNN based ML model performance at 8000 K camera white balance setting (a) Error histogram (b) Regression for training data (c) Regression for test data.

TABLE 5. Mean square error (MSE) of the CCT prediction models during training and testing.

Camera white balance setting (°K)	Training data		Testing data	
	Sample Size	MSE	Sample Size	MSE
5000	85	78.02	30	38350.97
6500	84	993.53	30	2463.88
8000	75	125.38	20	119.63
10000	86	273.58	23	137.56

10000 K white balance. Also, MSE from the 10000 K white balance model testing samples suggests superior performance to the other models in question.




FIGURE 14. BNN based ML model performance at 10000 K camera white balance setting (a) Error histogram (b) Regression for training data (c) Regression for test data.

The spectral power distribution of traditional light sources like incandescent bulbs and fluorescent lamps significantly differs from LED light sources. The model has a scope of bias since it was developed from an LED smart batten measurement data. This problem is addressed with additional light measurements using traditional sources and a different LED fixture in the darkroom, whose SPDs are shown in Fig. 15. The 10000 K white balance-based model is re-trained with these additional measurements. These added measurements ensured a versatile model for CCT prediction.

The robustness of the model is evaluated in two ways. One, by creating lighting scenes with LED lamps operating at different CCT values in a given scene. The model’s performance

TABLE 6. CCT prediction via bayesian neural network (BNN) in mixed lighting conditions with camera white balance set at 10000 K.

Lamp 1 (°K)	Lamp 2 (°K)	Lamp 3 (°K)	Lamp 4 (°K)	Actual effective CCT (°K)	Predicted effective CCT (°K)	% Error
~2800	~2800	~5700	~5700	4033	4061	0.69
~4200	~4200	~5700	~5700	4790	4793	0.06
~5000	~5000	~5700	~5700	5323	5336	0.24
~2800	~3500	~4200	~5000	3667	3697	0.82
~2800	~4200	~4200	~5700	3992	4040	1.20
~5700	~5000	~4200	~3500	4274	4283	0.21
~5700	~5700	~3500	~3500	4275	4494	0.44
~3500	~5700	~5700	~3500	4552	4533	0.42
~5000	~3500	~3500	~5700	4023	4064	1.02




FIGURE 15. SPD of the (a) incandescent bulb, (b) fluorescent lamp, (c) & (d) LED fixture when operated at cool white and warm white light output, respectively, were used to re-train the 10000 K white balance-based model.

TABLE 7. CCT prediction with different light sources and lighting levels.

Light source	Lighting level (lux)	Actual CCT (°K)	Predicted CCT (°K)	% Error
Sunlight	18868	4017	3858	3.96
	90	3347	3452	3.14
Incandescent bulb	837	2634	2672	1.44
	263	2623	2725	3.89
Fluorescent tube light	400	5783	6005	3.84
	63	5885	6104	3.72
New LED fixture	131	5342	5515	3.24
	419	3474	2510	1.04
	126	2895	2909	0.48

is tabulated in Table 6. Two, measurements were carried out under various light sources and light levels. The results are

shown in Table 7. The ColorChecker chart images were taken with the camera’s white balance setting set to 10000 K.

The proposed model gave steady performance even during dimming conditions, as shown in Table 7.

V. CONCLUSION

A novel technique to predict the correlated color temperature in a scene due to the lighting condition of the surrounding using the camera as the sole sensor is proposed in this paper. Macbeth ColorChecker chart is placed in the scene, and the image is captured using a DSLR camera. The pixel data of the six spectrally neutral patches of the ColorChecker chart is used to compute color difference based on the CIEDE2000 formula. The Bayesian neural network-based model predicts the CCT value using the color difference values of six neutral patches as inputs.

The authors would like to emphasize that the white balance setting in the camera plays a crucial role when the image is used for photometric analysis. The resulting pixel values of the image due to incorrect white balance set automatically or manually will lead to erroneous measurements. For the proposed model, it is experimentally found that color difference values obtained with white balance setting in the camera as 10000 K provided the best fit than that of 5000 K, 6500 K, and 8000 K. The correlated color temperature prediction error is less than 5%, with a white balance setting of 10000 K. The prediction error was within the limit even when the scene was illuminated with different CCT values sources. The model’s performance is consistent for a wide range of illuminance levels. With the help of computation tools, the discussed technique requires only a single scene image with a ColorChecker chart. The proposed method successfully addresses the challenge of CCT measurement in a complex lighting scene.

A DSLR camera with a fixed focal length lens (prime lens) is employed during the study. The authors believe that the proposed technique can be carried out using calibrated mobile phone cameras, thereby reducing the overall cost of the system. The model’s accuracy can be further improved with more measurements and re-training. Reducing the complexity of

the model by decreasing the number of inputs to the neural network can be explored. The RAW image information might further enhance data quality.

REFERENCES

- [1] R. Soler and E. Voss, "Biologically relevant lighting: An industry perspective," *Frontiers Neurosci.*, vol. 15, p. 635, Jun. 2021, doi: [10.3389/fnins.2021.637221](https://doi.org/10.3389/fnins.2021.637221).
- [2] C. Papatsimpa and J.-P. Linnartz, "Personalized office lighting for circadian health and improved sleep," *Sensors*, vol. 20, no. 16, p. 4569, Aug. 2020, doi: [10.3390/s20164569](https://doi.org/10.3390/s20164569).
- [3] M. C. Giménez, L. M. Geerdinck, M. Versteylen, P. Leffers, G. J. B. M. Meekes, H. Herremans, B. de Ruyter, J. W. Bikker, P. M. J. C. Kuijpers, and L. J. M. Schlangen, "Patient room lighting influences on sleep, appraisal and mood in hospitalized people," *J. Sleep Res.*, vol. 26, no. 2, pp. 236–246, Apr. 2017, doi: [10.1111/jsr.12470](https://doi.org/10.1111/jsr.12470).
- [4] Y. Zhang, Y. Gao, Y. He, Y. Shi, and K. Liang, "Research on the color temperature & white balance for multimedia sensor," *Proc. Comput. Sci.*, vol. 107, pp. 878–884, Jan. 2017, doi: [10.1016/j.procs.2017.03.187](https://doi.org/10.1016/j.procs.2017.03.187).
- [5] R. Poling and H. Cai, "Calculating luminous flux radiated to a camera lens via high dynamic range photogrammetry," *Lighting Res. Technol.*, vol. 53, no. 2, pp. 119–145, Apr. 2021, doi: [10.1177/1477153520921442](https://doi.org/10.1177/1477153520921442).
- [6] S.-I. Yun and K.-S. Kim, "Sky luminance measurements using CCD camera and comparisons with calculation models for predicting indoor illuminance," *Sustainability*, vol. 10, no. 5, p. 1556, May 2018, doi: [10.3390/su10051556](https://doi.org/10.3390/su10051556).
- [7] A. Zatari, G. Dodds, K. Mcmenemy, and R. Robinson, "Glare, luminance, and illuminance measurements of road lighting using vehicle mounted CCD cameras," *LEUKOS-J. Illum. Eng. Soc. North America*, vol. 1, no. 2, pp. 85–106, Feb. 2005, doi: [10.1582/LEUKOS.2004.01.02.005](https://doi.org/10.1582/LEUKOS.2004.01.02.005).
- [8] M. Inanici, "Evaluation of high dynamic range photography as a luminance data acquisition system," *Lighting Res. Technol.*, vol. 38, no. 2, pp. 123–134, Jun. 2006, doi: [10.1191/1365782806li164oa](https://doi.org/10.1191/1365782806li164oa).
- [9] H. Cai, "Luminance gradient for evaluating lighting," *Lighting Res. Technol.*, vol. 48, no. 2, pp. 155–175, Apr. 2016, doi: [10.1177/1477153513512501](https://doi.org/10.1177/1477153513512501).
- [10] T. S. S. Kumar, C. P. Kurian, K. Shama, and K. R. Shailesh, "High dynamic imaging for photometry and graphic arts evaluation," *J. Inst. Eng. India, B*, vol. 99, no. 4, pp. 383–389, Aug. 2018, doi: [10.1007/s40031-018-0327-7](https://doi.org/10.1007/s40031-018-0327-7).
- [11] *Colorimetry—Part 6: CIEDE2000 Colour-Difference Formula*, Standard ISO/CIE 11664-6:2014(E) (ISO/CIE, 2014), ISO and CIE, 2014.
- [12] M. R. Luo, G. Cui, and B. Rigg, "The development of the CIE 2000 colour-difference formula: CIEDE2000," *Color Res. Appl.*, vol. 26, no. 5, pp. 340–350, Oct. 2001, doi: [10.1002/col.1049](https://doi.org/10.1002/col.1049).
- [13] xrite.com and pentone.com. (2009). *Complete Guide to Color Management*. [Online]. Available: https://xritephoto.com/documents/literature/EN/L11-144_CompleteGuideToColorManagement_EN.pdf
- [14] J. S. B. Valencia, F. E. L. Giraldo, and J. F. V. Bonilla, "Calibration method for correlated color temperature (CCT) measurement using RGB color sensors," in *Proc. Symp. Signals, Images Artif. Vis.*, 2013, pp. 1–6, doi: [10.1109/STSIVA.2013.6644921](https://doi.org/10.1109/STSIVA.2013.6644921).
- [15] S. Jain, L. Fernandes, C. Regnier, and V. Garg, "Circadian lighting in a space daylight by a tubular daylight device," *IOP Conf. Ser., Earth Environ. Sci.*, vol. 238, Mar. 2019, Art. no. 012030, doi: [10.1088/1755-1315/238/1/012030](https://doi.org/10.1088/1755-1315/238/1/012030).
- [16] H. Chen and S. Y. Hui, "Dynamic prediction of correlated color temperature and color rendering index of phosphor-coated white light-emitting diodes," *IEEE Trans. Ind. Electron.*, vol. 61, no. 2, pp. 784–797, Feb. 2014, doi: [10.1109/TIE.2013.2251736](https://doi.org/10.1109/TIE.2013.2251736).
- [17] (Jan. 22, 2010). *Colorimetric Values for ColorChecker Family of Targets*. [Online]. Available: https://xritephoto.com/ph_product_overview.aspx?ID=820&Action=support&SupportID=5159
- [18] A. Gilchrist and J. Nobbs, "Colorimetry, theory," in *Encyclopedia of Spectroscopy and Spectrometry*. Amsterdam, The Netherlands: Elsevier, 2016, pp. 328–333. [Online]. Available: <https://www.sciencedirect.com/science/article/pii/B9780128032244001242>, doi: [10.1016/B978-0-12-803224-4.00124-2](https://doi.org/10.1016/B978-0-12-803224-4.00124-2).



VEDAVYASA KAMATH received the M.Tech. degree in energy management, lighting and auditing from the Manipal Academy of Higher Education, Manipal, Karnataka, India, in 2013.

He is currently a Faculty Member and a Research Scholar with the Manipal Institute of Technology, MAHE. His research interests include lighting science, machine learning, and building automation. He has ten years of teaching experience. He is a Life Member of the Professional Body, Indian Society of Lighting Engineers.

He is currently a Faculty Member and a Research Scholar with the Manipal Institute of Technology, MAHE. His research interests include lighting science, machine learning, and building automation. He has ten years of teaching experience. He is a Life Member of the Professional Body, Indian Society of Lighting Engineers.



CIJI PEARL KURIAN (Senior Member, IEEE) was born in India, in 1964. She received the B.Tech. degree in electrical and electronics engineering from Calicut University, Kerala, in 1986, the M.Tech degree in lighting Science and engineering from Mangalore University, Karnataka, in 1994, and the Ph.D. degree in electrical engineering from Manipal University, Manipal, India, in 2007.

Since 1987, she has been teaching with the Department of Electrical and Electronics Engineering, Manipal Institute of Technology, Manipal (a constituent institution of the Manipal Academy of Higher Education), India. Her research interests include lighting controls-technology and applications.

Dr. Kurian is a fellow of the Institution of Engineers India and a Life Member of Professional Bodies, Indian Society of Lighting Engineers, Indian Society for Technical Education, and Systems Society of India. She is the Editor of the *Manipal Journal of Science and Technology* (MJST).



U. SUPRABHA PADIYAR received the M.Tech. degree in power electronics, drives, and control from the Manipal Academy of Higher Education, Manipal, Karnataka, India, in 2014. She is currently Faculty with the Manipal Institute of Technology, MAHE, and a Research Scholar with the National Institute of Technology, Suratkal, Karnataka. Her research interests include power electronics, drives, electric vehicles, and battery management systems.